

RF TEST REPORT

For

Luoyang Fabao Office Furniture Co., Ltd

Product Name: biometric Electronic safe

Test Model(s): FB-C100Z

Report Reference No. : DACE260410009RL001

FCC ID : 2BVTE-FB-C100Z

Applicant's Name : Luoyang Fabao Office Furniture Co., Ltd

Address : Group 16, Xipangcun Village, Pangcun Town, Luolong District, Luoyang, Henan, China

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15.247

Date of Receipt : April 10, 2026

Date of Test : April 10, 2026 to April 21, 2026

Date of Issue : April 21, 2026

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Apply for company information

Applicant's Name	:	Luoyang Fabao Office Furniture Co., Ltd
Address	:	Group 16, Xipangcun Village, Pangcun Town, Luolong District, Luoyang, Henan, China
Product Name	:	biometric Electronic safe
Test Model(s)	:	FB-C100Z
Series Model(s)	:	FB-C80Z, FB-C150Z, FB-C180Z, FB-C45Z, FB-G45Z, FB-G180Z, FB-C60Z, FB-C70Z, FB-G60Z, FB-G70Z, FB-G30Z
Test Specification Standard(s)	:	47 CFR Part 15.247

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Lucy Mo

Lucy Mo / Test Engineer

April 21, 2026

Supervised by:

Arron Liu

Arron Liu / Project Engineer

April 21, 2026

Approved by:

Tom Chen

Tom Chen / Manager

April 21, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260410009RL001	April 21, 2026

CONTENTS

1	TEST SUMMARY	6
1.1	TEST STANDARDS	6
1.2	SUMMARY OF TEST RESULT	6
2	GENERAL INFORMATION	7
2.1	CLIENT INFORMATION	7
2.2	DESCRIPTION OF DEVICE (EUT).....	7
2.3	DESCRIPTION OF TEST MODES.....	7
2.4	DESCRIPTION OF SUPPORT UNITS	7
2.5	OPERATION FREQUENCY EACH OF CHANNEL.....	8
2.6	EQUIPMENTS USED DURING THE TEST	9
2.7	STATEMENT OF THE MEASUREMENT UNCERTAINTY	11
2.8	IDENTIFICATION OF TESTING LABORATORY	11
2.9	ANNOUNCEMENT	11
3	EVALUATION RESULTS (EVALUATION).....	12
3.1	ANTENNA REQUIREMENT.....	12
3.1.1	Conclusion:.....	12
4	RADIO SPECTRUM MATTER TEST RESULTS (RF).....	13
4.1	6dB BANDWIDTH.....	13
4.1.1	E.U.T. Operation:.....	13
4.1.2	Test Setup Diagram:.....	13
4.1.3	Test Data:	14
4.2	MAXIMUM CONDUCTED OUTPUT POWER	15
4.2.1	E.U.T. Operation:.....	15
4.2.2	Test Setup Diagram:.....	15
4.2.3	Test Data:	15
4.3	POWER SPECTRAL DENSITY	16
4.3.1	E.U.T. Operation:.....	16
4.3.2	Test Setup Diagram:.....	16
4.3.3	Test Data:	16
4.4	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	17
4.4.1	E.U.T. Operation:.....	17
4.4.2	Test Setup Diagram:.....	17
4.4.3	Test Data:	17
4.5	BAND EDGE EMISSIONS (RADIATED)	18
4.5.1	E.U.T. Operation:.....	18
4.5.2	Test Data:	19
4.6	EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz)	23
4.6.1	E.U.T. Operation:.....	24
4.6.2	Test Data:	25
4.7	EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz).....	27
4.7.1	E.U.T. Operation:.....	28
4.7.2	Test Data:	29
5	TEST SETUP PHOTOS	35
6	PHOTOS OF THE EUT	36
	APPENDIX	37
1.	-6dB BANDWIDTH.....	38

2. 99% OCCUPIED BANDWIDTH	43
3. DUTY CYCLE.....	48
4. MAX. OUTPUT POWER	53
5. POWER SPECTRAL DENSITY.....	54
6. BANDEDGE.....	59
7. SPURIOUS EMISSION.....	66

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.247	---	47 CFR 15.203	Pass
6dB Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2020, section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Luoyang Fabao Office Furniture Co., Ltd
Address : Group 16, Xipangcun Village, Pangcun Town, Luolong District, Luoyang, Henan, China

Manufacturer : Luoyang Fabao Office Furniture Co., Ltd
Address : Group 16, Xipangcun Village, Pangcun Town, Luolong District, Luoyang, Henan, China

2.2 Description of Device (EUT)

Product Name:	biometric Electronic safe
Model/Type reference:	FB-C100Z
Series Model:	FB-C80Z, FB-C150Z, FB-C180Z, FB-C45Z, FB-G45Z, FB-G180Z, FB-C60Z, FB-C70Z, FB-G60Z, FB-G70Z, FB-G30Z
Model Difference:	All the model are the same circuit and RF module, only the model name and appearance size are different. Test sample model: FB-C100Z
Trade Mark:	N/A
Power Supply:	DC 6V by battery
Operation Frequency:	2412-2462MHz
Number of Channels:	802.11b/g/n(HT20): 11 Channels
Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type:	PCB Antenna
Antenna Gain:	2.45dBi
Hardware Version:	V1.0
Software Version:	V1.0

2.3 Description of Test Modes

No	Title	Description
TM1	2.4GWIFI TX Mode	Keep the EUT in 802.11b/g/n20 transmitting mode at lowest, middle and highest channel.
Test Environment		Normal Voltage(DC): 6V

2.4 Description of Support Units

The EUT was tested as an independent device.

2.5 Operation Frequency each of channel

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2462	10	2457	11	2462	12	2467
13	2472	/	/	/	/	/	/

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	802.11b/g/n(HT20)
	Frequency (MHz)
Lowest channel	2412MHz
Middle channel	2442MHz
Highest channel	2472MHz

2.6 Equipments Used During The Test

Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(shenzhen) Co.,Ltd.	RTS-01	V1.0.0	/	/
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Vector Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01

Band edge emissions (Radiated)
Emissions in frequency bands (below 1GHz)
Emissions in frequency bands (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2026-04-14	2027-04-13
Cable(LF)#2	Schwarzbeck	/	/	2026-04-13	2027-04-12
Cable(LF)#1	Schwarzbeck	/	/	2026-04-14	2027-04-13
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2026-04-14	2027-04-13
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2026-04-14	2027-04-13
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2026-04-14	2027-04-13
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2026-04-14	2027-04-13
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2026-04-14	2027-04-13
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2026-04-14	2027-04-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2026-04-14	2027-04-13
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2024-09-28	2026-09-27

2.7 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Occupied Bandwidth	$\pm 3.63\%$
RF conducted power	$\pm 0.733\text{dB}$
RF power density	$\pm 0.234\%$
Conducted Spurious emissions	$\pm 1.98\text{dB}$
Radiated Emission (Above 1GHz)	$\pm 5.46\text{dB}$
Radiated Emission (Below 1GHz)	$\pm 5.79\text{dB}$

Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2.8 Identification of Testing Laboratory

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342
Test Firm Registration Number:	778666
A2LA Certificate Number:	6270.01

2.9 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client(item 2.2). When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)

4.1 6dB Bandwidth


Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

4.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.9 °C	Humidity:	52 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.1.2 Test Setup Diagram:

--



4.1.3 Test Data:

Please Refer to Appendix for Details.


4.2 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020, section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.9.2 Maximum conducted (average) output power

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.9 °C	Humidity:	50 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Please Refer to Appendix for Details.


4.3 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.10, Maximum power spectral density level in the fundamental emission

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.3 °C	Humidity:	47 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.1 °C	Humidity:	55 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.

4.5 Band edge emissions (Radiated)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.10.5.2		

4.5.1 E.U.T. Operation:

Operating Environment:			
Temperature:	23.7 °C	Humidity:	55 %
Atmospheric Pressure:	102 kPa		
Pretest mode:	TM1		
Final test mode:	TM1		


4.5.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	2310.000	41.82	-6.63	35.19	74.00	-38.81	peak		P	
2 *	2310.000	32.17	-6.63	25.54	54.00	-28.46	AVG		P	
3	2390.000	40.17	-6.42	33.75	74.00	-40.25	peak		P	
4	2390.000	29.21	-6.42	22.79	54.00	-31.21	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2310.000	41.33	-6.63	34.70	74.00	-39.30	peak			P	
2	2310.000	30.41	-6.63	23.78	54.00	-30.22	AVG			P	
3	2390.000	44.08	-6.42	37.66	74.00	-36.34	peak			P	
4 *	2390.000	33.38	-6.42	26.96	54.00	-27.04	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2483.500	43.03	-6.17	36.86	74.00	-37.14	peak			P	
2 *	2483.500	33.48	-6.17	27.31	54.00	-26.69	AVG			P	
3	2500.000	41.50	-6.13	35.37	74.00	-38.63	peak			P	
4	2500.000	31.10	-6.13	24.97	54.00	-29.03	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	2483.500	46.83	-6.17	40.66	74.00	-33.34	peak		P	
2 *	2483.500	35.29	-6.17	29.12	54.00	-24.88	AVG		P	
3	2500.000	42.58	-6.13	36.45	74.00	-37.55	peak		P	
4	2500.000	31.49	-6.13	25.36	54.00	-28.64	AVG		P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be recorded in the test report.

4.6 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.		
Test Method:	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Remark: 1) For emission below 1GHz, through pre-scan found the worst case is the lowest		


	channel. Only the worst case is recorded in the report. 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
--	---

4.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.5 °C	Humidity:	52 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.6.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	32.5198	26.18	-2.91	23.27	40.00	-16.73	QP	100		P	
2	56.0007	27.22	-13.82	13.40	40.00	-26.60	QP	100		P	
3	132.6850	26.75	-6.88	19.87	43.50	-23.63	QP	100		P	
4	208.5803	27.18	-9.98	17.20	43.50	-26.30	QP	100		P	
5	435.5898	26.56	-4.32	22.24	46.00	-23.76	QP	100		P	
6	609.9217	26.53	-1.50	25.03	46.00	-20.97	QP	100		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	82.9385	34.87	-12.93	21.94	40.00	-18.06	QP	100		P	
2	141.8262	26.45	-7.45	19.00	43.50	-24.50	QP	100		P	
3	205.6751	26.36	-9.66	16.70	43.50	-26.80	QP	100		P	
4	364.2595	26.44	-6.76	19.68	46.00	-26.32	QP	100		P	
5	477.1694	26.14	-3.34	22.80	46.00	-23.20	QP	100		P	
6	711.6734	26.06	0.55	26.61	46.00	-19.39	QP	100		P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be of 802.11b mode recorded in the test report.

4.7 Emissions in frequency bands (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Remark:		


	1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report. 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
--	--

4.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.6 °C	Humidity:	47 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.7.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	4818.750	43.42	-0.65	42.77	74.00	-31.23	peak		P	
2	4818.750	30.28	-0.65	29.63	54.00	-24.37	AVG		P	
3	9413.000	38.61	8.14	46.75	74.00	-27.25	peak		P	
4	9413.000	25.76	8.14	33.90	54.00	-20.10	AVG		P	
5	12515.000	36.90	11.06	47.96	74.00	-26.04	peak		P	
6 *	12515.000	24.82	11.06	35.88	54.00	-18.12	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4818.750	52.92	-0.65	52.27	74.00	-21.73	peak			P	
2 *	4818.750	39.43	-0.65	38.78	54.00	-15.22	AVG			P	
3	8590.500	36.36	7.59	43.95	74.00	-30.05	peak			P	
4	8590.500	24.86	7.59	32.45	54.00	-21.55	AVG			P	
5	12350.500	37.03	10.73	47.76	74.00	-26.24	peak			P	
6	12350.500	25.20	10.73	35.93	54.00	-18.07	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	57.07	-0.45	56.62	74.00	-17.38	peak			P	
2 *	4877.500	41.73	-0.45	41.28	54.00	-12.72	AVG			P	
3	7309.750	39.91	4.55	44.46	74.00	-29.54	peak			P	
4	7309.750	29.17	4.55	33.72	54.00	-20.28	AVG			P	
5	10682.000	37.73	9.13	46.86	74.00	-27.14	peak			P	
6	10682.000	26.53	9.13	35.66	54.00	-18.34	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	49.50	-0.45	49.05	74.00	-24.95	peak			P	
2	4877.500	35.06	-0.45	34.61	54.00	-19.39	AVG			P	
3	8367.250	37.96	7.23	45.19	74.00	-28.81	peak			P	
4	8367.250	24.80	7.23	32.03	54.00	-21.97	AVG			P	
5	10893.500	38.83	9.30	48.13	74.00	-25.87	peak			P	
6 *	10893.500	25.43	9.30	34.73	54.00	-19.27	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	4924.500	49.39	-0.30	49.09	74.00	-24.91	peak		P	
2 *	4924.500	36.26	-0.30	35.96	54.00	-18.04	AVG		P	
3	8285.000	36.96	7.11	44.07	74.00	-29.93	peak		P	
4	8285.000	25.12	7.11	32.23	54.00	-21.77	AVG		P	
5	10505.750	39.37	9.01	48.38	74.00	-25.62	peak		P	
6	10505.750	26.41	9.01	35.42	54.00	-18.58	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4924.500	53.22	-0.30	52.92	74.00	-21.08	peak			P	
2 *	4924.500	40.35	-0.30	40.05	54.00	-13.95	AVG			P	
3	7380.250	45.18	4.67	49.85	74.00	-24.15	peak			P	
4	7380.250	31.35	4.67	36.02	54.00	-17.98	AVG			P	
5	10705.500	37.26	9.15	46.41	74.00	-27.59	peak			P	
6	10705.500	26.23	9.15	35.38	54.00	-18.62	AVG			P	

Remark: Margin = Level - Limit, Level = Test receiver reading + correction factor


The test software will only record the worst test angle and height, and only the worst case will be recorded in the test report.

5 TEST SETUP PHOTOS

Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)



6 PHOTOS OF THE EUT


Refer to Appendix - EUT Photos for EUT External Photo and Internal Photo.

Appendix



1. -6dB Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	9.25	500	Pass
NVNT	ANT1	802.11b	2437.00	9.25	500	Pass
NVNT	ANT1	802.11b	2462.00	9.24	500	Pass
NVNT	ANT1	802.11g	2412.00	16.54	500	Pass
NVNT	ANT1	802.11g	2437.00	16.51	500	Pass
NVNT	ANT1	802.11g	2462.00	16.46	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	17.69	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.63	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.74	500	Pass


-6dB_Bandwidth_NVNT_ANT1_802_11b_2412




-6dB_Bandwidth_NVNT_ANT1_802_11b_2437









-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412




-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437




2. 99% Occupied Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	802.11b	2412.00	14.076
NVNT	ANT1	802.11b	2437.00	14.145
NVNT	ANT1	802.11b	2462.00	14.081
NVNT	ANT1	802.11g	2412.00	17.707
NVNT	ANT1	802.11g	2437.00	17.709
NVNT	ANT1	802.11g	2462.00	17.702
NVNT	ANT1	802.11n(HT20)	2412.00	18.600
NVNT	ANT1	802.11n(HT20)	2437.00	18.697
NVNT	ANT1	802.11n(HT20)	2462.00	18.608


99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2462




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2462




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412



99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462




3. Duty Cycle

Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	99.20	0.00
NVNT	ANT1	802.11b	2437.00	99.04	0.00
NVNT	ANT1	802.11b	2462.00	99.04	0.00
NVNT	ANT1	802.11g	2412.00	95.41	0.20
NVNT	ANT1	802.11g	2437.00	94.55	0.24
NVNT	ANT1	802.11g	2462.00	94.55	0.24
NVNT	ANT1	802.11n(HT20)	2412.00	95.10	0.22
NVNT	ANT1	802.11n(HT20)	2437.00	95.10	0.22
NVNT	ANT1	802.11n(HT20)	2462.00	94.17	0.26


Duty_Cycle_NVNT_ANT1_802_11b_2412




Duty_Cycle_NVNT_ANT1_802_11b_2437




Duty_Cycle_NVNT_ANT1_802_11b_2462






Duty_Cycle_NVNT_ANT1_802_11g_2412





Duty_Cycle_NVNT_ANT1_802_11g_2437



Duty_Cycle_NVNT_ANT1_802_11g_2462






4. MAX. Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	19.20	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	18.66	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	18.57	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	23.75	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	23.77	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	23.63	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	22.86	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	22.57	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	22.70	30	Pass

5. Power Spectral Density

Condition	Antenna	Modulation	Frequency (MHz)	SA_PSD(dBm/30kHz)	Duty factor(dB)	RB factor(dB)	PSD(dBm/3kHz)	limit(dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	4.24	N/A	-10.00	-5.76	8	Pass
NVNT	ANT1	802.11b	2437.00	3.28	N/A	-10.00	-6.72	8	Pass
NVNT	ANT1	802.11b	2462.00	4.11	N/A	-10.00	-5.89	8	Pass
NVNT	ANT1	802.11g	2412.00	1.51	N/A	-10.00	-8.49	8	Pass
NVNT	ANT1	802.11g	2437.00	1.01	N/A	-10.00	-8.99	8	Pass
NVNT	ANT1	802.11g	2462.00	1.42	N/A	-10.00	-8.58	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	0.11	N/A	-10.00	-9.89	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-0.20	N/A	-10.00	-10.20	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-0.24	N/A	-10.00	-10.24	8	Pass


Power_Spectral_Density_NVNT_ANT1_802_11b_2412




Power_Spectral_Density_NVNT_ANT1_802_11b_2437




Power_Spectral_Density_NVNT_ANT1_802_11b_2462




Power_Spectral_Density_NVNT_ANT1_802_11g_2412




Power_Spectral_Density_NVNT_ANT1_802_11g_2437





Power_Spectral_Density_NVNT_ANT1_802_11g_2462



Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2412




Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2437




6. Bandedge

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2399.824	7.779	-41.789	-12.221	Pass
NVNT	ANT1	802.11b	2462.00	2496.976	7.378	-49.000	-12.622	Pass
NVNT	ANT1	802.11g	2412.00	2398.928	5.326	-28.177	-14.674	Pass
NVNT	ANT1	802.11g	2462.00	2483.536	5.262	-37.637	-14.738	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2399.824	4.583	-28.222	-15.417	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2483.824	4.995	-39.454	-15.005	Pass


1_Reference_Level_NVNT_ANT1_802_11b_2412




2_Bandedge_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2462




2_Bandedge_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Bandedge_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Bandedge_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2412



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2462




7. Spurious Emission

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	24990.012	7.779	-35.933	-12.221	Pass
NVNT	ANT1	802.11b	2437.00	24970.036	7.211	-42.339	-12.789	Pass
NVNT	ANT1	802.11b	2462.00	24970.036	7.378	-35.433	-12.622	Pass
NVNT	ANT1	802.11g	2412.00	24513.085	5.326	-43.124	-14.674	Pass
NVNT	ANT1	802.11g	2437.00	24480.624	5.500	-41.990	-14.500	Pass
NVNT	ANT1	802.11g	2462.00	24563.025	5.262	-43.589	-14.738	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	24910.108	4.583	-43.023	-15.417	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24468.139	4.360	-40.497	-15.640	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	24967.539	4.995	-43.790	-15.005	Pass


1_Reference_Level_NVNT_ANT1_802_11b_2412




2_Spurious_Emission_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2437




2_Spurious_Emission_NVNT_ANT1_802_11b_2437




1_Reference_Level_NVNT_ANT1_802_11b_2462




2_Spurious_Emission_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Spurious_Emission_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2437




2_Spurious_Emission_NVNT_ANT1_802_11g_2437




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Spurious_Emission_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2437



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462



2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2462



***** End of Report *****