


Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	3448.918	19.37	33.00	52.37	68.20	15.83	PASS	Horizontal	PK
2	5047.2819	25.01	32.86	57.87	74.00	16.13	PASS	Horizontal	PK
3	6449.838	28.40	32.31	60.71	68.20	7.49	PASS	Horizontal	PK
4	9680.5672	1.17	52.99	54.16	68.20	14.04	PASS	Horizontal	PK
5	13740.2296	7.23	51.43	58.66	68.20	9.54	PASS	Horizontal	PK
6	17045.0018	12.39	51.30	63.69	68.20	4.51	PASS	Horizontal	PK
7	5005.2602	24.82	10.51	35.33	54.00	18.67	PASS	Horizontal	AV

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	3453.3181	19.30	32.38	51.68	68.20	16.52	PASS	Vertical	PK
2	4990.7396	24.66	33.27	57.93	74.00	16.07	PASS	Vertical	PK
3	6485.6994	28.63	33.77	62.40	68.20	5.80	PASS	Vertical	PK
4	9707.2483	1.16	53.18	54.34	68.20	13.86	PASS	Vertical	PK
5	14375.975	9.07	49.46	58.53	68.20	9.67	PASS	Vertical	PK
6	17583.2233	14.04	49.50	63.54	68.20	4.66	PASS	Vertical	PK
7	5003.5001	24.78	10.55	35.33	54.00	18.67	PASS	Vertical	AV

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19010.2804	-26.26	61.07	34.81	74.00	39.19	PASS	Horizontal	PK
2	20956.9183	-25.92	60.47	34.55	74.00	39.45	PASS	Horizontal	PK
3	24033.5213	-22.06	57.24	35.18	68.20	33.02	PASS	Horizontal	PK
4	27111.0044	-21.87	56.94	35.07	68.20	33.13	PASS	Horizontal	PK
5	31330.7732	-19.82	53.63	33.81	74.00	40.19	PASS	Horizontal	PK
6	35338.4535	-16.03	49.31	33.28	68.20	34.92	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5755MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19127.3251	-26.13	61.13	35.00	74.00	39.00	PASS	Vertical	PK
2	21030.8412	-25.96	60.42	34.46	74.00	39.54	PASS	Vertical	PK
3	24060.8024	-22.15	57.37	35.22	68.20	32.98	PASS	Vertical	PK
4	27519.3408	-21.59	57.07	35.48	68.20	32.72	PASS	Vertical	PK
5	31791.0316	-19.89	53.51	33.62	74.00	40.38	PASS	Vertical	PK
6	35886.7155	-16.98	49.56	32.58	68.20	35.62	PASS	Vertical	PK

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	3496.2198	19.32	32.92	52.24	68.20	15.96	PASS	Horizontal	PK
2	4997.1199	24.69	33.83	58.52	74.00	15.48	PASS	Horizontal	PK
3	6443.4577	28.28	33.15	61.43	68.20	6.77	PASS	Horizontal	PK
4	9746.3499	1.10	52.83	53.93	68.20	14.27	PASS	Horizontal	PK
5	13743.4497	7.23	51.11	58.34	68.20	9.86	PASS	Horizontal	PK
6	17111.2444	12.31	52.26	64.57	68.20	3.63	PASS	Horizontal	PK
7	5017.3607	24.83	10.27	35.10	54.00	18.90	PASS	Horizontal	AV

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	3468.2787	19.25	32.88	52.13	68.20	16.07	PASS	Vertical	PK
2	5027.7011	24.92	33.28	58.20	74.00	15.80	PASS	Vertical	PK
3	6453.3581	28.38	32.55	60.93	68.20	7.27	PASS	Vertical	PK
4	9679.6472	1.17	53.26	54.43	68.20	13.77	PASS	Vertical	PK
5	13684.1074	7.02	51.68	58.70	68.20	9.50	PASS	Vertical	PK
6	17024.761	12.51	51.26	63.77	68.20	4.43	PASS	Vertical	PK
7	5009.6604	24.92	10.30	35.22	54.00	18.78	PASS	Vertical	AV

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	\	Test_Date	2026/7/28


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19287.4915	-25.87	60.44	34.57	74.00	39.43	PASS	Horizontal	PK
2	21295.7318	-25.81	59.86	34.05	74.00	39.95	PASS	Horizontal	PK
3	23925.277	-22.09	57.71	35.62	74.00	38.38	PASS	Horizontal	PK
4	26714.1086	-21.36	56.56	35.20	68.20	33.00	PASS	Horizontal	PK
5	29193.1677	-21.47	56.60	35.13	68.20	33.07	PASS	Horizontal	PK
6	32385.0554	-18.13	53.61	35.48	68.20	32.72	PASS	Horizontal	PK
7	36553.7822	-15.97	48.82	32.85	68.20	35.35	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE40) Transmitting	Test_Frequency	5795MHz
Tset_Engineer	\	Test_Date	2026/7/28

Test Graph



Suspected List

NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19071.0028	-26.20	60.83	34.63	74.00	39.37	PASS	Vertical	PK
2	20235.2894	-25.50	60.08	34.58	74.00	39.42	PASS	Vertical	PK
3	23519.5808	-23.26	57.60	34.34	68.20	33.86	PASS	Vertical	PK
4	25551.5821	-20.89	55.70	34.81	68.20	33.39	PASS	Vertical	PK
5	29171.1668	-21.46	56.52	35.06	68.20	33.14	PASS	Vertical	PK
6	32427.2971	-18.15	53.14	34.99	68.20	33.21	PASS	Vertical	PK

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:




Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

2) Scan from 9kHz to 40GHz, the disturbance above 18GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The report records the lowest Peak value. If the Peak value is greater than 54dBμV/m, then the Average value at that time is recorded.

5.9 Radiated Emission which fall in the restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.407 (b)				
Test Method:	ANSI C63.10-2020				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed				

	the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. Note: (i) $EIRP = ((E*d)^2) / 30$ where: • E is the field strength in V/m; • d is the measurement distance in meters; • EIRP is the equivalent isotropically radiated power in watts. (ii) Working in dB units, the above equation is equivalent to: $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$ (iii) Or, if d is 3 meters: $EIRP[dBm] = E[dB\mu V/m] - 95.2$
Test Setup:	 Figure 1. Below 30MHz  Figure 2. 30MHz to 1GHz  Figure 3. Above 1 GHz
Test Procedure:	j. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: