



EMC TEST REPORT

Test item description: Smart Power Bank

FCC ID: 2BVUD-BST0155

Trademark(s): Besiter

Model/Type reference: BST-0155

S/N: /

Report No.: CTB26040904704E01

Applicant's name: Shenzhen Besiter Power Bank Co.,Ltd.

Address: Building 65/66 Longwangmiao Industrial Park, Baishixia Community, Fuyong Subdistrict, BaoAn District, Shenzhen, Guangdong, China

Manufacturer: Shenzhen Besiter Power Bank Co.,Ltd.

Address: Building 65/66 Longwangmiao Industrial Park, Baishixia Community, Fuyong Subdistrict, BaoAn District, Shenzhen, Guangdong, China

Prepared by: Shenzhen CTB Testing Technology Co., Ltd.

Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt: Apr. 09, 2026

Date of Test(s): Apr. 09, 2026 to Apr. 28, 2026

Date of Issue: Apr. 28, 2026

Test Standard(s): CFR47, FCC Part 15 Subpart B, ANSI C63.4: 2014

Test Result: Pass

In the configuration tested, the EUT complied with the standards specified above.

Compiled by:

Reviewed by:

Approved by:

Blake cai

Bin Mei

Rita Xiao

Black cai

Bin Mei

Rita Xiao

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. The tested sample(s) and the sample information are provided by the applicant. The authenticity, accuracy, and completeness of the provided information are the sole responsibility of the applicant. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The result decision rules of our laboratory are based solely on the direct comparison between the actual measured values of test results and the standard limits, without considering the measurement uncertainty. "★" indicates the testing items were fulfilled by subcontracted lab. "×" indicates the items are not in CNAS accreditation scope.

Table of Contents

1.	Description of version	3
2.	Test summary.....	4
3.	Measurement uncertainty	5
4.	General information.....	6
4.1.	Description of EUT	6
4.2.	Description of accessory device	6
4.3.	Test conditions	6
4.4.	Block diagram of EUT configuration	6
4.5.	Operating condition of EUT	6
5.	List of Test and Measurement Instruments	8
6.	Conducted Emission	10
6.1.	Limit.....	10
6.2.	Test setup	10
6.3.	EMI test receiver setup	10
6.4.	Test procedure	10
6.5.	Test results	11
7.	Radiated emissions.....	13
7.1.	Limit.....	13
7.2.	Test setup	13
7.3.	EMI test receiver setup and spectrum analyzer setup	14
7.4.	Test procedure	14
7.5.	Corrected Amplitude & Margin Calculation	14
7.6.	Test results	15
8.	Photographs of test setup	17

1. Description of version

Report No.	Issue Date	Description	Approved
CTB26040904704E01	Apr. 28, 2026	Original	Valid

2. Test summary

Test procedures according to the technical standards:

Standard	Test Item	Test Result
§15.107	Conducted Emission	PASS
§15.109	Radiated Emission	PASS

Remark:

Test according to ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.

3. Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

Test Item	Frequency	Expanded Uncertainty (U_{Lab})
Conducted Emission	150 kHz to 30 MHz	± 3.1 dB
Radiated Emission	30 MHz to 1000 MHz	± 4.1 dB
Radiated Emission	1000 MHz to 6000 MHz	± 4.8 dB

4. General information

4.1. Description of EUT

Test item description:	Smart Power Bank
Trademark(s):	Besiter
Model/Type reference:	BST-0155
Serial Model No.	N/A
Model Difference	N/A
Ratings:	DC 3.7V by battery
Configuration	☒ Table-top ☐ Floor-standing
The highest frequency of the internal sources of the EUT	☐ below 1.705 MHz, the measurement shall only be made up to 30 MHz. ☒ between 1.705 MHz and 108 MHz, the measurement shall only be made up to 1 GHz. ☐ between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. ☐ between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. ☐ above 1 GHz, the measurement shall be made up to 5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


4.2. Description of accessory device

No.	Device Type	Brand	Model	Specification	Note
1	Adapter	JYIN	JY-05100C	/	AE

4.3. Test conditions

Temperature: 15-25°C
 Relative Humidity: 30-60 %
 Atmospheric pressure: 800hPa-1060hPa

4.4. Block diagram of EUT configuration



4.5. Operating condition of EUT

Operating condition	Mode 1*	Charging	Test Voltage	AC 120V/50Hz
Operating condition	Mode 2	Full Load(Type-C: 5V DC, 2.1A Max)	Test Voltage	9V
Operating condition	Mode 3	Full Load(Lightning: 5V	Test Voltage	3.7V

		DC, 2.1A Max)		
Operating condition	Mode 4	Full Load(Micro USB: 5V DC, 2.1A Max)	Test Voltage	3.7V

Note: This test covers all possible operating modes of the device, only the worst data are list in report. The worst data are shows (*) is the nearest standard limit which were recorded in this report.

5. List of Test and Measurement Instruments

Continuous disturbance							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated Date	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2024/6/22	2027/6/21
2	LISN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/5/22	2026/5/21
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/5/22	2026/5/21
4	Coaxial cable	ZDECL	Z302S	18091904	/	2025/5/22	2026/5/21
5	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/18	2026/6/17
6	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/9/19	2026/9/18
7	EZ-EMC	Frad	EMC-con3A1.1	/	/	/	/
8	Current Probe	FCC	F-52B	199453	/	2025/5/24	2026/5/23
9	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
10	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

Radiated emission(No.1 Chamber)							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2024/6/23	2027/6/22
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2025/6/1	2026/5/31
3	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/29	2026/6/28
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/3	2026/6/2
5	Amplifier	HP	8447E	2945A02747	/	2025/5/23	2026/5/22
6	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/2	2026/6/1
7	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/5/23	2026/5/22
8	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/5/23	2026/5/22
9	Coaxial cable	ETS	RFC-SNS-100-NMS-80	/	/	2025/5/24	2026/5/23
10	Coaxial cable	ETS	RFC-SN-100-NMS-20	/	/	2025/5/24	2026/5/23
11	Coaxial cable	ETS	RFC-SNS-100-SMS-20	/	/	2025/5/24	2026/5/23

12	Coaxial cable	ETS	RFC-NNS-100-NMS-300	/	/	2025/5/24	2026/5/23
13	EMI test software	Frad	EZ-EMC	Ver/ FA-03A2 RE	/	/	/
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

6. Conducted Emission

6.1. Limit

Except for Class A devices:


Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

For Class A devices:

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	79	66
0.5-30	73	60

6.2. Test setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

The setup of EUT is according with ANSI C63.4 measurement procedure. Specification used with FCC Part 15 limits.

6.3. EMI test receiver setup


Frequency Range	9kHz-30MHz
Resolution Bandwidth	200Hz (9kHz-150kHz) 9kHz (150kHz-30MHz)

6.4. Test procedure

1. Measurement was performed in shielded room, and instruments used were followed clause 4 of ANSI C63.4.
2. Detailed test procedure was following clause 7 of ANSI C63.4.
3. Frequency range 150kHz – 30MHz was checked and EMI receiver measurement bandwidth was set to 9 kHz.

6.5. Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1660	40.40	10.07	50.47	65.16	-14.69	QP
2		0.1660	24.89	10.07	34.96	55.16	-20.20	AVG
3		0.2500	33.02	10.08	43.10	61.76	-18.66	QP
4		0.2500	15.01	10.08	25.09	51.76	-26.67	AVG
5		0.5860	32.70	10.10	42.80	56.00	-13.20	QP
6		0.5860	18.88	10.10	28.98	46.00	-17.02	AVG
7	*	2.6660	35.00	10.19	45.19	56.00	-10.81	QP
8		2.6660	16.54	10.19	26.73	46.00	-19.27	AVG
9		4.2180	33.21	10.25	43.46	56.00	-12.54	QP
10		4.2180	14.24	10.25	24.49	46.00	-21.51	AVG
11		17.2420	31.27	10.83	42.10	60.00	-17.90	QP
12		17.2420	13.27	10.83	24.10	50.00	-25.90	AVG

Note: Result=Reading + Factor
Over Limit=Result - Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1660	37.27	10.07	47.34	65.16	-17.82	QP
2		0.1660	21.64	10.07	31.71	55.16	-23.45	AVG
3		0.6500	28.94	10.10	39.04	56.00	-16.96	QP
4		0.6500	11.93	10.10	22.03	46.00	-23.97	AVG
5		1.4740	29.11	10.15	39.26	56.00	-16.74	QP
6		1.4740	11.18	10.15	21.33	46.00	-24.67	AVG
7	*	2.6060	36.63	10.19	46.82	56.00	-9.18	QP
8		2.6060	17.49	10.19	27.68	46.00	-18.32	AVG
9		4.3460	29.40	10.26	39.66	56.00	-16.34	QP
10		4.3460	16.02	10.26	26.28	46.00	-19.72	AVG
11		16.1340	31.60	10.78	42.38	60.00	-17.62	QP
12		16.1340	12.07	10.78	22.85	50.00	-27.15	AVG

Note: Result=Reading + Factor
Over Limit=Result – Limit

7. Radiated emissions

7.1. Limit

Except for Class A devices (at 3m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

For Class A devices (at 10m):


Frequency of emission (MHz)	Field strength (microvolts/meter)	
	(microvolts/meter)	(dB μ V/m)
30-88	90	39
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

7.2. Test setup

Radiated Emission Test Set-Up Frequency Below 1 GHz



Radiated Emission Test Set-Up Frequency Above 1GHz



The radiated tests were performed in 3 meter Chamber test site, using the setup accordance with the ANSI C63.4:2014.

7.3. EMI test receiver setup and spectrum analyzer setup

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz-1000MHz	100kHz	300kHz	120kHz	QP
Above 1GHz	1MHz	3MHz	/	PK
	1MHz	10Hz	/	AVG

7.4. Test procedure

1. The measurement was performed in a semi-anechoic chamber, and instruments used were followed clause 4 of ANSI C63.4
2. Detailed test procedure was following clause 8 of ANSI C63.4.

7.5. Corrected Amplitude & Margin Calculation

1. The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

2. The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

7.6. Test results


Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV/m	dB/m	dB	
1		40.0644	26.56	-5.86	20.70	40.00	-19.30	QP
2		72.0843	26.33	-8.01	18.32	40.00	-21.68	QP
3		161.4742	26.35	-3.42	22.93	43.50	-20.57	QP
4		322.7540	26.15	-2.15	24.00	46.00	-22.00	QP
5		570.6100	25.25	3.09	28.34	46.00	-17.66	QP
6	*	957.1148	26.91	9.26	36.17	46.00	-9.83	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

Temperature:	23°C	Relative Humidity:	54 %
Pressure:	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	43.3534	31.88	-6.06	25.82	40.00	-14.18	QP
2		108.8377	28.01	-6.95	21.06	43.50	-22.44	QP
3		141.5777	29.01	-5.23	23.78	43.50	-19.72	QP
4		405.3766	26.80	-0.80	26.00	46.00	-20.00	QP
5		633.9073	25.28	4.80	30.08	46.00	-15.92	QP
6		974.0436	26.17	9.18	35.35	54.00	-18.65	QP

Note: Result=Reading+Factor
Over Limit=Result-Limit

8. Photographs of test setup

Radiated Emission



CE



End of report