



MPE Report

Report No.: STS2603230H01

Issued for

Shenzhen Friendship Star Digital Company Limited

ROOM 2302 SHENHUA COMMERCE BUILDING JIABING
RD LUOHU DISTRICT SHENZHEN CITY CHINA

Product Name: PORTABLE DISPLAY

Brand Name: UEME, SYNAGY, FOYU, KALLAK

Model Name: S37

Series Model(s): S37U, S37S, S37F, S37K

FCC ID: 2BVUJS37AA

Test Standards: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name: Shenzhen Friendship Star Digital Company Limited
Address: ROOM 2302 SHENHUA COMMERCE BUILDING JIABING RD
LUOHU DISTRICT SHENZHEN CITY CHINA
Manufacturer's Name: SHENZHEN JOYAR SMART MANUFACTURING TECHNOLOGY
LIMITED
Address: Registered Address: 1F, 2F, 3F, 4F, Workshop I, Yudafu Industrial
Park, No.10, Xingye West Road, Heyi Community, Shajing Street,
Baoan District, Shenzhen City, Guangdong Province, China

Product Description

Product Name: PORTABLE DISPLAY
Brand: UEME, SYNAGY, FOYU, KALLAK
Model Number: S37
Series Model(s): S37U, S37S, S37F, S37K
Standards: FCC 47CFR §2.1091
447498 D04 Interim General RF Exposure Guidance v01

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item: 30 Mar. 2026
Date (s) of performance of tests: 30 Mar. 2026~22 Apr. 2026
Date of Issue: 22 Apr. 2026
Test Result: **Pass**

Testing Engineer :

(Aaron Bu)

Technical Manager :

(Skylar Li)

Authorized Signatory :

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR §2.1091 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.2 LIMIT	7
2.3 TEST RESULT	10



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	22 Apr. 2026	STS2603230H01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	PORTABLE DISPLAY	
Brand	UEME, SYNAGY, FOYU, KALLAK	
Model Name	S37	
Series Model(s)	S37U, S37S, S37F, S37K	
Model Difference	It's just a different model	
Product Description	The EUT is PORTABLE DISPLAY	
	Operation Frequency:	Bluetooth: 2402~2480 MHz 2.4G WLAN: 802.11b/g/n (20MHz): 2412~2472MHz 802.11n (40MHz):2422~2462MHz 5G RLAN: IEEE 802.11a: 5.180GHz-5.240GHz IEEE 802.11a:5.260GHz-5.320GHz IEEE 802.11a:5.500GHz-5.700GHz IEEE 802.11a:5.745GHz-5.825GHz
	Modulation Type:	BLE: GFSK BT BR(1Mbps): GFSK 2.4G WLAN: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 5G RLAN: 802.11a(OFDM):BPSK,QPSK,16-QAM,64-QAM
	Antenna Type:	BT:PCB Antenna 2.4G WLAN/5G RLAN:FPC Antenna
	Antenna Gain:	Bluetooth:0dBi 2.4G WLAN/5G RLAN:-3dBi
Power Rating	Input: DC12V/2A	
Adapter	Model: BPS-PN25B Brand:Xusheng Input: 100Vac - 240Vac Output: DC5V/3A; DC9V/2.77A; DC12V/2.10A	
Battery	Model: 505751-2S1P Rated Voltage: 7.7V Charge Limit Voltage: 8.8V Capacity: 2150mAh	
Hardware Version	V04	
Software Version	JOYAR_S37_UI_MONITOR_1080_CN_V1.0.6_hw2.1	



1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for P_{th}, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P_{th,i} = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP_j = the ERP of fixed, mobile, or portable RF source j.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310.



2.3 TEST RESULT

Tune up

RF Function	Tune Up Power (dBm)	Tune Up Power (dBm)
BT	-1±1	0
BLE Low Channel	0±1	1
BLE Mid Channel	2±1	3
BLE High Channel	0±1	1
2.4G WLAN 802.11b	18±1	19
2.4G WLAN 802.11g/n20	17±1	18
2.4G WLAN 802.11n40	15±1	16
5.2G RLAN	12±1	13
5.3G RLAN	12±1	13
5.6G RLAN	11±1	12
5.8G RLAN	12±1	13

RF Function	Frequency (GHz)	Separation distance (cm)	Tune Up Power (dBm)	Tune Up Power (W)	Limit (W)	Ratio	Result
BT	2.441	20	0	0.001	0.768	0.001	Pass
BLE	2.44	20	3	0.002	0.768	0.003	Pass
2.4G WLAN	2.462	20	19	0.079	0.768	0.103	Pass
5.2G RLAN	5.24	20	13	0.020	0.768	0.026	Pass
5.3G RLAN	5.26	20	13	0.020	0.768	0.026	Pass
5.6G RLAN	5.58	20	12	0.016	0.768	0.021	Pass
5.8G RLAN	5.825	20	13	0.020	0.768	0.026	Pass

Multiple transmission:

$$\text{BLE} + 5.2\text{G RLAN} = 0.003 + 0.026 = 0.029 < 1$$

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

$$2. \text{ERP} = \text{EIRP} - 2.15$$

*****END OF THE REPORT*****