



FCC Test Report

Report No: FCS202604293W01

Issued for

Applicant:	Guangzhou Xingshijie Electronic Technology Co., Ltd.
Address:	Room 301, Building 2, No.10, Yongxing East Erheng Road, Longgui Street, Baiyun District, Guangzhou City,Guangdong Province,China
Product Name:	car dash camera
Brand Name:	N/A
Model Name:	E49+E7
Series Model:	E49+E7, E89+E7, E80+E7, E45+E7, E46+E7, E47+E7, E73+E7, E77+E7, E12+E7, E200+E7, E90+E7, E93+E7, E61+E7, E36+E7, E30+E7, E50+E7, E100+E7, E101+E7, E102+E7, E81+E7, E85+E7, E86+E7, E62+E7, E63+E7, E75+E7, E78+E7, E37+E7, E300+E7, E301+E7
FCC ID:	2BVVY-E49ANDE7
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.FCS-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name..... : Guangzhou Xingshijie Electronic Technology Co., Ltd.

Address..... : Room 301, Building 2, No.10, Yongxing East Erheng Road, Longgui Street, Baiyun District, Guangzhou City,Guangdong Province,China

Manufacture's Name..... : GUANGZHOU YSD TECHNOLOGY & ELECTRONICS CO.,LTD

Address..... : No 10,Second Street,Yongxing East Road,Longgui,Baiyun District,Guangzhou City,Guangdong Province, China

Product Description

Product Name..... : car dash camera

Brand Name..... : N/A

Model Name..... : E49+E7

Series Model..... : E49+E7, E89+E7, E80+E7, E45+E7, E46+E7, E47+E7, E73+E7, E77+E7, E12+E7, E200+E7, E90+E7, E93+E7, E61+E7, E36+E7, E30+E7, E50+E7, E100+E7, E101+E7, E102+E7, E81+E7, E85+E7, E86+E7, E62+E7, E63+E7, E75+E7, E78+E7, E37+E7, E300+E7, E301+E7

Test Standards..... : FCC Rules and Regulations Part 15 Subpart C, Section 247

Test Procedure..... : C63.10-2020+Cor. 1-2023

This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document..

Date of Test..... :

Date (s) of performance of tests. : Apr. 24, 2026~Apr. 29, 2026

Date of Issue..... : Apr. 29, 2026

Test Result..... : Pass

Tested by

:

Jojo Wu

(Jojo Wu)

Reviewed by

:

Jojo Wu

(Jojo Wu)

Approved by

:

Jack Wang

(Jack Wang)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.4 EQUIPMENTS LIST	12
3. 6DB BANDWIDTH	13
3.1 Limit	13
3.2 Test Procedure	13
3.3 Test setup	13
3.4 Test results	14
4. CONDUCTED OUTPUT POWER	24
4.1 limit	24
4.2 test procedure	24
4.3 TEST SETUP	24
4.5 test results	24
5. POWER SPECTRAL DENSITY	25
5.1 LIMIT	25
5.2 TEST PROCEDURE	25
5.3 TEST SETUP	25
5.4 TEST RESULTS	26
5.5 original test data	27
6. Band edge and spurious(conducted)	32
6.1 LIMIT	32
6.2 TEST PROCEDURE	32
6.3 TEST SETUP	32
6.4 TEST RESULTS	33
6.5 ORIGINAL TEST DATA	33
7. RADIATED EMISSION MEASUREMENT	43

Table of Contents	Page
7.1 RADIATED EMISSION LIMITS	43
7.2 TEST PROCEDURE	44
7.3 TESTSETUP	45
7.4. TEST RESULTS	46
8. CONDUCTED EMISSION MEASUREMENT	55
8.1 LIMIT	55
8.2 TEST PROCEDURE	55
8.3 TEST SETUP	56
8.4 TEST RESULTS	56
9. ANTENNA REQUIREMENT	57
9.1 STANDARD REQUIREMENT	57
9.2 RESULT	57

Revision History

Rev.	Issue Date	Effect Page	Contents
00	Apr. 29, 2026	N/A	N/A

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC 15.247 (a) (2)	6dB Bandwidth	PASS	--
FCC 15.247 (b) (3)	Conducted Output Power	PASS	--
FCC 15.247 (e)	Power Spectral Density	PASS	--
FCC 15.247 (d)	Band-edge and Spurious Emissions (Conducted)	PASS	--
FCC 15.247 (d) FCC 15.209 FCC 15.205	Radiated Spurious Emissions	PASS	--
FCC 15.247 (d) FCC 15.209 FCC 15.205	Radiated Band Edge Compliance	PASS	--
FCC 15.207	Power Line Conducted Emission	N/A	--
FCC 15.203	Antenna requirement	PASS	--
15.205	Restricted Band Edge Emission	PASS	--

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) All tests are according to ANSI C63.10-2020+Cor. 1-2023

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number: 5545.01	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.71\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.98\text{ dB}$
3	Conducted Emission (9KHz-150KHz)	$\pm 4.13\text{ dB}$
4	Conducted Emission (150KHz-30MHz)	$\pm 4.74\text{ dB}$
5	All emissions, radiated (<1G) 9KHz-30MHz	$\pm 3.1\text{ dB}$
6	All emissions, radiated (<1G) 30MHz-1000MHz	$\pm 3.2\text{ dB}$
7	All emissions, radiated 1GHz -18GHz	$\pm 3.66\text{ dB}$
8	All emissions, radiated 18GHz -40GHz	$\pm 4.31\text{ dB}$
9	Occupied bandwidth	4(%)
10	PSD	$\pm 1.73\text{dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	car dash camera
Trade Name	N/A
Model Name	E49+E7
Series Model	E49+E7, E89+E7, E80+E7, E45+E7, E46+E7, E47+E7, E73+E7, E77+E7, E12+E7, E200+E7, E90+E7, E93+E7, E61+E7, E36+E7, E30+E7, E50+E7, E100+E7, E101+E7, E102+E7, E81+E7, E85+E7, E86+E7, E62+E7, E63+E7, E75+E7, E78+E7, E37+E7, E300+E7, E301+E7
Model Difference	The above product with same circuit, PCB layout, electrical parts, materials and wiring structures, Appearance shape, the materials of decorative accessories is same, the only difference is the model name and colour.
Channel List	Please refer to the Note 3.
Operation frequency	IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz
Modulation:	IEEE 802.11b: DSSS (CCK, QPSK, BPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter rate:	IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 150 Mbps
Power Supply	Input voltage:DC 12-24V Output voltage: DC 5V 2.5A
Battery	N/A
Report number	FCS202604293W01
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Cannot support MIMO modes

3.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		


4. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	2.5	WIFI Antenna

2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Block diagram of EUT configuration for test



Test software: the FCC tool

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	8	1	LCH: CH1	2412
	8	1	MCH: CH6	2437
	8	1	HCH: CH11	2462
IEEE 802.11g	20	6	LCH: CH1	2412
	20	6	MCH: CH6	2437
	20	6	HCH: CH11	2462
IEEE 802.11n HT20	20	MCS 8	LCH: CH1	2412
	20	MCS 8	MCH: CH6	2437
	20	MCS 8	HCH: CH11	2462

Note:

- (1) According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test,
- (2) The test voltage was tuned from 85% to 115% of the Nominal rate supply votage, and found that the worst case was the nominal rated supply condition, So the report just shows that condition's data

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
1	Adapter	Xiaomi	AD652G	N/A	this adapter is for testing only in repor

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2025.08.25	2026.08.24
Signal Analyzer	R&S	FSV40-N	FCS-E012	2025.08.25	2026.08.24
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2025.08.25	2026.08.24
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2025.08.25	2026.08.24
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2025.08.25	2026.08.24
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2025.08.25	2026.08.24
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2025.08.25	2026.08.24
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2025.08.25	2026.08.24
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2025.08.25	2026.08.24
Temperature & Humidity	HTC-1	victor	FCS-E005	2025.09.01	2026.08.31
Testing Software	EZ-EMC(Ver.STSLAB 03A1 RE)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2025.08.25	2026.08.24
LISN	R&S	ENV216	FCS-E007	2025.08.25	2026.08.24
LISN	ETS	3810/2NM	FCS-E009	2025.08.25	2026.08.24
Temperature & Humidity	HTC-1	victor	FCS-E008	2025.09.01	2026.08.31
Testing Software	EZ-EMC(Ver.EMC-CON 3A1.1)				

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
MXA SIGNAL Analyzer	Keysight	N9020A	FCS-E015	2025.08.25	2026.08.24
Spectrum Analyzer	Agilent	E4447A	MY50180039	2025.08.25	2026.08.24
Spectrum Analyzer	R&S	FSV-40	101499	2025.08.25	2026.08.24
Power Sensor	Agilent	UX2021XA	FCS-E021	2025.08.25	2026.08.24
Testing Software	LzRf V1.0				

3. 6DB BANDWIDTH

3.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz

3.2 Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows

RBW: 1% to 5% of the OBW but not less than 100 kHz.

VBW: Set the VBW $\geq [3 \times \text{RBW}]$.


Detector Mode: Peak

Sweep time: auto

Trace mode Max hold

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

3.3 Test setup



3.4 Test results

TestMode	Channel (MHz)	6dB Bandwidth (MHz)	Limit [MHz]	Verdict
802.11b	2412	9.72	0.5	Pass
802.11b	2437	9.72	0.5	Pass
802.11b	2462	10.11	0.5	Pass
802.11g	2412	16.53	0.5	Pass
802.11g	2437	16.56	0.5	Pass
802.11g	2462	16.65	0.5	Pass
802.11n 20	2412	17.55	0.5	Pass
802.11n 20	2437	17.58	0.5	Pass
802.11n 20	2462	17.61	0.5	Pass

3.5 Original Test Data

802.11b-CH2412MHZ




802.11b-CH2437MHZ




802.11b-CH2462MHZ




802.11g H2412MHZ



802.11g CH2437MHZ




802.11g CH2462MHZ




802.11n 20-2412MHz



802.11n 20-2437MHz



802.11n 20-2462MHz



4. CONDUCTED OUTPUT POWER


4.1 limit

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 test procedure

- Connect each EUT's antenna output to power sensor by RF cable
- Measure the PK output power of each antenna port by power sensor. The testing follows the558074 D01 15.247 Meas Guidance v05r02

4.3 TEST SETUP



4.5 test results

TestMode	Channel (MHz)	Result (dBm)	Limit (dBm)	Verdict
802.11b	2412	3.35	30	Pass
802.11b	2437	3.26	30	Pass
802.11b	2462	3.35	30	Pass
802.11g	2412	3.34	30	Pass
802.11g	2437	3.14	30	Pass
802.11g	2462	3.35	30	Pass
802.11n 20	2412	3.18	30	Pass
802.11n 20	2437	3.19	30	Pass
802.11n 20	2462	3.17	30	Pass

5. POWER SPECTRAL DENSITY

5.1 LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.


(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 TEST SETUP



5.4 TEST RESULTS

TestMode	Channel (MHz)	Result (dBm/3KHz)	Limit (dBm/3KHz)	Verdict
802.11b	2412	-25.650	8	Pass
802.11b	2437	-27.614	8	Pass
802.11b	2462	-27.664	8	Pass
802.11g	2412	-31.086	8	Pass
802.11g	2437	-30.854	8	Pass
802.11g	2462	-31.040	8	Pass
802.11n 20	2412	-30.299	8	Pass
802.11n 20	2437	-29.563	8	Pass
802.11n 20	2462	-29.661	8	Pass

5.5 original test data

802.11b-2412MHz




802.11b-2437MHz




802.11b-2462MHz




802.11g-2412MHz




802.11g-2437MHz




802.11g-2462MHz




802.11n 20-2412MHz



802.11n 20-2437MHz



802.11n 20-2462MHz



6. Band edge and spurious(conducted)

6.1 LIMIT

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

6.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Establish Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

6.3 TEST SETUP




6.4 TEST RESULTS


Eut set mode	CH or Frequency	Result
802.11b	CH1	Pass
	CH6	Pass
	CH11	Pass
802.11g	CH1	Pass
	CH6	Pass
	CH11	Pass
802.11n 20	CH1	Pass
	CH6	Pass
	CH11	Pass

6.5 ORIGINAL TEST DATA


802.11b Low CH 1




802.11b Middle CH 6




802.11b High CH 11




802.11g low CH 1




802.11g Middle CH 6




802.11g high CH 11




802.11n20 Low CH 1



802.11n20 Middle CH 6




802.11n20 High CH 11




Spurious emissions (802.11b)


802.11b low CH, 2412MHZ
30MHz-25GHZ



802.11b Middle CH, 2437MHZ
30MHz-25GHZ




802.11b High CH, 2462MHz 30MHz-25GHZ




(802.11g)


802.11g Low CH, 2412MHz 30MHz-10GHZ




802.11g Middle CH, 2437MHz 30MHz-25GHZ




802.11g High CH, 2462MHz 30MHz-25GHZ




802.11n 20 Low CH, 2412MHz 30MHz-25GHZ



802.11n 20 Middle CH, 2437MHz 30MHz-25GHZ



802.11n 20 High CH, 2462MHz
30MHz-25GHZ



7. RADIATED EMISSION MEASUREMENT

7.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020+Cor. 1-2023 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2403 MHz Upper Band Edge: 2479 to 2500 MHz
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz / 10 Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

7.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

7.3 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.4. TEST RESULTS

(9KHz-30MHz)

Temperature:	24.7°C	Relative Humidity:	61%
Test Voltage:	DC 24V	Test Mode:	802.11n

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


(30MHz-1000MHz)

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	DC 24V	Phase:	Horizontal
Test Mode:	802.11b(worst)		

Radiated Emission Measurement

File :145

Data :#1



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.2925	30.23	-12.30	17.93	40.00	-22.07	peak
2	71.8320	48.53	-15.27	33.26	40.00	-6.74	peak
3	135.9822	31.59	-12.55	19.04	43.50	-24.46	peak
4	249.4250	36.06	-13.14	22.92	46.00	-23.08	peak
5	477.1694	27.93	-7.28	20.65	46.00	-25.35	peak
6	938.8326	27.79	0.25	28.04	46.00	-17.96	peak

Note: 1. Margin = Result (Result =Reading + Factor)-Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.


3. Test setup: RBW: 100 kHz, VBW: 300 kHz, Sweep time: auto.

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	DC 24V	Phase:	Vertical
Test Mode:	802.11b(worst)		

Radiated Emission Measurement

File :145

Data :#2



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.9546	43.38	-12.30	31.08	40.00	-8.92	peak
2	74.9191	53.49	-15.99	37.50	40.00	-2.50	peak
3	135.9822	36.22	-12.55	23.67	43.50	-19.83	peak
4	350.4768	28.55	-10.39	18.16	46.00	-27.84	peak
5	636.1340	27.03	-4.16	22.87	46.00	-23.13	peak
6	996.4996	26.72	0.75	27.47	54.00	-26.53	peak

Note: 1. Margin = Result (Result =Reading + Factor)-Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 100 kHz, VBW: 300 kHz, Sweep time: auto.

(1GHz~25GHz) Restricted band and Spurious emission Requirements

802.11b(Worst)-Low
Peak value

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	35.95	31.78	8.6	32.09	44.24	74	-29.76	Vertical
7236	33.94	36.15	11.65	32	49.74	74	-24.26	Vertical
9648	34.82	37.95	14.14	31.62	55.29	74	-18.71	Vertical
12060	*					74		Vertical
14472	*					74		Vertical
16884	*					74		Vertical
4824	38.55	31.78	8.6	32.09	46.84	74	-27.16	Horizontal
7236	33.74	36.15	11.65	32	49.54	74	-24.46	Horizontal
9648	32.87	37.95	14.14	31.62	53.34	74	-20.66	Horizontal
12060	*					74		Horizontal
14472	*					74		Horizontal
16884	*					74		Horizontal

Average value

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.65	31.78	8.6	32.09	36.94	54	-17.06	Vertical
7236.00	20.79	36.15	11.65	32	36.59	54	-17.41	Vertical
9648.00	19.53	37.95	14.14	31.62	40	54	-14	Vertical
12060.00	*					54		Vertical
14472.00	*					54		Vertical
16884.00	*					54		Vertical
4824.00	32.67	31.78	8.6	32.09	40.96	54	-13.04	Horizontal
7236.00	22.61	36.15	11.65	32	38.41	54	-15.59	Horizontal
9648.00	19.72	37.95	14.14	31.62	40.19	54	-13.81	Horizontal
12060.00	*					54		Horizontal
14472.00	*					54		Horizontal
16884.00	*					54		Horizontal

802.11b(Worst)-Middle
Peak value

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	37.43	31.85	8.67	32.12	45.83	74	-28.17	Vertical
7311.00	31.64	36.37	11.72	31.89	47.84	74	-26.16	Vertical
9748.00	31.71	38.35	14.25	31.62	52.69	74	-21.31	Vertical
12185.00	*					74		Vertical
14622.00	*					74		Vertical
17059.00	*					74		Vertical
4874.00	41.85	31.85	8.67	32.12	50.25	74	-23.75	Horizontal
7311.00	33.54	36.37	11.72	31.89	49.74	74	-24.26	Horizontal
9748.00	33.62	38.35	14.25	31.62	54.6	74	-19.4	Horizontal
12185.00	*					74		Horizontal
14622.00	*					74		Horizontal
17059.00	*					74		Horizontal

Average value

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	26.71	31.85	8.67	32.12	35.11	54	-18.89	Vertical
7311.00	21.64	36.37	11.72	31.89	37.84	54	-16.16	Vertical
9748.00	17.73	38.35	14.25	31.62	38.71	54	-15.29	Vertical
12185.00	*					54		Vertical
14622.00	*					54		Vertical
17059.00	*					54		Vertical
4874.00	29	31.85	8.67	32.12	37.4	54	-16.6	Horizontal
7311.00	22.47	36.37	11.72	31.89	38.67	54	-15.33	Horizontal
9748.00	21.59	38.35	14.25	31.62	42.57	54	-11.43	Horizontal
12185.00	*					54		Horizontal
14622.00	*					54		Horizontal
17059.00	*					54		Horizontal

802.11b(Worst)-High
Peak value

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	34.67	31.93	8.73	32.16	43.17	74	-30.83	Vertical
7386.00	33.49	36.59	11.79	31.78	50.09	74	-23.91	Vertical
9848.00	33.88	38.81	14.38	31.88	55.19	74	-18.81	Vertical
12310.00	*					74		Vertical
14772.00	*					74		Vertical
17234.00	*					74		Vertical
4924.00	39.24	31.93	8.73	32.16	47.74	74	-26.26	Horizontal
7386.00	35.03	36.59	11.79	31.78	51.63	74	-22.37	Horizontal
9848.00	32.61	38.81	14.38	31.88	53.92	74	-20.08	Horizontal
12310.00	*					74		Horizontal
14772.00	*					74		Horizontal
17234.00	*					74		Horizontal

Average value

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	24.74	31.93	8.73	32.16	33.24	54	-20.76	Vertical
7386.00	18.85	36.59	11.79	31.78	35.45	54	-18.55	Vertical
9848.00	17.97	38.81	14.38	31.88	39.28	54	-14.72	Vertical
12310.00	*					54		Vertical
14772.00	*					54		Vertical
17234.00	*					54		Vertical
4924.00	33.19	31.93	8.73	32.16	41.69	54	-12.31	Horizontal
7386.00	23.13	36.59	11.79	31.78	39.73	54	-14.27	Horizontal
9848.00	20.35	38.81	14.38	31.88	41.66	54	-12.34	Horizontal
12310.00	*					54		Horizontal
14772.00	*					54		Horizontal
17234.00	*					54		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss- Preamplifier Factor
2. The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
3. "**", means this data is the too weak instrument of signal is unable to test.

Radiated Band Edge data

802.11 b low CH

Peak value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390	50.25	27.59	5.38	30.18	53.04	74	-20.96	Horizontal
2400	53.73	27.58	5.39	30.18	56.52	74	-17.48	Horizontal
2390	49.13	27.59	5.38	30.18	51.92	74	-22.08	Vertical
2400	54.58	27.58	5.39	30.18	57.37	74	-16.63	Vertical
Average value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390	39.27	27.59	5.38	30.18	42.06	54	-11.94	Horizontal
2400	42.86	27.58	5.39	30.18	47.97	54	-6.03	Horizontal
2390	37.48	27.59	5.38	30.18	40.27	54	-13.73	Vertical
2400	42.04	27.58	5.39	30.18	44.83	54	-9.17	Vertical

802.11 b High CH

Peak value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.5	49.59	27.53	5.47	29.93	52.66	74	-21.34	Horizontal
2500	47.23	27.55	5.49	29.93	50.34	74	-23.66	Horizontal
2483.5	49.04	27.53	5.47	29.93	52.11	74	-21.89	Vertical
2500	45.41	27.55	5.49	29.93	48.52	74	-25.48	Vertical
Average value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.5	39.13	27.53	5.47	29.93	42.2	54	-11.8	Horizontal
2500	35.8	27.55	5.49	29.93	38.91	54	-15.09	Horizontal
2483.5	36.65	27.53	5.47	29.93	39.72	54	-14.28	Vertical
2500	33.8	27.55	5.49	29.93	36.91	54	-17.09	Vertical

802.11 g Low CH

Peak value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390	63.3	27.59	5.38	30.18	66.09	74	-7.91	Horizontal
2400	63.58	27.58	5.39	30.18	66.37	74	-7.63	Horizontal
2390	59.47	27.59	5.38	30.18	62.26	74	-11.74	Vertical
2400	61.69	27.58	5.39	30.18	64.48	74	-9.52	Vertical
Average value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390	45.6	27.59	5.38	30.18	48.39	54	-5.61	Horizontal
2400	42.86	27.58	5.39	30.18	44.38	54	-9.62	Horizontal
2390	43.14	27.59	5.38	30.18	45.93	54	-8.07	Vertical
2400	41.69	27.58	5.39	30.18	44.48	54	-9.52	Vertical

802.11 g High CH

Peak value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.5	55.18	27.53	5.47	29.93	58.25	74	-15.75	Horizontal
2500	48.43	27.55	5.49	29.93	51.54	74	-22.46	Horizontal
2483.5	50.27	27.53	5.47	29.93	53.34	74	-20.66	Vertical
2500	46.72	27.55	5.49	29.93	49.83	74	-24.17	Vertical
Average value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.5	38.06	27.53	5.47	29.93	41.13	54	-12.87	Horizontal
2500	36.16	27.55	5.49	29.93	39.27	54	-14.73	Horizontal
2483.5	36.61	27.53	5.47	29.93	39.68	54	-14.32	Vertical
2500	34.47	27.55	5.49	29.93	37.58	54	-16.42	Vertical

802.11 N 20 Low CH

Peak value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390	63.34	27.59	5.38	30.18	66.13	74	-7.87	Horizontal
2400	63.87	27.58	5.39	30.18	66.66	74	-7.34	Horizontal
2390	59.25	27.59	5.38	30.18	62.04	74	-11.96	Vertical
2400	61.67	27.58	5.39	30.18	64.46	74	-9.54	Vertical
Average value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390	41.35	27.59	5.38	30.18	44.14	54	-9.86	Horizontal
2400	42.86	27.58	5.39	30.18	49.32	54	-4.68	Horizontal
2390	43.89	27.59	5.38	30.18	46.68	54	-7.32	Vertical
2400	41.69	27.58	5.39	30.18	44.48	54	-9.52	Vertical

802.11 N 20 High CH

Peak value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.5	54.09	27.53	5.47	29.93	57.16	74	-16.84	Horizontal
2500	48.51	27.55	5.49	29.93	51.62	74	-22.38	Horizontal
2483.5	50.24	27.53	5.47	29.93	53.31	74	-20.69	Vertical
2500	46.62	27.55	5.49	29.93	49.73	74	-24.27	Vertical
Average value								
Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.5	38.04	27.53	5.47	29.93	41.11	54	-12.89	Horizontal
2500	36.2	27.55	5.49	29.93	39.31	54	-14.69	Horizontal
2483.5	36.87	27.53	5.47	29.93	39.94	54	-14.06	Vertical
2500	34.49	27.55	5.49	29.93	37.6	54	-16.4	Vertical

Remark.

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
- 2.The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.

8. CONDUCTED EMISSION MEASUREMENT

8.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


8.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

8.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

8.4 TEST RESULTS

Temperature:	--°C	Relative Humidity:	--%
Phase:	L/N	Test Mode:	N/A
Test Voltage:	N/A		

Note: Not applicable

9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.2 RESULT

The antennas used for this product are PCB antenna antenna and other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.5dBi.

*****END OF THE REPORT*****