

FCC RADIO TEST REPORT

FCC ID: 2BVW2L3BXX

Product: IONNYK LINN

Trade Mark: IONNYK

Model No.: L3BXX

Family Model: N/A

Report No.: N25102800737E

Issue Date: Mar. 20, 2026

Prepared for

INKcoming SA

92 Avenue Reine Astrid, 1310 La Hulpe, BELGIUM

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : INKcoming SA
Address : 92 Avenue Reine Astrid, 1310 La Hulpe, BELGIUM
Manufacturer's Name : INKcoming SA
Address : 92 Avenue Reine Astrid, 1310 La Hulpe, BELGIUM

Product description

Product name : IONNYK LINN
Trademark : IONNYK
Model and/or type reference : L3BXX
Family Model : N/A
Test Sample Number : S2510280099-1#

Standards : FCC Part15.407

Test procedure ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to
C63.10a-2024
KDB 789033 D02 General UNII Test Procedures New Rules v02r01
KDB 905462 D03 Client Without DFS New Rules v01r02
KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Oct. 28, 2025 ~ Mar. 20, 2026

Date of Issue Mar. 20, 2026

Test Result **Pass**

Prepared By : Allen Liu
Allen Liu
(Project Engineer)

Reviewed By : Aaron Cheng
Aaron Cheng
(Supervisor)

Approved By : Alex Li
Alex Li
(Manager)

Table of Contents

	Page
1. SUMMARY OF TEST RESULTS	7
1.1 FACILITIES AND ACCREDITATIONS	8
1.2 MEASUREMENT UNCERTAINTY	8
2. GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	13
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	14
3. EMC EMISSION TEST	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.1.1 APPLICABLE STANDARD	16
3.1.2 CONFORMANCE LIMIT	16
3.1.3 TEST CONFIGURATION	16
3.1.4 TEST PROCEDURE	17
3.2 RADIATED EMISSION MEASUREMENT	24
3.2.1 APPLICABLE STANDARD	24
3.2.2 CONFORMANCE LIMIT	24
3.2.3 MEASURING INSTRUMENTS	24
3.2.4 TEST CONFIGURATION	25
3.2.5 TEST PROCEDURE	26
3.2.6 TEST RESULTS (9KHZ – 30 MHZ)	27
3.2.7 TEST RESULTS (30MHZ – 1GHZ)	28
4 POWER SPECTRAL DENSITY TEST	68
4.1 APPLIED PROCEDURES / LIMIT	68
4.2 TEST PROCEDURE	69
4.3 DEVIATION FROM STANDARD	69
4.4 TEST SETUP	69
4.5 EUT OPERATION CONDITIONS	69
4.6 TEST RESULTS	70
5. 26DB & 99% EMISSION BANDWIDTH	71
5.1 APPLIED PROCEDURES / LIMIT	71
5.2 TEST PROCEDURE	71
5.3 EUT OPERATION CONDITIONS	72
5.4 TEST RESULTS	72
6. MINIMUM 6 DB BANDWIDTH	73

Table of Contents

	Page
6.1 APPLIED PROCEDURES / LIMIT	73
6.2 EST PROCEDURE	73
6.3 DEVIATION FROM STANDARD	73
6.4 TEST SETUP	73
6.5 EUT OPERATION CONDITIONS	73
6.6 TEST RESULTS	74
7. MAXIMUM CONDUCTED OUTPUT POWER	75
7.1 PPLIED PROCEDURES / LIMIT	75
7.6 TEST RESULTS	77
8. OUT OF BAND EMISSIONS	78
8.1 APPLICABLE STANDARD	78
8.2 TEST PROCEDURE	78
8.3 DEVIATION FROM STANDARD	78
8.4 TEST SETUP	78
8.5 EUT OPERATION CONDITIONS	79
8.6 TEST RESULTS	80
9. FREQUENCY STABILITY MEASUREMENT	81
9.1 LIMIT	81
9.2 TEST PROCEDURES	81
9.3 TEST SETUP LAYOUT	81
9.4 EUT OPERATION DURING TEST	81
9.5 TEST RESULTS	82
10. DYNAMIC FREQUENCY SELECTION(DFS)	91
10.1 APPLICABILITY OF DFS REQUIREMENTS	91
10.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE NOTEBOOKING	91
10.3 DFS RESPONSE REQUIREMENT VALUES	92
10.4 SHORT PULSE RADAR TEST WAVEFORMS	92
10.5 CALIBRATION SETUP AND DFS TEST RESULTS	93
10.6 CONDUCTED CALIBRATION SETUP	93
10.7 RADAR WAVEFORM CALIBRATION RESULT	93
10.8 IN-SERVICE NOTEBOOKING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD	94
10.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST	95

Table of Contents

	Page
11. ANTENNA REQUIREMENT	96
11.1 STANDARD REQUIREMENT	96
11.2 EUT ANTENNA	96

Revision History

Report No.	Version	Description	Issued Date
N25102800737E	Rev.01	Initial issue of report	Mar. 20, 2026

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4) 15.407(b)(8)(9)	Spurious Radiated Emissions	PASS	
15.407 (a)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)	Maximum Conducted Output Power	PASS	
15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4)	Band Edge	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.407(g)	Frequency Stability Measurement	PASS	
15.407(h)	Dynamic Frequency Selection(DFS)	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	(Note 3)

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) This device operates with a duty cycle greater than 99%
- (3) The product is a client device, and the data transmission is limited by the AP.
When the information to be sent is missing or the operation fails,
the device will automatically stop sending and directly connect to the AP correctly again.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong,
People's Republic of China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and
CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District,
Shenzhen, Guangdong, People's Republic of China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a
standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of
approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test(9-150kHz)	3.7dB
2	Conducted Emission Test(0.15-30MHz)	3.3dB
3	RF power, conducted	1.34dB
4	Power Spectral Density, conducted	0.91dB
5	Occupied bandwidth	1.00%
6	Spurious emissions, conducted	2.71dB
7	Radio Frequency	0.21ppm
8	All emissions, radiated(9kHz~30MHz)	5.26dB
9	All emissions, radiated(30MHz~1G)	4.90dB
10	All emissions, radiated(1G~18G)	5.10dB
11	All emissions, radiated(18G~40G)	5.76dB
12	Time	5%
13	Temperature	1°C
14	Humidity	5%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	IONNYK LINN	
Trade Mark	IONNYK	
Model Name	L3BXX	
Family Model	N/A	
Model Difference	N/A	
FCC ID	2BVW2L3BXX	
Product Description	Mode Supported	☒ 802.11a
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM
	Operating Frequency Range	☒ U-NII-1: 5150 MHz ~5250MHz ☒ U-NII-2: 5500MHz~5700MHz ☒ U-NII-3: 5725 MHz ~5850 MHz
	Function:	☐ Outdoor AP ☐ Indoor AP ☐ Fixed P2P ☒ Client
	DFS type:	☐ master devices ☐ Slave devices with radar detection ☒ Slave devices without radar detection
	Support TPC	☐ YES ☒ NO
	Antenna Type	Chip Antenna
	Antenna Gain	☒ 5.2G/5.6G WIFI: 2.6dBi ☒ 5.8G WIFI: 2.6dBi
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.	
Adapter	Model: BZT-0502000 Input: 100-240VAC~50/60Hz 0.3A Output: 5.0V $\overline{\text{---}}$ 2A	
Battery	DC 3.8V, 12400mAh, 47.12Wh	
Rating	DC 3.8V from battery or DC 5V from adapter	
Connecting I/O Port(s)	Please refer to the User's Manual	
HW Version	3.1.2	
FW version:	3.7.2	

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- Frequency and Channel list:

Band	20MHz	
	Channel	Frequency
U-NII-1	36	5180 MHz
	40	5200 MHz
	44	5220 MHz
	48	5240 MHz
U-NII-2C	100	5500 MHz
	104	5520 MHz
	108	5540 MHz
	112	5560 MHz
	116	5580 MHz
	120	5600 MHz
	124	5620 MHz
	128	5640 MHz
	132	5660 MHz
	136	5680 MHz
U-NII-3	140	5700 MHz
	149	5745 MHz
	153	5765 MHz
	157	5785 MHz
	161	5805 MHz
	165	5825 MHz

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a CH36/ CH40/ CH48/CH100/CH120/CH140/CH149/ CH157/CH165

For Conducted Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a CH36/ CH40/ CH48/ CH100/CH120/CH140/CH149/ CH157/CH165

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	IONNYK LINN	L3BXX	N/A	EUT
AE-2	Adapter	BZT-0502000	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	YES	NO	1.2m
C-2	RF Cable	YES	NO	0.1m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2025.04.24	2026.04.23	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025.04.17	2026.04.16	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2025.04.17	2026.04.16	1 year
4	Test Receiver	R&S	ESPI7	101318	2025.04.17	2026.04.16	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2025.04.17	2026.04.16	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2025.04.17	2026.04.16	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2025.04.17	2026.04.16	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2023.05.06	2026.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A
17	MICRO-TRONIC FILTER	Mini-Circuits	BRM50716	G224	2024.04.26	2027.04.25	3 year
18	High and Low Temperature Box	WEISS	WT 20/40 EMC Simpac	58226119460030	2025.07.02	2028.07.01	3 year

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2025.04.17	2026.04.16	1 year
2	LISN	R&S	ENV216	101313	2025.04.16	2026.04.15	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2025.04.16	2026.04.15	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	23.3℃	Relative Humidity :	50%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	38.60	19.59	58.19	65.57	-7.38	QP
0.1580	22.37	19.59	41.96	55.57	-13.61	AVG
0.3140	30.27	19.54	49.81	59.86	-10.05	QP
0.3140	17.17	19.54	36.71	49.86	-13.15	AVG
0.4740	29.58	19.56	49.14	56.44	-7.30	QP
0.4740	14.32	19.56	33.88	46.44	-12.56	AVG
0.5700	31.15	19.57	50.72	56.00	-5.28	QP
0.5700	18.85	19.57	38.42	46.00	-7.58	AVG
0.6780	31.52	19.58	51.10	56.00	-4.90	QP
0.6780	17.54	19.58	37.12	46.00	-8.88	AVG
10.8220	42.79	10.09	52.88	60.00	-7.12	QP
10.8220	28.20	10.09	38.29	50.00	-11.71	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	23.3℃	Relative Humidity :	50%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	41.79	19.53	61.32	65.57	-4.25	QP
0.1580	23.54	19.53	43.07	55.57	-12.50	AVG
0.2140	36.46	19.53	55.99	63.05	-7.06	QP
0.2140	20.07	19.53	39.60	53.05	-13.45	AVG
0.3180	32.88	19.54	52.42	59.76	-7.34	QP
0.3180	17.32	19.54	36.86	49.76	-12.90	AVG
0.5820	32.03	19.58	51.61	56.00	-4.39	QP
0.5820	15.29	19.58	34.87	46.00	-11.13	AVG
1.1019	29.42	19.63	49.05	56.00	-6.95	QP
1.1019	12.28	19.63	31.91	46.00	-14.09	AVG
10.5740	34.36	20.01	54.37	60.00	-5.63	QP
10.5740	18.57	20.01	38.58	50.00	-11.42	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	23.3℃	Relative Humidity :	50%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2020	35.04	19.53	54.57	63.53	-8.96	QP
0.2020	24.14	19.53	43.67	53.53	-9.86	AVG
0.3020	32.96	19.54	52.50	60.19	-7.69	QP
0.3020	21.70	19.54	41.24	50.19	-8.95	AVG
0.5940	33.50	19.57	53.07	56.00	-2.93	QP
0.5940	20.06	19.57	39.63	46.00	-6.37	AVG
0.6540	33.70	19.58	53.28	56.00	-2.72	QP
0.6540	20.66	19.58	40.24	46.00	-5.76	AVG
1.0540	31.92	19.59	51.51	56.00	-4.49	QP
1.0540	18.93	19.59	38.52	46.00	-7.48	AVG
10.9420	42.90	10.02	52.92	60.00	-7.08	QP
10.9420	26.24	10.02	36.26	50.00	-13.74	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	23.3℃	Relative Humidity :	50%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3020	34.09	19.54	53.63	60.19	-6.56	QP
0.3020	17.16	19.54	36.70	50.19	-13.49	AVG
0.5860	34.98	19.59	54.57	56.00	-1.43	QP
0.5860	16.39	19.59	35.98	46.00	-10.02	AVG
0.6540	36.36	19.61	55.97	56.00	-0.03	QP
0.6540	16.78	19.61	36.39	46.00	-9.61	AVG
1.1220	31.58	19.63	51.21	56.00	-4.79	QP
1.1220	10.25	19.63	29.88	46.00	-16.12	AVG
1.4819	32.98	19.65	52.63	56.00	-3.37	QP
1.4819	12.13	19.65	31.78	46.00	-14.22	AVG
10.9620	46.29	9.28	55.57	60.00	-4.43	QP
10.9620	27.14	9.28	36.42	50.00	-13.58	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	23.3℃	Relative Humidity :	50%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	38.60	19.59	58.19	65.57	-7.38	QP
0.1580	22.37	19.59	41.96	55.57	-13.61	AVG
0.3140	29.27	19.54	48.81	59.86	-11.05	QP
0.3140	16.17	19.54	35.71	49.86	-14.15	AVG
0.4740	30.08	19.56	49.64	56.44	-6.80	QP
0.4740	14.82	19.56	34.38	46.44	-12.06	AVG
0.5780	32.99	19.57	52.56	56.00	-3.44	QP
0.5780	20.35	19.57	39.92	46.00	-6.08	AVG
0.6780	33.02	19.58	52.60	56.00	-3.40	QP
0.6780	19.04	19.58	38.62	46.00	-7.38	AVG
10.8220	42.79	10.09	52.88	60.00	-7.12	QP
10.8220	28.20	10.09	38.29	50.00	-11.71	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	23.3℃	Relative Humidity :	50%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	40.79	19.53	60.32	65.57	-5.25	QP
0.1580	22.54	19.53	42.07	55.57	-13.50	AVG
0.3180	32.38	19.54	51.92	59.76	-7.84	QP
0.3180	18.12	19.54	37.66	49.76	-12.10	AVG
0.5820	34.53	19.58	54.11	56.00	-1.89	QP
0.5820	17.79	19.58	37.37	46.00	-8.63	AVG
0.6660	29.73	19.61	49.34	56.00	-6.66	QP
0.6660	14.75	19.61	34.36	46.00	-11.64	AVG
0.7900	28.85	19.63	48.48	56.00	-7.52	QP
0.7900	12.90	19.63	32.53	46.00	-13.47	AVG
11.2660	44.39	9.16	53.55	60.00	-6.45	QP
11.2660	29.42	9.16	38.58	50.00	-11.42	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407 and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407: radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHZ – 30 MHZ)

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	26 °C	Relative Humidity :	54%
Pressure:	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHZ – 1GHZ)

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25.1℃	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX(5.2G WIFI)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.3992	16.15	16.98	33.13	40.00	-6.87	QP
V	44.5867	8.79	19.58	28.37	40.00	-11.63	QP
V	84.1100	22.44	14.62	37.06	40.00	-2.94	QP
V	131.7573	17.76	14.87	32.63	43.50	-10.87	QP
V	143.8291	19.20	14.78	33.98	43.50	-9.52	QP
V	216.0240	14.01	18.29	32.30	46.00	-13.70	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBUV)	(dB)	(dBUV/m)	(dBUV/m)	(dB)	
H	52.9453	6.91	19.72	26.63	40.00	-13.37	QP
H	84.1100	13.69	14.62	28.31	40.00	-11.69	QP
H	119.8555	13.47	16.26	29.73	43.50	-13.77	QP
H	143.8291	17.54	14.78	32.32	43.50	-11.18	QP
H	204.2375	17.18	18.08	35.26	43.50	-8.24	QP
H	821.7103	8.30	29.38	37.68	46.00	-8.32	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit




Note (1) All modes have been tested, just the worst mode has been recorded in the report.
 (2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25.1℃	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX(5.6G WIFI)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	30.0000	13.24	17.09	30.33	40.00	-9.67	QP
V	60.0690	10.55	19.13	29.68	40.00	-10.32	QP
V	83.8155	21.98	14.52	36.50	40.00	-3.50	QP
V	143.8293	19.87	14.78	34.65	43.50	-8.85	QP
V	158.1123	19.34	14.84	34.18	43.50	-9.32	QP
V	191.7450	16.02	16.99	33.01	43.50	-10.49	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBUV)	(dB)	(dBUV/m)	(dBUV/m)	(dB)	
H	46.1779	7.27	19.89	27.16	40.00	-12.84	QP
H	83.8155	15.22	14.52	29.74	40.00	-10.26	QP
H	120.2766	15.90	16.20	32.10	43.50	-11.40	QP
H	143.8293	17.44	14.78	32.22	43.50	-11.28	QP
H	191.7450	18.32	16.99	35.31	43.50	-8.19	QP
H	216.0240	15.51	18.29	33.80	46.00	-12.20	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit




Note (1) All modes have been tested, just the worst mode has been recorded in the report.
 (2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25.1℃	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX(5.8G WIFI)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.3992	14.65	16.98	31.63	40.00	-8.37	QP
V	59.4405	7.04	19.04	26.08	40.00	-13.92	QP
V	84.1100	21.44	14.62	36.06	40.00	-3.94	QP
V	120.2766	13.55	16.20	29.75	43.50	-13.75	QP
V	143.8291	18.20	14.78	32.98	43.50	-10.52	QP
V	216.0240	13.01	18.29	31.30	46.00	-14.70	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	52.9453	5.41	19.72	25.13	40.00	-14.87	QP
H	84.1100	12.19	14.62	26.81	40.00	-13.19	QP
H	107.8876	8.68	17.99	26.67	43.50	-16.83	QP
H	119.8555	12.97	16.26	29.23	43.50	-14.27	QP
H	143.8291	17.54	14.78	32.32	43.50	-11.18	QP
H	204.2375	17.18	18.08	35.26	43.50	-8.24	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note (1) All modes have been tested, just the worst mode has been recorded in the report.

(2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	23.2 °C	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX(5.2G) - 802.11a_5180~5240MHz		

5180

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2078.225	55.29	-12.66	42.63	68.20	-25.57	peak
V	3003.025	53.45	-9.48	43.97	68.20	-24.23	peak
V	5179.025	51.18	-6.19	44.99	68.20	-23.21	peak
V	8516.125	48.13	-0.66	47.47	68.20	-20.73	peak
V	14194.125	45.32	5.66	50.98	68.20	-17.22	peak
V	17999.575	42.46	13.61	56.07	74.00	-17.93	peak
V	18000.000	32.22	13.61	45.83	54.00	-8.17	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2085.450	54.85	-12.60	42.25	68.20	-25.95	peak
H	3280.550	53.36	-9.23	44.13	68.20	-24.07	peak
H	7913.900	49.12	-1.52	47.60	68.20	-20.60	peak
H	13456.750	44.94	5.33	50.27	68.20	-17.93	peak
H	16572.850	43.92	6.47	50.39	68.20	-17.81	peak
H	17968.975	41.30	13.47	54.77	74.00	-19.23	peak
H	17968.975	33.69	13.47	47.16	54.00	-6.84	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5200

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2132.200	54.75	-12.67	42.08	68.20	-26.12	peak
V	5479.075	51.30	-5.62	45.68	68.20	-22.52	peak
V	6689.050	50.28	-3.01	47.27	68.20	-20.93	peak
V	8596.875	47.93	-0.49	47.44	68.20	-20.76	peak
V	13454.200	45.71	5.32	51.03	68.20	-17.17	peak
V	17984.700	42.06	13.54	55.60	74.00	-18.40	peak
V	17984.700	33.72	13.54	47.26	54.00	-6.74	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2012.350	54.93	-13.42	41.51	68.20	-26.69	peak
H	3373.200	53.43	-9.50	43.93	68.20	-24.27	peak
H	7955.550	49.13	-1.33	47.80	68.20	-20.40	peak
H	10588.425	46.16	2.70	48.86	68.20	-19.34	peak
H	13969.725	45.64	5.56	51.20	68.20	-17.00	peak
H	17983.425	41.25	13.53	54.78	74.00	-19.22	peak
H	17983.425	33.74	13.53	47.27	54.00	-6.73	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5240

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2098.200	54.52	-12.49	42.03	68.20	-26.17	peak
V	2928.650	53.70	-10.05	43.65	68.20	-24.55	peak
V	4924.875	52.90	-6.73	46.17	74.00	-27.83	peak
V	4955.475	43.90	-6.03	37.87	54.00	-16.13	AVG
V	7923.250	49.16	-1.45	47.71	68.20	-20.49	peak
V	13281.225	45.75	5.13	50.88	74.00	-23.12	peak
V	13379.400	37.92	5.10	43.02	54.00	-10.98	AVG
V	17967.700	41.13	13.45	54.58	74.00	-19.42	peak
V	17967.700	33.79	13.45	47.24	54.00	-6.76	AVG


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2133.900	54.50	-12.68	41.82	68.20	-26.38	peak
H	3428.450	53.75	-9.60	44.15	68.20	-24.05	peak
H	4944.850	44.20	-6.14	38.06	54.00	-15.94	AVG
H	4954.200	51.88	-6.03	45.85	74.00	-28.15	peak
H	10534.875	46.86	2.14	49.00	68.20	-19.20	peak
H	13471.200	45.63	5.40	51.03	68.20	-17.17	peak
H	17977.475	33.85	13.50	47.35	54.00	-6.65	AVG
H	18000.000	38.83	13.61	52.44	74.00	-21.56	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	23.2 °C	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX(5.6G) - 802.11a_5500~5700MHz		

5500

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2089.700	54.83	-12.56	42.27	68.20	-25.93	peak
V	3322.625	53.77	-9.37	44.40	68.20	-23.80	peak
V	4917.225	53.10	-6.97	46.13	74.00	-27.87	peak
V	4946.550	44.32	-6.09	38.23	54.00	-15.77	AVG
V	7895.625	50.28	-1.64	48.64	68.20	-19.56	peak
V	12810.750	45.74	4.16	49.90	68.20	-18.30	peak
V	17955.375	42.84	13.41	56.25	74.00	-17.75	peak
V	17955.375	34.49	13.41	47.90	54.00	-6.10	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2081.625	54.97	-12.62	42.35	68.20	-25.85	peak
H	3311.575	53.46	-9.39	44.07	68.20	-24.13	peak
H	5851.375	51.13	-5.17	45.96	68.20	-22.24	peak
H	10494.500	47.18	1.75	48.93	68.20	-19.27	peak
H	14302.075	44.92	5.80	50.72	68.20	-17.48	peak
H	18000.000	39.89	13.61	53.50	74.00	-20.50	peak
H	18000.000	33.44	13.61	47.05	54.00	-6.95	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5600

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2081.200	54.48	-12.62	41.86	68.20	-26.34	peak
V	4932.525	52.01	-6.51	45.50	74.00	-28.50	peak
V	4952.075	43.68	-6.02	37.66	54.00	-16.34	AVG
V	7831.875	49.43	-1.88	47.55	68.20	-20.65	peak
V	10062.275	46.93	1.78	48.71	68.20	-19.49	peak
V	12772.075	45.27	4.24	49.51	68.20	-18.69	peak
V	17986.400	42.08	13.55	55.63	74.00	-18.37	peak
V	17986.400	33.80	13.55	47.35	54.00	-6.65	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2110.100	54.76	-12.54	42.22	68.20	-25.98	peak
H	3552.975	54.44	-10.04	44.40	68.20	-23.80	peak
H	4945.700	52.07	-6.12	45.95	74.00	-28.05	peak
H	4945.700	44.08	-6.12	37.96	54.00	-16.04	AVG
H	10041.025	47.69	1.56	49.25	68.20	-18.95	peak
H	13514.975	45.15	5.45	50.60	68.20	-17.60	peak
H	17983.850	41.26	13.53	54.79	74.00	-19.21	peak
H	17983.850	34.07	13.53	47.60	54.00	-6.40	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5700

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2075.675	55.29	-12.68	42.61	68.20	-25.59	peak
V	3001.750	52.73	-9.47	43.26	68.20	-24.94	peak
V	4913.400	52.11	-7.08	45.03	74.00	-28.97	peak
V	4913.400	44.92	-7.08	37.84	54.00	-16.16	AVG
V	7821.675	49.61	-1.75	47.86	68.20	-20.34	peak
V	12188.125	37.95	4.53	42.48	54.00	-11.52	AVG
V	12235.725	45.67	4.74	50.41	74.00	-23.59	peak
V	17993.625	33.73	13.58	47.31	54.00	-6.69	AVG
V	18000.000	38.99	13.61	52.60	74.00	-21.40	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2121.150	54.42	-12.60	41.82	68.20	-26.38	peak
H	3310.300	52.89	-9.39	43.50	68.20	-24.70	peak
H	5480.350	51.76	-5.60	46.16	68.20	-22.04	peak
H	7193.100	50.03	-2.14	47.89	68.20	-20.31	peak
H	12157.525	46.00	4.61	50.61	74.00	-23.39	peak
H	12286.300	37.58	5.09	42.67	54.00	-11.33	AVG
H	17985.975	41.83	13.55	55.38	74.00	-18.62	peak
H	17985.975	33.74	13.55	47.29	54.00	-6.71	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	23.2 °C	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX (5.8G) - 802.11a_5745~5825MHz		

5745

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2100.750	54.75	-12.49	42.26	68.20	-25.94	peak
V	3370.225	55.14	-9.49	45.65	68.20	-22.55	peak
V	5490.975	51.04	-5.43	45.61	68.20	-22.59	peak
V	7780.450	48.49	-1.58	46.91	68.20	-21.29	peak
V	12200.450	46.07	4.49	50.56	74.00	-23.44	peak
V	12256.550	38.14	4.89	43.03	54.00	-10.97	AVG
V	17999.575	42.28	13.61	55.89	74.00	-18.11	peak
V	17999.575	34.04	13.61	47.65	54.00	-6.35	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2085.875	55.64	-12.60	43.04	68.20	-25.16	peak
H	3023.425	54.31	-9.54	44.77	68.20	-23.43	peak
H	5485.025	52.06	-5.53	46.53	68.20	-21.67	peak
H	7216.900	49.85	-2.26	47.59	68.20	-20.61	peak
H	11959.475	37.31	5.23	42.54	54.00	-11.46	AVG
H	12031.300	45.75	5.12	50.87	74.00	-23.13	peak
H	17991.925	41.83	13.58	55.41	74.00	-18.59	peak
H	17991.925	34.41	13.58	47.99	54.00	-6.01	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5785

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	2099.050	54.33	-12.49	41.84	68.20	-26.36	peak
V	4937.625	52.58	-6.35	46.23	74.00	-27.77	peak
V	4937.625	44.28	-6.35	37.93	54.00	-16.07	AVG
V	6593.000	50.22	-3.26	46.96	68.20	-21.24	peak
V	10052.925	47.30	1.69	48.99	68.20	-19.21	peak
V	13149.475	45.82	4.65	50.47	68.20	-17.73	peak
V	17970.250	41.67	13.47	55.14	74.00	-18.86	peak
V	17970.250	34.34	13.47	47.81	54.00	-6.19	AVG


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2100.750	54.66	-12.49	42.17	68.20	-26.03	peak
H	3306.050	53.86	-9.41	44.45	68.20	-23.75	peak
H	4881.525	44.69	-7.25	37.44	54.00	-16.56	AVG
H	4894.700	53.44	-7.42	46.02	74.00	-27.98	peak
H	7814.875	49.28	-1.66	47.62	68.20	-20.58	peak
H	12246.350	45.97	4.81	50.78	74.00	-23.22	peak
H	12261.650	38.25	4.92	43.17	54.00	-10.83	AVG
H	17976.200	41.36	13.50	54.86	74.00	-19.14	peak
H	17976.200	34.08	13.50	47.58	54.00	-6.42	AVG


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5825

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1647.700	57.14	-16.76	40.38	68.20	-27.82	peak
V	2828.775	54.51	-10.29	44.22	74.00	-29.78	peak
V	2828.775	45.85	-10.29	35.56	54.00	-18.44	AVG
V	4947.400	52.13	-6.07	46.06	74.00	-27.94	peak
V	4947.400	44.51	-6.07	38.44	54.00	-15.56	AVG
V	7223.275	49.89	-2.38	47.51	68.20	-20.69	peak
V	12153.275	45.72	4.62	50.34	74.00	-23.66	peak
V	12153.275	38.47	4.62	43.09	54.00	-10.91	AVG
V	17984.275	41.57	13.54	55.11	74.00	-18.89	peak
V	17984.275	34.12	13.54	47.66	54.00	-6.34	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	2110.950	55.05	-12.55	42.50	68.20	-25.70	peak
H	3091.425	53.47	-9.56	43.91	68.20	-24.29	peak
H	4894.700	53.59	-7.42	46.17	74.00	-27.83	peak
H	4909.575	45.26	-7.19	38.07	54.00	-15.93	AVG
H	7947.900	48.89	-1.29	47.60	68.20	-20.60	peak
H	12006.225	36.91	5.25	42.16	54.00	-11.84	AVG
H	12022.800	46.48	5.17	51.65	74.00	-22.35	peak
H	17957.075	41.86	13.41	55.27	74.00	-18.73	peak
H	17957.075	34.11	13.41	47.52	54.00	-6.48	AVG


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



3.2.9 TEST RESULTS (18GHZ-40GHZ)

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25.4 °C	Relative Humidity :	47.7%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX (5.2G)-802.11a 5180MHz~5240MHz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	20550.725	49.29	-12.14	37.15	54.00	-16.85	AVG
V	20646.377	61.99	-12.14	49.85	74.00	-24.15	peak
V	34420.290	57.68	-4.38	53.30	68.20	-14.90	peak
V	39585.507	59.40	-3.71	55.69	68.20	-12.51	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5180MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	20359.420	62.04	-12.50	49.54	74.00	-24.46	peak
H	20359.420	50.54	-12.50	38.04	54.00	-15.96	AVG
H	30657.971	59.58	-7.91	51.67	68.20	-16.53	peak
H	39681.159	60.11	-3.67	56.44	68.20	-11.76	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5180MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25.4 °C	Relative Humidity :	47.7%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX (5.6G)-802.11a 5500MHz~5700MHz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	20359.420	62.63	-12.50	50.13	74.00	-23.87	peak
V	20359.420	50.72	-12.50	38.22	54.00	-15.78	AVG
V	30594.203	60.79	-7.94	52.85	68.20	-15.35	peak
V	39904.348	59.60	-3.60	56.00	68.20	-12.20	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5500MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	21315.942	62.78	-12.23	50.55	74.00	-23.45	peak
H	21315.942	49.40	-12.23	37.17	54.00	-16.83	AVG
H	31200.000	59.33	-7.12	52.21	68.20	-15.99	peak
H	39936.232	60.65	-3.60	57.05	68.20	-11.15	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5500MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25.4 °C	Relative Humidity :	47.7%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX (5.8G)-802.11a 5745MHz~5825MHz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
V	20359.420	63.19	-12.50	50.69	74.00	-23.31	peak
V	20359.420	50.84	-12.50	38.34	54.00	-15.66	AVG
V	31136.232	60.39	-7.30	53.09	68.20	-15.11	peak
V	34515.942	58.23	-4.20	54.03	68.20	-14.17	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5745MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	20295.652	50.38	-12.66	37.72	54.00	-16.28	AVG
H	20327.536	63.13	-12.58	50.55	74.00	-23.45	peak
H	31136.232	60.27	-7.30	52.97	68.20	-15.23	peak
H	39904.348	59.39	-3.60	55.79	68.20	-12.41	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5745MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



3.2.10 Radiated Spurious at Band Edges

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	26.4 °C	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX (5.2G)-802.11a 5180MHz~5240MHz, TX (5.6G)-802.11a 5500MHz~5700MHz, TX (5.8G)-802.11a 5745MHz~5825MHz		

5.2G

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	5350.000	52.63	-0.79	51.84	74.00	-22.16	peak
V	5350.000	41.13	-0.79	40.34	54.00	-13.66	AVG


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5350.000	52.51	-0.79	51.72	74.00	-22.28	peak
H	5350.000	41.43	-0.79	40.64	54.00	-13.36	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	5150.000	54.13	0.10	54.23	74.00	-19.77	peak
V	5150.000	43.37	0.10	43.47	54.00	-10.53	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5150.000	57.09	0.10	57.19	74.00	-16.81	peak
H	5150.000	42.78	0.10	42.88	54.00	-11.12	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5.6G

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	5470.000	58.01	0.23	58.24	68.20	-9.96	peak
V	5470.000	44.94	0.23	45.17	68.20	-23.03	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5470.000	63.21	0.23	63.44	68.20	-4.76	peak
H	5470.000	47.88	0.23	48.11	68.20	-20.09	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5.8G

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	5934.200	-53.03	13.27	-39.76	-27.00	-12.76	peak

Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
H	5940.660	-53.21	13.34	-39.87	-27.00	-12.87	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
V	5629.905	-52.99	12.04	-40.95	-27.00	-13.95	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
H	5621.295	-52.99	12.01	-40.98	-27.00	-13.98	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



4 POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

4.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3$ RBW.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHz is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2 (5500-5700MHz), Band 3 (5745-5825MHz)		

Test data reference attachment.

5. 26DB & 99% EMISSION BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

5.2 TEST PROCEDURE

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2 (5500-5700MHz), Band 3 (5745-5825MHz)		

Test data reference attachment.

6. MINIMUM 6 DB BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

6.2 EST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX (5G) Mode Frequency Band 3 (5725-5850MHz)		

Test data reference attachment.

7. MAXIMUM CONDUCTED OUTPUT POWER

7.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5250~5350	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5470~5725	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5725~5850	1W


7.2 TEST PROCEDURE

- Method PM-G is measurement using a gated RF average power meter. Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2 (5500-5700MHz), Band 3 (5745-5825MHz)		

Test data reference attachment.

8. OUT OF BAND EMISSIONS

8.1 APPLICABLE STANDARD

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(10) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.


8.2 TEST PROCEDURE

The testing per ANSI C63.10 Section 12.7.4.2

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

EUT :	IONNYK LINN	Model Name :	L3BXX
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V

Test data reference attachment.

9. Frequency Stability Measurement


9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm
- t6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is -20°C~70°C.

9.3 TEST SETUP LAYOUT



9.4 EUT OPERATION DURING TEST

1. The EUT was programmed to be in continuously un-modulation transmitting mode.

9.5 TEST RESULTS

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5180.0054	5180	0.0054	1.0346
		V max (V)	4.37	5180.0085	5180	0.0085	1.6335
		V min (V)	3.23	5180.0074	5180	0.0074	1.4344
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5180.0071	5180	0.0071	1.3794
		T (°C)	-10	5180.0086	5180	0.0086	1.6646
		T (°C)	0	5180.0055	5180	0.0055	1.0680
		T (°C)	10	5180.0081	5180	0.0081	1.5731
		T (°C)	20	5180.0066	5180	0.0066	1.2652
		T (°C)	30	5180.0050	5180	0.0050	0.9709
		T (°C)	40	5180.0079	5180	0.0079	1.5161
		T (°C)	50	5180.0029	5180	0.0029	0.5596
		T (°C)	60	5180.0007	5180	0.0007	0.1293
		T (°C)	70	5180.0030	5180	0.0030	0.5866
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5200.0060	5200	0.0060	1.1555
		V max (V)	4.37	5200.0054	5200	0.0054	1.0289
		V min (V)	3.23	5200.0041	5200	0.0041	0.7907
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5200.0086	5200	0.0086	1.6626
		T (°C)	-10	5200.0065	5200	0.0065	1.2587
		T (°C)	0	5200.0047	5200	0.0047	0.8971
		T (°C)	10	5200.0009	5200	0.0009	0.1804
		T (°C)	20	5200.0068	5200	0.0068	1.3118
		T (°C)	30	5200.0071	5200	0.0071	1.3706
		T (°C)	40	5200.0027	5200	0.0027	0.5195
		T (°C)	50	5200.0092	5200	0.0092	1.7598
		T (°C)	60	5200.0077	5200	0.0077	1.4815
		T (°C)	70	5200.0046	5200	0.0046	0.8900
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5240.0001	5240	0.0001	0.0134
		V max (V)	4.37	5240.0005	5240	0.0005	0.0920
		V min (V)	3.23	5240.0075	5240	0.0075	1.4355
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5240.0004	5240	0.0004	0.0707
		T (°C)	-10	5240.0064	5240	0.0064	1.2171
		T (°C)	0	5240.0052	5240	0.0052	0.9946
		T (°C)	10	5240.0089	5240	0.0089	1.7016
		T (°C)	20	5240.0032	5240	0.0032	0.6022
		T (°C)	30	5240.0093	5240	0.0093	1.7763
		T (°C)	40	5240.0090	5240	0.0090	1.7110
		T (°C)	50	5240.0073	5240	0.0073	1.3947
		T (°C)	60	5240.0002	5240	0.0002	0.0328
		T (°C)	70	5240.0047	5240	0.0047	0.8984
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Frequency Band 2 (5500-5700MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5500.0048	5500	0.00476	0.8657
		V max (V)	4.37	5500.0088	5500	0.00877	1.5945
		V min (V)	3.23	5500.0053	5500	0.00532	0.9670
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5500.0075	5500	0.00751	1.3663
		T (°C)	-10	5500.0097	5500	0.00973	1.7694
		T (°C)	0	5500.0000	5500	0.00004	0.0074
		T (°C)	10	5500.0010	5500	0.00104	0.1894
		T (°C)	20	5500.0005	5500	0.00047	0.0847
		T (°C)	30	5500.0091	5500	0.00915	1.6635
		T (°C)	40	5500.0026	5500	0.00262	0.4764
		T (°C)	50	5500.0003	5500	0.00034	0.0621
		T (°C)	60	5500.0065	5500	0.00646	1.1752
		T (°C)	70	5500.0058	5500	0.00581	1.0569
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

Page V01 Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5600.0003	5600	0.00028	0.0495
		V max (V)	4.37	5600.0093	5600	0.00929	1.6594
		V min (V)	3.23	5600.0011	5600	0.00113	0.2019
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5600.0009	5600	0.00095	0.1689
		T (°C)	-10	5600.0069	5600	0.00690	1.2321
		T (°C)	0	5600.0003	5600	0.00026	0.0457
		T (°C)	10	5600.0082	5600	0.00816	1.4568
		T (°C)	20	5600.0092	5600	0.00924	1.6491
		T (°C)	30	5600.0074	5600	0.00744	1.3283
		T (°C)	40	5600.0053	5600	0.00527	0.9419
		T (°C)	50	5600.0061	5600	0.00606	1.0820
		T (°C)	60	5600.0092	5600	0.00922	1.6457
		T (°C)	70	5600.0013	5600	0.00129	0.2303
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5700.0090	5700	0.00901	1.5816
		V max (V)	4.37	5700.0071	5700	0.00705	1.2375
		V min (V)	3.23	5700.0065	5700	0.00648	1.1360
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5700.0050	5700	0.00498	0.8729
		T (°C)	-10	5700.0070	5700	0.00704	1.2351
		T (°C)	0	5700.0099	5700	0.00988	1.7338
		T (°C)	10	5700.0098	5700	0.00980	1.7200
		T (°C)	20	5700.0092	5700	0.00922	1.6171
		T (°C)	30	5700.0016	5700	0.00161	0.2828
		T (°C)	40	5700.0071	5700	0.00711	1.2476
		T (°C)	50	5700.0042	5700	0.00423	0.7421
		T (°C)	60	5700.0057	5700	0.00574	1.0063
		T (°C)	70	5700.0069	5700	0.00693	1.2153
Limits				Within 5470-5725MHz			
Result				Complies			

EUT :	IONNYK LINN	Model Name. :	L3BXX
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Frequency(5745-5850MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5745.0005	5745	0.00052	0.0908
		V max (V)	4.37	5745.0086	5745	0.00860	1.4976
		V min (V)	3.23	5745.0023	5745	0.00225	0.3922
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5745.0029	5745	0.00286	0.4978
		T (°C)	-10	5745.0046	5745	0.00457	0.7957
		T (°C)	0	5745.0023	5745	0.00229	0.3979
		T (°C)	10	5745.0023	5745	0.00234	0.4075
		T (°C)	20	5745.0065	5745	0.00646	1.1248
		T (°C)	30	5745.0074	5745	0.00740	1.2876
		T (°C)	40	5745.0073	5745	0.00729	1.2688
		T (°C)	50	5745.0015	5745	0.00146	0.2540
		T (°C)	60	5745.0056	5745	0.00560	0.9752
		T (°C)	70	5745.0052	5745	0.00522	0.9085
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5785.0096	5785	0.00960	1.6597
		V max (V)	4.37	5785.0092	5785	0.00916	1.5827
		V min (V)	3.23	5785.0088	5785	0.00878	1.5173
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5785.0096	5785	0.00961	1.6604
		T (°C)	-10	5785.0093	5785	0.00930	1.6077
		T (°C)	0	5785.0041	5785	0.00414	0.7156
		T (°C)	10	5785.0071	5785	0.00707	1.2219
		T (°C)	20	5785.0068	5785	0.00678	1.1723
		T (°C)	30	5785.0058	5785	0.00578	0.9995
		T (°C)	40	5785.0057	5785	0.00573	0.9900
		T (°C)	50	5785.0095	5785	0.00955	1.6507
		T (°C)	60	5785.0073	5785	0.00731	1.2635
		T (°C)	70	5785.0021	5785	0.00213	0.3680
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.8	5825.0003	5825	0.00035	0.0598
		V max (V)	4.37	5825.0004	5825	0.00042	0.0721
		V min (V)	3.23	5825.0023	5825	0.00225	0.3867
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.8	T (°C)	-20	5825.0082	5825	0.00817	1.4034
		T (°C)	-10	5825.0057	5825	0.00569	0.9772
		T (°C)	0	5825.0060	5825	0.00599	1.0282
		T (°C)	10	5825.0087	5825	0.00871	1.4959
		T (°C)	20	5825.0001	5825	0.00015	0.0254
		T (°C)	30	5825.0059	5825	0.00588	1.0100
		T (°C)	40	5825.0046	5825	0.00460	0.7903
		T (°C)	50	5825.0035	5825	0.00350	0.6016
		T (°C)	60	5825.0040	5825	0.00401	0.6878
		T (°C)	70	5825.0019	5825	0.00193	0.3316
Limits				Within 5745-5850MHz			
Result				Complies			

10. DYNAMIC FREQUENCY SELECTION(DFS)

10.1 APPLICABILITY OF DFS REQUIREMENTS

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes
Client Beacon Test	N/A	Yes	Yes

Additional requirements for devices with multiple bandwidth modes	Operational Mode	
	Master or Client With Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

10.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE NOTEBOOKING

Maximum Transmit Power	Value (see notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP $<$ 200 milliwatt and power spectral density $<$ 10 dBm/MHz	-62 dBm
EIRP $<$ 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: EIRP is based on the highest antenna gain.	

10.3 DFS RESPONSE REQUIREMENT VALUES

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth See Note 3.

Note 1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

10.4 SHORT PULSE RADAR TEST WAVEFORMS

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B	$\text{Roundup}\left(\frac{1}{360} \cdot \frac{19 \cdot 10^6}{\text{PRI}_{\text{min}}}\right)$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.


If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

10.5 CALIBRATION SETUP AND DFS TEST RESULTS

Radar Waveform Calibration Procedure

- 1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master
- 2) The interference Radar Detection Threshold Level is $-62\text{dBm} + 3.69\text{dBi} = -58.31\text{dBm}$ that had been taken into account the output power range and antenna gain.
- 3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz. The spectrum analyzer had offset -1.0dB to compensate RF cable loss 1.0dB.
- 4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} + 3.69\text{dBi} + 1\text{dB} = -57.31\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.

10.6 CONDUCTED CALIBRATION SETUP



Wireless AP	Manufacturer	ASUSTek Computer Inc
	Model NO.	AX5400
	FCC ID	MSQ-RTAXJ300

Note:1. The Slave device associated with the EUT during these tests does not have radar detection capability.

2. WLAN traffic is generated by using the iperf software to send packets from the Master IP address to the Slave IP address.

3. The time required for the master and slave devices to fully start up is 120s.

4. EUT does not support TPC.


10.7 RADAR WAVEFORM CALIBRATION RESULT

Test data reference attachment.

10.8 IN-SERVICE NOTEBOOKING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD

TEST CONFIGURATION:

Setup for Client with injection at the Master



TEST PROCEDURE:

1. The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device
3. A trigger is provided from the pulse generator to the DFS Notebooking system in order to capture the traffic and the occurrence of the radar pulse.
4. EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is Streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom In 600ms plot of the Short Pulse Radar Type
7. Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
8. Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

TEST MODE:

Mode	Frequency (MHz)
a	5500

10.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST

Test data reference attachment.

11. ANTENNA REQUIREMENT

11.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

11.2 EUT ANTENNA

The EUT antenna is Chip Antenna. It comply with the standard requirement.

END OF REPORT