

FCC PART 15 SUBPART C

Yardlake Power Bank

MODEL No.: Fq002

FCC ID: 2BVWG-FQ002

REPORT NO.: SZNTT26038269E1-1

ISSUE DATE: Sept. 15, 2026

Prepared for

Huizhou Fengqi Electronics Co., Ltd.

No. 10 Area, 5th Floor, Building C, Factory 3, No. 359 Longhai 4th Road, West District, Daya Bay, Huiyang District, Huizhou City, Guangdong Province, China

Prepared by

Shenzhen NTT Testing Technology Co., Ltd.

1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang Industrial Park No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district, Bao 'an District, Shenzhen City, China

TEL: 0755-27889935



TABLE OF CONTENT

Test Report Description	Page
1. SUMMARY OF TEST RESULTS	5
2. GENERAL INFORMATION	6
2.1. Description of Device (EUT).....	6
2.2. Description of Support Units.....	6
2.3. Test Mode.....	7
2.4. Description of Test Facility.....	8
2.5. Measurement Uncertainty.....	8
3. MEASURING DEVICE AND TEST EQUIPMENT	9
4. 20DB BANDWIDTH	11
4.1. Test Procedure.....	11
4.2. Test Setup.....	11
4.3. Test Results.....	11
5. POWER LINE CONDUCTED EMISSION MEASUREMENT	12
5.1. Block Diagram of Test Setup.....	12
5.2. Limits.....	12
5.3. Test Procedure.....	12
5.4. Measuring Results.....	13
6. RADIATED EMISSION TEST	16
6.1. Measurement Procedure.....	16
6.2. Test SET-UP (Block Diagram of Configuration).....	16
6.3. Radiated Emission Limit.....	17
6.4. Measurement Result.....	19
7. TEST PHOTOGRAPHS AND EUT PHOTOGRAPHS	25



TEST REPORT DESCRIPTION

Applicant : Huizhou Fengqi Electronics Co., Ltd.

Address : No. 10 Area, 5th Floor, Building C, Factory 3, No. 359 Longhai 4th Road, West District, Daya Bay, Huiyang District, Huizhou City, Guangdong Province, China

Manufacturer : Huizhou Fengqi Electronics Co., Ltd.

Address : No. 10 Area, 5th Floor, Building C, Factory 3, No. 359 Longhai 4th Road, West District, Daya Bay, Huiyang District, Huizhou City, Guangdong Province, China

EUT : Yardlake Power Bank

Model Name : Fq002

Trademark : Yardlake

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by Shenzhen NTT Testing Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15C

The test results of this report relate only to the tested sample identified in this report.

Prepared by(Test Engineer):
Gary Lu

Gary Lu

Reviewer(Supervisor):
Cindy Qin

Cindy Qin

Approved(Manager):
Abel Yu





Modified Information

Version	Report No.	Revision Data	Summary
Ver.1.0	SZNTT26038269E1-1	Sept. 15, 2026	Original Version



1. SUMMARY OF TEST RESULTS

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass



2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT : Yardlake Power Bank

Model Number : Fq002

Model different : N/A

Power Rating : Battery Energy: 7.7VDC/77Wh(10000mAh, Two Cells in Series)
Multiple-port Output: 5V=3A
Wireless Output: 5W/7.5W/10W/15W/25W
USB-C Input: 5V=3A, 9V=3A, 12V=2.5A
USB-C Output: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A
USB-C Female Input: 5V=3A, 9V=2A, 12V=2.5A
USB-C Female Output: 5V=3A, 9V=2A, 12V=2.5A, 15V=2A, 20V=1.5A
Lightning Output: 5V=2.4A

Operation : 111-365kHz
Frequency for WPT

Modulation : MSK

Antenna Type : Coil Antenna

Date of Received : Sept. 07, 2026

Date of Test : Sept. 07, 2026 to Sept. 15, 2026

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Yardlake Power Bank	N/A	Fq002	N/A	EUT
E-2	Phone 1	iPhone	iPhone 14	N/A	Auxiliary
E-3	Phone 2	Xiaomi	Xiaomi 14	N/A	Auxiliary
E-4	Phone 3	IQOO	IQOO z9turbo	N/A	Auxiliary
E-5	Adapter	N/A	X2903	N/A	Auxiliary

Note: (1)The support equipment was authorized by Declaration of Confirmation.
(2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.3. Test Mode

Mode	Description	Remark
1	EUT + Phone 3 (25W)	5%
2		50%
3		95%
4	EUT + Phone 3 (15W)	5%
5		50%
6		95%
7	EUT + Phone 3 (10W)	5%
8		50%
9		95%
10	EUT + Phone 3 (7.5W)	5%
11		50%
12		95%
13	EUT + Phone 3 (5W)	5%
14		50%
15		95%
13	Adapter + EUT + Phone 3 (25W)	5%
14		50%
15		95%
16	Adapter + EUT + Phone 3 (15W)	5%
17		50%
18		95%
19	Adapter + EUT + Phone 3 (10W)	5%
20		50%
21		95%
22	Adapter + EUT + Phone 3 (7.5W)	5%
23		50%
24		95%
25	Adapter + EUT + Phone 3 (5W)	5%
26		50%
27		95%
28	EUT + Phone 3 (5W) + Lightning (Phone 1) + USB-C (Phone 2)	5%
29		50%
30		95%
31	EUT + USB-C (Phone 2) (5V/3A)	Full Load
32	EUT + USB-C (Phone 2) (9V/3A)	Full Load
33	EUT + USB-C (Phone 2) (20V/1.5A)	Full Load
34	EUT + USB-C Female (Phone 3) (5V/3A)	Full Load
35	EUT + USB-C Female (Phone 3) (9V/3A)	Full Load
36	EUT + USB-C Female (Phone 3) (20V/1.5A)	Full Load
37	Adapter + EUT + USB-C (Phone 2) (5V/3A)	Full Load
38	Adapter + EUT + USB-C (Phone 2) (9V/3A)	Full Load
39	Adapter + EUT + USB-C (Phone 2) (20V/1.5A)	Full Load
40	Adapter + EUT + USB-C Cable (Phone 3) (5V/3A)	Full Load
41	Adapter + EUT + USB-C Cable (Phone 3) (9V/3A)	Full Load
42	Adapter + EUT + USB-C Cable (Phone 3) (20V/1.5A)	Full Load
43	EUT + Lightning (Phone 1) (5V/2.4A)	Full Load
44	Adapter + EUT + Lightning (Phone 1) (5V/2.4A)	Full Load
49	EUT+USB-C Female (Phone 3)+USB-C (Phone 2)+Lightning (Phone 1)	Full Load
Note:1. All test modes were pre-tested, but we only recorded the worst case in this report.		



2.4. Description of Test Facility

Site Description

Designation Number: CN3446
EMC Lab. : Test Firm Registration Number: 129414
Accredited by ANAB, Dec. 19, 2025
The Certificate Registration Number is AT-3446
Name of Firm : Shenzhen NTT Testing Technology Co., Ltd.
1B, Building 2, Factory Building & 103, Building 3, Factory Building,
Site Location : Dayang Industrial Park No.4, Industrial Avenue, Tangwei Community,
Fuhai Sub-district, Bao'an District, Shenzhen City, China

2.5. Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(9KHz~30MHz)	$\pm 4.51\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Remark: When making a conformity declaration based on test results for regulations/standards or specifications, the default is to use Clause 4.2.1 of ILAC-G8:09/2019 and the guidelines on decision rules and conformity declaration in IEC Guide 115:2023.	



3. MEASURING DEVICE AND TEST EQUIPMENT

Radiated emission & Radio Frequency Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2025/07/24	2028/07/23
EMI Test Receiver	ESPI	101018	ROHDE&SCHWARZ	2026/09/04	2027/09/03
Amplifier (30MHz-1GHz)	BBV 9745	00431	SCHWARZBECK	2026/09/04	2027/09/03
Bilog Antenna (30MHz-1GHz)	VULB9168	1858	SCHWARZBECK	2026/09/05	2027/09/04
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHWARZBECK	2026/09/05	2027/09/04
Preamplifier (1GHz-18GHz)	BBV 9718D	0024	SCHWARZBECK	2026/09/04	2027/09/03
Spectrum Analyzer (10Hz-40GHz)	FSV 40	100952	Rohde & Schwarz	2026/09/04	2027/09/03
Preamplifier (18GHz-40GHz)	BBV 9721	0056	SCHWARZBECK	2026/09/04	2027/09/03
Double Ridge Guide Horn Antenna (18GHz-40GHz)	SAS-574	588	A.H.System	2026/09/05	2027/09/04
Loop Antenna (9KHz-30MHz)	FMZB 1513-60	014	SCHWARZBECK	2026/09/04	2027/09/03
Amplifier (9KHz-30MHz)	CVP 9222 C	00109	SCHWARZBECK	2026/09/04	2027/09/03
MXG Signal Analyzer	N9020A	MY50510202	Agilent	2026/09/04	2027/09/03
MXG Vector Signal Generator	N5182A	MY50140020	Agilent	2026/09/04	2027/09/03
MXG Analog Signal Generator	N5181A	MY47420919	Agilent	2026/09/04	2027/09/03
Power Sensor	TR1029-2	512364	Techoy	2026/09/04	2027/09/03
RF Swith	TR1029-1	512364	Techoy	2026/09/04	2027/09/03
Cable	DA800- 4000MM	NA	DA	2026/09/04	2027/09/03
Cable	DA800- 11000MM	NA	DA	2026/09/04	2027/09/03



Conducted emission Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	HSRCE944	/	HTEC	2025/04/30	2028/04/29
EMI Test Receiver	ESCI	100881/003	ROHDE&SCHWARZ	2026/09/04	2027/09/03
LISN	AMN6500	101185	ROHDE&SCHWARZ	2026/09/04	2027/09/03
LISN	NNLK 8129	00603	SCHWARZBECK	2026/09/04	2027/09/03
Pulse Limiters	VTSD 9561 F	00343	SCHWARZBECK	2026/09/04	2027/09/03
Cable	RG223-2M	/	RG	2026/09/04	2027/09/03

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ-EMC	Ver.EMC-CON 3A1.1+
2	EMC radiation test system	FALA	EZ-EMC	Ver.FA-03A2 RE+
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0



4. 20DB BANDWIDTH

4.1. Test Procedure

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1-5%OBW.

Set the video bandwidth (VBW) =3RBW.

Set Span= 1KHz

Set Detector = Peak.


Set Trace mode = Max hold.

Set Sweep = auto couple.

Measure and record the results in the test report.


Note: Since the measured signal is CW-like, it is not practical to adjust the RBW according to C63.10, as the measured bandwidth will always follow the RBW, resulting in approximately twice the RBW.

4.2. Test Setup




4.3. Test Results

Frequency (KHz)	20dB bandwidth (Hz)	99% bandwidth (Hz)	Result
360	522	747	Pass



5. POWER LINE CONDUCTED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup



LISN: Line Impedance Stabilization Network

AE: Associated equipment

EUT: Equipment under test

5.2. Limits

FCC Part 15.207

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50 ~ 5.00	56.0	46.0
5.00 ~ 30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

5.3. Test Procedure

The EUT was placed on a desk 0.8 m height from the metal ground plane and 0.4 m from the conducting wall of the shielding room and it was kept at least 0.8 m from any other grounded conducting surface. The size of the table will nominally be 1.5 m x1.0 m.

The rear of the arrangement shall be flush with the back of the supporting tabletop unless that would not be possible or typical of normal use.

All units of equipment forming the system under test (includes the EUT as well as connected peripherals and associated equipment or devices) shall be arranged such that a nominal 0.1 m separation is achieved between the neighboring units.

Connect EUT to the power mains through a line impedance stabilization network (LISN). Where the mains cable supplied by the manufacturer is longer than 1 m, the excess should be folded at the centre into a bundle no longer than 0.4 m, so that its length is shortened to 1 m.

All the support units are connecting to the other LISN.



The LISN provides 50 ohm coupling impedance for the measuring instrument.

Both sides of AC line were checked for maximum conducted interference.

The frequency range from 150 kHz to 30 MHz was sweep.

Set the test-receiver system to quasi peak detect function and average detect function, and to measure the conducted emissions values.

Test results were obtained from the following equation:

Emission Level (dBμV) = LISN Factor (dB) + Cable Loss (dB) + Reading (dBμV)


Margin (dB) = Emission Level (dBμV) - Limit (dBμV)

5.4. Measuring Results

PASS.



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase:	L
Test Voltage:	AC 120V/60Hz	Mode:	Mode 13




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1548	29.78	19.70	49.48	65.74	-16.26	QP
2	0.1548	13.81	19.70	33.51	55.74	-22.23	AVG
3	0.2424	25.44	19.97	45.41	62.01	-16.60	QP
4	0.2424	8.91	19.97	28.88	52.01	-23.13	AVG
5 *	0.7139	23.03	20.06	43.09	56.00	-12.91	QP
6	0.7139	9.96	20.06	30.02	46.00	-15.98	AVG
7	0.7347	19.84	20.06	39.90	56.00	-16.10	QP
8	0.7347	-0.27	20.06	19.79	46.00	-26.21	AVG
9	13.7009	15.80	20.06	35.86	60.00	-24.14	QP
10	13.7009	5.52	20.06	25.58	50.00	-24.42	AVG
11	19.2053	17.81	20.17	37.98	60.00	-22.02	QP
12	19.2053	6.70	20.17	26.87	50.00	-23.13	AVG

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase:	N
Test Voltage:	AC 120V/60Hz	Mode:	Mode 13



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1611	28.75	19.75	48.50	65.41	-16.91	QP
2	0.1611	13.89	19.75	33.64	55.41	-21.77	AVG
3	0.2500	23.05	19.97	43.02	61.76	-18.74	QP
4	0.2500	1.84	19.97	21.81	51.76	-29.95	AVG
5	0.5689	19.35	19.99	39.34	56.00	-16.66	QP
6	0.5689	1.80	19.99	21.79	46.00	-24.21	AVG
7 *	0.7044	21.95	20.07	42.02	56.00	-13.98	QP
8	0.7044	5.23	20.07	25.30	46.00	-20.70	AVG
9	18.9970	16.98	20.17	37.15	60.00	-22.85	QP
10	18.9970	7.94	20.17	28.11	50.00	-21.89	AVG
11	20.5445	15.36	20.21	35.57	60.00	-24.43	QP
12	20.5445	4.77	20.21	24.98	50.00	-25.02	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor


6. RADIATED EMISSION TEST

6.1.Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.
5. Use the following receiver/spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW=200Hz for 9KHz to 150KHz,
RBW=9kHz for 150KHz to 30MHz,
RBW=120KHz for 30MHz to 1GHz
VBW $\geq 3 \times$ RBW
Sweep = auto
Detector function = QP
Trace = max hold

6.2.Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



6.3. Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation Frequency tion at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	$2400 / F(\text{KHz})$	300m	$10000 * 2400 / F(\text{KHz})$	$20\log 2400 / F(\text{KHz}) + 80$
0.490 – 1.705	$24000 / F(\text{KHz})$	30m	$100 * 24000 / F(\text{KHz})$	$20\log 24000 / F(\text{KHz}) + 40$
1.705 – 30.00	30	30m	$100 * 30$	$20\log 30 + 40$
30.0 – 88.0	100	3m	100	$20\log 100$
88.0 – 216.0	150	3m	150	$20\log 150$
216.0 – 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$



15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark: 1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205, and the emissions located in restricted bands also comply with 15.209 limit.



6.4.Measurement Result


Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80


Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Pol.	Coplanar
Test Voltage:	DC 3.85V	Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0185	27.57	28.28	55.85	122.24	-66.39	peak
2	0.0520	26.92	27.88	54.80	113.27	-58.47	peak
3	0.0710	26.42	27.66	54.08	110.57	-56.49	peak
4	0.1110	26.13	27.25	53.38	106.69	-53.31	peak
5 *	0.1259	31.98	27.17	59.15	105.60	-46.45	peak
6	0.1292	28.99	27.15	56.14	105.37	-49.23	peak



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1815	20.25	26.95	47.20	102.42	-55.22	peak
2	0.1893	20.83	26.92	47.75	102.06	-54.31	peak
3	0.2521	21.77	26.73	48.50	99.57	-51.07	peak
4	0.3614	23.57	26.39	49.96	96.44	-46.48	peak
5	0.6577	14.92	25.46	40.38	71.30	-30.92	peak
6 *	3.2070	17.43	22.59	40.02	69.54	-29.52	peak

Note:


Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.


Margin = Emission Level- Limit.



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Pol.	Coaxial
Test Voltage:	DC 3.85V	Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0558	37.84	27.84	65.48	112.69	-47.21	peak
2	0.0594	38.21	27.79	66.00	112.12	-46.12	peak
3	0.0655	37.99	27.72	65.71	111.27	-45.56	peak
4	0.1097	36.57	27.26	63.83	106.79	-42.96	peak
5 *	0.1267	41.84	27.17	68.81	105.54	-36.73	peak
6	0.1389	34.35	27.10	61.45	104.74	-43.29	peak



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.2083	32.04	26.86	58.90	101.23	-42.33	peak
2	0.2290	32.92	26.80	59.72	100.40	-40.68	peak
3	0.3573	38.25	26.40	64.65	96.54	-31.89	peak
4 *	1.0710	26.27	24.31	50.58	67.17	-16.59	peak
5	1.7716	26.28	23.51	49.79	69.54	-19.75	peak
6	2.5000	27.28	22.98	50.26	69.54	-19.28	peak

Note:

Pre-scan in the all of mode, the worst case in of was recorded.


Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level- Limit.



30MHz-1GHz:


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3.85V	Mode:	Model 13



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	33.5624	35.65	-16.65	19.00	40.00	-21.00	QP
2	37.2854	34.30	-15.93	18.37	40.00	-21.63	QP
3	52.0251	32.21	-14.32	17.89	40.00	-22.11	QP
4	100.9339	40.08	-16.30	23.78	43.50	-19.72	QP
5	246.8150	37.95	-15.37	22.58	46.00	-23.42	QP
6	287.9904	42.83	-14.06	28.77	46.00	-17.23	QP



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Vertical
Test Voltage:	DC 3.85V	Mode:	Model 13



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



7. TEST PHOTOGRAPHS AND EUT PHOTOGRAPHS

Please see the attachment for details.

-----End of Report-----