Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No. ..... :	**CTA26040801103**
FCC ID. ..... :	**2BVWM-S30SE**
Compiled by (position+printed name+signature)..:	File administrators Zoey Cao
Supervised by (position+printed name+signature)..:	Project Engineer Ace Chai
Approved by (position+printed name+signature)..:	RF Manager Eric Wang
Date of issue ..... :	Apr. 30, 2026

Testing Laboratory Name ..... :	**Shenzhen CTA Testing Technology Co., Ltd.**
Address ..... :	Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name ..... :	**SHARE3DCAM LIMITED**
Address ..... :	Room 3502, Yuehai Landmark Building, No. 2018, Buxin Road, Dongxiao Community, Dongxiao Sub-district, Luohu District, Shenzhen, China

Test specification ..... :	
Standard ..... :	**FCC Part 15 Subpart E 15.407**
TRF Originator ..... :	Shenzhen CTA Testing Technology Co., Ltd.

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description ..... :	**Real-Scene 3D LiDAR Scanner**
Trade Mark ..... :	SHARE3DCAM
Manufacturer ..... :	**SHARE3DCAM LIMITED**
Model/Type reference ..... :	SHARE3DCAM S30 SE
Listed Models ..... :	N/A
Modulation ..... :	OFDM/OFDMA
Frequency ..... :	From 5180MHz-5240MHz, 5745MHz-5825MHz
Rating ..... :	Input: 20V⎓ 1.5A Battery: 14.4V 3150mAh 45.36Wh
Result ..... :	**PASS**

TEST REPORT

Equipment under Test	:	Real-Scene 3D LiDAR Scanner
Model /Type	:	SHARE3DCAM S30 SE
Applicant	:	**SHARE3DCAM LIMITED**
Address	:	Room 3502, Yuehai Landmark Building, No. 2018, Buxin Road, Dongxiao Community, Dongxiao Sub-district, Luohu District, Shenzhen, China
Manufacturer	:	**SHARE3DCAM LIMITED**
Address	:	Room 3502, Yuehai Landmark Building, No. 2018, Buxin Road, Dongxiao Community, Dongxiao Sub-district, Luohu District, Shenzhen, China

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 TEST STANDARDS....4
2 SUMMARY....5
2.1 General Remarks....5
2.2 Product Description....5
2.3 Equipment Under Test....5
2.4 Short description of the Equipment under Test (EUT)....6
2.5 EUT configuration....6
2.6 EUT operation mode....6
2.7 Block Diagram of Test Setup....7
2.8 Related Submittal(s) / Grant (s)....7
2.9 Modifications....7
3 TEST ENVIRONMENT....8
3.1 Address of the test laboratory....8
3.2 Test Facility....8
3.3 Environmental conditions....8
3.4 Test Description....9
3.5 Statement of the measurement uncertainty....9
3.6 Equipments Used during the Test....11
4 TEST CONDITIONS AND RESULTS....12
4.1 AC Power Conducted Emission....12
4.2 Radiated and Conducted Unwanted Emissions....17
4.3 Maximum Conducted Average Output Power....26
4.4 Power Spectral Density....28
4.5 Emission Bandwidth (26dB Bandwidth)....30
4.6 Minimum Emission Bandwidth (6dB Bandwidth)....31
4.7 Frequency Stability....32
4.8 On Time and Duty Cycle....34
4.9 Antenna Requirement....35
4.10 Emissions at Restricted Band....36
5 Test Setup Photos of the EUT....40
6 Photos of the EUT....41

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15 Subpart E—Unlicensed National Information Infrastructure Devices
ANSI C63.10-2020 +Cor. 1-2023+ C63.10a-2024+ Errata to C63.10a-2024: American National Standard for Testing Unlicensed Wireless Devices
KDB789033 D02: General UNII Test Procedures New Rules v02r01

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Apr. 08, 2026
Testing commenced on	:	Apr. 08, 2026
Testing concluded on	:	Apr. 30, 2026

2.2 Product Description

Product Description:	Real-Scene 3D LiDAR Scanner
Model:	SHARE3DCAM S30 SE
Power supply:	Input: 20V⎓ 1.5A Battery: 14.4V 3150mAh 45.36Wh
Adapter information:	Model: Q366 Input: AC 100-240V 50/60Hz 1.5A Max C1 PD OUTPUT: DC 5V 3A, 9V 3A, 12V 3A, 15V 3A, 20V 3.25A 65W (MAX) C2 PD OUTPUT: DC 5V 3A, 9V 3A, 12V 3A, 15V 3A, 20V 3.25A 65W (MAX) USB-A OUTPUT: DC 4.5V 5A, 5V 4.5A, 5V 3A, 9V 3A, 12V 2.5A 30W (MAX) C1+C2: 45W+20W 65W (MAX) C1+A1: 45W+18W (MAX) C2+A1: 5V 3.6A 18W Max. TOTAL POWER: 65W MAX
Hardware version:	V1.0
Software version:	V1.0
Testing sample ID：	CTA260408011-1# (Engineer sample) CTA260408011-2# (Normal sample)

WIFI

	20MHz system	40MHz system	80MHz system	160MHz system
Supported type:	802.11a 802.11n 802.11ac 802.11ax	802.11n 802.11ac 802.11ax	N/A	N/A
Operation frequency:	5180MHz-5240MHz 5745MHz-5825MHz	5190MHz-5230MHz 5755MHz-5795MHz	N/A	N/A
Modulation:	OFDM OFDMA	OFDM OFDMA	N/A	N/A
Channel number:	9	4	N/A	N/A
Channel separation:	20MHz	40MHz	N/A	N/A
Supported partial RU configurations:	Only Support Full RU			
Antenna type:	PIFA antenna			
Antenna gain:	1.15 dBi for 5180-5240MHz for Antenna 1&2 1.18 dBi for 5745-5825MHz for Antenna 1&2			

2.3 Equipment Under Test

Power supply system utilised

Refer to section 2.2

2.4 Short description of the Equipment under Test (EUT)

This is a Real-Scene 3D LiDAR Scanner.
For more details, refer to the user's manual of the EUT.

Test Software Version	Tools software(ADB command)		
Frequency	5180 MHz	5220 MHz	5240 MHz
802.11a	Default	Default	Default
802.11n20	Default	Default	Default
802.11ac20	Default	Default	Default
802.11ax20	Default	Default	Default
Frequency	5190 MHz	/	5230 MHz
802.11n40	Default	/	Default
802.11ac40	Default	/	Default
802.11ax40	Default	/	Default

Test Software Version	Tools software(ADB command)		
Frequency	5745 MHz	5785 MHz	5825 MHz
802.11a	Default	Default	Default
802.11n20	Default	Default	Default
802.11ac20	Default	Default	Default
802.11ax20	Default	Default	Default
Frequency	5755 MHz	/	5795 MHz
802.11n40	Default	/	Default
802.11ac40	Default	/	Default
802.11ax40	Default	/	Default

2.5 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer
○ - supplied by the lab

	/	

2.6 EUT operation mode

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.
All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band：

Operating band	20MHz		40MHz		80MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190	--	--
	40	5200				
	44	5220	46	5230		
	48	5240				
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755	--	--
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825	--	--	--	--

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

2.7 Block Diagram of Test Setup



2.8 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.9 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.
Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:
FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:
Radiated Emission:

Temperature:	25 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing：

Temperature:	25 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

AC Power Conducted Emission

Temperature:	24 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS Note1
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	PASS Note2
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.407(h)	Dynamic Frequency Selection	N/A Note 3
FCC Part 15.203/15.247(b)	Antenna Requirement	PASS

Note 1: Apply to U-NII 1 band.
Note 2: Apply to U-NII 3 band only.
Note 3: This device not work in DFS band.

Data Rate Used:
Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	6 Mbps
	11n(20MHz),11ac(20MHz)/OFDM, 11ax(20MHz)/OFDMA	MCS0
	11n(40MHz),11ac(40MHz)/OFDM, 11ax(40MHz)/OFDMA	MCS0

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.
Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.02 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Output Peak power	30MHz~18GHz	0.55 dB	(1)
Power spectral density	/	0.57 dB	(1)
Spectrum bandwidth	/	1.1%	(1)

Radiated spurious emission (30MHz-1GHz)	30~1000MHz	4.10 dB	(1)
Radiated spurious emission (1GHz-18GHz)	1~18GHz	4.32 dB	(1)
Radiated spurious emission (18GHz-40GHz)	18-40GHz	5.54 dB	(1)
Time	/	±2%	(1)

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	CTA-308	2025/08/04	2026/08/03
LISN	R&S	ENV216	CTA-314	2025/07/30	2026/07/29
EMI Test Receiver	R&S	ESPI	CTA-307	2025/07/30	2026/07/29
EMI Test Receiver	R&S	ESCI	CTA-306	2025/07/30	2026/07/29
Spectrum Analyzer	Agilent	N9020A	CTA-342	2025/07/30	2026/07/29
Vector Signal generator	Agilent	N5182A	CTA-305	2025/07/30	2026/07/29
Analog Signal Generator	R&S	E4421B	CTA-304	2025/07/30	2026/07/29
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	CTA-302	2025/07/30	2026/07/29
Temperature and humidity meter	Chigo	ZG-7020	CTA-326	2025/07/31	2026/07/30
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	CTA-310	2023/10/17	2026/10/16
Horn Antenna	Schwarzbeck	BBHA 9120D	CTA-309	2023/10/13	2026/10/12
Loop Antenna	Zhinan	ZN30900C	CTA-311	2023/10/17	2026/10/16
Horn Antenna	Schwarzbeck	BBHA 9170	CTA-346	2025/05/18	2028/05/17
Amplifier	Schwarzbeck	BBV9745	CTA-312	2025/07/30	2026/07/29
Amplifier	Tonscend	TAP-011840	CTA-313	2025/07/30	2026/07/29
Automatic control unit	Tonscend	JS0806-2	CTA-351	2025/07/30	2026/07/29
Amplifier	SKET	LNPA 1840G-50	CTA-345	2025/05/17	2026/05/16
Spectrum analyzer	R&S	FSV40-N	CTA-344	2025/05/17	2026/05/16
5GFilter	CONCEPT	CNF05150M0585 0Q16A	CTA-366	2025/07/31	2026/07/30
6dB attenuator	Shanghaihuaxiang	GZL-TS5-6-6	CTA-347	2025/05/17	2026/05/16
Programmable Constant Temperature And Humidity Test Chamber	DONGGUAN JINGYU	HT-H-408	CTA-053	2025/07/30	2026/07/29
EMI Test Software	Tonscend	TS®JS32-RE	5.0.0.2	N/A	N/A
EMI Test Software	Tonscend	TS®JS32-CE	5.0.0.1	N/A	N/A
RF Test Software	Tonscend	TS®JS1120-3	3.1.65	N/A	N/A
RF Test Software	Tonscend	TS®JS1120	3.1.46	N/A	N/A

Note: The automatic control unit integrated Power sensor

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a Multi-System Scannerop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
2 Support equipment, if needed, was placed as per ANSI C63.10-2020
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT.The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following：

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

TEST RESULTS

Passed

Please refer to the below test data:

Remark:

1. 1. All modes of 802.11a/n/11ac/11ax were test at Low, Middle, and High channel; only the worst result of a Middle Channel was reported as below:

2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

5.2GWIFI:

Power supply:	DC 20.0V from adapter AC 120V/60Hz	Polarization	L



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading[dBµV]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.186	9.97	35.16	45.13	64.21	19.08	21.76	31.73	54.21	22.48	PASS
2	0.7035	10.43	38.44	48.87	56.00	7.13	22.81	33.24	46.00	12.76	PASS
3	1.617	10.46	30.44	40.90	56.00	15.10	18.25	28.71	46.00	17.29	PASS
4	4.1055	10.76	25.73	36.49	56.00	19.51	10.47	21.23	46.00	24.77	PASS
5	7.8225	11.23	25.51	36.74	60.00	23.26	9.28	20.51	50.00	29.49	PASS
6	19.968	12.91	17.36	30.27	60.00	29.73	6.18	19.09	50.00	30.91	PASS

Note:1).QP Value (dBµV)= QP Reading (dBµV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). QPMargin(dB) = QP Limit (dBµV) - QP Value (dBµV)

4). AVMargin(dB) = AV Limit (dBµV) - AV Value (dBµV)

Power supply:	DC 20.0V from adapter AC 120V/60Hz	Polarization	N



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading[dBµV]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.204	9.94	31.53	41.47	63.45	21.98	19.54	29.48	53.45	23.97	PASS
2	0.7035	10.34	33.17	43.51	56.00	12.49	16.95	27.29	46.00	18.71	PASS
3	1.5855	10.42	28.95	39.37	56.00	16.63	17.56	27.98	46.00	18.02	PASS
4	5.424	10.98	22.05	33.03	60.00	26.97	8.52	19.50	50.00	30.50	PASS
5	13.5105	12.12	17.60	29.72	60.00	30.28	4.71	16.83	50.00	33.17	PASS
6	28.797	13.71	16.26	29.97	60.00	30.03	4.55	18.26	50.00	31.74	PASS

Note:1).QP Value (dBµV)= QP Reading (dBµV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). QPMargin(dB) = QP Limit (dBµV) - QP Value (dBµV)
4). AVMargin(dB) = AV Limit (dBµV) - AV Value (dBµV)

5.8GWIFI:

Power supply:	DC 20.0V from adapter AC 120V/60Hz	Polarization	L



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading[dBµV]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.231	9.78	29.66	39.44	62.41	22.97	19.06	28.84	52.41	23.57	PASS
2	0.699	10.42	32.52	42.94	56.00	13.06	18.70	29.12	46.00	16.88	PASS
3	1.671	10.47	28.55	39.02	56.00	16.98	17.46	27.93	46.00	18.07	PASS
4	4.416	10.80	24.00	34.80	56.00	21.20	7.63	18.43	46.00	27.57	PASS
5	8.0835	11.27	21.83	33.10	60.00	26.90	6.20	17.47	50.00	32.53	PASS
6	19.0455	12.77	17.57	30.34	60.00	29.66	4.61	17.38	50.00	32.62	PASS

Note:1).QP Value (dBµV)= QP Reading (dBµV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). QPMargin(dB) = QP Limit (dBµV) - QP Value (dBµV)
4). AVMargin(dB) = AV Limit (dBµV) - AV Value (dBµV)

Power supply:	DC 20.0V from adapter AC 120V/60Hz	Polarization	N



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading[dBµV]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.2535	9.63	29.81	39.44	61.64	22.20	20.31	29.94	51.64	21.70	PASS
2	0.888	10.35	27.96	38.31	56.00	17.69	17.46	27.81	46.00	18.19	PASS
3	2.1255	10.46	24.18	34.64	56.00	21.36	13.64	24.10	46.00	21.90	PASS
4	5.379	10.97	20.78	31.75	60.00	28.25	7.07	18.04	50.00	31.96	PASS
5	11.328	11.80	16.84	28.64	60.00	31.36	4.81	16.61	50.00	33.39	PASS
6	24.594	13.39	16.93	30.32	60.00	29.68	5.37	18.76	50.00	31.24	PASS

Note:1).QP Value (dBµV)= QP Reading (dBµV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). QPMargin(dB) = QP Limit (dBµV) - QP Value (dBµV)
4). AVMargin(dB) = AV Limit (dBµV) - AV Value (dBµV)

4.2 Radiated and Conducted Unwanted Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) Note1
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

(5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209

(6)In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

Conducted measurement Test Procedure:

The testing follows the ANSI C63.10 Section 12.7.6 and 6.10.4:

The procedure for peak unwanted emissions measurements above 1000 MHz is as follows:
b) Peak emission levels are measured by setting the instrument as follows:
1) RBW = 1 MHz.
2) VBW $\geqslant$ [3 $\times$ RBW]
3) Detector = peak.
4) Sweep time = No faster than coupled (auto) time.
5) Trace mode = max-hold.
6) Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, then the time required for the trace to stabilize will increase by a factor of approximately 1 / D, where D is the duty cycle. For example, at 50% duty cycle, the measurement time will increase by a factor of two, relative to measurement time for continuous transmission.

Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

Note:RF Conducted test Offset= cable loss,For conducted spurious emission test, cable loss is the maximum value in the range of test.

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz





Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All modes of 802.11a/n/11ac/11ax have been tested for below 1GHz test, only the worst case 802.11a low channel was recorded.
3. All modes of 802.11a/n/11ac/11ax have been tested for above 1GHz test, only the worst case 802.11a was recorded.
4. Radiated emission test from 9 KHz to 40GHz harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

5. Conducted emission test from 30MHz to 40GHz harmonic of fundamental was verified, and emission margin is greater than 20dB in 27GHz to 40GHz and not recorded in this report.

5.2G WIFI :

For 30MHz-1GHz

Horizontal



Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	37.8812	48.98	36.51	-12.47	40.00	3.49	Horizontal
2	69.285	46.06	31.40	-14.66	40.00	8.60	Horizontal
3	108.2062	40.81	27.85	-12.96	43.50	15.65	Horizontal
4	185.0788	45.02	30.23	-14.79	43.50	13.27	Horizontal
5	275.5312	41.05	28.52	-12.53	46.00	17.48	Horizontal
6	624.9738	35.33	29.38	-5.95	46.00	16.62	Horizontal

Note:1).Level (dBµV/m)= Reading (dBµV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBµV/m) - Level (dBµV/m)

Vertical



Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	43.7012	47.10	36.00	-11.10	40.00	4.00	Vertical
2	69.8912	50.52	35.54	-14.98	40.00	4.46	Vertical
3	109.4188	52.84	39.72	-13.12	43.50	3.78	Vertical
4	212.7238	44.76	31.06	-13.70	43.50	12.44	Vertical
5	374.9562	39.61	28.73	-10.88	46.00	17.27	Vertical
6	720.0338	31.81	27.62	-4.19	46.00	18.38	Vertical

Note:1).Level (dBµV/m)= Reading (dBµV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBµV/m) - Level (dBµV/m)

5.8G WIFI :

For 30MHz-1GHz

Horizontal



Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	53.4012	46.84	36.08	-10.76	40.00	3.92	Horizontal
2	69.285	47.49	32.83	-14.66	40.00	7.17	Horizontal
3	106.8725	40.67	27.94	-12.73	43.50	15.56	Horizontal
4	185.0788	44.80	30.01	-14.79	43.50	13.49	Horizontal
5	374.9562	40.17	29.29	-10.88	46.00	16.71	Horizontal
6	624.9738	36.76	30.81	-5.95	46.00	15.19	Horizontal

Note:1).Level (dBµV/m)= Reading (dBµV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Limit (dBµV/m) - Level (dBµV/m)

Vertical



Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	36.305	47.85	34.81	-13.04	40.00	5.19	Vertical
2	70.6188	49.76	34.54	-15.22	40.00	5.46	Vertical
3	106.145	50.24	37.59	-12.65	43.50	5.91	Vertical
4	146.4	54.41	37.51	-16.90	43.50	5.99	Vertical
5	278.0775	41.49	29.04	-12.45	46.00	16.96	Vertical
6	899.3625	29.20	27.31	-1.89	46.00	18.69	Vertical

Note:1).Level (dBµV/m)= Reading (dBµV)+ Factor (dB/m)
2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
3). Margin(dB) = Limit (dBµV/m) - Level (dBµV/m)

For 1GHz to 40GHz

Note: All modes of 802.11a/n/11ac/11ax have been tested for above 1GHz test, only the worst case 802.11n20 MIMO mode was recorded.

U-NII 1 & 802.11n20 Mode (above 1GHz)

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00	10360.0	60.29	PK	H	68.3	8.01	65.99	38.90	8.19	52.79	-5.70
(5180MHz)	10360.0	50.33	AV	H	54.0	3.67	56.03	38.90	8.19	52.79	-5.70
44.00	10440.0	60.24	PK	H	68.3	8.06	65.93	38.94	8.22	52.85	-5.69
(5220MHz)	10440.0	50.26	AV	H	54.0	3.74	55.95	38.94	8.22	52.85	-5.69
48.00	10480.0	59.48	PK	H	68.3	8.82	65.14	38.98	8.24	52.88	-5.66
(5240MHz)	10480.0	50.12	AV	H	54.0	3.88	55.78	38.98	8.24	52.88	-5.66

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00	10360.0	56.41	PK	V	68.3	11.89	62.11	38.90	8.19	52.79	-5.70
(5180MHz)	10360.0	46.90	AV	V	54.0	7.10	52.60	38.90	8.19	52.79	-5.70
44.00	10440.0	56.66	PK	V	68.3	11.64	62.35	38.94	8.22	52.85	-5.69
(5220MHz)	10440.0	47.54	AV	V	54.0	6.46	53.23	38.94	8.22	52.85	-5.69
48.00	10480.0	56.11	PK	V	68.3	12.19	61.77	38.98	8.24	52.88	-5.66
(5240MHz)	10480.0	45.90	AV	V	54.0	8.10	51.56	38.98	8.24	52.88	-5.66

U-NII 3 & 802.11n20 Mode (above 1GHz)

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
149.00	11490.0	61.41	PK	H	68.3	6.89	66.71	39.41	8.69	53.40	-5.30
(5745MHz)	11490.0	50.73	AV	H	54.0	3.27	56.03	39.41	8.69	53.40	-5.30
157.00	11570.0	62.56	PK	H	68.3	5.74	67.92	39.33	8.72	53.41	-5.36
(5785MHz)	11570.0	51.19	AV	H	54.0	2.81	56.55	39.33	8.72	53.41	-5.36
165.00	11650.0	62.53	PK	H	68.3	5.77	67.95	39.25	8.76	53.43	-5.42
(5825MHz)	11650.0	51.20	AV	H	54.0	2.80	56.62	39.25	8.76	53.43	-5.42

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
149.00	11490.0	56.84	PK	V	68.3	11.46	62.14	39.41	8.69	53.40	-5.30
(5745MHz)	11490.0	47.37	AV	V	54.0	6.63	52.67	39.41	8.69	53.40	-5.30
157.00	11570.0	58.73	PK	V	68.3	9.57	64.09	39.33	8.72	53.41	-5.36
(5785MHz)	11570.0	47.35	AV	V	54.0	6.65	52.71	39.33	8.72	53.41	-5.36
165.00	11650.0	58.73	PK	V	68.3	9.57	64.15	39.25	8.76	53.43	-5.42
(5825MHz)	11650.0	47.82	AV	V	54.0	6.18	53.24	39.25	8.76	53.43	-5.42

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

4.3 Maximum Conducted Average Output Power

Limit

For the band 5.15-5.25 GHz.
(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.
(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.
(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.
(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.
Method PM is Measurement using an RF average power sensor. The procedure for this method is as follows:
1. The testing follows the ANSI C63.10 Section 12.4.3
2. The maximum average conducted output power may be measured using a broadband average RF power sensor.
3. The power sensor shall have a video bandwidth that is greater than or equal to the OBW bandwidth and shall use a fast-responding diode detector.

Test Configuration

Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

Total Output Average power(dBm)= Output Average power(dBm)+ Duty Factor(dB)

MIMO

Test Mode	Freq(MHz)	Antenna 1 Result [dBm]	Antenna 2 Result [dBm]	MIMO Result [dBm]	Limit [dBm]	Verdict
11N20SISO MIMO	5180	14.49	14.32	17.42	≤23.98	PASS
	5220	14.89	14.61	17.76	≤23.98	PASS
	5240	14.68	14.07	17.40	≤23.98	PASS
	5745	13.92	13.85	16.90	≤30.00	PASS
	5785	14.09	13.79	16.95	≤30.00	PASS
	5825	14.08	13.84	16.97	≤30.00	PASS
11N40SISO MIMO	5190	14.83	14.52	17.69	≤23.98	PASS
	5230	14.75	14.63	17.70	≤23.98	PASS
	5755	14.13	13.93	17.04	≤30.00	PASS
	5795	14.31	14.31	17.32	≤30.00	PASS
11AC20SISO MIMO	5180	14.38	14.4	17.40	≤23.98	PASS
	5220	14.61	14.45	17.54	≤23.98	PASS
	5240	14.38	14.39	17.40	≤23.98	PASS
	5745	13.92	13.94	16.94	≤30.00	PASS
	5785	13.94	13.93	16.95	≤30.00	PASS
	5825	13.88	13.81	16.86	≤30.00	PASS
11AC40SISO MIMO	5190	14.3	13.98	17.15	≤23.98	PASS
	5230	14.42	14.1	17.27	≤23.98	PASS
	5755	13.85	13.83	16.85	≤30.00	PASS
	5795	13.94	13.91	16.94	≤30.00	PASS
11AX20SISO MIMO	5180	14.34	14.16	17.26	≤23.98	PASS
	5220	14.45	14.36	17.42	≤23.98	PASS
	5240	14.34	14.15	17.26	≤23.98	PASS
	5745	13.92	13.58	16.76	≤30.00	PASS
	5785	14.04	13.77	16.92	≤30.00	PASS
	5825	13.9	13.52	16.72	≤30.00	PASS
11AX40SISO MIMO	5190	14.12	14.09	17.12	≤23.98	PASS
	5230	14.39	14.25	17.33	≤23.98	PASS
	5755	13.99	13.72	16.87	≤30.00	PASS
	5795	14.14	13.97	17.07	≤30.00	PASS

4.4 Power Spectral Density

Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.note1

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.note1

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. note1

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. note1

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. note1, note2

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 500KHz for U-NII 3 band.
3. Set the VBW ≥ 3× RBW.
4. Set the span to encompass the entire EBW.
5. Detector = Average.
6. Sweep time = auto couple.
7. Trace mode = Average hold.
8. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum power level.

Test Configuration

Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

MIMO

Test Mode	Freq(MHz)	Antenna1 For 5.2G [dBm/MHz] / For 5.8G [dBm/500KHz]	Antenna2 For 5.2G [dBm/MHz] / For 5.8G [dBm/500KHz]	MIMO For 5.2G [dBm/MHz] / For 5.8G [dBm/500KHz]	Limit [dBm]	Verdict
11N20SISO MIMO	5180	4.41	4.08	7.26	≤11.00	PASS
	5220	4.71	4.47	7.60	≤11.00	PASS
	5240	4.53	3.91	7.24	≤11.00	PASS
	5745	0.53	0.14	3.35	≤30.00	PASS
	5785	0.71	0.55	3.64	≤30.00	PASS
	5825	0.55	0.2	3.39	≤30.00	PASS
11N40SISO MIMO	5190	1.27	0.93	4.11	≤11.00	PASS
	5230	1.38	1.06	4.23	≤11.00	PASS
	5755	-2.3	-3.07	0.34	≤30.00	PASS
	5795	-2.12	-2.45	0.73	≤30.00	PASS
11AC20SISO MIMO	5180	4.09	4.18	7.15	≤11.00	PASS
	5220	4.53	4.31	7.43	≤11.00	PASS
	5240	3.88	4	6.95	≤11.00	PASS
	5745	0.29	-0.16	3.08	≤30.00	PASS
	5785	0.1	0.4	3.26	≤30.00	PASS
	5825	0.18	0.06	3.13	≤30.00	PASS
11AC40SISO MIMO	5190	0.71	0.22	3.48	≤11.00	PASS
	5230	0.74	0.59	3.68	≤11.00	PASS
	5755	-2.83	-2.87	0.16	≤30.00	PASS
	5795	-2.52	-2.83	0.34	≤30.00	PASS
11AX20SISO MIMO	5180	4.08	3.66	6.89	≤11.00	PASS
	5220	3.9	3.82	6.87	≤11.00	PASS
	5240	4.06	3.97	7.03	≤11.00	PASS
	5745	-0.09	-0.38	2.78	≤30.00	PASS
	5785	0.67	0.18	3.44	≤30.00	PASS
	5825	-0.08	-0.76	2.60	≤30.00	PASS
11AX40SISO MIMO	5190	0.52	0.26	3.40	≤11.00	PASS
	5230	0.86	0.77	3.83	≤11.00	PASS
	5755	-2.69	-3.26	0.04	≤30.00	PASS
	5795	-2.39	-2.76	0.44	≤30.00	PASS

Total Power Spectral Density (dBm/MHz)= Power Spectral Density (dBm/MHz)+ Duty Factor (dB)
Remark: P.S.D(dBm/500KHz)= P.S.D(dBm/300KHz)+10 log (500 kHz/300KHz)+ Duty factor.

RBW factor = 10 log (500 KHz / 300 KHz) = 2.22 dB

4.5 Emission Bandwidth (26dB Bandwidth)

Limit

No Limits for 26dBc Bandwith

Test Procedure

The procedure for this method is as follows:
a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
b) Set the VBW > RBW.
c) Detector = peak.
d) Trace mode = max-hold.
e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

Test Configuration

Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

4.6 Minimum Emission Bandwidth (6dB Bandwidth)

Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

The following procedure shall be used for measuring this bandwidth:
a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 × RBW.
c) Detector = Peak.
d) Trace mode = max-hold.
e) Sweep = No faster than coupled (auto) time.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration

Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI

4.7 Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:
The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20℃ operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30℃. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10℃ increased per stage until the highest temperature of +50℃ reached.

Frequency Stability under Voltage Variations:
Set chamber temperature to 20℃. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.
Reduce the input voltage to specify extreme voltage variation (±15%) and endpoint, record the maximum frequency change.

TEST RESULTS

Reference Frequency: 802.11ac channel=36 frequency=5180MHz					
Voltage (V)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
DC 14.4	-30	138.09	0.026659	Within the band of operation	Pass
	-20	126.08	0.024340		
	-10	103.03	0.019890		
	0	160.22	0.030931		
	10	159.10	0.030715		
	20	143.01	0.027608		
	30	105.16	0.020300		
	40	135.99	0.026254		
	50	153.04	0.029544		
DC 16.8	25	95.19	0.018376		
DC 13.6	25	133.02	0.025679		

Reference Frequency: 802.11ac channel=149 frequency=5745MHz					
Voltage (V)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
DC 14.4	-30	117.12	0.020386	Within the band of operation	Pass
	-20	167.95	0.029234		
	-10	120.01	0.020890		
	0	154.15	0.026832		
	10	134.21	0.023362		
	20	112.99	0.019668		
	30	149.03	0.025940		
	40	136.92	0.023834		
	50	143.14	0.024916		
DC 16.8	25	157.10	0.027345		
DC 13.6	25	116.21	0.020229		

4.8 On Time and Duty Cycle

Standard Applicable

None; for reporting purpose only.

TEST CONFIGURATION



Test Procedures

1). Set the Centre frequency of the spectrum analyzer to the transmitting frequency;
2). Set the span=0MHz, RBW=8MHz, VBW=8MHz, Sweep time=Auto;
3). Detector = peak;
4). Trace mode = Single hold.

TEST RESULTS

Please refer to FCC Appendix RF Test Data for 5GWIFI

4.9 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart E Section 15.407(a) (2):

If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connected Construction

The PIFA antenna maximum gain of antenna was 1.15 dBi for 5180-5240MHz for Antenna 1&2
1.18 dBi for 5745-5825MHz for Antenna 1&2.

Remark:The antenna gain is provided by the customer , if the data provided by the customer is not accurate, Shenzhen CTA Testing Technology Co., Ltd. does not assume any responsibility.

4.10 Emissions at Restricted Band

Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION

Test Procedures

According to ANSI C63.10 Field Strength Approach (linear terms):

$$E = EIRP - 20 \log d + 104.8$$

Where:
E is the electric field strength in dBuV/m
EIRP is the equivalent isotropically radiated power in dBm
d is the specified measurement distance in m
f) Compare the resultant electric field strength level with the applicable regulatory limit.
g) Perform the radiated spurious emission test.

Where all terms are as previously defined.

1). Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2). Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to an EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3). Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=3MHz for RMS detector, Max Hold=Average, Trace=100times for AV test.
4). Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5). Repeat above procedures until all measured frequencies were complete.
6). Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7). Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8). Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).

9). For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10). Compare the resultant electric field strength level to the applicable regulatory limit.
11). Perform radiated spurious emission test duress until all measured frequencies were complete.

Test Results

Please refer to FCC Appendix RF Test Data for 5GWIFI.

MIMO:

TestMode	ChName	Freq (MHz)	Detector	Freq [MHz]	Ant 1 Result [dBm]	Ant 2 Result [dBm]	MIMO Result [dBm]	Limit [dBm]	Verdict
11N20SISO	Low	5180	AV	4500.000	-59.53	-59.35	-56.43	≤-41.20	PASS
			AV	5142.600	-51.12	-54.29	-49.41	≤-41.20	PASS
			AV	5150.000	-51.75	-54.53	-49.91	≤-41.20	PASS
			Peak	4500.000	-51.98	-51.96	-48.96	≤-27.00	PASS
			Peak	5148.900	-41.4	-45.5	-39.97	≤-27.00	PASS
			Peak	5150.000	-43.1	-45.91	-41.27	≤-27.00	PASS
	High	5240	AV	5350.000	-55.22	-55.25	-52.22	≤-41.20	PASS
			AV	5357.040	-54.61	-54.76	-51.67	≤-41.20	PASS
			AV	5460.000	-56.1	-57.07	-53.55	≤-41.20	PASS
			Peak	5350.000	-47.38	-48.12	-44.72	≤-27.00	PASS
			Peak	5353.680	-44.87	-44.69	-41.77	≤-27.00	PASS
			Peak	5460.000	-49.39	-49.41	-46.39	≤-27.00	PASS
	Low	5745	Peak	5650.000	-49.107	-49.349	-46.22	≤-27.00	PASS
			Peak	5700.000	-47.81	-48.44	-45.10	≤10.00	PASS
			Peak	5720.000	-41.61	-45.94	-40.25	≤15.60	PASS
			Peak	5725.000	-38.01	-40.49	-36.07	≤27.00	PASS
	High	5825	Peak	5850.000	-42.148	-41.756	-38.94	≤27.00	PASS
			Peak	5855.000	-44.73	-44.89	-41.80	≤15.60	PASS
			Peak	5875.000	-46.75	-47.87	-44.26	≤10.00	PASS
			Peak	5925.000	-48.47	-48.68	-45.56	≤-27.00	PASS
11N40SISO	Low	5190	AV	4500.000	-59.44	-59.7	-56.56	≤-41.20	PASS
			AV	5149.600	-51.12	-50.91	-48.00	≤-41.20	PASS
			AV	5150.000	-51.8	-51.06	-48.40	≤-41.20	PASS
			Peak	4500.000	-51.98	-51.9	-48.93	≤-27.00	PASS
			Peak	5146.100	-40.51	-42.35	-38.32	≤-27.00	PASS
			Peak	5150.000	-42.74	-41.9	-39.29	≤-27.00	PASS
	High	5230	AV	5350.000	-54.91	-54.46	-51.67	≤-41.20	PASS
			AV	5356.260	-54.33	-54.44	-51.37	≤-41.20	PASS
			AV	5460.000	-56.64	-56.14	-53.37	≤-41.20	PASS
			Peak	5350.000	-45.08	-45.06	-42.06	≤-27.00	PASS
			Peak	5351.320	-44.67	-44.79	-41.72	≤-27.00	PASS
			Peak	5460.000	-48.54	-49.2	-45.85	≤-27.00	PASS
	Low	5755	Peak	5650.000	-49.057	-49.703	-46.36	≤-27.00	PASS
			Peak	5700.000	-47.22	-45.53	-43.28	≤10.00	PASS
			Peak	5720.000	-36.93	-39.74	-35.10	≤15.60	PASS
			Peak	5725.000	-39.07	-39.37	-36.21	≤27.00	PASS
	High	5795	Peak	5850.000	-40.942	-44.144	-39.24	≤27.00	PASS
			Peak	5855.000	-46.51	-44.91	-42.63	≤15.60	PASS
			Peak	5875.000	-46.59	-47.93	-44.20	≤10.00	PASS
			Peak	5925.000	-49.28	-46.7	-44.79	≤-27.00	PASS
11AC20SISO	Low	5180	AV	4500.000	-59.83	-59.49	-56.65	≤-41.20	PASS
			AV	5143.300	-50.97	-50.64	-47.79	≤-41.20	PASS
			AV	5150.000	-51.27	-50.74	-47.99	≤-41.20	PASS
			Peak	4500.000	-51.69	-52.66	-49.14	≤-27.00	PASS
			Peak	5140.500	-42.26	-41.37	-38.78	≤-27.00	PASS
			Peak	5150.000	-43.81	-43.53	-40.66	≤-27.00	PASS
	High	5240	AV	5350.000	-54.79	-55.28	-52.02	≤-41.20	PASS
			AV	5358.960	-54.79	-54.4	-51.58	≤-41.20	PASS
			AV	5460.000	-56.65	-56.48	-53.55	≤-41.20	PASS
			Peak	5350.000	-47.2	-45.47	-43.24	≤-27.00	PASS
			Peak	5364.480	-44.8	-44.54	-41.66	≤-27.00	PASS
			Peak	5460.000	-49.12	-49.1	-46.10	≤-27.00	PASS
	Low	5745	Peak	5650.000	-47.779	-47.509	-44.63	≤-27.00	PASS

			Peak	5700.000	-48.75	-48.97	-45.85	≤10.00	PASS
			Peak	5720.000	-44.31	-41.05	-39.37	≤15.60	PASS
			Peak	5725.000	-40.99	-39.83	-37.36	≤27.00	PASS
	High	5825	Peak	5850.000	-39.228	-37.918	-35.51	≤27.00	PASS
			Peak	5855.000	-44.62	-45.7	-42.12	≤15.60	PASS
			Peak	5875.000	-49.44	-48.14	-45.73	≤10.00	PASS
			Peak	5925.000	-47.72	-48.95	-45.28	≤-27.00	PASS
11AC40SISO	Low	5190	AV	4500.000	-59.56	-59.46	-56.50	≤-41.20	PASS
			AV	5149.600	-50.45	-51.14	-47.77	≤-41.20	PASS
			AV	5150.000	-50	-50.61	-47.28	≤-41.20	PASS
			Peak	4500.000	-52.81	-51.32	-48.99	≤-27.00	PASS
			Peak	5149.600	-39.66	-41.27	-37.38	≤-27.00	PASS
			Peak	5150.000	-40.51	-39.25	-36.82	≤-27.00	PASS
	High	5230	AV	5350.000	-55.62	-55.24	-52.42	≤-41.20	PASS
			AV	5356.260	-54.39	-54.79	-51.58	≤-41.20	PASS
			AV	5460.000	-55.83	-56.17	-52.99	≤-41.20	PASS
			Peak	5350.000	-47.8	-47.1	-44.43	≤-27.00	PASS
			Peak	5370.300	-45.1	-44.41	-41.73	≤-27.00	PASS
			Peak	5460.000	-48.24	-48.3	-45.26	≤-27.00	PASS
	Low	5755	Peak	5650.000	-48.606	-48.125	-45.35	≤-27.00	PASS
			Peak	5700.000	-45.82	-44.6	-42.16	≤10.00	PASS
			Peak	5720.000	-36.88	-40.33	-35.26	≤15.60	PASS
			Peak	5725.000	-38.86	-40.75	-36.69	≤27.00	PASS
	High	5795	Peak	5850.000	-45.46	-44.423	-41.90	≤27.00	PASS
			Peak	5855.000	-45.71	-46.86	-43.24	≤15.60	PASS
			Peak	5875.000	-47.61	-46.91	-44.24	≤10.00	PASS
			Peak	5925.000	-50.47	-49.6	-47.00	≤-27.00	PASS
11AX20SISO	Low	5180	AV	4500.000	-59.45	-60.07	-56.74	≤-41.20	PASS
			AV	5141.200	-51.29	-54.17	-49.49	≤-41.20	PASS
			AV	5150.000	-51.76	-54.12	-49.77	≤-41.20	PASS
			Peak	4500.000	-52.41	-50.9	-48.58	≤-27.00	PASS
			Peak	5148.900	-42.28	-44.51	-40.24	≤-27.00	PASS
			Peak	5150.000	-43.3	-45.49	-41.25	≤-27.00	PASS
	High	5240	AV	5350.000	-55.17	-54.88	-52.01	≤-41.20	PASS
			AV	5351.520	-54.8	-54.67	-51.72	≤-41.20	PASS
			AV	5460.000	-56.25	-56.43	-53.33	≤-41.20	PASS
			Peak	5350.000	-48.59	-47.08	-44.76	≤-27.00	PASS
			Peak	5378.160	-44.43	-45.01	-41.70	≤-27.00	PASS
			Peak	5460.000	-49.29	-50.18	-46.70	≤-27.00	PASS
	Low	5745	Peak	5650.000	-48.141	-48.867	-45.48	≤-27.00	PASS
			Peak	5700.000	-47.7	-47.53	-44.60	≤10.00	PASS
			Peak	5720.000	-43.36	-42.72	-40.02	≤15.60	PASS
			Peak	5725.000	-38.27	-38.39	-35.32	≤27.00	PASS
	High	5825	Peak	5850.000	-40.061	-37.415	-35.53	≤27.00	PASS
			Peak	5855.000	-46.38	-43.11	-41.43	≤15.60	PASS
			Peak	5875.000	-46.93	-47.76	-44.31	≤10.00	PASS
			Peak	5925.000	-47.9	-49.73	-45.71	≤-27.00	PASS
11AX40SISO	Low	5190	AV	4500.000	-59.44	-59.43	-56.42	≤-41.20	PASS
			AV	5149.600	-50.37	-49.67	-47.00	≤-41.20	PASS
			AV	5150.000	-50.84	-49.83	-47.30	≤-41.20	PASS
			Peak	4500.000	-51.36	-49.51	-47.33	≤-27.00	PASS
			Peak	5146.800	-39.61	-40.37	-36.96	≤-27.00	PASS
			Peak	5150.000	-42.09	-40.62	-38.28	≤-27.00	PASS
	High	5230	AV	5350.000	-54.82	-54.54	-51.67	≤-41.20	PASS
			AV	5352.100	-54.25	-54.3	-51.26	≤-41.20	PASS
			AV	5460.000	-56.02	-55.99	-52.99	≤-41.20	PASS
			Peak	5350.000	-45.99	-46.88	-43.40	≤-27.00	PASS
			Peak	5361.200	-44.58	-45.7	-42.09	≤-27.00	PASS
			Peak	5460.000	-48.19	-47.93	-45.05	≤-27.00	PASS
	Low	5755	Peak	5650.000	-49.324	-48.321	-45.78	≤-27.00	PASS
			Peak	5700.000	-46	-46.65	-43.30	≤10.00	PASS
			Peak	5720.000	-39	-37.43	-35.13	≤15.60	PASS
			Peak	5725.000	-39.86	-41.05	-37.40	≤27.00	PASS
	High	5795	Peak	5850.000	-43.052	-43.728	-40.37	≤27.00	PASS
			Peak	5855.000	-44.81	-46.25	-42.46	≤15.60	PASS
			Peak	5875.000	-47.31	-46.76	-44.02	≤10.00	PASS
			Peak	5925.000	-46.41	-47.94	-44.10	≤-27.00	PASS

Remark:
1). Test results including cable loss;
2). Measured at difference Packet Type for each mode and recorded worst case for each mode.
3). “---“means that the fundamental frequency not for 15.209 limits requirement.
4). Measured at Hopping and Non-Hopping mode, recorded worst at Non-Hopping mode.
5). The other emission levels were very low against the limit.
6). The average measurement was not performed when the peak measured data under the limit of average detection.
7). Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=3MHz/Sweep time=Auto/Detector=RMS, Max Hold=Average,Trace=100times.
8). Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

5 Test Setup Photos of the EUT







6 Photos of the EUT

Reference to the test report No. **CTA26040801101.**

********** End of Report **********