


Test Report No:
2650520R-RFUSV01S-A

TEST REPORT

FCC Rules & Regulations

Product Name	Peplink Pepwave Wireless Product
Brand Name	 PEPWAVE
Model No.	Balance 310 5G BPL-310-5GP-T-PRM MAX Orbit 8 MAX-ORB-8-T-PRM
FCC ID	2BVXV-P1BE04
Applicant's Name / Address	PSG TECHNOLOGIES (S) PTE. LIMITED 68 CIRCULAR ROAD, #02-01, SINGAPORE 049422
Manufacturer's Name	PSG TECHNOLOGIES (S) PTE. LIMITED
Test Method Requested, Standard	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Verdict Summary	IN COMPLIANCE
Documented by Jinn Chen	
Approved By Steven Tsai	
Date of Receipt	2026/05/20
Date of Issue	2026/07/15
Report Version	V1.0

INDEX

	page
Competences and Guarantees.....	4
General Conditions	4
Revision History	5
Summary of Test Result.....	6
1. General Information.....	7
1.1. EUT Description	7
1.2. EUT Information	8
1.3. Testing Location Information	8
1.4. Measurement Uncertainty	9
1.5. List of Test Equipment	10
2. Test Configuration of EUT	11
2.1. Test Condition.....	11
2.2. Test Frequency Mode.....	11
2.3. Duty Cycle	11
2.4. Measurement Configuration.....	13
2.5. Tested System Details.....	14
2.6. Configuration of Tested System	14
2.7. EUT Operating Procedures	15
3. AC Power Line Conducted Emission	16
3.1. Test Setup	16
3.2. Test Limit	16
3.3. Test Procedure	16
3.4. Test Result of AC Power Line Conducted Emission	16
4. 6 dB Bandwidth	17
4.1. Test Setup	17
4.2. Test Limit	17
4.3. Test Procedures	17
4.4. Test Result of 6dB Bandwidth	17
5. Maximum Conducted Output Power	18
5.1. Test Setup	18
5.2. Test Limit	18
5.3. Test Procedures	18
5.4. Test Result of Maximum Conducted Output Power	18
6. Power Spectral Density	19
6.1. Test Setup	19
6.2. Test Limit	19

6.3.	Test Procedures	19
6.4.	Test Result of Power Spectral Density	19
7.	Antenna Port Conducted Emission	20
7.1.	Test Setup	20
7.2.	Test Limit	20
7.3.	Test Procedure	20
7.4.	Test Result of Antenna Port Conducted Emission	20
8.	Radiated Emission	21
8.1.	Test Setup	21
8.2.	Test Limit	22
8.3.	Test Procedure	22
8.4.	Test Result of Radiated Emission	22
Appendix A. Test Result of AC Power Line Conducted Emission		
Appendix B. Test Result of 6 dB Bandwidth		
Appendix C. Test Result of Maximum Conducted Output Power		
Appendix D. Test Result of Power Spectral Density		
Appendix E. Test Result of Antenna Port Conducted Emission		
Appendix F. Test Result of Radiated Emission		
Appendix G. Test Setup Photograph		

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	2026/07/15

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
3	AC Power Line Conducted Emission	PASS	-
4	6 dB Bandwidth	PASS	-
5	Maximum Conducted Output Power	PASS	-
6	Power Spectral Density	PASS	-
7	Antenna Port Conducted Emission	PASS	-
8	Radiated Emission	PASS	-

Comments and Explanations

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1. General Information

1.1. EUT Description

Frequency Range	2400 ~ 2483.5 MHz	
Operating Frequency / Channel Number	IEEE 802.11b/g/n/ac/ax/be (20 MHz)	2412 ~ 2462 MHz / 11 Channels
	IEEE 802.11n/ac/ax/be (40 MHz)	2422 ~ 2452 MHz / 7 Channels
Type of Modulation	IEEE 802.11b	DSSS-DBPSK, DQPSK, CCK
	IEEE 802.11g/n	OFDM-BPSK, QPSK, 16QAM, 64QAM
	IEEE 802.11ac	OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM
	IEEE 802.11ax	OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
	IEEE 802.11be	OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM

Accessories Information					
No.	Equipment Name	Brand Name	Model No.	Rating	Remark
1	Adapter	FSP	FSP280-AWAU3	INPUT: 100-240V~,3.3A, 50-60Hz OUTPUT: 54.0V=5.19A 280.0W	With power cable: Non-shielded, 1.6m, with one ferrite core bonded.
No.	Equipment Name	Description			
2	Power Cord	Non-shielded, 1.8m			

The difference for each model is shown as below:

Model No.	Configuration
Balance 310 5G BPL-310-5GP-T-PRM	With WWAN Module
MAX Orbit 8 MAX-ORB-8-T-PRM	Remove WWAN module, antenna ports and SIM slots.

From the above models, model: Balance 310 5G was selected as representative model for the test and its data was recorded in this report.

Antenna Information				
Item.	Brand Name	Part No.	Type	Gain (dBi)
1	WIESON	ARY121-1976-001-00	Omni-directional	2.25

Directional Gain (dBi)	5.26
------------------------	------

Note:

1. The antenna of EUT conforms to FCC 15.203.
2. For IEEE 802.11b/g/n/ac/ax/be Mode: (2TX, 2RX)

1.2. EUT Information

EUT Power Type	From Adapter			
EUT Function	☒	Point-to-multipoint	☐	Point-to-point
Beamforming Function	☐	With beamforming	☒	Without beamforming
Resource Unit of 802.11ax/be	☒	Full RU	☐	Partial RU

1.3. Testing Location Information

USA	FCC Designation Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No. 85, Wenlin St., Linkou Dist., New Taipei City 244017, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual	Test Date	Tested By
AC Power Line	Temperature (°C)	10~40 °C	24.2 °C	2026/06/10	Leo Chen
Conducted Emission	Humidity (%RH)	10~90 %	62.6 %		
RF Conducted Emission	Temperature (°C)	10~40 °C	23.3~24.2 °C	2026/06/09 ~ 2026/06/17	Leo Chen
	Humidity (%RH)	10~90 %	61.5~65.6 %		
Radiated Emission	Temperature (°C)	10~40 °C	22.5~22.7 °C	2026/06/01 ~ 2026/06/11	Caster Liao
	Humidity (%RH)	10~90 %	60.6~61.2 %		

1.4. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
AC Power Line Conducted Emission	± 3.73 dB
6dB Bandwidth	± 1580.61 Hz
Maximum Conducted Output Power	Spectrum Analyzer: ± 2.13 dB Power Meter: ± 1.06 dB
Power Spectral Density	± 2.13 dB
Antenna Port Conducted Emission	± 2.13 dB
Radiated Emission	9 kHz~30 MHz: ± 3.30 dB 30 MHz~1 GHz: ± 5.39 dB 1 GHz~18 GHz: ± 4.24 dB 18 GHz~40 GHz: ± 3.62 dB
Duty Cycle	± 0.62 %

1.5. List of Test Equipment

For Conduction Measurements / HY-SR01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2026/04/20	2027/04/19
V	Two-Line V-Network	R&S	ENV216	101306	2026/03/27	2028/03/26
V	Two-Line V-Network	R&S	ENV216	101307	2025/08/06	2027/08/05
V	Coaxial Cable	SUHNER	RG400_BNC	RF001	2026/01/10	2027/01/09

Note:

1. Two-Line V-Network is calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Conducted Measurements / HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103467	2026/04/24	2027/04/23
V	Spectrum Analyzer	KEYSIGHT	N9010A	MY54510317	2025/08/04	2026/08/03
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2026/04/30	2027/04/29
V	Wideband Power Sensor	KEYSIGHT	N1923A	MY59240002	2026/05/06	2027/05/05
V	Wideband Power Sensor	KEYSIGHT	N1923A	MY59240003	2026/05/06	2027/05/05

Note:

1. All equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version : DTC_RF_Tool_Release V2.0.37.

For Radiated Measurements /HY-CB01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Loop Antenna	TESEQ	HLA6121	49611	2026/02/04	2027/02/03
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0675	2025/08/14	2027/08/13
V	Horn Antenna	RF SPIN	DRH18-E	210802A18ES	2026/03/26	2028/03/25
V	Horn Antenna	Com-Power	AH-840	101100	2025/10/07	2027/10/06
V	Pre-Amplifier	SGH	SGH0301	20230308-1	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC051845SE	980632	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980362	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2026/01/10	2027/01/09
V	Coaxial Cable	EMCI	EMC102-KM-KM-600	160311	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HC360-2.92M/2.92M-7.0M	202108-1	2026/01/10	2027/01/09
V	Filter	MICRO TRONICS	BRM20887	G001	2026/01/05	2027/01/04
	Filter	MICRO TRONICS	BRM50716	067	2026/01/05	2027/01/04
V	EMI Test Receiver	R&S	ESR3	102793	2025/12/01	2026/11/30
V	Spectrum Analyzer	R&S	FSV3044	101115	2025/12/22	2026/12/21
V	Coaxial Cable	SUHNER	SUCOFLEX 106	25450/6	2026/01/10	2027/01/09
V	Coaxial Cable	SUHNER	SUCOFLEX 106	36738-6	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800	202212-5	2026/01/10	2027/01/09
V	Coaxial Cable	EMCI	EMC106	151113	2026/01/10	2027/01/09
V	Radio communication test station	Anritsu	MT8000A	6262134961	2026/05/04	2027/05/03
V	Radio communication test station	Anritsu	8820C	6201091166	2026/04/13	2027/04/12

Note:

1. Bi-Log Antenna and Horn Antenna are calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition	
Testing Voltage	AC 120V/60Hz to DC 54V (AC Adapter)

2.2. Test Frequency Mode

Test Software Version	QSPR / Version 6.00.00258.1
-----------------------	-----------------------------

2.3. Duty Cycle

Modulation	On Times (ms)	On+Off Times (ms)	Duty Cycle (%)	Duty Factor (dB)	VBW (Hz)
802.11b (20 MHz)	0.6880	0.8500	80.94	0.92	2000
802.11g (20 MHz)	1.9550	2.0150	97.02	0.13	1000
802.11be (20 MHz)	5.3800	5.5400	97.11	0.13	200
802.11be (40 MHz)	5.4203	5.5362	97.91	0.09	200



2.4. Measurement Configuration

Test Mode	Mode 1 (Transmit)	802.11b (20 MHz)
		802.11g (20 MHz)
		802.11be (20 MHz)
		802.11be (40 MHz)


Note:

1. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. For radiated emission below 1 GHz and AC power line conducted emission have performed all modes of operation were investigated and the worst-case emissions are reported.
3. Lowest data rates are tested in each mode. Only worst case is shown in the report.
(802.11b is 1 Mbps, 802.11g is 6 Mbps, 802.11be is MCS0.)
4. The modulation and bandwidth are similar across 802.11n mode, 802.11ac mode, 802.11ax mode, and 802.11be mode. Therefore, the worst case was evaluated and selected to represent the 802.11be modes in the test report.

2.5. Tested System Details

No.	Equipment	Brand Name	Model No.	Serial No.	Power Cord
1	Adapter	FSP	FSP280-AWAU3	N/A	N/A
2	Notebook PC	ACER	N19Q7	N/A	N/A
3	LAN Hub	TP-LINK	TL-SG108	2161597000471	N/A
4	Notebook PC	DELL	P62G	CY9FJC2	N/A
5	Notebook PC	DELL	Latitude 5501	GS9GL13	N/A
6	Notebook PC	DELL	Latitude E5440	FS9TK32	N/A
7	SFP	Dawnray	SFP+10G-T	N/A	N/A
8	SIM Card	R&S	CMW-Z06	N/A	N/A
9	FLASH	Transcend	JetFlash 790C/64GB	N/A	N/A
10	FLASH	Transcend	JetFlash 790C/64GB	N/A	N/A

2.6. Configuration of Tested System




2.7. EUT Operating Procedures

1	Setup the EUT as shown in Section 2.6.
2	Execute software "QSPR / Version 6.00.00258.1" on the Notebook PC.
3	Configure the test mode, the test channel, and the data rate.
4	Verify that the EUT works properly.

3. AC Power Line Conducted Emission

3.1. Test Setup



3.2. Test Limit

Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

3.3. Test Procedure


The EUT was setup according to ANSI C63.10-2020 for AC Power Line Conducted Emissions.

3.4. Test Result of AC Power Line Conducted Emission

Refer as Appendix A

4. 6 dB Bandwidth

4.1. Test Setup



4.2. Test Limit

The 6 dB bandwidth: ≥ 500 kHz.

4.3. Test Procedures


The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.

4.4. Test Result of 6dB Bandwidth

Refer as Appendix B

5. Maximum Conducted Output Power

5.1. Test Setup



5.2. Test Limit

The Maximum Conducted Output Power shall be less 30 dBm (1 Watt).

5.3. Test Procedures


The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.

5.4. Test Result of Maximum Conducted Output Power

Refer as Appendix C

6. Power Spectral Density

6.1. Test Setup



6.2. Test Limit

The power spectral density conducted from the intentional radiated to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedures


The EUT was setup according to ANSI C63.10-2020; tested according to DTS test procedure of KDB 558074.

6.4. Test Result of Power Spectral Density

Refer as Appendix D

7. Antenna Port Conducted Emission

7.1. Test Setup



7.2. Test Limit

RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30

Remarks:

1. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limit.
2. If the transmitter complies with the conducted power limit based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.3. Test Procedure

The EUT was setup according to ANSI C63.10-2020 and tested according to DTS test procedure of KDB 558074.


7.4. Test Result of Antenna Port Conducted Emission

Refer as Appendix E


8. Radiated Emission

8.1. Test Setup


9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



Above 1 GHz



8.2. Test Limit

Frequency (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	20 log (2400/F(kHz))	300
0.490 – 1.705	24000/F(kHz)	20 log (24000/F(kHz))	30
1.705 - 30	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Remarks:

1. Field strength (dBuV/m) = 20 log Field strength (uV/m)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

8.3. Test Procedure

The EUT was setup according to ANSI C63.10-2020 and tested according to DTS test procedure of KDB 558074.

The EUT and its simulators are placed on a turn table which is 0.8 or 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10-2020 on radiated measurement.

On any frequency or frequencies from 9 kHz(include The the lowest oscillator frequency generated within the device up to the 10th harmonic) to 1000 MHz, the limit shown are based on measuring equipment employing a quasi-peak detector function and on any frequency or frequencies above 1000 MHz the radiated limit shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth below 1 GHz setting on the field strength meter is 120 kHz and above 1 GHz is 1 MHz.

8.4. Test Result of Radiated Emission

Refer as Appendix F