



TEST REPORT

Applicant: JAWAWAKEN TECHNOLOGY CO., LTD.
Address of Applicant: Room 2403, East Tower, Lupu Building, No. 60 Xingke Road, Xili Street, Nanshan District, Shenzhen City, Guangdong Province China
Manufacturer: JAWAWAKEN TECHNOLOGY CO., LTD.
Address of Manufacturer: Room 2403, East Tower, Lupu Building, No. 60 Xingke Road, Xili Street, Nanshan District, Shenzhen City, Guangdong Province China
Product Name: Mini PC
Model No.: LS5, LS5 mini, LS5 PRO, LS5 ULTRA, LS5 MAX, LS5 AI
Trade Mark: jwawaken
FCC ID: 2BVYQ-LS5
Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
Date of Test: Mar.14, 2025-Mar.25, 2026
Date of report issued: Mar.26, 2026

Remark:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Reviewed by:

Approved by:

Project Engineer

Project Manager

Authorized Signature



Report Revision History		
Report No.	Description	Issue Date
ET-26030855E03	Original	Mar.26,2026



Contents

Page

1	TEST SUMMARY	4
1.1	MEASUREMENT UNCERTAINTY	4
2	GENERAL INFORMATION	5
2.1	GENERAL DESCRIPTION OF EUT	5
2.2	TEST MODE	7
2.3	DESCRIPTION OF SUPPORT UNITS	8
2.4	TEST FACILITY	8
2.5	ADDITIONAL INSTRUCTIONS.....	8
3	TEST INSTRUMENTS LIST	9
4	TEST RESULTS AND MEASUREMENT DATA	10
4.1	ANTENNA REQUIREMENT	10
4.2	CONDUCTED EMISSIONS	11
4.3	DUTY CYCLE.....	14
4.4	CONDUCTED OUTPUT POWER	18
4.5	OCCUPY BANDWIDTH	20
4.6	POWER SPECTRAL DENSITY	36
4.7	BAND EDGE.....	53
4.7.1	Conducted test Method	53
4.8	SPURIOUS EMISSION	79
4.8.1	Radiated Emission Method	79
4.9	FREQUENCY STABILITY	89
5	TEST SETUP PHOTO	95
6	EUT CONSTRUCTIONAL DETAILS.....	95

1 Test Summary

Test Item	Section in CFR 47	Result	Test by
Antenna requirement	47CFR part 15.203	Pass	/
AC Power Line Conducted Emission	47CFR part 15.207	Pass	Jason Huang
Conducted Output Power	47CFR part 15.407 (a)(1)/(a)(3)	Pass	Kara Wu
26dB Bandwidth	47CFR part 15.407 (a)(12)	Pass	Kara Wu
6dB Bandwidth	47CFR part 15.407 (e)	Pass	Kara Wu
Power Spectral Density	47CFR part 15.407(a)(1)/(a)(3)	Pass	Kara Wu
Band Edge	47CFR part 15.407(b)(1)/(b)(4)	Pass	Kara Wu
Spurious Emission	47CFR part 15.205/15.209 47CFR part 15.407(b)(1)/(b)(4)/(b)(8)	Pass	Jason Huang
Frequency Stability	47CFR part 15.407(g)	Pass	Kara Wu

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10-2020+COR 1-2023 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
3. Note: Compliance determination rules
 - 1). The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacture. If measurement uncertainty is taken into account, the applicant/manufacture will bear all possible risks of non-compliance.
 - 2). The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"

1.1 Measurement Uncertainty

Test Item	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	0.72%	(1)
RF output power, conducted	±0.67 dB	(1)
Power Spectral Density, conducted	±0.51 dB	(1)
Unwanted Emissions, conducted	±0.64 dB	(1)
AC Power Line Conducted Emission	± 3.38 dB	(1)
Radiated emissions 9K-30MHz	±4.26 dB	(1)
Radiated emissions 30M- 1GHz	±4.88 dB	(1)
Radiated emissions 1GHz-18GHz	± 4.16 dB	(1)
Radiated emissions 18GHz-40GHz	±4.14 dB	(1)
Frequency error	Uc=6X10 ⁻⁷	(1)
Duty Cycle	0.03	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.



2 General Information

2.1 General Description of EUT

Product Name:	Mini PC
Model No.:	LS5, LS5 mini,LS5 PRO,LS5 ULTRA,LS5 MAX,LS5 AI
Difference of model(s)	All the model are the same circuit and RF module, except the model names and housing colors.
Test Model:	LS5
Hardware Version:	N/A
Software Version:	N/A
Power supply:	DC 19V From Adapter
Adapter information:	Model: HKA12019063-0A3 INPUT:AC 100-240V 50/60Hz Output:DC 19V 6.32A
Battery:	N/A
Radio Technology:	5G RLAN
Operation Frequency:	☒ 5180-5240MHz for 802.11a/n20/ac20 5190-5230MHz for 802.11n40/ac40 5210MHz for 802.11ac80 ☒ 5745-5825 MHz for 802.11a/n20/ac20 5755-5795 MHz for 802.11n40/ac40 5775MHz for 802.11 ac80
Channel numbers:	☒ 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band; 2 channels for 802.11 n40/ac40 in the 5190-5230MHz band ; 1 channels for 802.11 ac80 in the 5210MHz band ; ☒ 5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40 in the 5755-5795MHz band ; 1 channels for 802.11 ac80 in the 5775MHz band
Channel bandwidth:	802.11an20/ ac20 : 20MHz 802.11n40/ac40 : 40MHz 802.11ac80 : 80MHz
Modulation technology:	Orthogonal Frequency Division Multiplexing (OFDM) with BPSK/QPSK/16QAM/64QAM/256QAM
Antenna Type:	FPC antenna
Antenna gain:	2.11dBi
Note: <i>1.For more details, refer to the user's manual of the EUT.</i> <i>2.Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information</i>	



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	38	5190MHz	40	5200MHz	42	5210MHz
44	5220MHz	46	5230MHz	48	5240MHz	/	/
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	153	5765MHz	155	5775MHz
157	5785MHz	159	5795MHz	161	5805MHz	/	/
165	5825MHz	/					

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)		
	802.11 a /n20/ac20	802.11 n40/ac40	802.11ac80
Lowest channel	5180	5190	5210
Middle channel	5200		
Highest channel	5240		

Test channel	Frequency (MHz)		
	802.11 a /n20/ac20	802.11 n40/ac40	802.11ac80
Lowest channel	5745	5755	5775
Middle channel	5785		
Highest channel	5825		

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pretest Mode	Description
Mode 1	802.11a / n20/ ac20 CH36/CH40/CH48 802.11a /n 20/ac 20 CH149/CH157/CH165
Mode 2	802.11n 40/ac40 CH38/CH46 802.11n 40/ac40 CH 151/CH159
Mode 3	802.11 ac80 CH 42/CH155
Mode 4	/
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a / n20/ ac20 CH36/CH40/CH48 802.11a /n 20/ac 20 CH149/CH157/CH165
Mode 2	802.11n 40/ac40 CH38/CH46 802.11n 40/ac40 CH 151/CH159
Mode 3	802.11 ac80 CH 42/CH155
Mode 4	/

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
1	Monitor	SKYWORTH	2BU1	/
2	Mouse	DELL	MS116	/
3	Keyboard	DELL	KB216t	/

2.4 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064
IC Company Number:	28440
IC CAB identifier:	CN0132
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

2.5 Additional Instructions

Test Software	DRTU.EXE
Power level setup	Default



3 Test Instruments list

Conducted Emission

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI3	102696	2026.3.05	2027.3.04
2	Artificial power network	schwarabeck	NSLK8127	8127483	2026.3.05	2027.3.04
3	Artificial power network	ETS	3186/2NM	1132	2026.3.05	2027.3.04
4	10dB attenuator	HUBER+SUHNER	10dB	/	2026.3.05	2027.3.04
5	Cable 4	HUBER SUNNER	3M	/	2026.3.05	2027.3.04
6	Absorbing Clamp	schwarabeck	MDS21	D69250	2025.3.06	2026.3.05

Radiated Emission & RF Conducted test:

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101214	2026.3.05	2027.3.04
2	Broadband antenna	schwarabeck	VULB9168	1064	2026.3.11	2028.3.10
3	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2026.3.08	2028.3.07
4	Amplifier	EMtrace	RP01A	50117	2026.3.05	2027.3.04
5	Amplifier	Space-Dtronics	EWLAN0118G-P40	19113001	2026.3.05	2027.3.04
6	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2026.3.05	2027.3.04
7	Power detector meter	MWRFTtest	MW100-PSB	MW201020JYT	2026.3.05	2027.3.04
8	Signal generator	Agilent	N5182A	MY49060455	2026.3.05	2027.3.04
9	Spectrum analyzer	Rohde&schwarz	FSV-40N	102137	2026.3.05	2027.3.04
10	Amplifier	SKET	LNPA_1840-50	SK2019040302	2026.3.05	2027.3.04
11	Horn antenna	schwarabeck	BBHA 9170	946	2026.3.08	2028.3.07
12	Loop antenna	schwarabeck	FMZB 1519 B	128	2026.3.08	2028.3.07
13	Cable 6	HUBER SUNNER	0.5M	/	2026.3.05	2027.3.04
14	Cable7	HUBER SUNNER	2.0M	/	2026.3.05	2027.3.04
15	Cable8	HUBER SUNNER	6.0M	/	2026.3.05	2027.3.04
16	Filter	Xin bo	XBLBQ-GTA29	210410-3-2	2026.3.05	2027.3.04
17	Power Sensor	Keysight	U2021XA	MY54111006	2026.3.05	2027.3.04
18	Temp. & Humidity Chamber	Jiecheng Instrument	QA-LP-80	20160705001	2026/3/06	2027/3/05

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFTtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4 Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:	47CFR Part 15.203
<i>15.203 requirement:</i> <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
The antenna is FPC antenna, the best case gain of the antenna is 2.11dBi, reference to the ET-26030855IP for details.	

4.2 Conducted Emissions


Test Requirement:	47CFR Part 15.207						
Test Method:	ANSI C63.10-2020+COR 1-2023 §6.2						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane <i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network						
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2020+COR 1-2023 on conducted measurement.						
Test Instruments:	Refer to section 3.0 for details						
Test mode:	Refer to section 2.2 for details						
Test environment:	Temp.:	24.2°C	Humid.:	51%	Press.:	1012mbar	
Test voltage:	AC 120V 60Hz						
Test results:	Pass						

Remark:

1. Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V/60Hz.


Measurement Result

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1590	40.93	9.97	50.90	65.52	-14.62	QP
2	0.1590	26.38	9.97	36.35	55.52	-19.17	AVG
3	0.3709	40.51	10.04	50.55	58.48	-7.93	QP
4	0.3709	33.42	10.04	43.46	48.48	-5.02	AVG
5	0.6900	38.33	10.08	48.41	56.00	-7.59	QP
6	0.6900	27.87	10.08	37.95	46.00	-8.05	AVG
7	1.1172	36.43	10.08	46.51	56.00	-9.49	QP
8	1.1172	25.11	10.08	35.19	46.00	-10.81	AVG
9	10.0500	36.77	10.08	46.85	60.00	-13.15	QP
10	10.0500	19.84	10.08	29.92	50.00	-20.08	AVG
11	24.6750	35.73	9.85	45.58	60.00	-14.42	QP
12	24.6750	20.81	9.85	30.66	50.00	-19.34	AVG

Neutral:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1621	38.56	9.97	48.53	65.36	-16.83	QP
2	0.1621	26.83	9.97	36.80	55.36	-18.56	AVG
3	0.3750	36.10	10.04	46.14	58.39	-12.25	QP
4	0.3750	29.98	10.04	40.02	48.39	-8.37	AVG
5	0.8067	29.82	10.09	39.91	56.00	-16.09	QP
6	0.8067	24.57	10.09	34.66	46.00	-11.34	AVG
7	1.3784	31.94	10.05	41.99	56.00	-14.01	QP
8	1.3784	22.87	10.05	32.92	46.00	-13.08	AVG
9	10.1760	35.55	10.08	45.63	60.00	-14.37	QP
10	10.1760	19.55	10.08	29.63	50.00	-20.37	AVG
11	24.4500	36.81	9.85	46.66	60.00	-13.34	QP
12	24.4500	20.94	9.85	30.79	50.00	-19.21	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Duty cycle

Test Method :	ANSI C63.10-2020+COR 1-2023§ 12.2	
Limit:	/	
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.4°C	Humid.: 41%RH
Test voltage:	DC 19V	
Test results:	Pass	

Measurement Result

5180-5240MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	100	0
TX 802.11n20 Mode	100	0
TX 802.11ac20 Mode	100	0
TX 802.11n40 Mode	100	0
TX 802.11ac40 Mode	100	0
TX 802.11ac80 Mode	100	0

5745-5825 MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	100	0
TX 802.11n20 Mode	100	0
TX 802.11ac20 Mode	100	0
TX 802.11n40 Mode	100	0
TX 802.11ac40 Mode	100	0
TX 802.11ac80 Mode	100	0


*Note: Duty cycle factor (dB) = $10 * \log (1/ \text{Duty cycle})$*




Test plot

5180-5240MHz


(802.11a) plot




(802.11 n20) plot




(802.11ac20) plot




(802.11 n40) plot



(802.11ac40) plot




(802.11ac80) plot






5745-5825 MHz


(802.11a) plot




(802.11 n20) plot




(802.11ac20) plot




(802.11 n40) plot




(802.11ac40) plot



(802.11ac80) plot



4.4 Conducted Output Power

Test Requirement:	47CFR Part 15.407 (a)(1)/(a)(3)	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 ANSI C63.10-2020+COR 1-2023 § 12.4.3.1	
Limit:	5150-5250MHz : 250mW 5725~5850MHz : 1W	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.4°C	Humid.: 41%RH
Test voltage:	DC 19V	
Test results:	Pass	



Measurement Result


5180-5240MHz

Test Mode	Test Channel	Frequency	Correction Factor	Output power	Total Power	Result
		(MHz)	(dB)	(dBm)	(dBm)	
802.11a	CH36	5180	0	14.12	14.12	Pass
	CH40	5200	0	14.00	14.00	Pass
	CH48	5240	0	14.33	14.33	Pass
802.11n20	CH36	5180	0	13.99	13.99	Pass
	CH40	5200	0	14.40	14.40	Pass
	CH48	5240	0	14.25	14.25	Pass
802.11ac20	CH36	5180	0	14.82	14.82	Pass
	CH40	5200	0	14.78	14.78	Pass
	CH48	5240	0	14.31	14.31	Pass
802.11n40	CH38	5190	0	13.03	13.03	Pass
	CH46	5230	0	13.08	13.08	Pass
802.11ac40	CH38	5190	0	13.09	13.09	Pass
	CH46	5230	0	13.40	13.40	Pass
802.11ac80	CH42	5210	0	12.32	12.32	Pass

5745-5825 MHz

Test Mode	Test Channel	Frequency	Correction Factor	Output power	Total Power	Result
		(MHz)	(dB)	(dBm)	(dBm)	
802.11a	CH149	5745	0	14.22	14.22	Pass
	CH157	5785	0	14.31	14.31	Pass
	CH165	5825	0	14.51	14.51	Pass
802.11n20	CH149	5745	0	14.66	14.66	Pass
	CH157	5785	0	14.39	14.39	Pass
	CH165	5825	0	14.32	14.32	Pass
802.11ac20	CH149	5745	0	14.71	14.71	Pass
	CH157	5785	0	14.10	14.10	Pass
	CH165	5825	0	14.34	14.34	Pass
802.11n40	CH151	5755	0	13.16	13.16	Pass
	CH159	5795	0	13.38	13.38	Pass
802.11ac40	CH151	5755	0	13.57	13.57	Pass
	CH159	5795	0	13.70	13.70	Pass
802.11ac80	CH42	5210	0	12.18	12.18	Pass

4.5 Occupancy Bandwidth


Test Requirement:	47CFR Part 15.407(a)(12)&15.407(e),	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, ANSI C63.10-2020+COR 1-2023§12.5	
Limit:	Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.4°C	Humid.: 41%RH
Test voltage:	DC 19V	
Test results:	Pass	

Measurement Result


5180-5240MHz

Condition	Mode	Frequency (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	29.70	Pass
NVNT	a	5200	29.96	Pass
NVNT	a	5240	30.00	Pass
NVNT	n20	5180	29.99	Pass
NVNT	n20	5200	30.00	Pass
NVNT	n20	5240	30.00	Pass
NVNT	n40	5190	59.68	Pass
NVNT	n40	5230	60.00	Pass
NVNT	ac20	5180	27.69	Pass
NVNT	ac20	5200	28.23	Pass
NVNT	ac20	5240	27.51	Pass
NVNT	ac40	5190	57.63	Pass
NVNT	ac40	5230	60.00	Pass
NVNT	ac80	5210	119.89	Pass


-26dB Bandwidth NVNT a 5180MHz Ant1




-26dB Bandwidth NVNT a 5200MHz Ant1




-26dB Bandwidth NVNT a 5240MHz Ant1




-26dB Bandwidth NVNT n20 5180MHz Ant1




-26dB Bandwidth NVNT n20 5200MHz Ant1




-26dB Bandwidth NVNT n20 5240MHz Ant1




-26dB Bandwidth NVNT n40 5190MHz Ant1




-26dB Bandwidth NVNT n40 5230MHz Ant1




-26dB Bandwidth NVNT ac20 5180MHz Ant1




-26dB Bandwidth NVNT ac20 5200MHz Ant1




-26dB Bandwidth NVNT ac20 5240MHz Ant1




-26dB Bandwidth NVNT ac40 5190MHz Ant1



-26dB Bandwidth NVNT ac40 5230MHz Ant1



-26dB Bandwidth NVNT ac80 5210MHz Ant1







5745-5825MHz

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	a	5745	16.34	0.5	Pass
NVNT	a	5785	16.33	0.5	Pass
NVNT	a	5825	16.35	0.5	Pass
NVNT	n20	5745	17.58	0.5	Pass
NVNT	n20	5785	17.58	0.5	Pass
NVNT	n20	5825	17.59	0.5	Pass
NVNT	n40	5755	36.07	0.5	Pass
NVNT	n40	5795	35.99	0.5	Pass
NVNT	ac20	5745	17.58	0.5	Pass
NVNT	ac20	5785	17.58	0.5	Pass
NVNT	ac20	5825	17.53	0.5	Pass
NVNT	ac40	5755	35.92	0.5	Pass
NVNT	ac40	5795	35.27	0.5	Pass
NVNT	ac80	5775	76.33	0.5	Pass


-6dB Bandwidth NVNT a 5745MHz Ant1




-6dB Bandwidth NVNT a 5785MHz Ant1




-6dB Bandwidth NVNT a 5825MHz Ant1




-6dB Bandwidth NVNT n20 5745MHz Ant1




-6dB Bandwidth NVNT n20 5785MHz Ant1




-6dB Bandwidth NVNT n20 5825MHz Ant1




-6dB Bandwidth NVNT n40 5755MHz Ant1




-6dB Bandwidth NVNT n40 5795MHz Ant1




-6dB Bandwidth NVNT ac20 5745MHz Ant1




-6dB Bandwidth NVNT ac20 5785MHz Ant1




-6dB Bandwidth NVNT ac20 5825MHz Ant1




-6dB Bandwidth NVNT ac40 5755MHz Ant1




-6dB Bandwidth NVNT ac40 5795MHz Ant1



-6dB Bandwidth NVNT ac80 5775MHz Ant1



4.6 Power Spectral Density

Test Requirement:	47CFR Part 15.407(a)(1)/ (a)(3)	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, ANSI C63.10-2020+COR 1-2023§12.6	
Limit:	Frequency band (MHz)	Limit
	5150-5250	≤17dBm/1MHz for master device
		≤11dBm/1MHz for client device
	5250-5350	≤11dBm/1MHz for client device
	5470-5725	≤11dBm/1MHz for client device
	5725-5850	≤30dBm/500kHz
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.4°C	Humid.: 41%RH
Test voltage:	DC 19V	
Test results:	Pass	




Measurement Result


5180-5240MHz

Mode	Frequency	Measured Power Density (dBm/MHz)	Correction Factor (dB)	Total Measured Power Density (dBm/MHz)	Limit (dBm/MHz)
802.11 a	5180 MHz	-0.047	0	-0.047	11
	5200 MHz	-0.103	0	-0.103	11
	5240 MHz	-0.102	0	-0.102	11
802.11 n20	5180 MHz	-0.618	0	-0.618	11
	5200 MHz	-0.14	0	-0.14	11
	5240 MHz	-0.291	0	-0.291	11
802.11 ac20	5180 MHz	-2.443	0	-2.443	11
	5200 MHz	-2.398	0	-2.398	11
	5240 MHz	-3.324	0	-3.324	11
802.11 n40	5190 MHz	-4.042	0	-4.042	11
	5230 MHz	-4.061	0	-4.061	11
802.11 ac40	5190 MHz	-4.361	0	-4.361	11
	5230 MHz	-4.102	0	-4.102	11
802.11 ac80	5210 MHz	-8.076	0	-8.076	11


PSD NVNT a 5180MHz Ant1




PSD NVNT a 5200MHz Ant1




PSD NVNT a 5240MHz Ant1




PSD NVNT n20 5180MHz Ant1




PSD NVNT n20 5200MHz Ant1




PSD NVNT n20 5240MHz Ant1




PSD NVNT n40 5190MHz Ant1




PSD NVNT n40 5230MHz Ant1




PSD NVNT ac20 5180MHz Ant1




PSD NVNT ac20 5200MHz Ant1




PSD NVNT ac20 5240MHz Ant1




PSD NVNT ac40 5190MHz Ant1



PSD NVNT ac40 5230MHz Ant1



PSD NVNT ac80 5210MHz Ant1






Mode	Frequency MHz	Measured Power Density (dBm/510KHz)	Measured Power Density (dBm/500KHz)	Correction Factor (dB)	Total Measured Power Density (dBm/500KHz)	Limit (dBm/500kHz)
802.11a	5745	-2.802	-2.888	0	-2.888	30
	5785	-2.778	-2.864	0	-2.864	30
	5825	-2.565	-2.651	0	-2.651	30
802.11n20	5745	-2.404	-2.49	0	-2.49	30
	5785	-2.952	-3.038	0	-3.038	30
	5825	-2.803	-2.889	0	-2.889	30
802.11ac20	5745	-2.373	-2.459	0	-2.459	30
	5785	-3.448	-3.534	0	-3.534	30
	5825	-2.661	-2.747	0	-2.747	30
802.11n40	5755	-7.438	-7.524	0	-7.524	30
	5795	-6.861	-6.947	0	-6.947	30
802.11ac40	5755	-6.855	-6.941	0	-6.941	30
	5795	-6.495	-6.581	0	-6.581	30
802.11ac80	5775	-11.429	-11.515	0	-11.515	30

Note: 1. If the measurement is X dBm/510kHz, thus $X \text{ dBm/510kHz} = (10^{X/10}) * (500 / 510) \text{ dBm/500kHz}$


2. Correction Factor (dB)= duty cycle factor

3. Total PSD= Measured PSD (dBm/510kHz) + Correction factor duty cycle (dB)


PSD NVNT a 5745MHz Ant1




PSD NVNT a 5785MHz Ant1




PSD NVNT a 5825MHz Ant1




PSD NVNT n20 5745MHz Ant1




PSD NVNT n20 5785MHz Ant1




PSD NVNT n20 5825MHz Ant1




PSD NVNT n40 5755MHz Ant1




PSD NVNT n40 5795MHz Ant1




PSD NVNT ac20 5745MHz Ant1




PSD NVNT ac20 5785MHz Ant1




PSD NVNT ac20 5825MHz Ant1




PSD NVNT ac40 5755MHz Ant1



PSD NVNT ac40 5795MHz Ant1




PSD NVNT ac80 5775MHz Ant1



4.7 Band edge

4.7.1 Conducted test Method

Test Requirement:	47CFR Part 15.209 and 15.205	
Test Method:	ANSI C63.10-2020+COR 1-2023 §6.10.2	
Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating solely in the 5.725-5.850 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.	
Test Procedure:	1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range. 3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span. 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. 5. Repeat above procedures until all measured frequencies were complete..	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.4°C	Humid.: 41%RH
Test voltage:	DC 19V	
Test results:	Pass	




Condition	Mode	Frequenc y (MHz)	Antenna	Max Value (dBc)	Antenna(dBi)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	a	5180	Ant1	-46.10	2.11	-43.99	-27	Pass
NVNT	a	5240	Ant1	-46.43	2.11	-44.32	-27	Pass
NVNT	n20	5180	Ant1	-45.90	2.11	-43.79	-27	Pass
NVNT	n20	5240	Ant1	-46.91	2.11	-44.80	-27	Pass
NVNT	n40	5190	Ant1	-47.22	2.11	-45.11	-27	Pass
NVNT	n40	5230	Ant1	-46.68	2.11	-44.57	-27	Pass
NVNT	ac20	5180	Ant1	-47.06	2.11	-44.95	-27	Pass
NVNT	ac20	5240	Ant1	-46.69	2.11	-44.58	-27	Pass
NVNT	ac40	5190	Ant1	-45.93	2.11	-43.82	-27	Pass
NVNT	ac40	5230	Ant1	-46.39	2.11	-44.28	-27	Pass
NVNT	ac80	5210	Ant1	-43.15	2.11	-41.04	-27	Pass




UNII-1


Band Edge NVNT a 5180MHz Low Ant1




Band Edge NVNT a 5240MHz High Ant1




Band Edge NVNT n20 5180MHz Low Ant1




Band Edge NVNT n20 5240MHz High Ant1




Band Edge NVNT n40 5190MHz Low Ant1




Band Edge NVNT n40 5230MHz High Ant1




Band Edge NVNT ac20 5180MHz Low Ant1




Band Edge NVNT ac20 5240MHz High Ant1




Band Edge NVNT ac40 5190MHz Low Ant1



Band Edge NVNT ac40 5230MHz High Ant1



Band Edge NVNT ac80 5210MHz Low Ant1






Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Antenna(dBi)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	a	5745	Ant1	-42.74	2.11	-40.63	-27	Pass
NVNT	a	5825	Ant1	-45.02	2.11	-42.91	-27	Pass
NVNT	n20	5745	Ant1	-43.13	2.11	-41.02	-27	Pass
NVNT	n20	5825	Ant1	-43.91	2.11	-41.80	-27	Pass
NVNT	n40	5755	Ant1	-38.98	2.11	-36.87	-27	Pass
NVNT	n40	5795	Ant1	-41.38	2.11	-39.27	-27	Pass
NVNT	ac20	5745	Ant1	-43.82	2.11	-41.71	-27	Pass
NVNT	ac20	5825	Ant1	-44.71	2.11	-42.60	-27	Pass
NVNT	ac40	5755	Ant1	-41.41	2.11	-39.30	-27	Pass
NVNT	ac40	5795	Ant1	-45.37	2.11	-43.26	-27	Pass
NVNT	ac80	5775	Ant1	-38.32	2.11	-36.21	-27	Pass

Note: The calculated value of Max Value+Antenna meets the requirement of meeting the minimum limit of - 27dBm/MHz, while also meeting the requirements of other limits




UNII-3


Band Edge NVNT a 5745MHz Low Ant1




Band Edge NVNT a 5825MHz High Ant1




Band Edge NVNT n20 5745MHz Low Ant1




Band Edge NVNT n20 5825MHz High Ant1




Band Edge NVNT n40 5755MHz Low Ant1




Band Edge NVNT n40 5795MHz High Ant1




Band Edge NVNT ac20 5745MHz Low Ant1




Band Edge NVNT ac20 5825MHz High Ant1



Band Edge NVNT ac40 5755MHz Low Ant1




Band Edge NVNT ac40 5795MHz High Ant1






Band Edge NVNT ac80 5775MHz Low Ant1



4.7.2 Radiated test Method

Test Requirement:	47CFR Part 15.209 and 15.205				
Test Method:	ANSI C63.10-2020+COR 1-2023 § 6.10				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			68.2		Peak Value
	Undesirable emission limits:				
	(1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.				
	(2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band.				
(3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.					
All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.					
Test setup:	Above 1GHz				
					

Test Procedure:	- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. - The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. - The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.4°C	Humid.: 41%RH
Test voltage:	DC 7.7V From Battery	
Test results:	Pass	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Two antennas are tested, only the worst case's (Main Antenna) data was showed.
4. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
5. According to KDB 789033 D02v02r01 section G) 1) d), for measurements above 1000 MHz @3m distance, the limit of field strength is computed as follows:

$$E[dBuV/m] = EIRP[dBm] + 95.2;$$
For example, if $EIRP = -27dBm$

$$E[dBuV/m] = -27 + 95.2 = 68.2dBuV/m.$$

$$E[dBuV/m] = 10 + 95.2 = 105.2dBuV/m.$$

$$E[dBuV/m] = 15.6 + 95.2 = 110.8dBuV/m.$$

$$E[dBuV/m] = 27 + 95.2 = 122.2dBuV/m$$



IEEE 802.11a Operation Frequency:5180MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5150	47.83	-7.53	40.30	74.00	-33.70	Horizontal	PK
5150	47.16	-7.53	39.63	74.00	-34.37	Vertical	PK
5150	38.43	-7.53	30.90	54.00	-23.10	Horizontal	AV
5150	37.89	-7.53	30.36	54.00	-23.64	Vertical	AV

IEEE 802.11a Operation Frequency:5240MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5350	43.52	-7.06	36.46	74.00	-37.54	Horizontal	PK
5350	48.56	-7.06	41.50	74.00	-32.50	Vertical	PK
5350	34.99	-7.06	27.93	54.00	-26.07	Horizontal	AV
5350	39.01	-7.06	31.95	54.00	-22.05	Vertical	AV

IEEE 802.11n20 Operation Frequency:5180MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5150	46.90	-7.53	39.37	74.00	-34.63	Horizontal	PK
5150	46.25	-7.53	38.72	74.00	-35.28	Vertical	PK
5150	37.68	-7.53	30.15	54.00	-23.85	Horizontal	AV
5150	37.15	-7.53	29.62	54.00	-24.38	Vertical	AV

IEEE 802.11n20 Operation Frequency:5240MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5350	42.68	-7.06	35.62	74.00	-38.38	Horizontal	PK
5350	47.62	-7.06	40.56	74.00	-33.44	Vertical	PK
5350	34.30	-7.06	27.24	54.00	-26.76	Horizontal	AV
5350	38.25	-7.06	31.19	54.00	-22.81	Vertical	AV



IEEE 802.11ac20 Operation Frequency:5180MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5150	49.26	-7.53	41.73	74.00	-32.27	Horizontal	PK
5150	48.55	-7.53	41.02	74.00	-32.98	Vertical	PK
5150	39.55	-7.53	32.02	54.00	-21.98	Horizontal	AV
5150	39.01	-7.53	31.48	54.00	-22.52	Vertical	AV

IEEE 802.11ac20 Operation Frequency:5240MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5350	44.82	-7.06	37.76	74.00	-36.24	Horizontal	PK
5350	50.00	-7.06	42.94	74.00	-31.06	Vertical	PK
5350	36.01	-7.06	28.95	54.00	-25.05	Horizontal	AV
5350	40.15	-7.06	33.09	54.00	-20.91	Vertical	AV

IEEE 802.11n40 Operation Frequency:5190MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5150	48.31	-7.53	40.78	74.00	-33.22	Horizontal	PK
5150	47.63	-7.53	40.10	74.00	-33.90	Vertical	PK
5150	38.80	-7.53	31.27	54.00	-22.73	Horizontal	AV
5150	38.27	-7.53	30.74	54.00	-23.26	Vertical	AV

IEEE 802.11n40 Operation Frequency:5230MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5350	43.96	-7.06	36.90	74.00	-37.10	Horizontal	PK
5350	49.04	-7.06	41.98	74.00	-32.02	Vertical	PK
5350	35.33	-7.06	28.27	54.00	-25.73	Horizontal	AV
5350	39.40	-7.06	32.34	54.00	-21.66	Vertical	AV

IEEE 802.11ac40 Operation Frequency:5190MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5150	50.65	-7.53	43.12	74.00	-30.88	Horizontal	PK
5150	49.96	-7.53	42.43	74.00	-31.57	Vertical	PK
5150	40.67	-7.53	33.14	54.00	-20.86	Horizontal	AV
5150	40.11	-7.53	32.58	54.00	-21.42	Vertical	AV



IEEE 802.11ac40 Operation Frequency:5230MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5350	46.09	-7.06	39.03	74.00	-34.97	Horizontal	PK
5350	51.44	-7.06	44.38	74.00	-29.62	Vertical	PK
5350	37.04	-7.06	29.98	54.00	-24.02	Horizontal	AV
5350	41.31	-7.06	34.25	54.00	-19.75	Vertical	AV

IEEE 802.11ac80 Operation Frequency:5210MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5150	50.19	-7.53	42.66	74.00	-31.34	Horizontal	PK
5150	49.49	-7.53	41.96	74.00	-32.04	Vertical	PK
5150	40.31	-7.53	32.78	54.00	-21.22	Horizontal	AV
5150	39.75	-7.53	32.22	54.00	-21.78	Vertical	AV

IEEE 802.11ac80 Operation Frequency:5210MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5350	45.67	-7.06	38.61	74.00	-35.39	Horizontal	PK
5350	50.96	-7.06	43.90	74.00	-30.10	Vertical	PK
5350	36.69	-7.06	29.63	54.00	-24.37	Horizontal	AV
5350	40.92	-7.06	33.86	54.00	-20.14	Vertical	AV



Measurement data:

IEEE 802.11a							
Operation Frequency:5745MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5650	47.48	-6.34	41.14	68.20	-27.06	Horizontal	PK
5650	35.44	-6.34	29.10	54.00	-24.90	Horizontal	AV
5700	45.02	-6.22	38.80	105.20	-66.40	Horizontal	PK
5700	34.10	-6.22	27.88	54.00	-26.12	Horizontal	AV
5720	48.17	-6.17	42.00	110.80	-68.80	Horizontal	PK
5720	37.18	-6.17	31.01	54.00	-22.99	Horizontal	AV
5725	49.59	-6.16	43.43	122.20	-78.77	Horizontal	PK
5725	38.29	-6.16	32.13	54.00	-21.87	Horizontal	AV
5650	49.98	-6.34	43.64	68.20	-24.56	Vertical	PK
5650	38.32	-6.34	31.98	54.00	-22.02	Vertical	AV
5700	53.98	-6.22	47.76	105.20	-57.44	Vertical	PK
5700	42.63	-6.22	36.41	54.00	-17.59	Vertical	AV
5720	50.88	-6.17	44.71	110.80	-66.09	Vertical	PK
5720	43.72	-6.17	37.55	54.00	-16.45	Vertical	AV
5725	48.51	-6.16	42.35	122.20	-79.85	Vertical	PK
5725	38.79	-6.16	32.63	54.00	-21.37	Vertical	AV

IEEE 802.11a							
Operation Frequency:5825MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5850	56.56	-5.87	50.69	122.20	-71.51	Vertical	PK
5850	42.74	-5.87	36.87	54.00	-17.13	Vertical	AV
5855	53.11	-5.85	47.26	110.80	-63.54	Vertical	PK
5855	43.72	-5.85	37.87	54.00	-16.13	Vertical	AV
5875	47.98	-5.80	42.18	105.20	-63.02	Vertical	PK
5875	36.03	-5.80	30.23	54.00	-23.77	Vertical	AV
5925	47.20	-5.68	41.52	68.20	-26.68	Vertical	PK
5925	37.19	-5.68	31.51	54.00	-22.49	Vertical	AV
5850	44.89	-5.87	39.02	122.20	-83.19	Horizontal	PK
5850	33.81	-5.87	27.94	54.00	-26.06	Horizontal	AV
5855	43.24	-5.85	37.39	110.80	-73.41	Horizontal	PK
5855	34.34	-5.85	28.49	54.00	-25.51	Horizontal	AV
5875	47.97	-5.80	42.17	105.20	-63.03	Horizontal	PK
5875	36.72	-5.80	30.92	54.00	-23.08	Horizontal	AV
5925	56.61	-5.68	50.93	68.20	-17.27	Horizontal	PK
5925	40.26	-5.68	34.58	54.00	-19.42	Horizontal	AV



IEEE 802.11n20							
Operation Frequency:5745MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5650	48.40	-6.34	42.06	68.20	-26.14	Horizontal	PK
5650	36.12	-6.34	29.78	54.00	-24.22	Horizontal	AV
5700	45.91	-6.22	39.69	105.20	-65.51	Horizontal	PK
5700	34.76	-6.22	28.54	54.00	-25.46	Horizontal	AV
5720	49.12	-6.17	42.95	110.80	-67.85	Horizontal	PK
5720	37.91	-6.17	31.74	54.00	-22.26	Horizontal	AV
5725	50.57	-6.16	44.41	122.20	-77.79	Horizontal	PK
5725	39.03	-6.16	32.87	54.00	-21.13	Horizontal	AV
5650	50.97	-6.34	44.63	68.20	-23.57	Vertical	PK
5650	39.06	-6.34	32.72	54.00	-21.28	Vertical	AV
5700	55.05	-6.22	48.83	105.20	-56.37	Vertical	PK
5700	43.46	-6.22	37.24	54.00	-16.76	Vertical	AV
5720	51.88	-6.17	45.71	110.80	-65.09	Vertical	PK
5720	44.57	-6.17	38.40	54.00	-15.60	Vertical	AV
5725	49.46	-6.16	43.30	122.20	-78.90	Vertical	PK
5725	39.55	-6.16	33.39	54.00	-20.61	Vertical	AV

IEEE 802.11n20							
Operation Frequency:5825MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5850	57.66	-5.87	51.79	122.20	-70.41	Vertical	PK
5850	43.58	-5.87	37.71	54.00	-16.29	Vertical	AV
5855	54.16	-5.85	48.31	110.80	-62.49	Vertical	PK
5855	44.57	-5.85	38.72	54.00	-15.28	Vertical	AV
5875	48.92	-5.80	43.12	105.20	-62.08	Vertical	PK
5875	36.73	-5.80	30.93	54.00	-23.07	Vertical	AV
5925	48.13	-5.68	42.45	68.20	-25.75	Vertical	PK
5925	37.92	-5.68	32.24	54.00	-21.76	Vertical	AV
5850	45.78	-5.87	39.91	122.20	-82.29	Horizontal	PK
5850	34.48	-5.87	28.61	54.00	-25.39	Horizontal	AV
5855	44.09	-5.85	38.24	110.80	-72.56	Horizontal	PK
5855	35.01	-5.85	29.16	54.00	-24.84	Horizontal	AV
5875	48.91	-5.80	43.11	105.20	-62.09	Horizontal	PK
5875	37.45	-5.80	31.65	54.00	-22.35	Horizontal	AV
5925	57.71	-5.68	52.03	68.20	-16.17	Horizontal	PK
5925	41.04	-5.68	35.36	54.00	-18.64	Horizontal	AV



IEEE 802.11ac20 Operation Frequency:5745MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5650	45.15	-6.34	38.81	68.20	-29.39	Horizontal	PK
5650	33.70	-6.34	27.36	54.00	-26.64	Horizontal	AV
5700	42.81	-6.22	36.59	105.20	-68.61	Horizontal	PK
5700	32.43	-6.22	26.21	54.00	-27.79	Horizontal	AV
5720	45.80	-6.17	39.63	110.80	-71.17	Horizontal	PK
5720	35.36	-6.17	29.19	54.00	-24.81	Horizontal	AV
5725	47.15	-6.16	40.99	122.20	-81.21	Horizontal	PK
5725	36.42	-6.16	30.26	54.00	-23.74	Horizontal	AV
5650	47.52	-6.34	41.18	68.20	-27.02	Vertical	PK
5650	36.44	-6.34	30.10	54.00	-23.90	Vertical	AV
5700	51.32	-6.22	45.10	105.20	-60.10	Vertical	PK
5700	40.53	-6.22	34.31	54.00	-19.69	Vertical	AV
5720	48.38	-6.17	42.21	110.80	-68.59	Vertical	PK
5720	41.57	-6.17	35.40	54.00	-18.60	Vertical	AV
5725	46.13	-6.16	39.97	122.20	-82.23	Vertical	PK
5725	36.90	-6.16	30.74	54.00	-23.26	Vertical	AV

IEEE 802.11ac20 Operation Frequency:5825MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5850	53.77	-5.87	47.90	122.20	-74.30	Vertical	PK
5850	40.64	-5.87	34.77	54.00	-19.23	Vertical	AV
5855	50.49	-5.85	44.64	110.80	-66.16	Vertical	PK
5855	41.57	-5.85	35.72	54.00	-18.28	Vertical	AV
5875	45.61	-5.80	39.81	105.20	-65.39	Vertical	PK
5875	34.26	-5.80	28.46	54.00	-25.54	Vertical	AV
5925	44.88	-5.68	39.20	68.20	-29.00	Vertical	PK
5925	35.37	-5.68	29.69	54.00	-24.31	Vertical	AV
5850	42.68	-5.87	36.81	122.20	-85.39	Horizontal	PK
5850	32.15	-5.87	26.28	54.00	-27.72	Horizontal	AV
5855	41.11	-5.85	35.26	110.80	-75.54	Horizontal	PK
5855	32.66	-5.85	26.81	54.00	-27.19	Horizontal	AV
5875	45.60	-5.80	39.80	105.20	-65.40	Horizontal	PK
5875	34.93	-5.80	29.13	54.00	-24.87	Horizontal	AV
5925	53.80	-5.68	48.12	68.20	-20.08	Horizontal	PK
5925	38.28	-5.68	32.60	54.00	-21.40	Horizontal	AV



IEEE 802.11n40 Operation Frequency:5755MHz							
Frequency (MHz)	Read Level (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization	Detect or Type
5650	47.93	-6.34	41.59	68.20	-26.61	Horizontal	PK
5650	35.77	-6.34	29.43	54.00	-24.57	Horizontal	AV
5700	45.46	-6.22	39.24	105.20	-65.96	Horizontal	PK
5700	34.44	-6.22	28.22	54.00	-25.78	Horizontal	AV
5720	48.65	-6.17	42.48	110.80	-68.32	Horizontal	PK
5720	37.54	-6.17	31.37	54.00	-22.63	Horizontal	AV
5725	50.09	-6.16	43.93	122.20	-78.27	Horizontal	PK
5725	38.66	-6.16	32.50	54.00	-21.50	Horizontal	AV
5650	50.48	-6.34	44.14	68.20	-24.06	Vertical	PK
5650	38.69	-6.34	32.35	54.00	-21.65	Vertical	AV
5700	54.52	-6.22	48.30	105.20	-56.90	Vertical	PK
5700	43.06	-6.22	36.84	54.00	-17.16	Vertical	AV
5720	51.38	-6.17	45.21	110.80	-65.59	Vertical	PK
5720	44.14	-6.17	37.97	54.00	-16.03	Vertical	AV
5725	48.98	-6.16	42.82	122.20	-79.38	Vertical	PK
5725	39.17	-6.16	33.01	54.00	-20.99	Vertical	AV

IEEE 802.11n40 Operation Frequency:5795MHz							
Frequency (MHz)	Read Level (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization	Detect or Type
5850	57.13	-5.87	51.26	122.20	-70.94	Vertical	PK
5850	43.16	-5.87	37.29	54.00	-16.71	Vertical	AV
5855	53.64	-5.85	47.79	110.80	-63.01	Vertical	PK
5855	44.14	-5.85	38.29	54.00	-15.71	Vertical	AV
5875	48.44	-5.80	42.64	105.20	-62.56	Vertical	PK
5875	36.38	-5.80	30.58	54.00	-23.42	Vertical	AV
5925	47.66	-5.68	41.98	68.20	-26.22	Vertical	PK
5925	37.55	-5.68	31.87	54.00	-22.13	Vertical	AV
5850	45.33	-5.87	39.46	122.20	-82.74	Horizontal	PK
5850	34.14	-5.87	28.27	54.00	-25.73	Horizontal	AV
5855	43.67	-5.85	37.82	110.80	-72.98	Horizontal	PK
5855	34.68	-5.85	28.83	54.00	-25.17	Horizontal	AV
5875	48.43	-5.80	42.63	105.20	-62.57	Horizontal	PK
5875	37.08	-5.80	31.28	54.00	-22.72	Horizontal	AV
5925	57.15	-5.68	51.47	68.20	-16.73	Horizontal	PK
5925	40.65	-5.68	34.97	54.00	-19.03	Horizontal	AV



IEEE 802.11ac40 Operation Frequency:5755MHz							
Frequency (MHz)	Read Level (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization	Detect or Type
5650	50.28	-6.34	43.94	68.20	-24.27	Horizontal	PK
5650	37.52	-6.34	31.18	54.00	-22.82	Horizontal	AV
5700	47.68	-6.22	41.46	105.20	-63.74	Horizontal	PK
5700	36.09	-6.22	29.87	54.00	-24.13	Horizontal	AV
5720	51.01	-6.17	44.84	110.80	-65.96	Horizontal	PK
5720	39.37	-6.17	33.20	54.00	-20.80	Horizontal	AV
5725	52.53	-6.16	46.37	122.20	-75.83	Horizontal	PK
5725	40.54	-6.16	34.38	54.00	-19.62	Horizontal	AV
5650	52.94	-6.34	46.60	68.20	-21.60	Vertical	PK
5650	40.57	-6.34	34.23	54.00	-19.77	Vertical	AV
5700	57.16	-6.22	50.94	105.20	-54.26	Vertical	PK
5700	45.15	-6.22	38.93	54.00	-15.07	Vertical	AV
5720	53.88	-6.17	47.71	110.80	-63.09	Vertical	PK
5720	46.30	-6.17	40.13	54.00	-13.87	Vertical	AV
5725	51.37	-6.16	45.21	122.20	-76.99	Vertical	PK
5725	41.08	-6.16	34.92	54.00	-19.08	Vertical	AV

IEEE 802.11ac40 Operation Frequency:5795MHz							
Frequency (MHz)	Read Level (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization	Detect or Type
5850	59.91	-5.87	54.04	122.20	-68.16	Vertical	PK
5850	45.27	-5.87	39.40	54.00	-14.60	Vertical	AV
5855	56.25	-5.85	50.40	110.80	-60.40	Vertical	PK
5855	46.30	-5.85	40.45	54.00	-13.55	Vertical	AV
5875	50.81	-5.80	45.01	105.20	-60.19	Vertical	PK
5875	38.14	-5.80	32.34	54.00	-21.66	Vertical	AV
5925	49.98	-5.68	44.30	68.20	-23.90	Vertical	PK
5925	39.38	-5.68	33.70	54.00	-20.30	Vertical	AV
5850	47.53	-5.87	41.66	122.20	-80.54	Horizontal	PK
5850	35.79	-5.87	29.92	54.00	-24.08	Horizontal	AV
5855	45.80	-5.85	39.95	110.80	-70.85	Horizontal	PK
5855	36.36	-5.85	30.51	54.00	-23.49	Horizontal	AV
5875	50.80	-5.80	45.00	105.20	-60.20	Horizontal	PK
5875	38.89	-5.80	33.09	54.00	-20.91	Horizontal	AV
5925	59.95	-5.68	54.27	68.20	-13.93	Horizontal	PK
5925	42.63	-5.68	36.95	54.00	-17.05	Horizontal	AV



IEEE 802.11ac80 Operation Frequency:5775MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5650	48.19	-6.34	41.85	68.20	-26.35	Horizontal	PK
5650	35.80	-6.34	29.46	54.00	-24.54	Horizontal	AV
5700	45.67	-6.22	39.45	105.20	-65.75	Horizontal	PK
5700	34.42	-6.22	28.20	54.00	-25.80	Horizontal	AV
5720	48.91	-6.17	42.74	110.80	-68.06	Horizontal	PK
5720	37.59	-6.17	31.42	54.00	-22.58	Horizontal	AV
5725	50.37	-6.16	44.21	122.20	-77.99	Horizontal	PK
5725	38.73	-6.16	32.57	54.00	-21.43	Horizontal	AV
5650	50.77	-6.34	44.43	68.20	-23.77	Vertical	PK
5650	38.77	-6.34	32.43	54.00	-21.57	Vertical	AV
5700	54.90	-6.22	48.68	105.20	-56.52	Vertical	PK
5700	43.21	-6.22	36.99	54.00	-17.01	Vertical	AV
5720	51.71	-6.17	45.54	110.80	-65.26	Vertical	PK
5720	44.33	-6.17	38.16	54.00	-15.84	Vertical	AV
5725	49.26	-6.16	43.10	122.20	-79.10	Vertical	PK
5725	39.26	-6.16	33.10	54.00	-20.90	Vertical	AV



IEEE 802.11ac80 Operation Frequency:5775MHz							
Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Detect or Type
5850	58.23	-5.87	52.36	122.20	-69.84	Vertical	PK
5850	43.99	-5.87	38.12	54.00	-15.88	Vertical	AV
5855	54.69	-5.85	48.84	110.80	-61.97	Vertical	PK
5855	45.00	-5.85	39.15	54.00	-14.85	Vertical	AV
5875	49.39	-5.80	43.59	105.20	-61.61	Vertical	PK
5875	37.07	-5.80	31.27	54.00	-22.73	Vertical	AV
5925	48.59	-5.68	42.91	68.20	-25.29	Vertical	PK
5925	38.28	-5.68	32.60	54.00	-21.40	Vertical	AV
5850	46.20	-5.87	40.33	122.20	-81.87	Horizontal	PK
5850	34.81	-5.87	28.94	54.00	-25.06	Horizontal	AV
5855	44.50	-5.85	38.65	110.80	-72.15	Horizontal	PK
5855	35.35	-5.85	29.50	54.00	-24.50	Horizontal	AV
5875	49.38	-5.80	43.58	105.20	-61.62	Horizontal	PK
5875	37.81	-5.80	32.01	54.00	-21.99	Horizontal	AV
5925	58.27	-5.68	52.59	68.20	-15.61	Horizontal	PK
5925	41.44	-5.68	35.76	54.00	-18.24	Horizontal	AV


Remark:

Factor =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

4.8 Spurious Emission

4.8.1 Radiated Emission Method

Test Requirement:	47CFR Part 15.209, Part 15E Section 15.407(b)(4)				
Test Method:	ANSI C63.10-2020+COR 1-2023§6.4&6.5&6.6				
Test Frequency Range:	9kHz to 40GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9kHz-150KHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (uV/m)	Value	Measurement Distance
	0.009MHz-0.490MHz		2400/F(KHz)	QP	300m
	0.490MHz-1.705MHz		24000/F(KHz)	QP	300m
	1.705MHz-30MHz		30	QP	30m
	30MHz-88MHz		100	QP	3m
	88MHz-216MHz		150	QP	
	216MHz-960MHz		200	QP	
	960MHz-1GHz		500	QP	
	Frequency		Limit (dBm/MHz)	Remark	
	Above 1GHz		-27.0	Peak Value	
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to1GHz				
					
	For radiated emissions above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remarks:

1. The report only shows the worst mode.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.
3. All models and modes have been tested, and the report only displays the worst mode 802.11ac20 (5180MHz) data

Measurement Data:


9 kHz ~ 30 MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Below 1GHz


Temperature:	23.3℃	Relative Humidity:	37%RH
Pressure:	101.2kPa	Test Voltage :	DC 19V From adapter
Test Mode :	TX- 802.11ac20 (5180MHz)		

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	89.9046	58.65	-25.41	33.24	43.50	-10.26	QP
2	150.0108	55.03	-20.50	34.53	43.50	-8.97	QP
3	277.0935	56.22	-21.46	34.76	46.00	-11.24	QP
4	517.2479	51.21	-13.73	37.48	46.00	-8.52	QP
5	742.2587	49.50	-8.27	41.23	46.00	-4.77	QP
6	890.7277	41.13	-5.60	35.53	46.00	-10.47	QP

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.0007	54.45	-21.55	32.90	40.00	-7.10	QP
2	37.4165	57.19	-21.34	35.85	40.00	-4.15	QP
3	148.4410	57.23	-20.68	36.55	43.50	-6.95	QP
4	742.2587	50.07	-8.27	41.80	46.00	-4.20	QP
5	890.7278	47.21	-5.60	41.61	46.00	-4.39	QP
6	1000.0000	41.76	-3.36	38.40	54.00	-15.60	QP

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The test data shows only the worst case 802.11ac mode

**Above 1GHz:**

Temperature:	23.3°C	Relative Humidity:	37%
Pressure:	101.2kPa	Test Voltage :	DC 19V
Test Mode :	5.2G TX- 802.11ac20		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5180MHz							
V	10360.00	43.36	1.77	45.13	68.20	-23.07	PK
V	10360.00	38.74	1.77	40.51	54.00	-13.49	AV
V	15540.00	43.85	7.72	51.57	74.00	-22.43	PK
V	15540.00	33.11	7.72	40.83	54.00	-13.17	AV
V	20720.00	53.34	-5.73	47.61	68.20	-20.59	PK
V	20720.00	47.54	-5.73	41.81	54.00	-12.19	AV
V	25900.00	51.81	-2.89	48.92	68.20	-19.28	PK
V	25900.00	47.01	-2.89	44.12	54.00	-9.88	AV
V	31080.00	46.57	1.66	48.23	68.20	-19.97	PK
V	31080.00	42.31	1.66	43.97	54.00	-10.03	AV
V	36260.00	44.73	4.63	49.36	68.20	-18.84	PK
V	36260.00	40.32	4.63	44.95	54.00	-9.05	AV
H	10360.00	44.40	1.77	46.17	68.20	-22.03	PK
H	10360.00	39.09	1.77	40.86	54.00	-13.14	AV
H	15540.00	43.41	7.72	51.13	74.00	-22.87	PK
H	15540.00	33.03	7.72	40.75	54.00	-13.25	AV
H	20720.00	55.09	-5.73	49.36	68.20	-18.84	PK
H	20720.00	49.93	-5.73	44.20	54.00	-9.80	AV
H	25900.00	51.91	-2.89	49.02	68.20	-19.18	PK
H	25900.00	46.83	-2.89	43.94	54.00	-10.06	AV
H	31080.00	45.74	1.66	47.40	68.20	-20.80	PK
H	31080.00	41.16	1.66	42.82	54.00	-11.18	AV
H	36260.00	45.79	4.63	50.42	68.20	-17.78	PK
H	36260.00	39.90	4.63	44.53	54.00	-9.47	AV

Remark:

- Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
- If peak below the average limit, the average emission was no test.
- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Middle Channel:5200Hz							
V	10400.00	43.97	1.85	45.82	68.20	-22.38	PK
V	10400.00	38.96	1.85	40.81	54.00	-13.19	AV
V	15600.00	43.52	7.64	51.16	74.00	-22.84	PK
V	15600.00	33.51	7.64	41.15	54.00	-12.85	AV
V	20800.00	52.18	-5.67	46.51	68.20	-21.69	PK
V	20800.00	47.93	-5.67	42.26	54.00	-11.74	AV
V	26000.00	52.13	-2.85	49.28	68.20	-18.92	PK
V	26000.00	47.17	-2.85	44.32	54.00	-9.68	AV
V	31200.00	47.33	1.57	48.90	68.20	-19.30	PK
V	31200.00	42.49	1.57	44.06	54.00	-9.94	AV
V	36400.00	43.36	4.93	48.29	68.20	-19.91	PK
V	36400.00	38.12	4.93	43.05	54.00	-10.95	AV
H	10400.00	43.49	1.85	45.34	68.20	-22.86	PK
H	10400.00	38.80	1.85	40.65	54.00	-13.35	AV
H	15600.00	44.33	7.64	51.97	74.00	-22.03	PK
H	15600.00	33.22	7.64	40.86	54.00	-13.14	AV
H	20800.00	54.79	-5.67	49.12	68.20	-19.08	PK
H	20800.00	49.78	-5.67	44.11	54.00	-9.89	AV
H	26000.00	51.91	-2.85	49.06	68.20	-19.14	PK
H	26000.00	46.84	-2.85	43.99	54.00	-10.01	AV
H	31200.00	46.72	1.57	48.29	68.20	-19.91	PK
H	31200.00	41.81	1.57	43.38	54.00	-10.62	AV
H	36400.00	45.09	4.93	50.02	68.20	-18.18	PK
H	36400.00	39.08	4.93	44.01	54.00	-9.99	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
High Channel:5240MHz							
V	10480.00	43.32	2.02	45.34	68.20	-22.86	PK
V	10480.00	38.47	2.02	40.49	54.00	-13.51	AV
V	15720.00	44.32	7.46	51.78	74.00	-22.22	PK
V	15720.00	33.18	7.46	40.64	54.00	-13.36	AV
V	20960.00	51.08	-5.56	45.52	68.20	-22.68	PK
V	20960.00	46.32	-5.56	40.76	54.00	-13.24	AV
V	26200.00	51.79	-2.50	49.29	68.20	-18.91	PK
V	26200.00	45.24	-2.50	42.74	54.00	-11.26	AV
V	31440.00	45.96	1.39	47.35	68.20	-20.85	PK
V	31440.00	41.15	1.39	42.54	54.00	-11.46	AV
V	36680.00	43.51	5.25	48.76	68.20	-19.44	PK
V	36680.00	38.63	5.25	43.88	54.00	-10.13	AV
H	10480.00	43.71	2.02	45.73	68.20	-22.47	PK
H	10480.00	38.90	2.02	40.92	54.00	-13.08	AV
H	15720.00	43.63	7.46	51.09	74.00	-22.91	PK
H	15720.00	32.98	7.46	40.44	54.00	-13.56	AV
H	20960.00	54.05	-5.56	48.49	68.20	-19.71	PK
H	20960.00	48.71	-5.56	43.15	54.00	-10.85	AV
H	26200.00	52.08	-2.50	49.58	68.20	-18.62	PK
H	26200.00	45.78	-2.50	43.28	54.00	-10.72	AV
H	31440.00	47.01	1.39	48.40	68.20	-19.80	PK
H	31440.00	41.49	1.39	42.88	54.00	-11.12	AV
H	36680.00	44.19	5.15	49.34	68.20	-18.86	PK
H	36680.00	39.20	5.15	44.35	54.00	-9.65	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Temperature:	23.3℃	Relative Humidity:	37%RH
Pressure:	101.2kPa	Test Voltage :	DC 3.85V
Test Mode :	5.8G TX- 802.11ac20		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5745MHz							
V	11490.00	49.23	3.31	52.54	74.00	-21.46	PK
V	11490.00	38.39	3.31	41.70	54.00	-12.30	AV
V	17235.00	36.02	10.10	46.12	68.20	-22.08	PK
V	17235.00	31.16	10.10	41.26	54.00	-12.74	AV
V	22980.00	56.07	-4.61	51.46	74.00	-22.54	PK
V	22980.00	45.10	-4.61	40.49	54.00	-13.51	AV
V	28725.00	48.33	0.87	49.20	68.20	-19.00	PK
V	28725.00	42.33	0.87	43.20	54.00	-10.80	AV
V	34470.00	45.55	3.82	49.37	68.20	-18.83	PK
V	34470.00	39.99	3.82	43.81	54.00	-10.19	AV
H	11490.00	47.54	3.31	50.85	74.00	-23.15	PK
H	11490.00	36.62	3.31	39.93	54.00	-14.07	AV
H	17235.00	35.49	10.10	45.59	68.20	-22.61	PK
H	17235.00	30.60	10.10	40.70	54.00	-13.30	AV
H	22980.00	58.49	-4.61	53.88	74.00	-20.12	PK
H	22980.00	46.87	-4.61	42.26	54.00	-11.75	AV
H	28725.00	48.50	0.87	49.37	68.20	-18.83	PK
H	28725.00	43.00	0.87	43.87	54.00	-10.13	AV
H	34470.00	46.10	3.82	49.92	68.20	-18.28	PK
H	34470.00	41.01	3.82	44.83	54.00	-9.17	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5785MHz							
V	11570.00	48.98	3.34	52.32	74.00	-21.68	PK
V	11570.00	37.50	3.34	40.84	54.00	-13.16	AV
V	17355.00	34.49	10.52	45.01	68.20	-23.19	PK
V	17355.00	30.54	10.52	41.06	54.00	-12.94	AV
V	23140.00	56.06	-4.66	51.40	74.00	-22.60	PK
V	23140.00	45.05	-4.66	40.39	54.00	-13.61	AV
V	28925.00	45.64	1.36	47.00	68.20	-21.20	PK
V	28925.00	40.66	1.36	42.02	54.00	-11.98	AV
V	34710.00	45.29	3.95	49.24	68.20	-18.96	PK
V	34710.00	39.49	3.95	43.44	54.00	-10.56	AV
H	11570.00	48.72	3.34	52.06	74.00	-21.94	PK
H	11570.00	37.28	3.34	40.62	54.00	-13.38	AV
H	17355.00	35.18	10.52	45.70	68.20	-22.50	PK
H	17355.00	30.18	10.52	40.70	54.00	-13.30	AV
H	23140.00	60.26	-4.66	55.60	74.00	-18.41	PK
H	23140.00	47.98	-4.66	43.32	54.00	-10.68	AV
H	28925.00	47.99	1.36	49.35	68.20	-18.85	PK
H	28925.00	42.16	1.36	43.52	54.00	-10.48	AV
H	34710.00	46.32	3.95	50.27	68.20	-17.93	PK
H	34710.00	40.83	3.95	44.78	54.00	-9.22	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5825MHz							
V	11650.00	47.92	3.36	51.28	74.00	-22.72	PK
V	11650.00	36.39	3.36	39.75	54.00	-14.25	AV
V	17475.00	35.75	10.93	46.68	68.20	-21.52	PK
V	17475.00	30.57	10.93	41.50	54.00	-12.50	AV
V	23300.00	54.01	-4.77	49.24	68.20	-18.96	PK
V	23300.00	48.02	-4.77	43.25	54.00	-10.75	AV
V	29125.00	44.16	1.65	45.81	68.20	-22.39	PK
V	29125.00	39.80	1.65	41.45	54.00	-12.55	AV
V	34950.00	43.98	4.09	48.07	68.20	-20.13	PK
V	34950.00	39.73	4.09	43.82	54.00	-10.18	AV
H	11650.00	48.13	3.36	51.49	74.00	-22.51	PK
H	11650.00	37.30	3.36	40.66	54.00	-13.34	AV
H	17475.00	35.47	10.93	46.40	68.20	-21.80	PK
H	17475.00	30.70	10.93	41.63	54.00	-12.37	AV
H	23300.00	52.37	-4.77	47.60	68.20	-20.60	PK
H	23300.00	47.29	-4.77	42.52	54.00	-11.48	AV
H	29125.00	47.68	1.65	49.33	68.20	-18.87	PK
H	29125.00	42.39	1.65	44.04	54.00	-9.96	AV
H	34950.00	45.57	4.09	49.66	68.20	-18.54	PK
H	34950.00	40.92	4.09	45.01	54.00	-8.99	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4.9 Frequency stability

Test Requirement:	47CFR Part 15.407(g)
Test Method:	ANSI C63.10-2020+COR 1-2023§6.8
Limit:	Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	a. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minute s. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test setup:	 Temperature Chamber Spectrum analyzer EUT Variable Power Supply Note : Measurement setup for testing on Antenna connector
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remark: Set the EUT transmits at un-modulation mode to test frequency stability.



Measurement data:

Frequency stability versus Temp.					
Power Supply: DC19V					
Temp. (°C)	Operating Frequency (MHz)	0 minute	2 minute	5 minute	10 minute
		Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)
-30	5180	5179.980	5179.969	5179.989	5179.969
	5190	5189.979	5189.969	5189.979	5189.989
	5200	5199.971	5199.991	5199.999	5199.987
	5210	5209.977	5209.999	5209.991	5209.991
	5220	5219.972	5219.991	5219.991	5219.979
	5230	5229.970	5229.970	5229.990	5229.970
	5240	5239.983	5239.990	5239.983	5239.983
-20	5180	5179.987	5179.999	5179.988	5179.987
	5190	5189.985	5189.993	5189.999	5189.985
	5200	5199.957	5199.991	5199.990	5199.990
	5210	5209.971	5209.999	5209.991	5209.999
	5220	5219.962	5219.991	5219.998	5219.962
	5230	5229.970	5229.970	5229.970	5229.969
	5240	5239.978	5239.990	5239.988	5239.987
-10	5180	5179.970	5179.999	5180.000	5179.993
	5190	5189.971	5190.000	5189.991	5189.991
	5200	5199.969	5199.991	5199.979	5199.969
	5210	5209.970	5209.999	5209.983	5209.970
	5220	5219.962	5219.991	5219.962	5219.969
	5230	5229.983	5230.012	5229.990	5230.044
	5240	5239.961	5239.990	5239.990	5239.990
0	5180	5179.981	5179.981	5179.969	5179.981
	5190	5189.968	5189.998	5189.996	5189.968
	5200	5199.983	5199.991	5199.983	5199.983
	5210	5209.979	5209.999	5209.970	5219.984
	5220	5219.984	5219.983	5219.981	5219.979
	5230	5229.991	5229.991	5229.985	5229.985
	5240	5239.975	5239.975	5239.975	5239.979
10	5180	5179.959	5180.000	5179.980	5179.969
	5190	5189.970	5189.991	5189.991	5189.969
	5200	5199.961	5199.979	5199.999	5199.961
	5210	5209.962	5209.991	5209.991	5209.991
	5220	5219.969	5219.969	5219.990	5219.969
	5230	5229.977	5229.990	5229.990	5229.987
	5240	5239.959	5239.959	5239.959	5239.991
20	5180	5179.980	5179.999	5180.000	5179.999
	5190	5189.976	5190.000	5189.991	5190.029



	5200	5199.971	5199.990	5199.999	5199.990
	5210	5209.977	5299.999	5209.991	5209.991
	5220	5219.972	5219.991	5219.991	5219.991
	5230	5229.970	5229.969	5229.969	5229.969
	5240	5239.943	5239.990	5239.969	5239.983
30	5180	5179.910	5179.967	5179.999	5179.997
	5190	5189.976	5189.976	5189.929	5189.976
	5200	5199.971	5199.994	5199.998	5199.968
	5210	5209.987	5209.997	5210.000	5209.987
	5220	5219.982	5219.982	5220.001	5219.982
	5230	5229.959	5230.001	5229.998	5229.959
	5240	5239.989	5240.001	5240.001	5240.001
40	5180	5179.970	5179.988	5179.990	5179.988
	5190	5189.971	5189.999	5189.991	5189.979
	5200	5199.981	5199.969	5200.001	5200.001
	5210	5209.969	5209.987	5209.993	5210.001
	5220	5219.962	5219.962	5220.001	5219.967
	5230	5229.983	5230.001	5229.990	5229.983
	5240	5239.981	5239.988	5239.988	5240.001
50	5180	5179.979	5179.999	5179.988	5179.979
	5190	5189.970	5189.989	5189.999	5189.970
	5200	5199.987	5199.991	5199.990	5200.001
	5210	5209.987	5210.001	5209.981	5209.985
	5220	5219.962	5220.001	5219.962	5219.962
	5230	5229.969	5229.969	5230.001	5229.969
	5240	5239.987	5239.987	5239.993	5239.987



Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VDC)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
16.13V	5180	5209.992	5179.993	5179.998	5179.980
	5190	5219.970	5189.993	5189.999	5189.976
	5200	5229.988	5200.001	5200.000	5199.971
	5210	5239.992	5209.989	5209.996	5209.977
	5220	5180.000	5219.997	5220.000	5219.972
	5230	5190.030	5229.970	5229.999	5229.970
	5240	5199.991	5239.989	5240.001	5239.983
19V	5180	5209.992	5180.001	5179.979	5179.979
	5190	5219.992	5190.001	5190.000	5190.032
	5200	5229.970	5199.989	5199.998	5199.989
	5210	5239.984	5209.967	5209.984	5209.967
	5220	5179.998	5219.989	5219.989	5219.985
	5230	5189.977	5229.899	5229.998	5229.969
	5240	5199.969	5239.979	5239.987	5239.979
21.85V	5180	5209.988	5179.980	5179.988	5179.979
	5190	5219.983	5189.976	5189.999	5189.987
	5200	5229.960	199.979	5199.990	199.979
	5210	5240.002	5209.977	5209.991	5209.987
	5220	5179.989	5219.983	5219.983	219.989
	5230	5189.980	5229.999	5229.969	5229.970
	5240	5200.002	5240.001	5239.988	5239.983



Frequency stability versus Temp.					
Power Supply: 19V DC					
Temp. (°C)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
-30	5745	5744.983	5744.983	5745.001	5744.983
	5755	5754.971	5754.997	5754.997	5754.993
	5775	5774.983	5774.996	5774.983	5774.983
	5785	5784.972	5784.999	5784.979	5784.979
	5795	5794.983	5794.983	5794.992	5794.983
	5825	5824.979	5824.991	5824.988	5824.979
-20	5745	5744.977	5744.981	5744.977	5744.987
	5755	5754.982	5754.997	5754.982	5754.989
	5775	5774.969	5774.969	5774.969	5774.979
	5785	5784.991	5784.999	5784.989	5784.993
	5795	5794.969	5794.969	5794.990	5794.969
	5825	5824.983	5824.991	5824.999	5824.983
-10	5745	5744.993	5744.992	5744.986	5744.986
	5755	5754.980	5754.989	5754.989	5754.989
	5775	5774.990	5774.996	5774.992	5774.982
	5785	5784.987	5784.982	5784.987	5784.987
	5795	5794.969	5794.983	5794.969	5794.985
	5825	5824.969	5824.991	5824.890	5824.991
0	5745	5744.987	5744.991	5744.992	5744.949
	5755	5754.983	5754.979	5754.979	5754.979
	5775	5774.978	5774.990	5775.001	5774.990
	5785	5784.964	5784.982	5784.992	5784.984
	5795	5794.960	5794.989	5794.988	5794.989
	5825	5824.958	5824.998	5824.991	5824.991
10	5745	5744.984	5744.989	5744.986	5744.989
	5755	5754.969	5754.969	5754.980	5754.969
	5775	5774.968	5774.968	5774.992	5774.939
	5785	5784.979	5784.969	5785.001	5784.969
	5795	5794.981	5794.990	5794.999	5794.990
	5825	5824.963	5824.969	5824.979	5824.969
20	5745	5744.984	5744.991	5745.001	5744.991
	5755	5754.976	5754.987	5754.987	5754.983
	5775	5774.979	5774.979	5774.969	5774.979
	5785	5784.980	5784.991	5784.988	5784.988
	5795	5794.984	5794.988	5794.982	5794.987
	5825	5824.980	5824.979	5824.982	5824.980
30	5745	5744.953	5745.002	5744.986	5745.048
	5755	5754.969	5754.989	5754.989	5754.979
	5775	5774.978	5774.980	5774.992	5774.979
	5785	5784.977	5784.969	5785.001	5784.969
	5795	5794.982	5794.989	5794.969	5794.989
	5825	5824.983	5824.963	5824.993	5824.969
40	5745	5744.964	5744.991	5744.986	5744.991
	5755	5754.991	5754.968	5754.972	5754.972
	5775	5774.963	5774.970	5774.991	5774.984
	5785	5784.985	5784.991	5784.985	5784.985



	5795	5794.982	5794.982	5794.989	5794.989
	5825	5824.981	5824.886	5824.689	5824.895
50	5745	5744.957	5744.991	5744.981	5744.957
	5755	5754.983	5754.989	5754.983	5754.983
	5775	5774.989	5774.869	5774.983	5754.981
	5785	5784.973	5784.991	5784.982	5784.89
	5795	5794.971	5794.895	5794.983	5794.969
	5825	5824.985	5824.985	5824.985	5824.983

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VDC)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
16.13V	5745	5744.973	5745.001	5744.989	5744.989
	5755	5754.969	5754.988	5754.969	5754.969
	5775	5774.968	5774.990	5775.001	5774.990
	5785	5784.993	5784.979	5784.979	5784.983
	5795	5794.969	5794.969	5794.990	5794.969
	5825	5824.970	5824.970	5824.970	5824.989
19V	5745	5744.983	5744.983	5744.986	5744.983
	5755	5754.979	5754.979	5754.979	5754.991
	5775	5774.988	5774.988	5774.992	5774.988
	5785	5784.981	5784.999	5785.001	5784.966
	5795	5794.978	5794.990	5794.959	5794.970
	5825	5824.963	5824.979	5824.979	5824.954
21.85V	5745	5744.883	5744.959	5744.985	5744.980
	5755	5754.980	5754.980	5755.001	5754.989
	5775	5774.976	5774.995	5775.001	5774.955
	5785	5784.982	5784.995	5784.988	5784.959
	5795	5794.981	5794.990	5794.999	5794.980
	5825	5824.963	5824.999	5824.969	5824.984



5 Test Setup Photo

Reference to the file No.: ET-26030855SP for details.

6 EUT Constructional Details

Reference to the file No.: ET-26030855EP and ET-26030855IP for details

-----END-----