

SPECIFICATIONS



Voltage	12V / 24V
Power Consumption	33w
Raw Lumen Output	5700Lm
Effective Lumen Output	2100Lm
Prak beam intensity	200,000cd
Prak beam distance	446m
Rotatation	360°
Tilt	110°
Wireless range	70m
Housing material	PC
Lens material	PC
IP Rating	IPX6
Operating Temperatures	-30 °C ~ +60 °C

Remote Specifications



	C2-317-003	C2-317-004
Voltage	3V(AAA1.5Vx2)	12V / 24V
Wireless range	70m	70m
Housing material	ASA	ASA
Operating Temperatures	-10 °C ~ +40 °C	-30 °C ~ +40 °C



WARNING Power supply should be less than 100w



C2-317 Remote Control LED Search Lights



C2-317-004
Remote control
(cabin)

C2-317-003
Remote control
(handheld)


IMPORTANT!

READ THESE INSTRUCTIONS BEFORE INSTALLING AND USING THIS PRODUCT.



Introduction

The spotlight uses a super bright that can illuminate objects up to 1,460 ft away. It is IP56 Weatherproof rated for extreme environments, with a UV weather resistant housing and fully enclosed tilt function driven by quiet motors that can withstand extreme temperatures (-22°F to 140°F or -30°C to 60°C). It has been designed and tested to withstand the harsh marine environments including high humidity, salt water spray, shock.

Precision circuitry allows for remarkable aiming and tracking with two speed choices.



OPERATION



FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

FCC Caution:

To ensure continued compliance, any changes or modifications not expressly approved by the party responsible for compliance may void the user's authority to operate this equipment.

NOTE: This equipment has been tested and found to comply with the limits for a class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.