

RF Exposure Evaluation

According to *KDB 447498 D01 General RF Exposure Guidance v06* and part 2.1093, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 5 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

BT								
Mode	Frequency (MHz)	Max Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Max Power (mW)	Min. Distance (mm)	Calc. thresholds	limit
GFSK	2402	-0.19	0 ± 1.0	1.0	1.2589	5.00	0.3902	3.0
	2441	-0.73	0 ± 1.0	1.0	1.2589	5.00	0.3934	3.0
	2480	-1.75	-1 ± 1.0	0.0	1.0000	5.00	0.3150	3.0
$\pi/4$ -DQPSK	2402	0.2	0 ± 1.0	1.0	1.2589	5.00	0.3902	3.0
	2441	-0.31	0 ± 1.0	1.0	1.2589	5.00	0.3934	3.0
	2480	-0.9	0 ± 1.0	1.0	1.2589	5.00	0.3965	3.0
8DPSK	2402	0.78	0 ± 1.0	1.0	1.2589	5.00	0.3902	3.0
	2441	0.3	0 ± 1.0	1.0	1.2589	5.00	0.3934	3.0
	2480	-0.31	0 ± 1.0	1.0	1.2589	5.00	0.3965	3.0

BLE								
Mode	Frequency (MHz)	Max Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Max Power (mW)	Min. Distance (mm)	Calc. thresholds	limit
GFSK	2402	-0.53	-1 ± 1.0	0.0	1.0000	5.00	0.3100	3.0
	2440	-1.02	-1 ± 1.0	0.0	1.0000	5.00	0.3124	3.0
	2480	-1.66	-1 ± 1.0	0.0	1.0000	5.00	0.3150	3.0

WIFI 2.4G														
Mode	Freque ncy (MHz)	Max Power (dBm)		Target power W/ tolerance (dBm)		Max tune up power tolerance (dBm)		Max Power (mW)		Min. Dist ance (mm)	Calc. thresholds			limit
		AN T1	AN T2	ANT 1	AN T2	AN T1	AN T2	ANT 1	AN T2		ANT 1	ANT 2	Su m	
802.1 1b	2412	8.97	8.85	8± 1.0	8± 1.0	9.0	9.0	7.94 33	7.94 33	5.00	2.46 22	2.46 22	N/A	3.0
	2437	8.74	8.62	8± 1.0	8± 1.0	9.0	9.0	7.94 33	7.94 33	5.00	2.48 16	2.48 16	N/A	3.0
	2462	8.53	8.41	8± 1.0	8± 1.0	9.0	9.0	7.94 33	7.94 33	5.00	2.50 18	2.50 18	N/A	3.0
802.1 1g	2412	8.85	8.71	8± 1.0	8± 1.0	9.0	9.0	7.94 33	7.94 33	5.00	2.46 22	2.46 22	N/A	3.0
	2437	8.67	8.49	8± 1.0	8± 1.0	9.0	9.0	7.94 33	7.94 33	5.00	2.48 16	2.48 16	N/A	3.0
	2462	8.42	8.28	8± 1.0	8± 1.0	9.0	9.0	7.94 33	7.94 33	5.00	2.50 18	2.50 18	N/A	3.0
802.1 1n20	2412	5.49	5.42	5± 1.0	5± 1.0	6.0	6.0	3.98 11	3.98 11	5.00	1.23 66	1.23 66	2.4 732	3.0
	2437	5.31	5.25	5± 1.0	5± 1.0	6.0	6.0	3.98 11	3.98 11	5.00	1.24 30	1.24 30	2.4 86	3.0
	2462	5.25	5.17	5± 1.0	5± 1.0	6.0	6.0	3.98 11	3.98 11	5.00	1.24 93	1.24 93	2.4 986	3.0
802.1 1n40	2422	5.51	5.43	5± 1.0	5± 1.0	6.0	6.0	3.98 11	3.98 11	5.00	1.23 91	1.23 91	2.4 782	3.0
	2437	5.36	5.31	5± 1.0	5± 1.0	6.0	6.0	3.98 11	3.98 11	5.00	1.24 30	1.24 30	2.4 86	3.0
	2452	5.21	5.18	5± 1.0	5± 1.0	6.0	6.0	3.98 11	3.98 11	5.00	1.24 68	1.24 68	2.4 936	3.0

WIFI 5.1G														
Mode	Freque ncy (MHz)	Max Power (dBm)		Target power W/ tolerance (dBm)		Max tune up power tolerance (dBm)		Max Power (mW)		Min. Dist ance (mm)	Calc. thresholds			limit
		AN T1	AN T2	ANT 1	AN T2	AN T1	AN T2	ANT 1	AN T2		ANT 1	ANT 2	Su m	
802.1 1a	5180	6.89	6.85	6± 1.0	6± 1.0	7.0	7.0	3.98 11	3.98 11	5.00	1.81 22	1.81 22	N/A	3.0
	5200	6.72	6.55	6± 1.0	6± 1.0	7.0	7.0	3.98 11	3.98 11	5.00	1.81 56	1.81 56	N/A	3.0
	5240	6.47	6.32	6± 1.0	6± 1.0	7.0	7.0	3.98 11	3.98 11	5.00	1.82 26	1.82 26	N/A	3.0
802.1 1n20	5180	3.55	3.49	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 34	1.14 34	2.2 868	3.0
	5200	3.42	3.36	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 56	1.14 56	2.2 912	3.0
	5240	3.20	3.15	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.15 00	1.15 00	2.3	3.0
802.1 1n40	5190	3.44	3.31	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 45	1.14 45	2.2 89	3.0
	5230	3.18	3.10	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 89	1.14 89	2.2 978	3.0
802.1 1ac20	5180	3.51	3.37	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 34	1.14 34	2.2 868	3.0
	5200	3.24	3.16	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 56	1.14 56	2.2 912	3.0
	5240	3.11	3.08	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.15 00	1.15 00	2.3	3.0
802.1 1ac40	5190	3.41	3.25	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 45	1.14 45	2.2 89	3.0
	5230	3.23	3.12	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 89	1.14 89	2.2 978	3.0
802.1 1ac80	5210	3.28	3.19	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.14 67	1.14 67	2.2 934	3.0

WIFI 5.8G														
Mode	Freque ncy (MHz)	Max Power (dBm)		Target power W/ tolerance (dBm)		Max tune up power tolerance (dBm)		Max Power (mW)		Min. Dist ance (mm)	Calc. thresholds			limit
		AN T1	AN T2	ANT 1	AN T2	AN T1	AN T2	ANT 1	AN T2		ANT 1	ANT 2	Su m	
802.1 1a	5745	6.93	6.85	6± 1.0	6± 1.0	7.0	7.0	3.98 11	3.98 11	5.00	2.40 26	2.40 26	N/A	3.0
	5785	6.77	6.65	6± 1.0	6± 1.0	7.0	7.0	3.98 11	3.98 11	5.00	2.41 09	2.41 09	N/A	3.0
	5825	6.62	6.51	6± 1.0	6± 1.0	7.0	7.0	3.98 11	3.98 11	5.00	2.41 92	2.41 92	N/A	3.0
802.1 1n20	5745	3.81	3.74	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 41	1.20 41	2.4 082	3.0
	5785	3.72	3.68	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 83	1.20 83	2.4 166	3.0
	5825	3.59	3.53	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.21 25	1.21 25	2.4 25	3.0
802.1 1n40	5755	3.83	3.79	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 52	1.20 52	2.4 104	3.0
	5795	3.75	3.63	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 94	1.20 94	2.4 188	3.0
802.1 1ac20	5745	3.87	3.71	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 41	1.20 41	2.4 082	3.0
	5785	3.76	3.62	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 83	1.20 83	2.4 166	3.0
	5825	3.61	3.49	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.21 25	1.21 25	2.4 25	3.0
802.1 1ac40	5755	3.80	3.69	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.21 25	1.21 25	2.4 25	3.0
	5795	3.67	3.51	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 52	1.20 52	2.4 104	3.0
802.1 1ac80	5775	3.79	3.75	3± 1.0	3± 1.0	4.0	4.0	2.51 19	2.51 19	5.00	1.20 73	1.20 73	2.4 146	3.0

Remark:

1. BT and wifi can transmit at the same time.
2. In the case of simultaneous launches for wifi and BT:
The Max Calc. Thresholds : BT:0.3965, WiFi:2.5018
BT and Wifi : $0.3965/3+2.5018/3=0.9661 \leq 1.0$
So a SAR test is not required