

FCC ID:2BW3D-UV01P

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE1M:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.885	1.94	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.493	1.78	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.521	1.79	2±1	3.00	2.00	<5	0.62843	3.00	YES

BLE2M:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.746	1.88	2±1	3.00	2.00	<5	0.61847	3.00	YES
	2.441	2.382	1.73	2±1	3.00	2.00	<5	0.62347	3.00	YES
	2.480	2.372	1.73	2±1	3.00	2.00	<5	0.62843	3.00	YES

2.4GWIFI:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	7.968	6.26	7±1	8.00	6.31	<5	1.95983	3.00	YES
	2.437	7.651	5.82	7±1	8.00	6.31	<5	1.96996	3.00	YES
	2.462	6.144	4.12	6±1	7.00	5.01	<5	1.57280	3.00	YES
802.11g	2.412	6.806	4.79	6±1	7.00	5.01	<5	1.55675	3.00	YES
	2.437	7.937	6.22	7±1	8.00	6.31	<5	1.96996	3.00	YES
	2.462	6.575	4.54	6±1	7.00	5.01	<5	1.57280	3.00	YES
802.11n(HT20)	2.412	7.709	5.90	7±1	8.00	6.31	<5	1.95983	3.00	YES
	2.437	6.195	4.16	6±1	7.00	5.01	<5	1.56480	3.00	YES
	2.462	6.659	4.63	6±1	7.00	5.01	<5	1.57280	3.00	YES
802.11n(HT40)	2.422	7.222	5.27	7±1	8.00	6.31	<5	1.96389	3.00	YES
	2.437	6.547	4.52	6±1	7.00	5.01	<5	1.56480	3.00	YES
	2.452	6.627	4.60	6±1	7.00	5.01	<5	1.56960	3.00	YES

Conclusion:

For the max result : $1.96996 \leq \text{FCC Limit } 3.0$ for 1g SAR.