

TEST REPORT

Reference No...... : WTA26D06174433W001
FCC ID..... : 2BW52-EN2073TX
Applicant : Fuzhou Gaoxinqu Jinshuoguo Electronic Technology Co., Ltd.
Address : 2nd floor, Building 14, No. 18, Yaoxi Road, Yaosha Village, Nanyu Town, Minhou County, Fuzhou City, Fujian Province
Manufacturer : Fuzhou Gaoxinqu Jinshuoguo Electronic Technology Co., Ltd.
Address : 2nd floor, Building 14, No. 18, Yaoxi Road, Yaosha Village, Nanyu Town, Minhou County, Fuzhou City, Fujian Province
Product : Transmitter
Model(s) : EN2073TX
Standards : FCC 47CFR Part 15 Subpart C Section 15.231
Date of Receipt Sample.... : 2026-06-24
Date of Test : 2026-06-29 to 2026-07-23
Date of Issue : 2026-08-19
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Estel Qian

Estel Qian/ Project Engineer

Approved by:



Deval Qin /Designated Reviewer

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 REVISION HISTORY.....	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.....	4
4.2 DETAILS OF E.U.T.	4
4.3 TEST MODE	4
5 EQUIPMENT USED DURING TEST.....	5
5.1 EQUIPMENTS LIST	5
5.2 MEASUREMENT UNCERTAINTY	6
5.3 TEST EQUIPMENT CALIBRATION	6
5.4 TEST FACILITY	6
5.5 SUBCONTRACTED	6
6 TEST SUMMARY	7
7 RADIATED SPURIOUS EMISSIONS	8
7.1 EUT OPERATION	8
7.2 TEST SETUP	9
7.3 SPECTRUM ANALYZER SETUP.....	10
7.4 TEST PROCEDURE	11
7.5 SUMMARY OF TEST RESULTS	11
8 DURATION TIME AND SILENT PERIOD.....	13
8.1 TEST PROCEDURE	13
8.2 TEST RESULT	13
9 EMISSION BANDWIDTH.....	15
9.1 TEST PROCEDURE	15
9.2 TEST RESULT	15
10 ANTENNA REQUIREMENT	16
11 RF EXPOSURE	16
12 PHOTOGRAPHS –TEST SETUP AND EUT	16

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTA26D06174433W001	2026-06-24	2026-06-29 to 2026-07-23	2026-08-19	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product Name: Transmitter
Model No.: EN2073TX
Model Description: N/A
Test Sample No.: 1-1/1
Hardware Version: EN2073(MA)R2
Software Version: YX8305_V12

4.2 Details of E.U.T.

Frequency Range: 433.92MHz
Type of Modulation: ASK
Antenna installation: Spiral Antenna

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Battery: DC 3V from AA battery * 2

4.3 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode	Channel
Transmitting	433.92MHz

5 Equipment Used during Test

5.1 Equipments List

3m Semi-anechoic Chamber for Radiation Emissions 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2026-04-07	2027-04-06
2	Amplifier	Agilent	8447D	2944A10178	2025-07-05 2026-07-04	2026-07-04 2027-07-03
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2025-07-20 2026-07-18	2026-07-19 2027-07-17
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2026-04-07	2027-04-06
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1314	2025-08-09	2026-08-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2025-07-04 2026-07-01	2026-07-03 2027-06-30
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2025-07-04 2026-07-01	2026-07-03 2027-06-30
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2025-07-08 2026-07-01	2026-07-07 2027-06-30
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2026-04-07	2027-04-06
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2025-07-05 2026-07-04	2026-07-04 2027-07-03
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2026-04-19	2027-04-18
4	Amplifier	ANRITSU	MH648A	M43381	2026-04-07	2027-04-06
5	Cable	HUBER+SUHNER	CBL2	525178	2026-04-07	2027-04-06
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025-07-04 2026-07-01	2026-07-03 2027-06-30
2	Spectrum Analyzer	R&S	FSP30	100091	2026-04-07	2027-04-06
3	Humidity Chamber	GF	GTH-225-40-1P	IAA061213	2025-07-04 2026-07-01	2026-07-03 2027-06-30
4	EXA Signal Analyzer	Keysight	N9010A	MY50520207	2026-04-07	2027-04-06

Test Software:

Test Item	Software name	Software version
Radiated Emission(3m)	EZ-EMC	EZ-EMC(RA-03A1-1)

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Confidence interval:95%. Confidence factor: k=2	

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R. China.

5.4 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.
Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

6 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	N/A*
Radiated Spurious Emissions	15.205(a) 15.209 15.231(b), (e)	Pass
Periodic Operation	15.231(e)	Pass
Emission Bandwidth	15.231(c)	Pass
Antenna Requirement	15.203	Pass
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	Pass
Note: Pass=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable *: The EUT is only powered by battery, no need to evaluate AC Power Conducted Emission.		

7 Radiated Spurious Emissions

Test Requirement: FCC Part15 §15.231(b), (e)

Test Method: ANSI C63.10-2020

Test Result: PASS

Measurement Distance: 3m

Limit:

Fundamental Frequency (MHz)	Field Strength of Fundamental (uV/m)	Field Strength of Fundamental (dBuV/m)	Field Strength of Spurious Emission (uV/m)	Field Strength of Spurious Emission (dBuV/m)
44.66-40.70	1,000	60	100	40
70-130	500	54	50	34
130-174	500 to 1,500*	54 to 63.52*	50 to 150*	34 to 43.52*
174-260	1,500	63.52	150	43.52
260-470	1,500 to 5,000*	63.52 to 74*	150 to 500*	43.52 to 54*
Above 470	5,000	74	500	54
* linear interpolations				

7.1 EUT Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 60.9% RH

Atmospheric Pressure: 101.4kPa


EUT Operation:

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep SpeedAuto
 IF Bandwidth.....10kHz
 Video Bandwidth.....10kHz
 Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth.....100kHz
 Video Bandwidth.....300kHz

Above 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth.....1MHz
 Video Bandwidth.....3MHz

7.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane; For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X, Y, Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Summary of Test Results

Test Frequency: 9 kHz~30 MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 5GHz

Frequency	Receiver Reading	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude (Peak)	FCC Part 15.231/15.209/205	
			Height	Polar			QP/AV Limit	Margin
(MHz)	(dBμV)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
433.92	43.80	93	1.7	H	-4.98	38.82	72.87	-34.05
433.92	35.55	108	1.5	V	-4.98	30.57	72.87	-42.30
867.84	29.87	235	2.0	H	4.5	34.37	52.87	-18.50
867.84	30.24	272	2.1	V	4.5	34.74	52.87	-18.13
1301.76	49.23	149	1.1	H	-13.95	35.28	54.00	-18.72
1301.76	52.28	120	2.2	V	-13.95	38.33	54.00	-15.67
1735.68	49.75	36	1.5	H	-10.91	38.84	52.87	-14.03
1735.68	50.50	88	2.4	V	-10.91	39.59	52.87	-13.28
3037.44	49.93	159	1.8	H	-9.14	40.79	52.87	-12.08
3037.44	50.41	30	2.1	V	-9.14	41.27	52.87	-11.60

Note:

1. the measurements were more than 20 dB below the limit and not reported.
2. If the spurious emissions maximized peak measured value complies with the QP/Average limit, it is unnecessary to perform QP/Average measurement.

8 Duration time and silent period

Test Requirement: 47CFR 15.231(e)

Test Method: ANSI C63.10:2020

Test Limit: §15.231(e)

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

Test Mode: Transmitting


8.1 Test Procedure

1. Spectrum analyzer setup as follow
Centre frequency = operating frequency
RBW = 100kHz
VBW = 300kHz
Span = 0Hz
2. Complete the test and save the recorded data


8.2 Test result

Item	Measured Value(s)	Limit (s)	Result
Duration	0.6496	≤ 1	Compliance
Silent period	29.28	$\geq 30 * \text{duration}$ and $\geq 10 \text{ s}$	Compliance


Test Plot refer to next page



Date: 21.JUL.2026 16:13:54



Date: 21.JUL.2026 16:07:39



Date: 21.JUL.2026 16:20:29

9 Emission Bandwidth

Test Requirement: 47CFR 15.231(c)

Test Method: ANSI C63.10:2020

Test Limit: §15.231(c)
The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Test Mode: Transmitting


9.1 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer. EUT and its simulators are placed on a table, let EUT working in test mode, then test it.
2. The bandwidth of the fundamental frequency was measure by spectrum analyser with:
RBW=1% to 5% of OBW, VBW=3 times of RBW.
The 20 dB bandwidth and 99% bandwidth were recorded.

9.2 Test Result

Frequency (MHz)	20dB Bandwidth Emission(kHz)	99% Bandwidth Emission(kHz)	Limit (kHz)	Result
433.92	11.28	25.32	1084.8	Compliance

Test Plot



10 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a Spring Antenna fulfil the requirement of this section.

Note: Please refer to EUT photos for more details.

11 RF Exposure

Remark: Please refer to RF Exposure Report: WTA26D06174433W002

12 Photographs –Test Setup and EUT

Note: Please refer to appendix: Appendix-EN2073TX-Photos.

=====End of Report=====