

TEST REPORT

Applicant : Foshan SolarUp Technology Co.,Ltd
Address : 2-5 / F, Building 10, Wanyang Innovation Park, Shunde No. 8, West Road, Baoyong Industrial Zone Longjiang Town, Shunde District, Foshan City, Guangdong Province, China
Manufacturer : Foshan SolarUp Technology Co.,Ltd
Address : 2-5 / F, Building 10, Wanyang Innovation Park, Shunde No. 8, West Road, Baoyong Industrial Zone Longjiang Town, Shunde District, Foshan City, Guangdong Province, China
Product Name : Solar Charge Controller
Model Number : VT4048, VT, XT, MPJ, MPQ, MRL, MRC, MRE, MPZ, MPK, MRT, MRF, MYC, MRH, MRK, SMPPT
Trademark : N/A
FCC ID : 2BW66-VT4048
Test Date : Jul. 03, 2026 - Jul. 10, 2026
Date of Report : Jul. 28, 2026
Test Result : This device described above has been tested by BKC, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.

Test Procedure Used:

Standards : FCC CFR Title 47 Part 15 Subpart C Section 15.249
ANSI C63.10-2020+Cor.1-2023

Prepared by(Test Engineer):
Carey Zheng



Reviewer(Supervisor):
Casey Wang



Approved(Manager):
Jerry Liao



TABLE OF CONTENT

1. General Information	4
1.1. Description of Device (EUT)	4
1.2. Channel List	4
1.3. Summary of test result	5
1.4. Special Accessories and Auxiliary Equipment	5
1.5. Block Diagram	5
1.6. Test mode	6
1.7. Test configuration	6
1.8. Test Conditions	6
1.9. Measurement Uncertainty (95% confidence levels, k=2)	6
1.10. Test Facility	7
1.11. Test Equipment	8
2. Conducted emission at the mains terminals test	9
2.1. Limit	9
2.2. Test Setup	9
2.3. Test Procedure	9
2.4. Test Result	9
3. Radiated Spurious Emissions	10
3.1. Limit	10
3.2. Test Setup	11
3.3. Test Procedure	13
3.4. Test Result	14
4. -20 dB Bandwidth Measurement	20
4.1. Limit	20
4.2. Test Setup	20
4.3. Test Procedure	20
4.4. Test Result	20
5. Antenna Requirement	22
6. Test Photographs	23
7. Appendix I: Photos of the EUT	24

Revision History of This Test Report

[illegible]

1. General Information

1.1. Description of Device (EUT)

EUT Name : Solar Charge Controller

Model No. : VT4048, VT, XT, MPJ, MPQ, MRL, MRC, MRE, MPZ, MPK, MRT, MRF, MYC, MRH, MRK, SMPPT

Model Difference : Only the model names are different. The main test model is VT4048.

Power Supply : DC 12V/24V/36V/48V $\equiv$ 40A

Operation frequency : 2402-2480MHz

Max. RF output power: : 100.06dBuV/m

Modulation : GFSK

Antenna Type : PCB antenna, Maximum Gain is 2.1dBi

Hardware Version : V1.0

Software Version : V1.0

Intend use environment : Residential, commercial and light industrial environment

1.2. Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

1.3. Summary of test result

RF PART		
Test Items	Test Requirement	Result
Antenna requirement	FCC part 15.203	PASS
AC Power Line Conducted Emission	FCC part 15.207	N/A
Field strength of the fundamental signal	FCC part 15.249 (a)	PASS
Spurious emissions	FCC part 15.249 (a) (d)/15.209	PASS
Band edge	FCC part 15.249 (d)/15.205	PASS
20dB Occupied Bandwidth	FCC part 15.215 (c)	PASS
Remark: N/A is an abbreviation for Not Applicable. Measurement Uncertainty is not taken into account for conformity statement		


1.4. Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Hardware Version	Software Version
Serial port board	/	USB-TTL-01	/	/
PC	DELL	DESKTOP-P4V7M AJ	21H1	Windows 10
DC Source	/	BKC-012	/	/


1.5. Block Diagram

Conducted Emission
N/A

Radiated Emission



RF Conducted Test



1.6. Test mode

The special RF test software was used to control EUT work in Continuous BLE TX mode, and select test channel, wireless mode.

Test mode	Low channel	Middle channel	High channel
GFSK	2402MHz	2440MHz	2480MHz
Note: /			

1.7. Test configuration

Test Software	RFTTest_exe
Power level setup	Default

1.8. Test Conditions

Category	Normal Conditions	Extreme Conditions
Temperature range	15-35℃	N/A
Humidity range	20-75%	N/A
Pressure range	86-106kPa	N/A
Power supply	DC 48V	N/A
Note: N/A is an abbreviation for Not Applicable.		

1.9. Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for radio frequency	$\pm 7 \times 10^{-8}$	
Conducted Emissions (150kHz~30MHz)	$\pm 2.54\text{dB}$	
Radiated Emission(9KHz~30MHz)	$\pm 1.6\text{ dB}$	
Radiated Emission(30MHz~1GHz)	Vertical: $\pm 4.14\text{dB}$ Horizontal: $\pm 4.25\text{dB}$	
Radiated Emission(1GHz~6GHz)	$\pm 3.9\text{dB}$	
Radiated Emission(6GHz~18GHz)	$\pm 4.3\text{dB}$	
Radiated Emission(18GHz~40GHz)	$\pm 3.38\text{dB}$	
Uncertainty for conducted RF Power	$\pm 0.20\text{dB}$	
Conducted spurious emissions	$\pm 0.24\text{dB}$	
Uncertainty for temperature	0.6℃	
Uncertainty for humidity	1%	
Bandwidth	$\pm 1.5 \times 10^{-6}$	
Time	$\pm 2\%$	
Duty Cycle	$\pm 2\%$	
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%		

1.10. Test Facility

Site Description		
Name of Firm	:	Shenzhen BKC Testing Co., Ltd.
Site Location	:	Room 103, 1/F, Huaya Building, Huaya Industrial Park, Longhua Community, Longhua District, Shenzhen, Guangdong, China.
ISED CAB identifier	:	CN0188
ISED Company Number	:	34333
FCC Designation Number	:	CN1416
FCC Test Firm Registration Number	:	701543



1.11. Test Equipment

Radiated Test Site(Below 1G and Above 1G)

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Antenna	Schwarzbeck	VULB 9168	01321	Mar. 20. 2025	Mar. 19. 2028
2	EMI Test Receiver	R&S	ESRP	101478	Mar. 10. 2025	Mar. 09. 2026
3	Preamplifier	HP	8447D	2727A05345	Mar. 10. 2025	Mar. 09. 2026
4	Double Ridged Broadband	SCHWARZBEC K	BBHA 9120D	02621	Mar. 10. 2025	Mar. 19. 2028
5	Preamplifier	Schwarzbeck	BBV 9718D	00041	Mar. 10. 2025	Mar. 09. 2026
6	Rf cables	HUBER+SUHNE R	8M-RE	N/A	Mar. 10. 2025	Mar. 09. 2026
7	Rf cables	HUBER+SUHNE R	1.5M-RE	N/A	Mar. 10. 2025	Mar. 09. 2026
8	Rf cables	HUBER+SUHNE R	1.5M-AP-RE	N/A	Mar. 10. 2025	Mar. 09. 2026
9	Loop antenna	TESEQ	HLA6121	58357	Mar. 09. 2025	Mar. 10. 2026
10	Spectrum analyzer	R&S	FSP40	200061	Feb. 13. 2025	Feb. 12. 2026
11	Double Ridged Broadband Horn Antenna	COM-POWER	AH-1840	10100009	Mar. 10. 2025	Mar. 09. 2026
12	Spectrum	Agilent	N9020A	MY50510311	Mar. 09. 2025	Mar. 10. 2026
13	High Pass Filter	Bafang	BSF5G	2024052610	Mar. 09. 2025	Mar. 10. 2026
14	RE Testing software	EZ	EZ-EMC	/	/	/

RF Test Site

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum	Agilent	N9020A	MY50510311	Mar. 09. 2025	Mar. 10. 2026
2	Vector source	Agilent	N5182A	MY47420223	Mar. 09. 2025	Mar. 10. 2026
3	All instrument	Rohde & Schwarz	CMW 500	101131	Mar. 09. 2025	Mar. 10. 2026
4	control unit	MW	MW100-RFCB	MW200411BK-34	Mar. 09. 2025	Mar. 10. 2026
5	RF Testing software	MW	MTS 8310	/	Mar. 09. 2025	/
6	Spectrum analyzer	R&S	FSP40	200061	Feb. 13. 2025	Feb. 12. 2026

Test software

Software name	RF Testing software
Software version	2.0.0.0
Software name	RE Testing software
Software version	EMEC-03A2 RE+
Software name	CE Testing software
Software version	EMEC-3A1+

2. Conducted emission at the mains terminals test


2.1.Limit

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020+Cor.1-2023
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

2.2.Test Setup



2.3.Test Procedure

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. For the actual test configuration, please refer to the related Item - EUT Test Photos.

2.4.Test Result

N/A

EUT power supply is provided by DC, is not applicable in this Test report.

3. Radiated Spurious Emissions

3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.249

Test Result: PASS

Measurement Distance: 3m

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	360KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Limit 1:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log(2400/F(\text{kHz})) + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log(24000/F(\text{kHz})) + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log(30) + 40$
30 ~ 88	100	3	100	$20\log(100)$
88 ~ 216	150	3	150	$20\log(150)$
216 ~ 960	200	3	200	$20\log(200)$
Above 960	500	3	500	$20\log(500)$


Limit 2:

§ 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.


3.2. Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



3.3. Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high - pass filter is used during radiated emissions above 1GHz measurement.




3.4. Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.


Test Frequency : 30MHz ~ 1GHz

Radiation Emission Test Data			
Temperature:	25.1 °C	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Horizontal
Test Voltage :	DC 48V	Test Mode	BLE Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	141.3298	41.70	-15.78	25.92	43.50	-17.58	QP
2 *	180.0165	49.04	-17.31	31.73	43.50	-11.77	QP
3	199.2855	48.16	-18.82	29.34	43.50	-14.16	QP
4	239.9874	48.73	-17.05	31.68	46.00	-14.32	QP
5	302.4812	41.93	-15.35	26.58	46.00	-19.42	QP
6	958.7943	36.67	-5.30	31.37	46.00	-14.63	QP

Radiation Emission Test Data			
Temperature:	25.1°C	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Vertical
Test Voltage :	DC 48V	Test Mode	BLE Transmitting



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	38.8878	44.70	-16.22	28.48	40.00	-11.52	QP
2	70.0902	45.27	-19.00	26.27	40.00	-13.73	QP
3	133.6188	43.88	-16.35	27.53	43.50	-15.97	QP
4	202.8103	49.17	-18.76	30.41	43.50	-13.09	QP
5	478.8455	45.83	-12.33	33.50	46.00	-12.50	QP
6	958.7943	36.28	-5.30	30.98	46.00	-15.02	QP

Remark:

1. Level = Reading + Correct Factor
2. Correct Factor=Antenna FCable Loss - Preamplifier Factor
3. Only the worst Data GFSK/2402MHz mode Record in the report.

Test Frequency 1GHz-25GHz:

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	54.32	33.55	5.81	31.52	58.10	74.00	-15.90	Pk
V	4804.00	22.30	33.55	5.81	31.52	26.08	54.00	-27.92	AV
V	7206.00	43.17	32.33	6.32	36.30	53.46	74.00	-20.54	Pk
V	7206.00	24.89	32.33	6.32	36.30	35.18	54.00	-18.82	AV
V	9608.00	40.85	31.85	7.45	37.80	54.25	74.00	-19.75	Pk
V	9608.00	29.62	31.85	7.45	37.80	43.02	54.00	-10.98	AV
V	12010.00	44.44	31.02	8.99	39.50	61.91	74.00	-12.09	Pk
V	12010.00	28.01	31.02	8.99	39.50	45.48	54.00	-8.52	AV
H	4804.00	43.31	33.55	5.77	31.52	47.05	74.00	-26.95	Pk
H	4804.00	22.67	33.55	5.77	31.52	26.41	54.00	-27.59	AV
H	7206.00	44.09	32.33	6.32	36.30	54.38	74.00	-19.62	Pk
H	7206.00	20.76	32.33	6.32	36.30	31.05	54.00	-22.95	AV
H	9608.00	44.06	31.85	7.45	37.80	57.46	74.00	-16.54	Pk
H	9608.00	27.36	31.85	7.45	37.80	40.76	54.00	-13.24	AV
H	12010.00	42.91	31.02	8.99	39.50	60.38	74.00	-13.62	Pk
H	12010.00	31.56	31.02	8.99	39.50	49.03	54.00	-4.97	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2440MHz									
V	4880.00	42.58	33.52	5.87	31.57	46.50	74.00	-27.50	Pk
V	4880.00	23.14	33.52	5.87	31.57	27.06	54.00	-26.94	AV
V	7320.00	43.85	32.29	6.37	36.35	54.28	74.00	-19.72	Pk
V	7320.00	23.21	32.29	6.37	36.35	33.64	54.00	-20.36	AV
V	9760.00	44.85	31.61	7.73	37.89	58.86	74.00	-15.14	Pk
V	9760.00	27.84	31.61	7.73	37.89	41.85	54.00	-12.15	AV
V	12200.00	46.04	30.83	9.36	39.57	64.14	74.00	-9.86	Pk
V	12200.00	31.31	30.83	9.36	39.57	49.41	54.00	-4.59	AV
H	4880.00	42.46	33.52	5.87	31.57	46.38	74.00	-27.62	Pk
H	4880.00	23.44	33.52	5.87	31.57	27.36	54.00	-26.64	AV
H	7320.00	44.13	32.29	6.37	36.35	54.56	74.00	-19.44	Pk
H	7320.00	24.89	32.29	6.37	36.35	35.32	54.00	-18.68	AV
H	9760.00	40.92	31.61	7.73	37.89	54.93	74.00	-19.07	Pk
H	9760.00	27.85	31.61	7.73	37.89	41.86	54.00	-12.14	AV
H	12200.00	42.25	30.83	9.36	39.57	60.35	74.00	-13.65	Pk
H	12200.00	27.68	30.83	9.36	39.57	45.78	54.00	-8.22	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	43.21	33.48	5.96	31.91	47.60	74.00	-26.40	Pk
V	4960.00	21.16	33.48	5.96	31.91	25.55	54.00	-28.45	AV
V	7440.00	43.69	32.12	6.53	36.75	54.85	74.00	-19.15	Pk
V	7440.00	22.04	32.12	6.53	36.75	33.20	54.00	-20.80	AV
V	9920.00	43.61	31.34	7.93	37.03	57.23	74.00	-16.77	Pk
V	9920.00	26.14	31.34	7.93	37.03	39.76	54.00	-14.24	AV
V	12400.00	42.01	30.66	10.21	39.07	60.63	74.00	-13.37	Pk
V	12400.00	30.55	30.66	10.21	39.07	49.17	54.00	-4.83	AV
H	4960.00	43.53	33.48	5.96	31.91	47.92	74.00	-26.08	Pk
H	4960.00	21.97	33.48	5.96	31.91	26.36	54.00	-27.64	AV
H	7440.00	42.37	32.12	6.53	36.75	53.53	74.00	-20.47	Pk
H	7440.00	24.56	32.12	6.53	36.75	35.72	54.00	-18.28	AV
H	9920.00	40.84	31.34	7.93	37.03	54.46	74.00	-19.54	Pk
H	9920.00	25.35	31.34	7.93	37.03	38.97	54.00	-15.03	AV
H	12400.00	43.52	30.66	10.21	39.07	62.14	74.00	-11.86	Pk
H	12400.00	31.54	30.66	10.21	39.07	50.16	54.00	-3.84	AV

Note: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Band Edge:

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margin (dB)	Detect or Type	Result
GFSK	Low Channel: 2402MHz										
	H	2310.00	54.11	34.58	5.66	24.69	49.88	74.00	-24.12	PK	PASS
	H	2310.00	44.35	34.58	5.66	24.69	40.12	54.00	-13.88	AV	PASS
	H	2390.00	53.57	34.56	5.71	24.51	49.23	74.00	-24.77	PK	PASS
	H	2390.00	44.54	34.56	5.71	24.51	40.20	54.00	-13.80	AV	PASS
	H	2400.00	54.49	34.55	5.77	24.58	50.29	74.00	-23.71	PK	PASS
	H	2400.00	44.72	34.55	5.77	24.58	40.52	54.00	-13.48	AV	PASS
	V	2310.00	53.89	34.58	5.66	24.69	49.66	74.00	-24.34	PK	PASS
	V	2310.00	44.86	34.58	5.66	24.69	40.63	54.00	-13.37	AV	PASS
	V	2390.00	54.45	34.56	5.71	24.51	50.11	74.00	-23.89	PK	PASS
	V	2390.00	44.21	34.56	5.71	24.51	39.87	54.00	-14.13	AV	PASS
	H	2400.00	53.97	34.55	5.77	24.58	49.77	74.00	-24.23	PK	PASS
	H	2400.00	44.44	34.55	5.77	24.58	40.24	54.00	-13.76	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	53.62	34.49	5.86	24.98	49.97	74.00	-24.03	PK	PASS
	H	2483.50	44.14	34.49	5.86	24.98	40.49	54.00	-13.51	AV	PASS
	H	2500.00	53.40	34.43	5.93	25.03	49.93	74.00	-24.07	PK	PASS
	H	2500.00	44.36	34.43	5.93	25.03	40.89	54.00	-13.11	AV	PASS
	V	2483.50	54.41	34.49	5.86	24.98	50.76	74.00	-23.24	PK	PASS
	V	2483.50	44.76	34.49	5.86	24.98	41.11	54.00	-12.89	AV	PASS
	V	2500.00	54.93	34.43	5.93	25.03	51.46	74.00	-22.54	PK	PASS
	V	2500.00	44.33	34.43	5.93	25.03	40.86	54.00	-13.14	AV	PASS
Remark:											
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier;											
Margin= Emission Level - Limit											

Field Strength of The Fundamental Signal Data

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	2402.000	101.95	34.55	5.77	26.51	99.68	114.00	-14.32	Pk
V	2402.000	81.33	34.55	5.77	26.51	79.06	94.00	-14.94	AV
H	2402.000	102.33	34.55	5.77	26.51	100.06	114.00	-13.94	Pk
H	2402.000	83.24	34.55	5.77	26.51	80.97	94.00	-13.03	AV
Mid Channel:2440MHz									
V	2440.000	101.74	34.51	5.81	26.53	99.57	114.00	-14.43	Pk
V	2440.000	81.14	34.51	5.81	26.53	78.97	94.00	-15.03	AV
H	2440.000	101.92	34.51	5.81	26.53	99.75	114.00	-14.25	Pk
H	2440.000	82.11	34.51	5.81	26.53	79.94	94.00	-14.06	AV
High Channel:2480MHz									
V	2480.000	101.65	34.49	5.85	26.79	99.80	114.00	-14.20	Pk
V	2480.000	80.94	34.49	5.85	26.79	79.09	94.00	-14.91	AV
H	2480.000	101.74	34.49	5.85	26.79	99.89	114.00	-14.11	Pk
H	2480.000	81.25	34.49	5.85	26.79	79.40	94.00	-14.60	AV

Remark:


1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
2. Margin= Emission Level - Limit

4. -20 dB Bandwidth Measurement

4.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.215

4.2.Test Setup




4.3.Test Procedure


1. Set the spectrum analyzer: RBW = 1%-5% OBW
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by -20 dB relative to the maximum level measured in the fundamental emission

4.4.Test Result


Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-20dB OBW (MHz)
GFSK	2402	Ant1	1.011	1.082
	2440	Ant1	1.010	1.061
	2480	Ant1	1.013	1.080



OBW NVNT 2402MHz Ant1



OBW NVNT 2440MHz Ant1



OBW NVNT 2480MHz Ant1

5. Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The antenna is PCB antenna which permanently attached, and the best case gain of the antenna is 2.1dBi. It complies with the standard requirement.



6. Test Photographs

Please see Attachment BKC26073806GE-3.



7. Appendix I: Photos of the EUT

Please see Attachment BKC26073806GE-4 and BKC26073806GE-5.

