



RF EXPOSURE EVALUATION

FCC ID:2BW9T-AMOS-03

Report Number..... : ZKT-260730L2046E-2

Date of Test..... July. 11, 2026 to Aug. 03, 2026

Date of issue..... Aug. 03, 2026

Total number of pages 8

Test Result PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : AMOS SWEETS INC.

Address : 732 S 6TH ST, STE R, LAS VEGAS, NEVADA, USA

Manufacturer's name : AMOS SWEETS INC.

Address : 732 S 6TH ST, STE R, LAS VEGAS, NEVADA, USA

Test specification:

Standard FCC 47CFR §2.1091
KDB 447498 D01 General RF Exposure Guidance v06

Test procedure /

Non-standard test method N/A

Test Report Form No. : TRF-EL-112_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2021-04-22

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : AMOS TastySounds Wireless Audio Lollipop

Trademark : AMOS

Model/Type reference..... : AMOS-03

Ratings..... : Input: DC 5V



Testing procedure and testing location:

Testing Laboratory: Shenzhen ZKT Technology Co., Ltd.
Address: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature): Jim Liu

Reviewer (name + signature): Jackson Fang

Approved (name + signature): Lake Xie





Table of Contents

	Page
1. VERSION	4
2. TEST FACILITY	5
3.GENERAL DESCRIPTION OF EUT	6



1. Version

Report No.	Version	Description	Approved
ZKT-260730L2046E-2	Rev.01	Initial issue of report	Aug. 03, 2026



2. TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 927491

Designation Number: CN1431

IC Registered No.: 27033

CAB identifier: CN0110



3.GENERAL DESCRIPTION OF EUT

Product Name:	AMOS TastySounds Wireless Audio Lollipop
Trade Mark:	AMOS
Model No.:	AMOS-03
Serial No.:	N/A
Model Different.:	N/A
Hardware Version:	V2.2
Software Version:	V1
Sample(s) Status:	Engineer sample
Sample Number:	ZKT-260730L2046
Channel numbers:	79
Operation Frequency:	2402MHz~2480MHz
Modulation technology:	GFSK, $\pi/4$ -DQPSK, 8DPSK(3Mbps)
Antenna Type:	SMD
Antenna gain:	2.7dBi
Power Supply:	Input: DC 5V
Battery Capacity:	Model: 400930 Brand: N/A Rated Voltage: 3.7V Capacity: 80mAh

Note1: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Note2: The EUT's all information provided by client.



According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison



Here,

For BLE

RF Function	output power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (dBm)
BT	-3.95	-4±1	-3

Mode	Frequency	Antenna Distance	RF output power including tune up (dBm)		SAR Test Exclusion Threshold	SAR Test Exclusion	Estimated SAR
	GHz		dBm	mw			
8DPSK(BT)	2.48	5	-3	0.501	0.158	Yes	/

Conclusion:

1. $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] < 3.0$.
2. SAR Test Exclusion Thresholds is 3.0 for separation distance 5mm. Therefore, SAR test is not required.