

承 認 書

SPECIFICATION FOR APPROVAL

客 戶: CUSTOMER:	
客 戶 料 號: CUST P/N:	
聚福 料 號: FINE P/N:	G43.5 Double-Slot - 6.5UH; Single Coil: 0.08× 48P-10TS
產 品 型 號: DESC:	Φ43.5MMX5.0MMX0.6MM
日 期: DATE:	2024/5/4
版 本: Version:	A.0

擬制 PREPARED BY	審核 CHECKED BY	批准 APPROVED BY	客戶承認 CUSTOMER APPROVE
陈小英 Chen Xiaoying	宁元 Ningyuan	周文韬 Zhou Wentao	

东莞聚福电子科技有限公司

Dongguan Jufu Electronic Technology Co., Ltd.

工廠地址：东莞市常平镇苏坑村

Factory Address: Sukeng Village, Changping Town, Dongguan City

TEL: 15015156515


FAX: 0769-84526500

E-mail: 281749556@qq.com


版本變更履歷

Version Change History

[illegible]

SPECIFICATION

产 品 型 号: DESC	Φ43.5MM*5MM*0.6MM	版本 Rev: A.0	客 户 CUST: 客户料号 CUST P/N:	XXX
一、尺寸 DIMENSION:(mm)			A	38.50±1.5
			B	20.5±0.5
			C	1.25 Max
			D	50±2
			E	4±2
			F	43.5±1
			G	10.0 ref
			H	1.6 Max
			I	5.3 ref
二、原理图 SCHEMATIC DIAGRAM:				
				

Note: Cross-shaped cutout; apply 1 – 2 layers of high-temperature adhesive tape (ref. width: 7 mm) around the cutout perimeter; use 1 mm thick foam backing adhesive.

序号 NO.	端子 TERMINAL		线径 WIRE	圈数 Turns	绕线方向 Winding Direction
1	S	F	silk-covered wire 0.08*48P	10Ts	CCW

温度 TEMPERATURE:25±10℃, 湿度 RELATIVE HUMIDITY:65±20%

序号 NO.	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND.	S-F	3.8uH ±20%Single Coil	100KHz/0.25V	LCZ METER 1062B
2	IND.	S-F	6.3uH ±10%Magnetic Plate	100KHz/0.25V	LCZ METER 1062B
3	DCR	S-F	≤50m Ω		LCZ METER 502B

擬制/日期 PREPARED BY/DATE	審核/日期 CHECKED BY/DATE
------------------------	-----------------------

陈小英 Chen Xiaoying2024/03/23	周文韬 Zhou Wentao2025/3/31
-----------------------------	--------------------------