

ShenzhenYu Sheng Communications

Shenzhen Yu Sheng Communications Electronics co., LTD

TEL: +86 0755-28640107

FAX: +86 755 28694967

APPROVAL

Version: A1

Customer

:

QC Description Spec
DESCRIPTION:

2.4G Built-in FPCAntenna100mm

Part No.
PART NO.:

YS030-0017

Customer Part No.
CUS PART NO.:

Date

D A T E:

2019-7-24

Sample Approval Stamp:

ENGINEERING ENGINEERING DEPARTMENT	QC Q C DEPARTMENT	SALES SALES DEPARTMENT

Customer Approval Stamp :

ENGINEERING ENGINEERING DEPARTMENT	QC Q C DEPARTMENT	PURCHASING PURCHASING DEPARTMENT

★CustomerCustomer Sample Confirmation Notes:

ShenzhenYu Sheng Communications

Shenzhen Yu Sheng Communications Electronics co., LTD

TEL: +86 0755-28640107

FAX: +86 755 28694967

Electrical and Mechanical Specifications

Elec. Perf. Specs		Electrical Specifications	
Frequency Range	2400-2500MHZ	Frequency Range	2400-2500MHZ
VSWR	≤ 2.0	VSWR	≤ 2.0
Gain	2.41DBI	GAIN	2.41DBI
Input Impedance	50 Ω	Input Impedance	50 Ω
Mech. Specs		Mechanical Specifications	
AntennaColor	BLACK	Antenna Color	BLACK
Connector Type	IPEX	Input connector	ipex
Operating Temperature	-40℃~+85℃	Working Temperature	-40℃~+85℃
Operating Humidity	20~80%	Working Humidity	20~80%

Product Photos:

Factory Address: 3F-4F, No.102 Aoxi Road, Aobei Village, Henggang Town, Longgang District, Shenzhen1023-4

ShenzhenYu Sheng Communications

Shenzhen Yu Sheng Communications Electronics co., LTD

TEL: +86 0755-28640107

FAX: +86 755 28694967



Dimension Drawing


Factory Address: 3F-4F, No.102 Aoxi Road, Aobei
Village, Henggang Town, Longgang District, Shenzhen 1023-4

ShenzhenYu Sheng Communications


Shenzhen Yu Sheng Communications Electronics co., LTD

TEL: +86 0755-28640107

FAX: +86 755 28694967



Packaging Drawing:



Factory Address: 3F-4F, No.102 Aoxi Road, Aobei Village, Henggang Town, Longgang District, Shenzhen 1023-4

ShenzhenYu Sheng Communications

Shenzhen Yu Sheng Communications Electronics co., LTD

TEL: +86 0755-28640107

FAX: +86 755 28694967

Environmental Performance Test:

Item	Test Conditions	Specification
Storage Environment	Test temperature, humidity, and air pressure (unless otherwise specified) are as follows: 1. 1. Temperature:-30℃~+80℃ 2. 2. Relative Humidity:45%-85% 3. 3. Air Pressure:86kpa-106kpa	Normal Electrical and Mechanical Performance
Temperature Cycling Test	Perform70℃and40℃for5cycles, then under normal conditions for 1-2H, inspect appearance quality.	Dimensions and mechanical and electrical performance shall meet requirements
Constant Damp Heat Test	Relative humidity $95\pm3\%$, test temperature:40℃.for2Hduration, Within5minof removing sample, measure electrical performance, under normal conditions for 1-2H, inspect appearance quality.	Dimensions and mechanical and electrical performance shall meet requirements
Vibration Test	Frequency range:10-55HZ, displacement amplitude:0.35MM, acceleration amplitude: 50.0M/S, sweep cycles:30times	Normal Electrical and Mechanical Performance
Drop Test	1Mfree fall from 1M height along mutually perpendicular axes for3times	Normal Electrical and Mechanical Performance

Factory Address: 3F-4F, No.102 Aoxi Road, Aobei Village,Henggang Town, Longgang District, Shenzhen1023-4


ShenzhenYu Sheng Communications

Shenzhen Yu Sheng Communications Electronics co., LTD


TEL: +86 0755-28640107

FAX: +86 755 28694967

Sample Test



Gain Test:



Factory Address: 3F-4F, No.102 Aoxi Road, Aobei Village, Henggang Town, Longgang District, Shenzhen 1023-4



ShenzhenYu Sheng Communications

Shenzhen Yu Sheng Communications Electronics co., LTD

TEL: +86 0755-28640107

FAX: +86 755 28694967

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Point Values											
Ant. Port Input Pwr. (dBm)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Tot. Rad. Pwr. (dBm)	-2.69	-2.52	-2.23	-2.04	-1.95	-2.28	-2.44	-2.49	-2.60	-2.83	-2.45
Peak EIRP (dBm)	1.46	1.67	1.98	2.24	2.24	1.94	1.91	2.04	2.12	2.05	2.41
Directivity (dBi)	4.15	4.19	4.21	4.28	4.19	4.22	4.36	4.52	4.72	4.87	4.86
Efficiency (dB)	-2.69	-2.52	-2.23	-2.04	-1.95	-2.28	-2.44	-2.49	-2.60	-2.83	-2.45
Efficiency (%)	53.80	56.00	59.80	62.50	63.80	59.20	57.00	56.40	55.00	52.20	56.90
Gain (dBi)	1.46	1.67	1.98	2.24	2.24	1.94	1.91	2.04	2.12	2.05	2.41
NHPRP $\pm\pi/4$ (dBm)	-3.69	-3.36	-2.92	-2.52	-2.55	-2.92	-3.24	-3.47	-3.56	-3.59	-2.96
NHPRP $\pm\pi/6$ (dBm)	-4.35	-4.03	-3.59	-3.20	-3.23	-3.60	-3.92	-4.14	-4.22	-4.26	-3.65
NHPRP $\pm\pi/8$ (dBm)	-4.96	-4.64	-4.21	-3.82	-3.85	-4.21	-4.53	-4.75	-4.83	-4.88	-4.29
Upper Hem. PRP (dBm)	-5.17	-4.93	-4.58	-4.35	-4.22	-4.52	-4.66	-4.67	-4.76	-4.96	-4.55
Lower Hem. PRP (dBm)	-6.30	-6.22	-6.01	-5.89	-5.85	-6.22	-6.43	-6.51	-6.65	-6.93	-6.61
Upper Hem. PRP (%)	30.38	32.14	34.79	36.77	37.80	35.31	34.18	34.09	33.41	31.88	35.06
Lower Hem. PRP (%)	23.45	23.85	25.03	25.78	26.03	23.90	22.78	22.33	21.60	20.29	21.82



Factory Address: 3F-4F, No.102 Aoxi Road, Aobei Village, Henggang Town, Longgang District, Shenzhen 1023-4