



EMF TEST REPORT

Product Name: LoRaWAN Type III Outdoor Gateway

Model Number: LGW915M

FCC ID: 2BWC6LGW915M

Issued For : AdoModel Tech Inc
6679 Peachtree IND BLVD STE N, Peachtree Corners,
Georgia, United States 30092-4303

Issued By : Shenzhen LGT Test Service Co., Ltd.
Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT26G061HA01

Sample Received Date: Jul. 09, 2026

Date of Test: Jul. 09, 2026 ~ Jul. 27, 2026

Date of Issue: Jul. 27, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: AdoModel Tech Inc

Address: 6679 Peachtree IND BLVD STE N, Peachtree Corners, Georgia,
United States 30092-4303

Manufacturer: AdoModel Tech Inc

Address: 6679 Peachtree IND BLVD STE N, Peachtree Corners, Georgia,
United States 30092-4303

Product Name: LoRaWAN Type III Outdoor Gateway

Trademark: RIVAIOT

Model Number: LGW915M

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR §2.1091 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

chris chen

Chris Chen
Engineer

Approved by:

V. Meati

Technical Director





TABLE OF CONTENTS

1 . GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	5
2 . FCC 47CFR § 2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	7
2.4 CLASSIFICATION	7
2.5 TEST RESULT	8



Revision History

Rev.	Issue Date	Revisions
00	Jul. 27, 2026	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	LoRaWAN Type III Outdoor Gateway	
Test Model Number:	LGW915M	
Series Number:	N/A	
Model Difference:	N/A	
Frequency Bands:	LORA	915MHz
	LTE	LTE Band 2:1850~1910MHz LTE Band 4:1710~1755MHz LTE Band 5: 824~849MHz LTE Band 12: 699-716MHz LTE Band 17:704~716MHz
Adapter:	Input: AC 100-240V 50/60Hz 0.8A Output: DC 48.0V 0.5A 24.0W	
Hardware Version:	N/A	
Software Version:	N/A	

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate:	FCC Registration No.: 746540
	CAB ID: CN0136



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
0.3-3.0	614	1.63	*(100)
3.0-30	1842/f	4.89/f	*(900/f ²)
30-300	61.4	0.163	1.0
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
0.3-1.34	614	1.63	*(100)
1.34-30	824/f	2.19/f	*(180/f ²)
30-300	27.5	0.073	0.2
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

* = Plane-wave equivalent power density.

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.5 TEST RESULT

Turn up Result

Mode	Turn up Power
LTE B2	24.5±1dBm
LTE B4	25±1dBm
LTE B5	24.5±1dBm
LTE B12	23.5±1dBm
LTE B17	23.5±1dBm
LORA	-3±1.5dBm

The MPE result of worst mode:

RF Function	Max Turn up Power (dBm)	Duty cycle factor	Max Power (dBm)	Max Power (mW)	ANT Gain (dBi)	ANT Gain (gain of antenna in linear scale)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
LTE Band 2	25.5	0	25.5	354.81	1.59	1.44	0.102	1.000	0.102	Pass
LTE Band 4	26	0	26	398.11	1.84	1.53	0.121	1.000	0.121	Pass
LTE Band 5	25.5	0	25.5	354.81	0.45	1.11	0.078	0.549	0.143	Pass
LTE Band 12	24.5	0	24.5	281.84	-1.85	0.65	0.037	0.466	0.079	Pass
LTE Band 17	24.5	0	24.5	281.84	-1.85	0.65	0.037	0.469	0.078	Pass

RF Function	Frequency (MHz)	Max Turn up Power (dBm)	Max Turn up Power (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
LORA	915	-1.50	0.7079458	0.0001408	0.610	0.00023	Pass

Multiple transmission: LORA + LTE Band 5=0.00023+0.143=0.1453 < 1

Note:

1. The RF Exposure is less than the limit, complies with the exemption requirements.

*****END OF THE REPORT*****