

TEST REPORT

EUT Description	LoRaWAN
Brand Name	RIVAIOT
Model Name	LoRa DTU
Additional Model No	NA
FCC ID	2BWC6LORA485DL
Date of Test Start/End	2026-9-18 / 2026-09-22

Applicant	AdoModel Tech Inc.
Address	6679Peachtree Industrial Blvd Suite N, Peachtree Corners, GA30092
Manufacturers	Same as Application
Address	Same as Application
Factory	Same as Application
Address	Same as Application

Reference Standards	447498 D01 General RF Exposure Guidance v06 (see section 1)
---------------------	--

Test Report identification	RL20260824005EG Rev. 00
Revision Control	This test report revision replaces any previous test report revision. (see Document Changes)

Test Result:	Pass*
*The EUT complied with the test item(s) of the above standard (s), refer to the test summary for details.	

Authorized for issue by:

 Jim Chen / Project Engineer	 Jason Li / Reviewer
--	--

Radiolink Testing (Shenzhen) Co., Ltd.
Room 103, Building B, Jinghang Industrial Park, Area 71, Xingdong Community, Xin'an Subdistrict, Bao'an District,
Shenzhen, Guangdong Province, China
Tel: +86 0755 23080694

Document Changes

Status	Date of issue	Revision	Description of the performed changes
Active	2026-09-22	Rev. 00	None (original version).



2 Contents

	Page
1 Cover Page.....	1
2 Contents.....	3
3 General Information.....	4
3.1 Details of E.U.T.....	4
3.2 Test Location.....	4
3.3 Test Facility.....	4
3.4 Deviation from Standards.....	4
3.5 Abnormalities from Standard Conditions.....	4
4 RF Exposure Evaluation For FCC.....	5
4.1 RF Exposure Compliance Requirement.....	5
4.1.1 Limits.....	5
4.1.2 Test Procedure.....	5
4.1.3 EUT RF Exposure Evaluation.....	5



3 General Information

3.1 Details of E.U.T.

Power supply:	Rated Voltage :12V Input Rated Current :2A Rated Power:3.4W
EUT Serial Number	S/N:26341D00001
Operating Frequency:	902.3MHz to 914.9MHz
Modulation Technique:	LoRa Chirp Spread Spectrum (CSS), FHSS as applicable
Modulation Type:	DSSS OQPSKLR
Number of Channels:	2
Antenna Type:	External omnidirectional antenna
Antenna Gain*:	☒ Provided by client
	3dBi

Note: *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Radiolink test lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

Remark:As above information is provided and confirmed by the applicant. Radiolink test lab is not liable to the accuracy, suitability, reliability or/and integrity of the information.

3.2 Test Location

All tests were performed at:

Radiolink Testing (Shenzhen) Co., Ltd.

Room 103, Building B, Jinghang Industrial Park, Area 71, Xingdong Community, Xin'an Subdistrict, Bao'an District, Shenzhen, Guangdong Province, China

Tel: +86 0755 23080694

No tests were sub-contracted.

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

. A2LA (Certificate No. 7572.01)

Radiolink Testing (Shenzhen) Co., Ltd, Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 7572.01.

3.4 Deviation from Standards

None

3.5 Abnormalities from Standard Conditions

None

4 RF Exposure Evaluation For FCC

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at test channel.

4.1.3 EUT RF Exposure Evaluation

Frequency Band	Technology	Max Conducted Power (dBm)	Max Conducted Power (mW)	Antenna Gain (dBi)	E Field Strength (mW/cm ²)	Limit (mW/cm ²)	Result
902.3 MHz	LoRa	18.43	69.66	3	0.0216	0.60	PASS
914.9 MHz	LoRa	17.87	61.24	3	0.0190	0.61	PASS

"Based on the declared maximum tune-up power and antenna gain, the MPE distance-weighted field strength/power density was calculated. The maximum MPE ratio (including simultaneous transmission) is less than 0.60, complying with the limits specified in 47 CFR 1.1307(b)(3)(i)(A) General RF Exposure Guidance v06."

- End of the Report -

Radiolink Testing (Shenzhen) Co., Ltd.

Room 103, Building B, Jinghang Industrial Park, Area 71, Xingdong Community, Xin'an Subdistrict, Bao'an District,
Shenzhen, Guangdong Province, China
Tel: +86 0755 23080694