



Shenzhen Shuodian Electronic Technology Co.,Ltd
Page number 1-10

SPECIFICATION

for

AT.24GTX-AE2BT antenna

Customer No.

Product No.

SD652-AT. 24GTX-AE2BT-FPC-200MM

Author: XiaofengZeng Review: Liming

Release Date: 2024. 01. 26

ShenZhen Shuodian Electronic Technology Co., Ltd

Room 508, West Building 64, Majialong Jinlong Industrial City, Nanshan District, Shenzhen

E-mail: sz_shuodian@163.com

Tel: 0755-86006322

Fax: 0755-86006323

Shenzhen Shuodian Electronic Technology Co.,Ltd



Contents

SPECIFICATION	1
SHENZHEN SHUODIAN ELECTRONIC TECHNOLOGY CO., LTD	1
CONTENTS	2
1. BILATERAL CONFIRMATION PAGE	3
2. GENERAL	4
3. GENERAL PRODUCT SPECIFICATIONS	4
4. SPECIFICATION DETIALS	5
4.1 MECHANICAL PROPERTIES	5
4.2 ELECTRIC PERFORMANCE	7
5. PRODUCT PACKAGING	9
6. DOCUMENT RESUME	10



1. Bilateral Confirmation page

1.1 Customer signature

Customer:

Seapartment/post	Sign	Date
Hardware Engineer/RD		
Mechanical/MD		
Project Manager/PM		
Commercial/Puchasing		
Checker		

1.2 Signature of ShuoDian Technology company

Seapartment/post	Sign	Date
Antenna Engineer/RD		
Mechanical/MD		
Project Manager/PM		
QA		
Checker		



2. General

2.1 Scope of application

This specification is only applicable to AT.24GTX-AE2BT antenna

2.2 Operating temperature range

Temperature range of this product: -20 ~ +65 °C

2.3 Storage temperature range:

This product is stored at - 30 ~ + 75 °C

3. General product specifications

NO.	ITEMS	DETAILS
1	Type	AT.24GTX-AE2BT antenna
2	Operating Frequency Band	2400-2500MHz
3	VSWR	≤ 2.0
4	Gain	1.0dBi
5	Impedance	50Ω
6	Antenna Type	Monopole
7	Antenna composition	FPC+CABLE
8	Entity Picture	



4. Specification Detials

4.1 Mechanical Properties

4.11 Product Composition:

No.	Material	Size (MM)
1	FPC	30.62*5.6 Black
2	CABLE	IPEX-1 ϕ 1.13 L=200 black

4.12 Apperance

Good appearance without scars 、 dirt、 protuberances, etc.

4.13 Antenna Picture and Structure Dimension

Productdrawings:

Shenzhen Shuodian Electronic Technology Co.,Ltd



4.2 Electric Performance


4.21 Test condition

Environment:	Equipment:
Temperature: 10℃——+30℃	Network Analyzer: KEYSIGHT E5071C
Humidity: ≤80% (+40℃)	Multi-probe microwave anechoic chamber
Atmospher: 750mmkg±30mmkg	

4.22 Test Data for Electrical Performance:

4.22.1 S11 of the Antenna:

Marker (MHZ)	2400	2450	2500
Returnloss	-13.2	-19.3	-17.0
VSWR	1.5	1.2	1.3






4. 22. 2 Passive gain、 efficiency and Radiation Pattern:

Frequency (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	0.51	0.63	0.75	0.89	1.03	1.05	1.25	1.12	1.07	1.02	0.74
Efficient (%)	38.88	38.11	40.70	42.33	46.34	47.29	49.21	44.52	41.31	39.31	38.46

Radiation Pattern 2450MHz

@2450MHz



5. Product Packaging

Manner of packing:

Packed in self sealed bags, 200 pcs each.

Shenzhen Shuodian Electronic Technology Co.,Ltd



6. Document Resume

Document No.	
Release Date	2024/01/26
Author	XiofengZeng
Review	LiMing

Revised History

Date	Version	Revised Record
2024/01/26	1.00	New Project