

TEST REPORT

Report No.: BCTC2605550334-2E

Applicant: Dongguan Dalingshan Shiyue Electronics Business
Department

Product Name: RETRACTABLE 87W CAR CHARGER

Test Model: PT-80

Tested Date: 2026-05-30 to 2026-05-31

Issued Date: 2026-06-12



Shenzhen BCTC Technology Co., Ltd.



FCC ID: 2BWD5-PT-80

Product Name: RETRACTABLE 87W CAR CHARGER

Trademark: N/A

Model/Type reference: PT-80
PT-80-1, PT-80-2, PT-80-3, PT-80-4, PT-80-5 PT-80-6, PT-80-7, PT-80-8
PT-80-9

Prepared For: Dongguan Dalingshan Shiyue Electronics Business Department

Address: Room 302, No. 1 four Alley, Bikeng east, jinju village, Dalingshangtown,
Dongguan city, Guangdong Province, China

Manufacturer: Dongguan Dalingshan Shiyue Electronics Business Department

Address: Room 302, No. 1 four Alley, Bikeng east, jinju village, Dalingshangtown,
Dongguan city, Guangdong Province, China

Prepared By: Shenzhen BCTC Technology Co., Ltd.

Address: Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang,
Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China.

Sample Received Date: 2026-05-30


Sample tested Date: 2026-05-30 to 2026-06-12

Report No.: BCTC2605550334-2E

Test Standards: FCC CFR 47 part1, 1.1307(b), 1.1310
KDB 680106 D01 Wireless Power Transfer v04


Test Results: PASS

Prepared by :



Louis Zeng /Editor

Reviewer by :



Mike Zheng / Supervisor

Approved by:



Sewen Guo/Manager

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Technology Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration	Page
1. Version	4
2. Product Information	5
2.1 Product Information	5
2.2 Test Setup Configuration	5
2.3 Support Equipment	6
2.4 Test Mode	6
3. Test Facility And Test Instrument Used	7
3.1 Test Facility	7
3.2 Test Instrument Used	7
4. Method Of Measurement	8
4.1 Applicable Standard	8
4.2 Block Diagram Of Test Setup	8
4.3 Limit	9
4.4 Test procedure	9
4.5 Equipment Approval Considerations	10
4.6 E and H field Strength	11
5. Photographs Of Test Set-Up	12

(Note: N/A Means Not Applicable)

1. Version

Report No.	Issue Date	Description	Approved
BCTC2309647432-1E	2026-06-12	Original	Valid


2. Product Information

2.1 Product Information

Model/Type reference:	PT-80 PT-80-1, PT-80-2, PT-80-3, PT-80-4, PT-80-5 PT-80-6, PT-80-7, PT-80-8 PT-80-9
Model differences:	All the model are the same circuit and RF module, except model names, the test model is PT-80.
Hardware Version:	N/A
Software Version:	N/A
Type of Modulation:	ASK
Operation Frequency:	325kHz
Antenna installation:	Loop coil antenna
Ratings:	Input: DC 12-24V TYPE-C1 cable: PD (5V/3A, 9V/3A,12V/3A) (Max 36W) TYPE-C2 cable: PD (5V/3A, 9V/3A,12V/3A) (Max 36W) Type-C port: 5V/3A USB-A: 5V/2.4A Wireless charging: Max 2.5W

2.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.



2.3 Support Equipment

No.	Cable Type	Quantity	Provider	Length (m)	Shielded	Note
1	DC	--	---	---	---	---
2	--	--	---	---	---	---

No.	Device Type	Brand	Model	Series No.	Note
E-1	RETRACTABLE 87W CAR CHARGER	N/A	PT-80	N/A	EUT
E-2	Dummy load	N/A	DL01	N/A	Auxiliary
E-3	Battery	N/A	N/A	N/A	Auxiliary

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

2.4 Test Mode

Test Mode 1	2.5W DC 12V
Test Mode 2	2.5W DC 24V

3. Test Facility And Test Instrument Used

3.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Technology Co., Ltd.

Address: Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China.

The site and apparatus are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-1:2019 other equivalent standards.

FCC Test Firm Registration Number: 754702

ANAB certificate registration number is: CN3479

3.2 Test Instrument Used

Name of instrument	Model	Manufacturer	Cal. Date	Due Date
Electro magnetic radiation tester	SMP160	Wavecontrol	May 12, 2026	May 13, 2027


4. Method Of Measurement

4.1 Applicable Standard


According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1093 RF exposure is calculated. According KDB680106 D01v04: RF Exposure Wireless Charging Apps v04.

4.2 Block Diagram Of Test Setup

A:



B:



4.3 Limit

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

4.4 Test procedure

- The RF exposure test was performed in anechoic chamber.
- The measurement probe was placed at 0 cm surrounding the device for test setup A; and the measurement Probe was placed from 0 cm to 20 cm, in 2 cm maximum increment measured from the edge of the device For the test setup B.
- The highest emission level was recorded and compared with limit as soon as measurement of each
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E , F) were completed.
- The EUT was measured according to the dictates of KDB680106 D01v04.
- Remark: The EUT's test position A, B, C, D , E and F is valid for the E and H field measurements.

4.5 Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01 v04

1) The power transfer frequency is below 1 MHz.

Yes, the device operate in the frequency range from 325KHz

2) The output power from each transmitting element is less than or equal to 15 watts.

Yes, the maximum output power of the primary coil is 2.5W.

3) A client device providing the maximum permitted load is placed in physical contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter.

4) Only § 2.1091-Mobile exposure conditions apply

Yes, EUT is a fixed state assessment

5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.

Yes, Conform to

6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time.

Yes, Conform to

4.6 E and H field Strength

We measured the H-Field Strength of 20cm, 22cm and 24cm, and recorded the test data of the worst 20cm Mobile: Test Mode 1 (Worst mode)

H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT


Frequency Range (MHz)	Test Position A(uT)	Test Position B(uT)	Test Position C(uT)	Test Position D(uT)	Test Position E(uT)	Test Position Top(uT)
0.325	0.072	0.069	0.065	0.075	0.077	0.076

Frequency Range (MHz)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position Top(A/m)	50% Limits Test (A/m)	Limits Test (A/m)
0.325	0.058	0.055	0.052	0.060	0.062	0.061	0.815	1.63

Note: A/m = uT ÷ 1.25

Frequency Range (MHz)	Test Position Front (V/m)	Test Position Rear (V/m)	Test Position Left (V/m)	Test Position Right (V/m)	Test Position Top (V/m)	50% Limits Test (V/m)	Limits (V/m)
0.325	0.061	0.072	0.076	0.075	0.067	307	614

5. Photographs Of Test Set-Up



STATEMENT

1. The equipment lists are traceable to the International System of Units (SI)
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC 17025:2017.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****

CO.176