



RF Exposure Evaluation

FOR

Shenzhen DAS IoT Technology Co., Ltd.

Face Recognition Terminal

Test Model: X2033

Prepared for : Shenzhen DAS IoT Technology Co., Ltd.
Address : 301 DAS Tower, 007 Kejinan 3rd Rd, HI-TECH Industrial Park,
Nanshan, Shenzhen, Guangdong P. R. CHINA

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 22, 2026
Number of tested samples : 2
Sample No. : A260518043-1, A260518043-2
Serial number : Prototype
Date of Test : May 22, 2026 ~ June 15, 2026
Date of Report : June 15, 2026



**RF Exposure Evaluation****Report Reference No. : LCSA05196023EC**

Date of Issue..... : June 15, 2026

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name..... : Shenzhen DAS IoT Technology Co., Ltd.**Address..... : 301 DAS Tower, 007 Kejinan 3rd Rd, HI-TECH Industrial Park,
Nanshan, Shenzhen, Guangdong P. R. CHINA**Test Specification**Standard..... : FCC KDB publication 447498 D01 General RF Exposure Guidance v06
FCC CFR 47 part1 1.1310
FCC CFR 47 part2 2.1091

Test Report Form No..... : TRF-4-E-214 A/0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Face Recognition TerminalTrade Mark..... : **inDAS**

Test Model..... : X2033

Ratings..... : Please Refer to Page 6

Result : Pass**Compiled by:**

Li Huan/ Administrator

Supervised by:

Kevin Huang/ RF Manager

Approved by:

Gavin Liang/ Manager





RF Exposure Evaluation

Test Report No. : LCSA05196023EC	<u>June 15, 2026</u> Date of issue
---	---------------------------------------

Test Model.....	: X2033
EUT.....	: Face Recognition Terminal
Applicant.....	: Shenzhen DAS IoT Technology Co., Ltd.
Address.....	: 301 DAS Tower, 007 Kejinan 3rd Rd, HI-TECH Industrial Park, Nanshan, Shenzhen, Guangdong P. R. CHINA
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen DAS IoT Technology Co., Ltd.
Address.....	: 301 DAS Tower, 007 Kejinan 3rd Rd, HI-TECH Industrial Park, Nanshan, Shenzhen, Guangdong P. R. CHINA
Telephone.....	: /
Fax.....	: /
Factory.....	: Shenzhen DAS IoT Technology Co., Ltd. Manufacturing Plant
Address.....	: Room 601, 6th Floor, Building 1 Block A, Xinqiaodong Advanced Manufacturing Industrial Park, Huangpu Community, Xinqiao Sub-district, Bao'an District, Shenzhen, Guangdong China
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	June 15, 2026	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method.....	7
3. Limit.....	7
4. MPE Calculation Method.....	8
5. Conducted Power.....	8
6. Manufacturing Tolerance.....	9
7. Measurement Results.....	10
8. Conclusion.....	10
9. Description of Test Facility.....	10
10.Measurement Uncertainty.....	10





1. Product Information

EUT	: Face Recognition Terminal
Test Model	: X2033
Ratings	: Input: 12.0V==2.0A For AC Adapter: Input: 100-240V~, 50/60Hz, 0.8A Output: 12.0V==2.0A, 24.0W MAX
Hardware Version	: /
Software Version	: /
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth(2412~2462MHz) 7 Channels for 40MHz bandwidth(2422~2452MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: FPC Antenna, 1.96dBi(max.)
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	
NFC	:
Operating Frequency	: 13.56MHz
Modulation Type	: ASK
Antenna Description	: Internal Antenna
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$S=PG/4\pi R^2$

Where: S=power density
P=power input to antenna
G=power gain of the antenna in the direction of interest relative to an isotropic radiator
R=distance to the center of radiation of the antenna

5. Conducted Power

[2.4G WIFI]			
Mode	Channel	Frequency (MHz)	Max Conducted Output Power (dBm)
IEEE 802.11b	1	2412	14.35
	6	2437	13.68
	11	2462	12.81
IEEE 802.11g	1	2412	12.53
	6	2437	12.03
	11	2462	11.32
IEEE 802.11n HT20	1	2412	12.72
	6	2437	12.27
	11	2462	11.55
IEEE 802.11n HT40	3	2422	12.13
	6	2437	11.31
	9	2452	11.7

Test Procedure

TX frequency range: 13.56MHz, Limit: $824/13.56=60.77V/m$
Device category: Mobile device (Distance: 20cm)
Max. Field Strength: 55.55dBuV/m @3m
 $@20cm=@3m+40*\log(3/0.2)=102.59dBuV/m$
For 13.56MHz: $102.59dBuV/m=10^{(102.59/20)/10^6}=0.135V/m < 60.77V/m$





6. Manufacturing Tolerance

[2.4G WIFI]			
IEEE 802.11b (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	13.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT40(Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0





7. Measurement Results

7.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	15.0	31.6228	1.96	1.5704	0.0099	1.0000
IEEE 802.11g	13.0	19.9526	1.96	1.5704	0.0062	1.0000
IEEE 802.11n HT20	13.0	19.9526	1.96	1.5704	0.0062	1.0000
IEEE 802.11n HT40	13.0	19.9526	1.96	1.5704	0.0062	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7.2 Simultaneous Transmission MPE Evaluation

The sample support one BT&BLE, another one NFC antenna transmit antenna, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$$TER = \sum_{k=1}^{N_s} \left(\frac{SAR_k}{SAR_{lim}} \right) + \sum_{k=1}^{N_f} \left(\frac{MPE_{field,k}}{MPE_{field,lim}} \right)^2 + \sum_{k=1}^{N_{pd}} \left(\frac{MPE_{pd,k}}{MPE_{pd,lim}} \right)$$

$\sum$ of MPE ratios ≤ 1.0

Max MPE ratios1	NFC Ant Max MPE ratios	$\sum$ MPE ratios	Limit	Results
0.0099	0.0022	0.0121	1.000	Pass

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

9. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

10. Measurement Uncertainty

BT/2.4G WLAN:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

-----THE END OF REPORT-----



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity