



FCC RADIO TEST REPORT

Applicant	: ZOOM Corporation
Address	: 4-4-3 Kanda-surugadai, Chiyoda-ku, Tokyo 101-0062, Japan
Equipment	: BTA-1a
Model No.	: ZD0460
Trade Name	: ZOOM
FCC ID	: 2BWEY-ZD0460

I HEREBY CERTIFY THAT:

The sample was received on Jun. 09, 2026 and the testing was completed on Jul. 07, 2026 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software.....	8
2.4 Description of Test System.....	9
2.5 General Information of Test.....	10
2.6 Measurement Uncertainty	10
3. Test Equipment and Ancillaries Used for Tests.....	11
4. Antenna Requirements.....	13
4.1 Standard Applicable	13
4.2 Antenna Construction and Directional Gain.....	13
5. Test of Conducted Emission.....	14
5.1 Test Limit	14
5.2 Test Procedures	14
5.3 Typical Test Setup	15
5.4 Test Result and Data.....	16
5.5 Test Photographs	18
6. Test of Spurious Emission (Radiated)	19
6.1 Test Limit	19
6.2 Test Procedures	20
6.3 Typical Test Setup	21
6.4 Test Result and Data (9kHz ~ 30MHz)	22
6.5 Test Result and Data (30MHz ~ 1GHz)	22
6.6 Test Result and Data (Bandedge).....	24
6.7 Test Result and Data (1GHz ~ 3GHz).....	40
6.8 Test Result and Data (3GHz ~ 18GHz).....	52
6.9 Test Result and Data (18GHz ~ 25GHz).....	76
6.10 Restricted Bands of Operation	78
6.11 Test Photographs (30MHz ~ 1GHz).....	79
6.12 Test Photographs (1GHz ~ 25GHz).....	80
7. Test of Spurious Emission (Conducted).....	82
7.1 Test Limit	82
7.2 Test Procedure	82
7.3 Test Setup Layout	82
7.4 Test Result and Data.....	82
8. On Time, Duty Cycle and Measurement methods	87
8.1 Test Limit	87
8.2 Test Procedure	87
8.3 Test Setup Layout	87
8.4 Test Result and Data.....	88



9.	6dB Bandwidth Measurement Data.....	89
9.1	Test Limit	89
9.2	Test Procedures	89
9.3	Test Setup Layout	89
9.4	Test Result and Data.....	89
10.	Maximum Peak Output Power	91
10.1	Test Limit	91
10.2	Test Procedures	91
10.3	Test Setup Layout	91
10.4	Test Result and Data.....	91
11.	Power Spectral Density	92
11.1	Test Limit	92
11.2	Test Procedures	92
11.3	Test Setup Layout	92
11.4	Test Result and Data.....	92



History of this test report

Report No	Issued Date	Description
26060060-TRFCC01	Jul. 15, 2026	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

**ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
FCC Rules and Regulations Part 15 Subpart C §15.247**

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
Note: Deviations Yes ☐ No ☒ *The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.		



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Equipment	BTA-1a
Model Name	ZD0460
Model Discrepancy	N/A
Frequency Range	BLE: 2400MHz-2483.5MHz
Modulation Type	GFSK
Data Rate	GFSK: 1Mbps, 2Mbps
EUT Power Rating:	DC 3.3V 10mA

Note: For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
*00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	*19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	*39	2480
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- The complete test system included support units and EUT for RF test.
- An executive program, "Non-Signaling_TEST (Ver.: 2.1)" under WIN10 system was executed to transmit and receive data via Wireless.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
Mode 1	GFSK (1Mbps) for AC120V
Mode 2	GFSK (2Mbps) for AC120V
Mode 3	GFSK (1Mbps) for AC240V
caused "Test Mode 1 and CH00:2402" generated the worst case, it was reported as the final data.	
Radiation Emissions (Below 1GHz)	
Test Mode	Operating Description
Mode 1	GFSK (1Mbps)
Mode 2	GFSK (2Mbps)
caused "Test Mode 1 and CH00:2402" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
Mode 1	GFSK (1Mbps)
Mode 2	GFSK (2Mbps)
caused "Test Mode 1~2" generated the worst case, they were reported as the final data.	

Below test Channel generated the worst case, they were reported as the final data.

TX

Modulation Type	Channel	Frequency (MHz)	Bandedge		1GHz~3GHz		3GHz~18GHz		18GHz~25GHz	
			Ver PK/AV	Hor PK/AV	Ver PK/AV	Hor PK/AV	Ver PK/AV	Hor PK/AV	Ver PK/AV	Hor PK/AV
GFSK (1Mbps)	0	2402	V	V	V	V	V	V	V	V
	19	2440	V	V	V	V	V	V		
	39	2480	V	V	V	V	V	V		
GFSK (2Mbps)	0	2402	V	V	V	V	V	V		
	19	2440	V	V	V	V	V	V		
	39	2480	V	V	V	V	V	V		



2.4 Description of Test System

AC Power Line Conducted Emission					
Equipment	Brand	Model	Serial No	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	GBNXC13 M064467	N/A	Adapter / 1.8m / NS
testfixture	Tailingwei	C1T42A20	N/A	N/A	N/A
USB Cable	UGREEN	Mini USB 5pin	N/A	1m / NS	N/A
Radiated Emissions (Below 1G) / Radiated Emissions (Above 1G) / RF Conducted					
Notebook	ASUS	P2430U	GBNXC13 M064467	N/A	Adapter / 1.8m / NS
testfixture	Tailingwei	C1T42A20	N/A	N/A	N/A
USB Cable	UGREEN	Mini USB 5pin	N/A	1m / NS	N/A



2.5 General Information of Test

Organization	CerpPASS Technology Corp.		
Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881		
	FCC	TW1439, TW1079	
	IC	4934E-1, 4934E-2	
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz		
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.		

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON02-NK	2026/07/07	27.4℃ / 48%	Peter Pan
Radiated Emissions	3M02-NK	2026/07/06	20.2℃ / 63%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2026/07/07	25.6℃ / 61%	Leon Huang

2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150kHz~30MHz)	±3.2dB
Radiated Spurious Emission(9kHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.2dB
Radiated Spurious Emission(1GHz~25GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±4.4%
20dB Bandwidth	±4.5%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±3.5%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	VULB 9168-1947	2026/02/10	2027/02/09
Active Loop Antenna	Schwarzbeck	FMZB 1513	00414	2026/02/04	2027/02/03
Double Ridged Guide Horn Antenna	RF SPAN	DRH18-E	210309A18-ES	2025/08/22	2026/08/21
Horn Antenna	RF SPIN	DRH0844	KV2E20A0844	2026/03/26	2027/03/25
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2026/06/24	2027/06/23
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2025/08/18	2026/08/17
Preamplifier	EMC INSTRUMENTS	EMC118A45V1S S	981069	2025/12/18	2026/12/17
Preamplifier	EMC INSTRUMENTS	EMC184045SEE	981159	2026/04/02	2027/04/01
Preamplifier	EM Electronics corp.	EM330	60659	2025/12/18	2026/12/17
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2026/07/01	2027/06/30
Cable-1m(30M-1G)	EMC INSTRUMENTS	EMCCFD400-N M-NM-1000	260301	2026/04/10	2027/04/09
Cable-3m(30M-1G)	EMC INSTRUMENTS	EMCCFD400-N M-NM-3000	260302	2026/04/10	2027/04/09
Cable-7m(30M-1G)	EMC INSTRUMENTS	EMCCFD400-N M-NM-7000	260303	2026/04/10	2027/04/09
Cable-8m(10M-26.5G)	HUBER SUHNER	SF126E	587396/126E	2025/10/15	2026/10/14
Cable-3m(10M-26.5G)	HUBER SUHNER	SF126E	587399/126E	2025/10/15	2026/10/14
Cable-1m(1G-26.5G)	HUBER SUHNER	SF126E	589848/126E	2025/10/15	2026/10/14
Cable-1m(1G-40G)	EMC INSTRUMENTS	EMC104HS-KM- KM-1000	260304	2026/04/10	2027/04/09
Cable-3m(1G-40G)	EMC INSTRUMENTS	EMC104HS-KM- KM-3000	260305	2026/04/10	2027/04/09
Cable-7m(1G-40G)	EMC INSTRUMENTS	EMC104HS-KM- KM-7000	260306	2026/04/10	2027/04/09
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	WOKEN	WFIL-H3000-18 000F-03	WR377WC2B1	2025/10/13	2026/10/12
Highpass Filter	WOKEN	WFIL-H7000-18 000F-01	WR468FWC2B 1	2025/10/03	2026/10/02
Hipass Filter	Warison	WFIL-H7500-18 000F-01	WRO5CFWC2 B1	2025/10/13	2026/10/12



Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2026/02/24	2027/02/23
Attenuator	KEYSIGHT	8491B	MY39250703	2026/01/29	2027/01/28
Cable-0.5m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2025/10/13	2026/10/12
Power Meter	Anritsu	ML2495A	1224005	2026/01/27	2027/01/26
Power Sensor	Anritsu	MA2411B	1207295	2026/01/27	2027/01/26
Switch Box	Theda	1-4	TW5451159	NA	NA

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR7	102888	2026/06/15	2027/06/14
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	1197	2025/09/22	2026/09/21
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	102185	2025/08/28	2026/08/27
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2026/07/01	2027/06/30
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Chip Antenna
Antenna Gain	1.75dBi



5. Test of Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2020+Cor.1-2023 and ANSI C63.10a-2024. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




5.3 Typical Test Setup





5.4 Test Result and Data

Power	: AC 120V/60Hz	Pol/Phase	: LINE
Test Mode	: Mode 1		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.5963	9.78	8.00	17.78	46.00	-28.22	Average	P
2	0.5963	9.78	29.01	38.79	56.00	-17.21	QP	P
3	0.8300	9.80	7.45	17.25	46.00	-28.75	Average	P
4	0.8300	9.80	26.46	36.26	56.00	-19.74	QP	P
5	1.4495	9.83	8.86	18.69	46.00	-27.31	Average	P
6	1.4495	9.83	25.70	35.53	56.00	-20.47	QP	P
7	2.7585	9.84	10.83	20.67	46.00	-25.33	Average	P
8	2.7585	9.84	20.81	30.65	56.00	-25.35	QP	P
9	8.8439	9.93	19.86	29.79	50.00	-20.21	Average	P
10	8.8439	9.93	26.90	36.83	60.00	-23.17	QP	P
11	13.8070	10.07	20.26	30.33	50.00	-19.67	Average	P
12	13.8070	10.07	27.69	37.76	60.00	-22.24	QP	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	: AC 120V/60Hz	Pol/Phase	: NEUTRAL
Test Mode	: Mode 1		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.5687	9.79	11.42	21.21	46.00	-24.79	Average	P
2	0.5687	9.79	29.33	39.12	56.00	-16.88	QP	P
3	0.8781	9.80	10.49	20.29	46.00	-25.71	Average	P
4	0.8781	9.80	30.66	40.46	56.00	-15.54	QP	P
5	1.4652	9.63	9.54	19.37	46.00	-26.63	Average	P
6	1.4652	9.83	28.27	38.10	56.00	-17.90	QP	P
7	2.7677	9.84	9.29	19.13	46.00	-26.87	Average	P
8	2.7677	9.84	22.74	32.58	56.00	-23.42	QP	P
9	8.8644	9.93	19.68	29.61	50.00	-20.39	Average	P
10	8.8644	9.93	27.67	37.60	60.00	-22.40	QP	P
11	15.9459	10.15	24.31	34.46	50.00	-15.54	Average	P
12	15.9459	10.15	31.46	41.61	60.00	-18.39	QP	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss




5.5 Test Photographs

Front View



Rear View





6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.(X AXIS is the worst.)




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	31.94	-10.94	43.82	32.88	40.00	-7.12	Peak	400	0	P
2	61.04	-10.49	44.29	33.80	40.00	-6.20	Peak	400	0	P
3	127.97	-12.44	44.77	32.33	43.50	-11.17	Peak	400	0	P
4	190.05	-12.42	44.61	32.19	43.50	-11.31	Peak	400	0	P
5	264.74	-11.01	42.64	31.63	46.00	-14.37	Peak	400	0	P
6	400.54	-7.08	39.01	31.93	46.00	-14.07	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	31.94	-10.94	42.05	31.11	40.00	-8.89	Peak	400	0	P
2	62.98	-10.78	44.48	33.70	40.00	-6.30	Peak	400	0	P
3	94.02	-16.22	50.08	33.86	43.50	-9.64	Peak	400	0	P
4	198.78	-12.91	41.36	28.45	43.50	-15.05	Peak	400	0	P
5	249.22	-11.42	48.23	36.81	46.00	-9.19	Peak	400	0	P
6	429.64	-6.41	36.85	30.44	46.00	-15.56	Peak	400	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (Bandedge)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2368.53	-6.67	54.95	48.28	74.00	-25.72	Peak	356	198	P
2	2401.86	-6.73	91.87	85.14	200.00	-114.86	Peak	356	198	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2385.80	-6.61	55.84	49.23	74.00	-24.77	Peak	105	108	P
2	2402.30	-6.73	95.99	89.26	200.00	-110.74	Peak	105	108	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2356.25	-6.64	55.00	48.36	74.00	-25.64	Peak	100	195	P
2	2439.75	-6.80	87.09	80.29	200.00	-119.71	Peak	100	195	P
3	2531.50	-6.61	56.07	49.46	74.00	-24.54	Peak	100	195	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2347.00	-6.59	55.06	48.47	74.00	-25.53	Peak	107	107	P
2	2439.75	-6.80	97.94	91.14	200.00	-108.86	Peak	107	107	P
3	2535.75	-6.56	55.14	48.58	74.00	-25.42	Peak	107	107	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-6.66	91.26	84.60	200.00	-115.40	Average	370	125	P
2	2488.32	-6.66	43.48	36.82	54.00	-17.18	Average	370	125	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.24	-6.66	92.40	85.74	200.00	-114.26	Peak	370	125	P
2	2483.68	-6.65	62.75	56.10	74.00	-17.90	Peak	370	125	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2479.84	-6.66	79.15	72.49	200.00	-127.51	Average	100	146	P
2	2517.44	-6.62	43.64	37.02	54.00	-16.98	Average	100	146	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2479.76	-6.66	93.52	86.86	200.00	-113.14	Peak	100	146	P
2	2483.76	-6.65	63.18	56.53	74.00	-17.47	Peak	100	146	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2389.43	-6.64	56.71	50.07	74.00	-23.93	Peak	353	125	P
2	2402.63	-6.73	93.50	86.77	200.00	-113.23	Peak	353	125	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2377.66	-6.58	56.25	49.67	74.00	-24.33	Peak	135	107	P
2	2402.63	-6.73	96.06	89.33	200.00	-110.67	Peak	135	107	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2368.50	-6.67	55.50	48.83	74.00	-25.17	Peak	382	125	P
2	2439.50	-6.80	96.21	89.41	200.00	-110.59	Peak	382	125	P
3	2517.50	-6.62	55.64	49.02	74.00	-24.98	Peak	382	125	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2346.00	-6.59	55.10	48.51	74.00	-25.49	Peak	178	138	P
2	2440.50	-6.80	97.49	90.69	200.00	-109.31	Peak	178	138	P
3	2503.00	-6.64	54.89	48.25	74.00	-25.75	Peak	178	138	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-6.66	88.45	81.79	200.00	-118.21	Average	328	125	P
2	2488.00	-6.66	43.69	37.03	54.00	-16.97	Average	328	125	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2479.52	-6.66	92.16	85.50	200.00	-114.50	Peak	328	125	P
2	2483.60	-6.65	60.81	54.16	74.00	-19.84	Peak	328	125	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2479.84	-6.66	91.02	84.36	200.00	-115.64	Average	123	107	P
2	2501.44	-6.64	43.54	36.90	54.00	-17.10	Average	123	107	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.40	-6.66	94.86	88.20	200.00	-111.80	Peak	123	107	P
2	2484.16	-6.65	63.06	56.41	74.00	-17.59	Peak	123	107	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Test Result and Data (1GHz ~ 3GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2690.00	-5.80	56.86	51.06	74.00	-22.94	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2998.00	-4.85	56.36	51.51	74.00	-22.49	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2730.00	-5.47	56.22	50.75	74.00	-23.25	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2986.00	-4.78	55.93	51.15	74.00	-22.85	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2704.00	-5.79	57.00	51.21	74.00	-22.79	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2986.00	-4.78	55.53	50.75	74.00	-23.25	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2902.00	-5.04	56.18	51.14	74.00	-22.86	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2956.00	-4.90	56.73	51.83	74.00	-22.17	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2910.00	-5.03	56.53	51.50	74.00	-22.50	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2838.00	-5.21	56.94	51.73	74.00	-22.27	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2986.00	-4.78	55.88	51.10	74.00	-22.90	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2684.00	-5.87	56.56	50.69	74.00	-23.31	Peak	100	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.8 Test Result and Data (3GHz ~ 18GHz)

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	6.38	36.26	42.64	54.00	-11.36	Average	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17745.00	5.44	49.59	55.03	74.00	-18.97	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17940.00	6.33	36.28	42.61	54.00	-11.39	Average	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	15045.00	6.20	48.59	54.79	74.00	-19.21	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17970.00	6.40	36.13	42.53	54.00	-11.47	Average	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17895.00	6.15	49.85	56.00	74.00	-18.00	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17970.00	6.40	36.15	42.55	54.00	-11.45	Average	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	15735.00	5.86	48.79	54.65	74.00	-19.35	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17970.00	6.40	35.95	42.35	54.00	-11.65	Average	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	6.38	48.73	55.11	74.00	-18.89	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17940.00	6.33	36.18	42.51	54.00	-11.49	Average	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	15375.00	5.80	50.05	55.85	74.00	-18.15	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17970.00	5.40	36.03	42.43	54.00	-11.57	Average	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17910.00	6.23	49.60	55.83	74.00	-18.17	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	6.38	36.23	42.61	54.00	-11.39	Average	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH00	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	15045.00	6.20	48.70	54.90	74.00	-19.10	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	6.38	36.17	42.55	54.00	-11.45	Average	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17760.00	5.50	49.17	54.67	74.00	-19.33	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17910.00	6.23	36.30	42.53	54.00	-11.47	Average	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH19	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17910.00	6.23	48.81	55.04	74.00	-18.96	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17910.00	6.23	36.37	42.60	54.00	-11.40	Average	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	15765.00	5.94	50.02	55.96	74.00	-18.04	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Average



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17955.00	6.38	36.33	42.71	54.00	-11.29	Average	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 2, CH39	Detector	:	Peak



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	17970.00	6.40	48.97	55.37	74.00	-18.63	Peak	100	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor

**6.9 Test Result and Data (18GHz ~ 25GHz)**

Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode2, CH39			



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	24636.00	1.69	44.74	46.43	74.00	-27.57	Peak	150	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V/60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode2, CH39			



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	24524.00	1.67	46.05	47.72	74.00	-26.28	Peak	150	0	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.10 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:


MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz




6.11 Test Photographs (30MHz ~ 1GHz)

Front View



Rear View






6.12 Test Photographs (1GHz ~ 25GHz)

Front View




Rear View





Side View





7. Test of Spurious Emission (Conducted)

7.1 Test Limit

According to the methods defined in ANSI C63.10-2020 Section 7.8.7


Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

According to the methods defined in ANSI C63.10-2020

- The transmitter output was connected to the spectrum analyzer via a low loss cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

7.3 Test Setup Layout




7.4 Test Result and Data

Note: Test plots refer to the following pages.




Modulation Type: GFSK (1Mbps)
CH00




Date: 7.JUL.2026 09:38:45


Modulation Type: GFSK (1Mbps)
CH19




Date: 7.JUL.2026 09:42:49




Date: 7.JUL.2026 09:38:20



Date: 7.JUL.2026 09:42:25



Date: 7.JUL.2026 09:39:10




Date: 7.JUL.2026 09:43:14




Modulation Type: GFSK (1Mbps)


CH39



Date: 7.JUL.2026 09:46:27




Date: 7.JUL.2026 09:46:03



Date: 7.JUL.2026 09:46:52




Modulation Type: GFSK (2Mbps)
CH00




Date: 7.JUL.2026 09:53:02


Modulation Type: GFSK (2Mbps)
CH19




Date: 7.JUL.2026 10:24:35




Date: 7.JUL.2026 09:52:37



Date: 7.JUL.2026 10:24:10




Date: 7.JUL.2026 09:53:26




Date: 7.JUL.2026 10:24:59




Modulation Type: GFSK (2Mbps)
CH39



Date: 7.JUL.2026 10:32:07



Date: 7.JUL.2026 10:31:42



Date: 7.JUL.2026 10:32:31



8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

According to the methods defined in ANSI C63.10-2020 Section 11.6
Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout






8.4 Test Result and Data


Modulation Type	On Time (msec)	Period Time (msec)	Duty Cycle (%)
GFSK(1Mbps)	0.42	2.79	15.19%
GFSK(2Mbps)	0.21	2.58	8.05%

Modulation Type: GFSK 1Mbps



Date: 7.JUL.2026 09:34:36

Modulation Type: GFSK 2Mbps



Date: 7.JUL.2026 09:50:17



9. 6dB Bandwidth Measurement Data

9.1 Test Limit


The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.8

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and $VBW \geq 3 \times RBW$.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout




9.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)
GFSK (1Mbps)	0	2402	708.00	500
	19	2440	705.00	500
	39	2480	705.00	500
GFSK (2Mbps)	0	2402	1140.00	500
	19	2440	1140.00	500
	39	2480	1152.00	500




Modulation Type: GFSK (1Mbps)
CH00




Date: 7.JUL.2026 09:37:29

Modulation Type: GFSK (2Mbps)
CH00




Date: 7.JUL.2026 09:51:05

Modulation Type: GFSK (1Mbps)
CH19




Date: 7.JUL.2026 09:40:45

Modulation Type: GFSK (2Mbps)
CH19




Date: 7.JUL.2026 10:22:36

Modulation Type: GFSK (1Mbps)
CH39



Date: 7.JUL.2026 09:44:32

Modulation Type: GFSK (2Mbps)
CH39



Date: 7.JUL.2026 10:30:12



10. Maximum Peak Output Power

10.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

10.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.9.1.2

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

Power Set	Modulation Type	Channel	Frequency (MHz)	Power Output (dBm)	Power Output (mW)
				Peak	Peak
3.1	GFSK (1Mbps)	0	2402	1.66	1.466
3.1		19	2440	1.58	1.439
3.1		39	2480	1.42	1.387
3.1	GFSK (2Mbps)	0	2402	1.51	1.416
3.1		19	2440	1.56	1.432
3.1		39	2480	1.41	1.384



11. Power Spectral Density


11.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

11.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.10.1

11.3 Test Setup Layout




11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 3kHz Bandwidth(dBm)	Limit
GFSK (1Mbps)	0	2402	-11.85	8.00
	19	2440	-11.89	8.00
	39	2480	-12.13	8.00
GFSK (2Mbps)	0	2402	-16.00	8.00
	19	2440	-15.79	8.00
	39	2480	-15.90	8.00

Note: Test plots refer to the following pages.




Modulation Type: GFSK (1Mbps)
CH00




Date: 7.JUL.2026 09:37:54

Modulation Type: GFSK (2Mbps)
CH00




Date: 7.JUL.2026 09:52:11

Modulation Type: GFSK (1Mbps)
CH19




Date: 7.JUL.2026 09:42:00

Modulation Type: GFSK (2Mbps)
CH19




Date: 7.JUL.2026 10:23:43

Modulation Type: GFSK (1Mbps)
CH39



Date: 7.JUL.2026 09:45:37

Modulation Type: GFSK (2Mbps)
CH39



Date: 7.JUL.2026 10:31:17

----- THE END OF REPORT -----