



FCC Test Report

Application No.: DNT2606013140R06349-08139
Applicant: DARK PROJECT HK LIMITED
Address of Applicant: OFFICE 3906, 39TH THE CTR 99 QUEEN'S RD CENTRAL CENTRAL HONG KONG
EUT Description: PC keyboard
Model No.: ALU68AWL
FCC ID: 2BWHQ-ALU68AWL
Power Supply: Input:DC 5V;DC 3.7V from rechargeable lithium-ion battery
Trade Mark: Dark Project
47 CFR Part 2, Subpart J
Standards: 47 CFR Part 15, Subpart C
ANSI C63.10: 2020
Date of Receipt: 2026/06/01
Date of Test: 2026/06/02 to 2026/06/12
Date of Issue: 2026/06/12
Test Result: **PASS**

Prepared By: Carl Lin (Testing Engineer)
Reviewed By: Wayne Lin (Project Engineer)
Approved By: Heise Shen (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

Guangdong DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	June 12, 2026	Valid	Original Report



1 Test Summary

Test Item	Test Requirement	Test Method	Test Result	Result
Antenna Requirement	15.203/247(b)	--	Clause 3.1	PASS
Duty Cycle	--	--	Clause 3.2	PASS
DTS (6 dB) Bandwidth	15.247 (a)(2)	ANSI C63.10: 2020	Clause 3.3	PASS
Conducted Output Power	15.247 (b)(3)	ANSI C63.10: 2020	Clause 3.4	PASS
Power Spectral Density	15.247 (e)	ANSI C63.10: 2020	Clause 3.5	PASS
Band-edge for RF Conducted Emissions	15.247(d)	ANSI C63.10: 2020	Clause 3.6	PASS
RF Conducted Spurious Emissions	15.247(d)	ANSI C63.10: 2020	Clause 3.7	PASS
Radiated Spurious Emissions	15.247(d);15.205/15.209	ANSI C63.10: 2020	Clause 3.8	PASS
Restricted bands around fundamental frequency (Radiated Emission)	15.247(d);15.205/15.209	ANSI C63.10: 2020	Clause 3.9	PASS
AC Power Line Conducted Emission	15.207	ANSI C63.10: 2020	Clause 3.10	PASS

Note:

1. "N/A" denotes test is not applicable in this test report.



Contents

1 Test Summary	3
2 General Information	5
2.1 Test Location	5
2.2 General Description of EUT	5
2.3 Test Environment	6
2.4 Channel List	6
2.5 Power Setting of Test Software	7
2.6 Assistant equipment used for test	7
2.7 Description of Support Units	7
2.8 Test Facility	7
2.9 Equipment List	8
2.10 Measurement Uncertainty (95% confidence levels, k=2)	10
3 Test results and Measurement Data	11
3.1 Antenna Requirement	11
3.2 Duty Cycle	12
3.3 DTS (6 dB) Bandwidth	13
3.4 Conducted Output Power	14
3.5 Power Spectral Density	15
3.6 Band-edge for RF Conducted Emissions	16
3.7 RF Conducted Spurious Emissions	17
3.8 Radiated Spurious Emissions	18
3.9 Restricted bands around fundamental frequency	26
3.10 AC Power Line Conducted Emissions	30
4 Appendix	33
Appendix A: Duty Cycle	33
Appendix B: DTS Bandwidth	35
Appendix C: Maximum conducted output power	37
Appendix D: Maximum power spectral density	39
Appendix E: Band edge measurements&Conducted Spurious Emission	41



2 General Information

2.1 Test Location

Company:	Guangdong DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Gali Lin

2.2 General Description of EUT

Manufacturer:	Dongguan Heiyan Zhizao Technology Co., Ltd.
Address of Manufacturer:	6/F, Building 4, Jiangxia International Huashang Yungu, No. 21 Jiangnan Avenue, Qishi Town, Dongguan City, Guangdong Province
Factory:	Dongguan Heiyan Zhizao Technology Co., Ltd.
Address of Factory:	6/F, Building 4, Jiangxia International Huashang Yungu, No. 21 Jiangnan Avenue, Qishi Town, Dongguan City, Guangdong Province
EUT Description:	PC keyboard
Model No.:	ALU68AWL
Additional Model(s):	/
Power Supply:	Input:DC 5V;DC 3.7V from rechargeable lithium-ion battery
Chip Type:	HFD582CHFS
Trade Mark:	Dark Project
Hardware Version:	V1.0
Software Version:	V1.0
Serial number	PR2606013140R06349
Operation Frequency:	2402MHz to 2480MHz
Type of Modulation:	GFSK
Sample Type:	☒ Portable Device, ☐ Module, ☐ Mobile Device
Antenna Type:	☐ External, ☒ Integrated
Antenna Ports	☒ Ant 1, ☐ Ant 2, ☐ Ant 3
Antenna Gain*:	☒ Provided by applicant 2.94dBi
RF Cable*:	☒ Provided by applicant 0.5dB(0.6~1GHz); 0.8dB(1.4~2GHz); 1.0dB(2.1~2.7GHz); 1.5dB(3~4GHz); 1.8dB(4.4~6GHz);
Note:	*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.



2.3 Test Environment

Operating Environment:	
Temperature:	20~25.0 °C
Humidity:	45~56 % RH
Atmospheric Pressure:	101.0~101.30 KPa
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

2.4 Channel List

Operation Frequency of each channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Remark:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2440MHz
The Highest channel	2480MHz



2.5 Power Setting of Test Software

Software Name	RFTest_0509_ble_hopping_boxed		
Frequency(MHz)	2402	2440	2480
BLE 1M Setting	Default	Default	Default
BLE 2M Setting	Default	Default	Default

2.6 Assistant equipment used for test

Code	Equipment	Manufacturer	Model No.	Equipment No.
1	Computer	acer	N22C8	EMC notebook01
2	Adapter	Xiaomi	HW-100225C00	N/A

2.7 Description of Support Units

The EUT has been tested independent unit

2.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Lab A:

• FCC, USA

Designation Number: CN1348

• A2LA (Certificate No. 7050.01)

GUANGDONG DN TESTING CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 7050.01.

• Innovation, Science and Economic Development Canada

GUANGDONG DN TESTING CO., LTD. EMC Laboratory has been recognized by ISED as an accredited testing laboratory. CAB identifier is CN0149.

IC#: 30755.



2.9 Equipment List

For Connect EUT Antenna Terminal Test					
Description	Manufacturer	Model	Serial Number	Cal date	Due date
Signal Generator	Keysight	N5181A-6G	MY48180415	2025-10-21	2026-10-20
Signal Generator	Keysight	N5182B	MY57300617	2025-10-21	2026-10-20
Power supply	Keysight	E3640A	ZB2022656	2025-10-21	2026-10-20
Radio Communication Tester	R&S	CMW500	105082	2025-10-21	2026-10-20
Spectrum Analyzer	Aglient	N9010A	MY52220200	2025-10-21	2026-10-20
BT/WIFI Test Software	Tonscend	JS1120 V3.1.83	NA	NA	NA
RF Control Unit	Tonscend	JS0806-2	22F8060581	NA	NA
Power Sensor	Anritsu	ML2495A	2129005	2025-10-21	2026-10-20
Pulse Power Sensor	Anritsu	MA2411B	1911397	2025-10-21	2026-10-20
temperature and humidity box	SCOTEK	SCD-C40-80PRO	6866682020008	2025-10-21	2026-10-20
RF Cable	ETS-LINDGREN	RFC-NMS-100-NMS-350-IN	NA	2025-10-21	2026-10-20

Test Equipment for Conducted Emission					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Receiver	R&S	ESCI3	101152	2025-10-21	2026-10-20
LISN	R&S	ENV216	102874	2025-10-21	2026-10-20
ISN	R&S	ENY81-CA6	1309.8590.03	2025-10-21	2026-10-20
RF Cable	ETS-LINDGREN	Cable-CE TS01	/	2025-10-21	2026-10-20

Test Equipment for Radiated Emission(30MHz-1000MHz)					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Receiver	R&S	ESR7	102497	2025-10-21	2026-10-20
Test Software	Tonscend	JS32-RE	NA	NA	NA
RF Cable	ETS-LINDGREN	RE Cable-TS01	NA	2025-10-21	2026-10-20



Log periodic antenna	ETS-LINDGREN	VULB 9168	01475	2025-10-21	2026-10-20
Pre-amplifier	Schwarzbeck	BBV9743B	00423	2025-10-21	2026-10-20
Attenuator 1	Shanghai Huaxiang	TS2-6-18-A	22061803	2025-10-21	2026-10-20
Attenuator 2	Shanghai Huaxiang	TS2-6-6-A	230927163	2025-10-21	2026-10-20

Test Equipment for Radiated Emission(Above 1000MHz)					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Frequency analyser	Keysight	N9010A	MY52221458	2025-10-21	2026-10-20
RF Cable	ETS-LINDGREN	RE Cable-TS02	NA	2025-10-21	2026-10-20
Horn Antenna	ETS-LINDGREN	3117	00252567	2025-10-21	2026-10-20
Double ridged waveguide antenna	ETS-LINDGREN	3116C	00251780	2025-10-21	2026-10-20
Test Software	Tonscend	JS32-RE	NA	NA	NA
Pre-amplifier	ETS-LINDGREN	3117-PA	252567	2025-10-21	2026-10-20
Pre-amplifier	ETS-LINDGREN	3116C-PA	251780	2025-10-21	2026-10-20

**2.10 Measurement Uncertainty (95% confidence levels, k=2)**

No.	Item	Measurement Uncertainty
1	DTS Bandwidth	$\pm 0.0196\%$
2	Maximum Conducted Output Power	$\pm 0.686 \text{ dB}$
3	Maximum Power Spectral Density Level	$\pm 0.743 \text{ dB}$
4	Band-edge Compliance	$\pm 1.328 \text{ dB}$
5	Unwanted Emissions In Non-restricted Freq Bands	9KHz-1GHz: $\pm 0.746 \text{ dB}$ 1GHz-26GHz: $\pm 1.328 \text{ dB}$

No.	Item	Measurement Uncertainty
1	Conduction Emission	$\pm 3.0 \text{ dB}$ (150kHz to 30MHz)
2	Radiated Emission	$\pm 4.8 \text{ dB}$ (Below 1GHz)
		$\pm 4.8 \text{ dB}$ (1GHz to 6GHz)
		$\pm 4.5 \text{ dB}$ (6GHz to 18GHz)
		$\pm 5.02 \text{ dB}$ (Above 18GHz)



3 Test results and Measurement Data

3.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.	
The antenna is connected to the motherboard, The best case gain of the antenna is 2.94dBi.	



3.2 Duty Cycle


Refer to section : **Appendix A**

Note:

- 1.If duty cycle $< 98\%$, the conducted average output power and average power spectral density should be add duty factor.
- 2.If duty cycle $\geq 98\%$, the EUT is consider to be transmitting continuously, the conducted average output power and average power spectral density no need to add duty factor (consider to be zero).
- 3.The conducted peak output power and peak power spectral density no need to consider duty factor.
- 4.The on-time time is transmission duration (T).




3.3 DTS (6 dB) Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2020 Section 11.8.1 Option 1
Test Setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, showing a frequency spectrum on its screen, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a table labeled 'Non-Conducted Table'. This table is supported by two vertical legs, which are in turn supported by a thick horizontal bar at the bottom labeled 'Ground Reference Plane'.
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the the worst case of GFSK
Limit:	≥ 500 kHz
Test Results:	Pass

The detailed test data see: **Appendix B**




3.4 Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2020 Section 11.9.1.1
Test Setup:	
Test Instruments:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the the worst case of GFSK
Limit:	30dBm
Test Results:	Pass

The detailed test data see: **Appendix C**




3.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2020 Section 11.10.2
Test Setup:	
Test Instruments:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the the worst case of GFSK
Limit:	$\leq 8.00\text{dBm}/3\text{kHz}$
Test Results:	Pass

The detailed test data see: **Appendix D**




3.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2020 Section 12.7.4.4
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the the worst case of GFSK
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

The detailed test data see: **Appendix E**



3.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2020 Section 11.11
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the worst case of GFSK;
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

The detailed test data see: **Appendix E**



3.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2020 Section 11.12				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz (DC $\geq$ 0.98) $\geq$ 1/T (DC<0.98)	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Remark: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				


**Test Setup:**

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.

Guangdong DN Testing Co., Ltd.




Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge + Transmitting mode.
Final Test Mode:	Pretest the EUT at Charging+Transmitting mode. Through Pre-scan, find the worst case of GFSK, Only the worst case is recorded in the report.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass




Test data

For 30-1000MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	45.72	40.89	-29.34	11.55	40.00	28.45	100	206	PK	H
2	108.00	42.98	-27.92	15.06	43.50	28.44	100	182	PK	H
3	263.82	44.04	-22.06	21.98	46.00	24.02	100	359	PK	H
4	441.56	39.54	-17.14	22.40	46.00	23.60	100	212	PK	H
5	715.54	37.92	-10.35	27.57	46.00	18.43	100	329	PK	H
6	924.52	37.36	-6.67	30.69	46.00	15.31	100	359	PK	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	50.37	37.93	-22.04	15.89	40.00	24.11	100	100	PK	V
2	119.65	48.05	-23.74	24.31	43.50	19.19	100	129	PK	V
3	190.08	48.35	-23.07	25.28	43.50	18.22	100	70	PK	V
4	576.80	37.40	-12.01	25.39	46.00	20.61	100	253	PK	V
5	800.33	38.81	-7.72	31.09	46.00	14.91	100	294	PK	V
6	939.07	37.89	-4.97	32.92	46.00	13.08	100	342	PK	V




For above 1GHz

BLE 1M 2402MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	50.23	-4.61	45.62	74.00	28.38	150	221	PK	H
2	7206.00	52.10	-1.76	50.34	74.00	23.66	150	194	PK	H
3	9608.00	43.12	0.88	44.00	74.00	30.00	150	294	PK	H
4	4804.00	43.72	-4.61	39.11	54.00	14.89	150	20	AV	H
5	7206.00	46.33	-1.76	44.57	54.00	9.43	150	194	AV	H
6	9608.00	33.83	0.88	34.71	54.00	19.29	150	356	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	48.45	-4.61	43.84	74.00	30.16	150	312	PK	V
2	7206.00	49.57	-1.76	47.81	74.00	26.19	150	155	PK	V
3	9608.00	42.29	0.88	43.17	74.00	30.83	150	4	PK	V
4	4804.00	43.62	-4.61	39.01	54.00	14.99	150	312	AV	V
5	7206.00	42.61	-1.76	40.85	54.00	13.15	150	73	AV	V
6	9608.00	34.06	0.88	34.94	54.00	19.06	150	73	AV	V



BLE 1M 2440MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4880.00	49.44	-4.71	44.73	74.00	29.27	150	247	PK	H
2	7320.97	56.86	-1.49	55.37	74.00	18.63	150	222	PK	H
3	9760.00	41.59	1.62	43.21	74.00	30.79	150	360	PK	H
4	4880.00	41.87	-4.71	37.16	54.00	16.84	150	222	AV	H
5	7320.00	48.99	-1.49	47.50	54.00	6.50	150	222	AV	H
6	9760.00	35.10	1.62	36.72	54.00	17.28	150	119	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4880.00	50.36	-4.71	45.65	74.00	28.35	150	305	PK	V
2	7320.00	50.37	-1.49	48.88	74.00	25.12	150	97	PK	V
3	9760.00	42.25	1.62	43.87	74.00	30.13	150	360	PK	V
4	4880.00	45.81	-4.71	41.10	54.00	12.90	150	254	AV	V
5	7320.00	45.58	-1.49	44.09	54.00	9.91	150	153	AV	V
6	9760.00	33.03	1.62	34.65	54.00	19.35	150	124	AV	V



BLE 1M 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	48.22	-4.86	43.36	74.00	30.64	150	148	PK	H
2	7440.00	54.38	-1.34	53.04	74.00	20.96	150	223	PK	H
3	9920.00	41.88	2.27	44.15	74.00	29.85	150	201	PK	H
4	4960.00	42.25	-4.86	37.39	54.00	16.61	150	248	AV	H
5	7440.00	47.93	-1.34	46.59	54.00	7.41	150	201	AV	H
6	9920.00	34.31	2.27	36.58	54.00	17.42	150	223	AV	H



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	50.79	-4.86	45.93	74.00	28.07	150	250	PK	V
2	7440.00	50.61	-1.34	49.27	74.00	24.73	150	120	PK	V
3	9920.00	42.20	2.27	44.47	74.00	29.53	150	197	PK	V
4	4960.00	45.21	-4.86	40.35	54.00	13.65	150	250	AV	V
5	7440.00	45.45	-1.34	44.11	54.00	9.89	150	120	AV	V
6	9920.00	34.00	2.27	36.27	54.00	17.73	150	147	AV	V



Note:

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:
$$\text{Result Level} = \text{Reading Level} + \text{Correct Factor}(\text{including Ant.Factor, Cable Factor etc.})$$
2. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
3. The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be report.
4. All channels had been pre-test, BLE_1M is the worst case, only the worst case was reported.



3.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2020 Section 11.12		
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz





Figure 2. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel - Test the EUT in the lowest channel , the Highest channel - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete.
Test Configuration:	Measurements Below 1000MHz


Guangdong DN Testing Co., Ltd.



	• RBW = 120 kHz • VBW = 300 kHz • Detector = Peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Charge + Transmitting mode. Through Pre-scan, find the worst case of GFSK Only the worst case is recorded in the report.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass

**Test Date**
BLE 1M 2402MHz


NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity
1	2381.70	56.10	-0.83	55.27	74.00	18.73	150	211	PK	H
2	2390.01	54.24	-0.80	53.44	74.00	20.56	150	17	PK	H
3	2381.03	45.37	-0.83	44.54	54.00	9.46	150	118	AV	H
4	2390.01	44.30	-0.80	43.50	54.00	10.50	150	97	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity
1	2382.73	55.99	-0.83	55.16	74.00	18.84	150	169	PK	V
2	2390.01	52.87	-0.80	52.07	74.00	21.93	150	102	PK	V
3	2383.63	45.30	-0.82	44.48	54.00	9.52	150	234	AV	V
4	2390.01	44.08	-0.80	43.28	54.00	10.72	150	223	AV	V



BLE 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity
1	2483.50	49.52	-0.29	49.23	74.00	24.77	150	222	PK	H
2	2487.92	51.28	-0.26	51.02	74.00	22.98	150	299	PK	H
3	2483.50	40.08	-0.29	39.79	54.00	14.21	150	245	AV	H
4	2489.46	40.70	-0.24	40.46	54.00	13.54	150	332	AV	H



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity
1	2483.51	49.54	-0.29	49.25	74.00	24.75	150	72	PK	V
2	2488.27	51.32	-0.26	51.06	74.00	22.94	150	49	PK	V
3	2483.51	39.87	-0.29	39.58	54.00	14.42	150	225	AV	V
4	2486.09	40.50	-0.27	40.23	54.00	13.77	150	280	AV	V


Note:

1. All channels had been pre-test, BLE_1M is the worst case, only the worst case was reported
2. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:

$$\text{Result Level} = \text{Reading Level} + \text{Correct Factor}(\text{including Ant.Factor, Cable Factor etc.})$$



3.10AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2020		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 2020 on conducted measurement.		
Test Setup:			




Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the the worst case of GFSK
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:




Final Data List

NO.	Freq. [MHz]	QP Reading Level [dBμV]	AV Reading Level [dBμV]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.204	37.51	10.3	9.93	47.44	63.45	16.01	20.23	53.45	33.22	PASS
2	0.564	36.16	31.03	9.84	46.00	56.00	10.00	40.87	46.00	5.13	PASS
3	1.113	29.44	19.5	9.72	39.16	56.00	16.84	29.22	46.00	16.78	PASS
4	1.6485	26.16	18.29	9.73	35.89	56.00	20.11	28.02	46.00	17.98	PASS
5	2.8995	26.43	17.17	9.74	36.17	56.00	19.83	26.91	46.00	19.09	PASS
6	4.209	26.89	16.69	9.76	36.65	56.00	19.35	26.45	46.00	19.55	PASS



Neutral Line:



Final Data List

NO.	Freq. [MHz]	QP Reading Level [dBμV]	AV Reading Level [dBμV]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.303	30.34	17.81	9.88	40.22	60.16	19.94	27.69	50.16	22.47	PASS
2	0.5685	36.89	26.25	9.76	46.65	56.00	9.35	36.01	46.00	9.99	PASS
3	0.906	28.17	16.53	9.74	37.91	56.00	18.09	26.27	46.00	19.73	PASS
4	1.653	27.06	16.89	9.74	36.80	56.00	19.20	26.63	46.00	19.37	PASS
5	2.2695	26.13	10.17	9.80	35.93	56.00	20.07	19.97	46.00	26.03	PASS
6	3.0435	26.94	11.94	9.87	36.81	56.00	19.19	21.81	46.00	24.19	PASS

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
3. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including LISN Factor and the Cable Factor etc.), The basic equation is as follows:
Result Level= Reading Level + Correct Factor(including LISN Factor, Cable Factor etc.)



4 Appendix


Appendix A: Duty Cycle

Test Result

Mode	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)	1/T
BLE 1M	0	0.107	0.237	45.34	0.4534	3.4352	9.3458
	19	0.108	0.237	45.40	0.4540	3.4294	9.2593
	39	0.108	0.237	45.40	0.4540	3.4294	9.2593
BLE 2M	0	0.068	0.197	34.30	0.3430	4.6471	14.7059
	19	0.068	0.197	34.30	0.3430	4.6471	14.7059
	39	0.067	0.197	34.27	0.3427	4.6509	14.9254



Test Graphs






Appendix B: DTS Bandwidth

Test Result

Mode	Channel	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
BLE 1M	0	2402	0.6600	≥0.5	PASS
	19	2440	0.6600		PASS
	39	2480	0.6600		PASS
BLE 2M	0	2402	1.130		PASS
	19	2440	1.120		PASS
	39	2480	1.170		PASS



Test Graphs





Appendix C: Maximum conducted output power

Test Result

Mode	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Limit (dBm)	Result
BLE 1M	0	-5.88	0.26	≤30	PASS
	19	-5.53	0.28	≤30	PASS
	39	-5.65	0.27	≤30	PASS
BLE 2M	0	-5.91	0.26	≤30	PASS
	19	-5.52	0.28	≤30	PASS
	39	-5.49	0.28	≤30	PASS




Test Graphs



Peak Output Power
BLE 1M_Channel 0



Peak Output Power
BLE 1M_Channel 19



Peak Output Power
BLE 1M_Channel 39



Peak Output Power
BLE 2M_Channel 0



Peak Output Power
BLE 2M_Channel 19



Peak Output Power
BLE 2M_Channel 39




Appendix D: Maximum power spectral density

Test Result

Mode	Channel	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
BLE 1M	0	-21.310	≤8	PASS
BLE 1M	19	-20.970	≤8	PASS
BLE 1M	39	-22.540	≤8	PASS
BLE 2M	0	-24.690	≤8	PASS
BLE 2M	19	-24.000	≤8	PASS
BLE 2M	39	-25.790	≤8	PASS



Test Graphs




**Appendix E: Band edge measurements&Conducted Spurious Emission****Test Result**




Mode	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
BLE 1M	0	2400.00	-56.079	-26.05	-30.029	PASS
		4804.89	-64.426	-26.05	-38.376	PASS
		7205.13	-46.392	-26.05	-20.341	PASS
		9609.74	-66.210	-26.05	-40.160	PASS
	19	4879.80	-64.346	-25.57	-38.776	PASS
		7319.37	-44.370	-25.57	-18.800	PASS
		9760.18	-65.144	-25.57	-39.574	PASS
		2483.50	-58.739	-25.84	-32.899	PASS
	39	4958.45	-65.488	-25.84	-39.648	PASS
		7441.10	-40.428	-25.84	-14.588	PASS
		9919.37	-66.073	-25.84	-40.233	PASS
		2400.00	-39.983	-26.07	-13.913	PASS
BLE 2M	0	4804.26	-62.861	-26.07	-36.791	PASS
		7205.75	-46.645	-26.07	-20.575	PASS
		9609.12	-66.195	-26.07	-40.125	PASS
		4880.42	-65.328	-25.59	-39.738	PASS
	19	7319.99	-43.648	-25.59	-18.058	PASS
		9761.43	-65.859	-25.59	-40.269	PASS
		2483.50	-56.959	-26.27	-30.689	PASS
	39	4960.33	-64.650	-26.27	-38.380	PASS
		7438.60	-41.767	-26.27	-15.497	PASS
		9919.37	-65.329	-26.27	-39.059	PASS
		2400.00	-39.983	-26.07	-13.913	PASS
		4804.26	-62.861	-26.07	-36.791	PASS

Note: input compensation coefficient (dB)= Cable Loss (dB)





Test Graphs



**In-Band Reference Level
BLE 1M Channel 19****In-Band Reference Level
BLE 2M Channel 19****30.0 MHz - 25000.0 MHz
BLE 1M Channel 19****30.0 MHz - 25000.0 MHz
BLE 2M Channel 19****In-Band Reference Level
BLE 1M Channel 39****In-Band Reference Level
BLE 2M Channel 39**



Out Of Band Emission BLE 1M_Channel 39	Out Of Band Emission BLE 2M_Channel 39																																																																								
 <table><tr><th>1</th><th>N</th><th>1</th><th>f</th><th>4.958 GHz</th><th>-66.488 dBm</th><th>FUNCTION</th><th>FUNCTION VALUE</th><th>FUNCTION VALUE</th></tr><tr><td>2</td><td>N</td><td>1</td><th>f</th><th>7.641 GHz</th><th>-60.628 dBm</th><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><th>f</th><th>9.919 GHz</th><th>-66.073 dBm</th><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><th>f</th><th>2.480 GHz</th><th>-7.145 dBm</th><td></td><td></td><td></td></tr></table>	1	N	1	f	4.958 GHz	-66.488 dBm	FUNCTION	FUNCTION VALUE	FUNCTION VALUE	2	N	1	f	7.641 GHz	-60.628 dBm				3	N	1	f	9.919 GHz	-66.073 dBm				4	N	1	f	2.480 GHz	-7.145 dBm				 <table><tr><th>1</th><th>N</th><th>1</th><th>f</th><th>4.960 GHz</th><th>-64.650 dBm</th><th>FUNCTION</th><th>FUNCTION VALUE</th><th>FUNCTION VALUE</th></tr><tr><td>2</td><td>N</td><td>1</td><th>f</th><th>7.638 GHz</th><th>-61.757 dBm</th><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><th>f</th><th>9.919 GHz</th><th>-66.329 dBm</th><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><th>f</th><th>2.480 GHz</th><th>-6.892 dBm</th><td></td><td></td><td></td></tr></table>	1	N	1	f	4.960 GHz	-64.650 dBm	FUNCTION	FUNCTION VALUE	FUNCTION VALUE	2	N	1	f	7.638 GHz	-61.757 dBm				3	N	1	f	9.919 GHz	-66.329 dBm				4	N	1	f	2.480 GHz	-6.892 dBm			
1	N	1	f	4.958 GHz	-66.488 dBm	FUNCTION	FUNCTION VALUE	FUNCTION VALUE																																																																	
2	N	1	f	7.641 GHz	-60.628 dBm																																																																				
3	N	1	f	9.919 GHz	-66.073 dBm																																																																				
4	N	1	f	2.480 GHz	-7.145 dBm																																																																				
1	N	1	f	4.960 GHz	-64.650 dBm	FUNCTION	FUNCTION VALUE	FUNCTION VALUE																																																																	
2	N	1	f	7.638 GHz	-61.757 dBm																																																																				
3	N	1	f	9.919 GHz	-66.329 dBm																																																																				
4	N	1	f	2.480 GHz	-6.892 dBm																																																																				
30.0 MHz - 25000.0 MHz BLE 1M_Channel 39	30.0 MHz - 25000.0 MHz BLE 2M_Channel 39																																																																								

The End Report