Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

47 CFR Part 15, Subpart C 15.247

Report Reference No.:	**CTL2605222153-WF**	
Compiled by: (printed name+signature)	Gary Gao	
Reviewed by: (printed name+signature)	Happy Guo	
Approved by: (printed name+signature)	Ivan Xie	

Product Name..... :	Bluetooth module
Model/Type reference..... :	NW-X28
List Model(s)..... :	QDJ-HALO2.6, QDJ-HALO2.6Pro, QDJ-HALO2.8, QDJ-HALO2.8Pro, QDJ-LOUD2.6B, QDJ-LOUD2.6W, QDJ-HOME1.6B, QDJ-HOME1.6W, QDJ-PARTY2.10, QDJ-LUM2.8, QDJ-LUM2.10, QDJ-LUM2.12, NW-X26, NW-X26Pro, NW-X26E, NW-X28Pro
Trade Mark..... :	N/A
FCC ID..... :	**2BWIABP1048B2**
Applicant's name..... :	**Guangzhou Nanwei Electronics Co.,Ltd**
Address of applicant..... :	15-2 Chaosheng Road, Xinya Street, Huadu District, Guangzhou, Guangdong, China
Test specification..... :	
Standard..... :	**47 CFR Part 15, Subpart C 15.247:** Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.
TRF Originator..... :	Shenzhen CTL Testing Technology Co., Ltd.
Master TRF..... :	Dated 2011-01
Date of receipt of test item..... :	June 3, 2026
Date of Test Date..... :	June 3, 2026-July 15, 2026
Date of Issue..... :	July 17, 2026
Result..... :	**Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2605222153-WF	July 17, 2026 Date of issue

Equipment under Test	:	Bluetooth module
Sample No	:	CTL260522211001, CTL260522211007
Model /Type	:	NW-X28
Listed Models	:	QDJ-HALO2.6, QDJ-HALO2.6Pro, QDJ-HALO2.8, QDJ-HALO2.8Pro, QDJ-LOUD2.6B, QDJ-LOUD2.6W, QDJ-HOME1.6B, QDJ-HOME1.6W, QDJ-PARTY2.10, QDJ-LUM2.8, QDJ-LUM2.10, QDJ-LUM2.12, NW-X26, NW-X26Pro, NW-X26E, NW-X28Pro
Applicant	:	**Guangzhou Nanwei Electronics Co.,Ltd**
Address	:	15-2 Chaosheng Road, Xinya Street, Huadu District, Guangzhou, Guangdong, China
Manufacturer	:	**Guangzhou Nanwei Electronics Co.,Ltd**
Address	:	15-2 Chaosheng Road, Xinya Street, Huadu District, Guangzhou, Guangdong, China

Test result	**Pass ***

*In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.
The device (Product Name: Bluetooth module) Models Name: NW-X28 , QDJ-HALO2.6, QDJ-HALO2.6Pro, QDJ-HALO2.8, QDJ-HALO2.8Pro, QDJ-LOUD2.6B, QDJ-LOUD2.6W, QDJ-HOME1.6B, QDJ-HOME1.6W, QDJ-PARTY2.10, QDJ-LUM2.8, QDJ-LUM2.10, QDJ-LUM2.12, NW-X26, NW-X26Pro, NW-X26E, NW-X28Pro have same electrical, PCB and BOM, only model names are different for marketing requirements.

** Modified History **

Revisions	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	July 17, 2026	CTL2605222153-WF	Tracy Qi

Table of Contents Page

1. SUMMARY 5

1.1. TEST STANDARDS 5
1.2. TEST DESCRIPTION 5
1.3. TEST FACILITY 6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY 6
1.5. AUXILIARY EQUIPMENT INFORMATION 7

2. GENERAL INFORMATION 8

2.1. ENVIRONMENTAL CONDITIONS 8
2.2. GENERAL DESCRIPTION OF EUT 8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY 9
2.4. EQUIPMENTS USED DURING THE TEST 10
2.5. RELATED SUBMITTAL(S) / GRANT (S) 11
2.6. MODIFICATIONS 11

3. TEST CONDITIONS AND RESULTS 12

3.1. CONDUCTED EMISSIONS TEST 12
3.2. RADIATED EMISSIONS AND BAND EDGE 15
3.3. MAXIMUM PEAK OUTPUT POWER 29
3.4. 20DB BANDWIDTH 30
3.5. FREQUENCY SEPARATION 31
3.6. NUMBER OF HOPPING FREQUENCY 32
3.7. TIME OF OCCUPANCY (DWELL TIME) 33
3.8. OUT-OF-BAND EMISSIONS 34
3.9. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 35
3.10. ANTENNA REQUIREMENT 36

4. TEST SETUP PHOTOS OF THE EUT 36

5. PHOTOS OF THE EUT 39

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

47 CFR Part 15, Subpart C 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024: American National Standard for Testing Unlicensed Wireless Devices

KDB 558074 D01 v05r02: KDB558074 D01 15.247 Meas Guidance v05r02

1.2. Test Description

47 CFR Part 15, Subpart C 15.247		
47 CFR Part 15, Subpart C 15.207	AC Power Conducted Emission	PASS
47 CFR Part 15, Subpart C 15.247(a)(1)(i)	20dB Bandwidth	PASS
47 CFR Part 15, Subpart C 15.247(d)	Spurious RF Conducted Emission	PASS
47 CFR Part 15, Subpart C 15.247(b)	Maximum Peak Output Power	PASS
47 CFR Part 15, Subpart C 15.247(a)	Pseudorandom Frequency Hopping Sequence	PASS
47 CFR Part 15, Subpart C 15.247(a)(1)(iii)	Number of hopping frequency& Time of Occupancy	PASS
47 CFR Part 15, Subpart C 15.247(a)(1)	Frequency Separation	PASS
47 CFR Part 15, Subpart C 15.205/15.209	Radiated Emissions	PASS
47 CFR Part 15, Subpart C 15.247(d)	Band Edge Compliance of RF Emission	PASS
47 CFR Part 15, Subpart C 15.203/15.247 (b)	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Test laboratory

Company Name:	Shenzhen CTL Testing Technology Co., Ltd.
Address 1:	Zone A.1/F..Warehouse 2.Baisha Technology Park, No.3011,Shahexi Road, Nanshan District,Shenzhen.518055,P.R.C.
Address 2:	Fl.A1, Bldg.A3, No.2533 GuanGuang Road, Fenghuang Community Fenghuang Street, Guangming District, Shenzhen, Guangdong, PR.C

1.3.2 Test location

All tests were performed at:

Company Name:	Shenzhen CTL Testing Technology Co., Ltd.
☐ Main location	Zone A.1/F..Warehouse 2.Baisha Technology Park, No.3011,Shahexi Road, Nanshan District,Shenzhen.518055,P.R.C.
☒ Satellite location	Fl.A1, Bldg.A3, No.2533 GuanGuang Road, Fenghuang Community Fenghuang Street, Guangming District, Shenzhen, Guangdong, PR.C

1.3.3 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC CAB identifier: CN0041

Main Company Number :9618B

Satellite Company Number:35187

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Main Company Number:9618B and Satellite Company Number:35187.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No.: CN1216. Test Firm Registration 399832.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole

responsibility of continued compliance of the device.
Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Conducted Emission 0.15-30MHz	±3.11dB	(1)
Radiated Emission 0.009~30MHz	±3.66dB	(1)
Radiated Emission 30~1000MHz	±4.5dB	(1)
Radiated Emission Above 1GHz	±5.08dB	(1)
20dB Emission Bandwidth	±1.9%	(1)
Carrier Frequency Separation	±1.9%	(1)
Maximum Power Spectral Density Level	±0.98 dB	(1)
Number of Hopping Channel	±1.9%	(1)
Time of Occupancy	±0.11%	(1)
Max Peak Conducted Output Power	±0.98 dB	(1)
Band-edge Spurious Emission	±1.21dB	(1)
Conducted RF Spurious Emission	9kHz-7GHz:±1.09dB 7GHz-26.5GHz: ±3.27dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.
(2) Decision rule for Statement of Conformity: The measurement uncertainty is not taken into account but only measured result.

1.5. Auxiliary equipment information

Manufacturer	Description	Model	Serial Number
HONOR	Notebook Computer	KPL-W00	EYQPM19330000109

Note: This Notebook Computer is provided by the laboratory and is only for auxiliary testing. The customer delivered the goods without an Notebook Computer.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	18°C-28°C
Relative Humidity:	30%-60%
Air Pressure:	965Pa-1030Pa

2.2. General Description of EUT

Product Name:	Bluetooth module
Model/Type reference:	NW-X28
EUT Rated Voltage:	DC 5V
Test Voltage:	DC 5V
Bluetooth	
Version:	Supported BR/EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	2.81dBi provided by ☒ Applicant ☐ Manufacturer

Note1: For more details, please refer to the user's manual of the EUT.
Note2:The model NW-X28 is selected as representative model for full tests

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency：

Channel	Frequency (MHz)
00	**2402**
01	2403
⋮	⋮
38	2440
39	**2441**
40	2442
⋮	⋮
77	2479
78	**2480**

Preliminary tests were performed in each mode and packet length of BT, and found worst case as bellow, finally test were conducted at those mode and recorded in this report.

Test Items	Worst case
Conducted Emissions	DH5 Low channel
Radiated Emissions and Band Edge	DH5
Maximum Conducted Output Power	DH5/2DH5/3DH5
20dB Bandwidth	DH5/2DH5/3DH5
Frequency Separation	DH5/2DH5/3DH5
Number of hopping frequency	DH5/2DH5/3DH5
Time of Occupancy (Dwell Time)	DH1/DH3/DH5 2DH1/2DH3/2DH5 3DH1/3DH3/3DH5
Out-of-band Emissions	DH5/2DH5/3DH5

RF Cable List and Details

RF Cable	RF Cable loss	RF Cable loss provided by
RG316	0.5dB	☒ Applicant ☐ Manufacturer ☐ Testing Laboratory(CTL)

Software Version: FrequencyTool_v0.3.1	
Test Mode	Power level
BT BR	2
BT EDR	2

2.4. Equipments Used during the Test

Conducted Emission					
Test Equipment	Manufacturer	Model No.	Serial No.	Last calibration	Calibration Due
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2026/01/05	2027/01/04
LISN	ROHDE & SCHWARZ	ESH2-Z5	860014/010	2026/01/05	2027/01/04
Limitator	ROHDE & SCHWARZ	ESH3-Z2	100408	2026/01/05	2027/01/04
Software:					
Name of Software:			Version:		
ES-K1			V1.71		

Radiated Emission					
Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
Active Loop Antenna	Da Ze	ZN30900A	/	2025/07/02	2026/07/01
Active Loop Antenna	Da Ze	ZN30900A	/	2026/06/30	2027/06/29
ULTRA-BROADBAND ANTENNA	Sunol Sciences Corp.	JB1 Antenna	A061713	2025/07/02	2026/07/01
ULTRA-BROADBAND ANTENNA	Sunol Sciences Corp.	JB1 Antenna	A061713	2026/06/28	2027/06/27
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2026/01/05	2027/01/04
Horn Antenna	Ocean Microwave	OBH100400	26999002	2025/07/03	2026/07/02
Horn Antenna	Ocean Microwave	OBH100400	26999002	2026/07/06	2027/07/05
Amplifier	MRT-AP01M06	MRT	S-001	2025/07/02	2026/07/01
Amplifier	MRT-AP01M06	MRT	S-001	2026/06/30	2027/06/29
Amplifier	Agilent	8449B	3008A02306	2026/01/05	2027/01/04
Amplifier	Brief&Smart	LNA-4018	2104197	2025/07/03	2026/07/02
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	100434	2025/07/02	2026/07/01
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	100434	2026/07/01	2027/06/30
Spectrum Analyzer	RS	FSP	1164.4391.38	2025/07/03	2026/07/02
Spectrum Analyzer	RS	FSP	1164.4391.38	2026/06/30	2027/06/29
DC power supply	Agilent	E3632A	MY40015577	2025/07/03	2026/07/02
DC power supply	Agilent	E3632A	MY40015577	2026/06/29	2027/06/28
Software:					
Name of Software:			Version:		
EZ_EMC(Below 1GHz)			V1.1.4.2		
EZ_EMC(Above 1GHz)			V1.1.4.2		

RF Conducted					
Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
Spectrum Analyzer	Keysight	N9020A	MY53420874	2025/07/03	2026/07/02
Spectrum Analyzer	Keysight	N9020A	MY53420874	2026/06/29	2027/06/28
Temperature/Humidity Meter	Ji Yu	MC501	/	2025/07/03	2026/07/02
Temperature/Humidity Meter	Ji Yu	MC501	/	2026/07/02	2027/07/01
Software:					
Name of Software:			Version:		
TST-PASS			V2.0.2		

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the 47 CFR Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
2. Support equipment, if needed, was placed as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Line:	L

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL260611631_fin"

6/11/2026 3:36PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	56.30	10.3	66	9.7	QP	L1	GND
0.154500	55.60	10.3	66	10.2	QP	L1	GND
3.160500	34.80	10.9	56	21.2	QP	L1	GND
3.390000	35.10	11.0	56	20.9	QP	L1	GND
4.213500	36.50	11.0	56	19.5	QP	L1	GND
4.515000	37.10	11.0	56	18.9	QP	L1	GND

MEASUREMENT RESULT: "CTL260611631_fin2"

6/11/2026 3:36PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	43.50	10.3	56	12.5	AV	L1	GND
1.918500	28.10	10.7	46	17.9	AV	L1	GND
2.688000	30.40	10.8	46	15.6	AV	L1	GND
3.840000	32.20	11.0	46	13.8	AV	L1	GND
5.374500	29.60	11.1	50	20.4	AV	L1	GND
27.001500	33.90	11.5	50	16.1	AV	L1	GND

Line:	N

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL260611630_fin"

6/11/2026 3:33PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	56.20	10.3	66	9.8	QP	N	GND
0.226500	44.90	10.3	63	17.7	QP	N	GND
2.872500	33.70	10.9	56	22.3	QP	N	GND
3.349500	34.40	11.0	56	21.6	QP	N	GND
4.870500	36.80	11.0	56	19.2	QP	N	GND
5.500500	34.40	11.1	60	25.6	QP	N	GND

MEASUREMENT RESULT: "CTL260611630_fin2"

6/11/2026 3:33PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154500	40.00	10.3	56	15.8	AV	N	GND
1.918500	28.10	10.7	46	17.9	AV	N	GND
2.688000	30.50	10.8	46	15.5	AV	N	GND
4.852500	30.30	11.0	46	15.7	AV	N	GND
5.244000	29.00	11.1	50	21.0	AV	N	GND
27.001500	33.80	11.5	50	16.2	AV	N	GND

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 0.8m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

TEST RESULTS

Remark:
1. We measured Radiated Emission at GFSK, π/4 DQPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode..
2. For below 1GHz testing recorded worst at GFSK DH5 low channel.
3. For above 1GHz testing recorded worst at GFSK DH5 low channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, Found the emission level are attenuated 20dB below the limits from 9 kHz to 30MHz, so it does not recorded in report.

For 30MHz-1GHz

Horizontal



Site LAB Chamber 1
Limit: FCC Part15 Class C_30-1000MHz
EUT:
M/N:
Mode: BT 2480MHz
Note: CTL2605222153-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.1053	3.37	20.31	23.68	40.00	16.32	peak	100	12	P	
2	701.7610	4.97	23.10	28.07	46.00	17.93	peak	100	149	P	
3	737.0712	5.84	23.55	29.39	46.00	16.61	peak	100	257	P	
4	796.1829	5.47	24.59	30.06	46.00	15.94	peak	100	42	P	
5	863.0562	6.15	25.02	31.17	46.00	14.83	peak	100	0	P	
6	955.4381	5.32	25.84	31.16	46.00	14.84	peak	100	3	P	

Vertical



Site LAB Chamber 1
Limit: FCC Part15 Class C_30-1000MHz
EUT:
M/N:
Mode: BT 2480MHz
Note: CTL2605222153-WF

Polarization: ***Vertical***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	31.0706	5.89	19.47	25.36	40.00	14.64	peak	100	94	P	
2	647.3856	7.06	22.97	30.03	46.00	15.97	peak	100	172	P	
3	848.0563	5.57	24.65	30.22	46.00	15.78	peak	100	45	P	
4	887.6099	5.11	25.34	30.45	46.00	15.55	peak	100	153	P	
5	925.7563	4.46	25.92	30.38	46.00	15.62	peak	100	221	P	
6	958.7943	3.93	26.05	29.98	46.00	16.02	peak	100	16	P	

For 1GHz to 25GHz

Horizontal



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: BT 2402MHz TX
Note: CTL2605222153-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2400.753	63.18	-18.53	44.65	74.00	29.35	peak	100	155	P	
2	4015.929	46.17	-8.97	37.20	74.00	36.80	peak	100	95	P	
3	4804.110	48.17	-9.05	39.12	74.00	34.88	peak	100	224	P	
4	8248.005	47.02	-3.71	43.31	74.00	30.69	peak	100	323	P	
5	11012.253	46.54	1.11	47.65	74.00	26.35	peak	100	135	P	
6	15003.422	48.64	3.24	51.88	74.00	22.12	peak	200	15	P	

Radiated Emission Measurement

File :RF2 Data :#6321 Date: 2026/06/11 Time: 18:58:06



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: BT 2441MHz TX
Note: CTL2605222153-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2442.751	55.98	-18.73	37.25	74.00	36.75	peak	100	94	P	
2	4039.212	46.27	-8.91	37.36	74.00	36.64	peak	100	125	P	
3	5664.525	46.39	-7.60	38.79	74.00	35.21	peak	100	75	P	
4	8248.005	47.34	-3.71	43.63	74.00	30.37	peak	100	293	P	
5	11044.129	46.45	0.99	47.44	74.00	26.56	peak	100	293	P	
6	14408.425	48.29	2.96	51.25	74.00	22.75	peak	200	165	P	

Radiated Emission Measurement

File :RF2 Data :#6323 Date: 2026/06/11 Time: 19:00:58



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: BT 2480MHz TX
Note: CTL2605222153-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2478.310	56.76	-18.63	38.13	74.00	35.87	peak	100	145	P	
2	4027.554	46.26	-8.93	37.33	74.00	36.67	peak	200	245	P	
3	5713.856	46.46	-7.30	39.16	74.00	34.84	peak	100	324	P	
4	7284.038	46.87	-5.02	41.85	74.00	32.15	peak	100	5	P	
5	11012.253	46.08	1.11	47.19	74.00	26.81	peak	100	45	P	
6	14960.120	48.62	2.82	51.44	74.00	22.56	peak	100	35	P	

Vertical



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: BT 2402MHz TX
Note: CTL2605222153-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2400.753	57.43	-18.53	38.90	74.00	35.10	peak	100	126	P	
2	2947.623	50.69	-13.58	37.11	74.00	36.89	peak	100	265	P	
3	4804.110	51.60	-9.05	42.55	74.00	31.45	peak	100	35	P	
4	8271.880	48.74	-4.35	44.39	74.00	29.61	peak	100	255	P	
5	11012.253	45.55	1.11	46.66	74.00	27.34	peak	200	45	P	
6	16315.231	47.85	4.45	52.30	74.00	21.70	peak	100	195	P	

Radiated Emission Measurement

File :RF2 Data :#6322 Date: 2026/06/11 Time: 18:58:52



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: BT 2441MHz TX
Note: CTL2605222153-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2442.751	53.45	-18.73	34.72	74.00	39.28	peak	100	175	P	
2	2956.155	49.31	-13.76	35.55	74.00	38.45	peak	200	0	P	
3	4015.929	46.18	-8.97	37.21	74.00	36.79	peak	100	226	P	
4	7179.527	46.51	-5.01	41.50	74.00	32.50	peak	100	155	P	
5	11076.096	46.59	0.89	47.48	74.00	26.52	peak	100	266	P	
6	15046.851	48.32	3.18	51.50	74.00	22.50	peak	100	55	P	



Site LAB Chamber 1
Limit: FCC PART 15C ABOVE 1GHz PK
EUT:
M/N:
Mode: BT 2480MHz TX
Note: CTL2605222153-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2478.310	55.78	-18.63	37.15	74.00	36.85	peak	200	155	P	
2	4027.554	46.47	-8.93	37.54	74.00	36.46	peak	100	155	P	
3	5813.812	45.81	-7.18	38.63	74.00	35.37	peak	100	355	P	
4	8248.005	47.76	-3.71	44.05	74.00	29.95	peak	100	295	P	
5	11012.253	46.78	1.11	47.89	74.00	26.11	peak	100	165	P	
6	15003.422	48.35	3.24	51.59	74.00	22.41	peak	100	75	P	

REMARKS:

1. 18GHz-26GHz not recorded for no spurious point have a margin of less than 20 dB with respect to the limits.
2. PK detector measurement value is lower than the average limit. Therefore, there is no need to test AV detector measurements.
3. While performing the testing, the notch filter is used for avoiding test instrument overload.

Results of Band Edges Test (Radiated)

Note：GFSK, Pi/4 DQPSK, 8DPSK all have been tested, only worse case GFSK is reported.

CH00	Horizontal



Site LAB Chamber 1
Limit: FCC PART 15C
EUT:
M/N:
Mode: BT 2402MHz
Note: CTL2605222153-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	25.38	31.55	56.93	74.00	17.07	peak	150	331	P	
2	2310.000	13.93	31.55	45.48	54.00	8.52	AVG	150	331	P	
3	2390.000	25.91	32.99	58.90	74.00	15.10	peak	150	269	P	
4	2390.000	14.30	32.99	47.29	54.00	6.71	AVG	150	269	P	
5	2401.956	71.77	33.26	105.03	74.00	-31.03	peak	150	222	F	
6	2401.984	71.42	33.26	104.68	54.00	-50.68	AVG	150	222	F	

CH00	Vertical



Site LAB Chamber 1
Limit: FCC PART 15C
EUT:
M/N:
Mode: BT 2402MHz
Note: CTL2605222153-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	24.95	31.55	56.50	74.00	17.50	peak	150	200	P	
2	2310.000	13.82	31.55	45.37	54.00	8.63	AVG	150	200	P	
3	2390.000	24.91	32.99	57.90	74.00	16.10	peak	150	168	P	
4	2390.000	14.18	32.99	47.17	54.00	6.83	AVG	150	168	P	
5	2401.846	67.59	33.27	100.86	74.00	-26.86	peak	150	13	F	
6	2401.970	67.28	33.26	100.54	54.00	-46.54	AVG	150	13	F	

CH78	Horizontal



Site LAB Chamber 1
Limit: FCC PART 15C
EUT:
M/N:
Mode: BT 2480MHz
Note: CTL2605222153-WF

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2480.046	62.65	33.02	95.67	54.00	-41.67	AVG	150	223	F	
2	2480.137	63.10	33.02	96.12	74.00	-22.12	peak	150	223	F	
3	2483.500	27.12	33.03	60.15	74.00	13.85	peak	150	223	P	
4	2483.500	20.91	33.03	53.94	54.00	0.06	AVG	150	223	P	
5	2490.097	25.84	33.05	58.89	74.00	15.11	peak	150	67	P	
6	2500.000	24.05	33.07	57.12	74.00	16.88	peak	150	21	P	
7	2500.000	13.58	33.07	46.65	54.00	7.35	AVG	150	21	P	
8	2503.944	14.27	33.37	47.64	54.00	6.36	AVG	150	146	P	

CH78	Vertical



Site LAB Chamber 1
Limit: FCC PART 15C
EUT:
M/N:
Mode: BT 2480MHz
Note: CTL2605222153-WF

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 25(C)
Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2480.018	57.73	33.02	90.75	54.00	-36.75	AVG	150	0	F	
2	2480.142	58.24	33.02	91.26	74.00	-17.26	peak	150	29	F	
3	2483.500	25.18	33.03	58.21	74.00	15.79	peak	150	0	P	
4	2483.500	17.33	33.03	50.36	54.00	3.64	AVG	150	0	P	
5	2500.000	24.66	33.07	57.73	74.00	16.27	peak	150	14	P	
6	2500.000	13.38	33.07	46.45	54.00	7.55	AVG	150	14	P	
7	2506.528	25.77	33.56	59.33	74.00	14.67	peak	150	122	P	
8	2509.316	13.57	33.77	47.34	54.00	6.66	AVG	150	44	P	

3.3. Maximum Peak Output Power

Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.

a) Set the RBW > 20 dB bandwidth of the emission being measured.

b) Set VBW ⩾ RBW.

c) Set span Approximately five times the 20 dB bandwidth, centered on a hopping channel.

d) Sweep time = Auto.

e) Detector=Peak.

f) Trace mode=Max hold.

g) Allow trace to fully stabilize.

h) Use peak marker function to determine the peak amplitude level..

Test Configuration

Test Results

Raw data reference to Section 2 of document No. CTL2605222153-WF_Bluetooth_Appendix.

3.4. 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW= 1% to 5% of the OBW, VBW= approximately 3×RBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration

Test Results

Raw data reference to Section 1 of document No. CTL2605222153-WF_Bluetooth_Appendix.

3.5. Frequency Separation

LIMIT

According to 15.247(a)(1),frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with300 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION

TEST RESULTS

Raw data reference to Section 3 of document No. CTL2605222153-WF_Bluetooth_Appendix.

3.6. Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 300 KHz RBW and 300 KHz VBW.

Test Configuration



Test Results

Raw data reference to Section 4 of document No. CTL2605222153-WF_Bluetooth_Appendix.

3.7. Time of Occupancy (Dwell Time)

Limit

The average time of occupancy on any channel shall not be greater than 400 milliseconds within a period of 400 milliseconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency, RBW shall be≤channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel, VBW=RBW, Span 0Hz.

Test Configuration



Test Results

Raw data reference to Section 5 of document No. CTL2605222153-WF_Bluetooth_Appendix.

3.8. Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF con-ducted or a radiated measurement, pro-vided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter com-plies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration

Test Results

Raw data reference to Section 6 of document No. CTL2605222153-WF_Bluetooth_Appendix.

3.9. Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE

For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement

The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

3.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The maximum gain of antenna was 2.81dBi.



4. Test Setup Photos of the EUT








KEYSIGHT
MXA
TST PASS
POWER

5. Photos of the EUT
















470
10V
VT
2R2
BT Antenna



********** End of Report **********