

TEST REPORT

Product Name : Wireless Kitchen Scale with Split Display
Model Number : KS17
FCC ID : 2BWMD-KS17

Prepared for : Shenzhen Faray InfoTech Co.,Ltd
Address : Room 401, Block A, Xichuang Technology Building,
No. 7025, Liuxian Avenue, Xili Community, Xili Street,
Nanshan District, Shenzhen China

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : 1&2/F., Building 2, Zone A, Zhongda Marine
Biotechnology Research and Development Base,
No.9, Xincheng Avenue, Songshanhu High-technology
Industrial Development Zone, Dongguan, Guangdong,
China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2607200028E00302R
Date of sample receipt : July 20, 2026
Date(s) of Tests : July 20, 2026 to August 16, 2026
Date of issue : August 17, 2026

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Shenzhen Faray InfoTech Co.,Ltd
Address : Room 401, Block A, Xichuang Technology Building, No. 7025, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen China
Manufacturer : Shenzhen Faray InfoTech Co.,Ltd
Address : Room 401, Block A, Xichuang Technology Building, No. 7025, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen China
Factory : Zhongshan Kangnuo Electronics Co.,Ltd
Address : 2F, No.9-1 Dongcheng North Road, Xinsheng Village, Xiaolan, Zhongshan, Guangdong, China 528400
EUT : Wireless Kitchen Scale with Split Display
Model Name : KS17
Trademark : Ultrean

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : July 20, 2026 to August 16, 2026

Prepared by :



Jessica Zhang /Editor

Reviewer :


Warren Deng /Supervisor

Approve & Authorized Signer :


Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2607200028E00302R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Wireless Kitchen Scale with Split Display
Model Number:	KS17
Sample:	E2607200028-01
Device Type:	BLE
Data Rate:	1Mbps for GFSK modulation
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	40 channels
Transmit Power Max:	-0.16 dBm(0.000964 W)
Antenna Gain:	1.84 dBi
Power supply:	DC 5V from USB DC 3.7V from battery
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 1.84 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	Calculation threshold(1-g SAR)
2402	GFSK(1M)	-0.16	0±1	1	0.3902	3
2440	GFSK(1M)	-0.39	0±1	1	0.3933	3
2480	GFSK(1M)	-1.09	-1±1	0	0.3150	3

According to KDB 447498 D01 V06, no stand-alone required for BLE antenna, and no simultaneous SAR measurement is required.

*** End of Report ***