

RF Exposure Evaluation Report

Product : Wireless Mouse
Trade mark : XUNJISHA(迅极鲨)
Model/Type reference : X7,X7 Pro,X8,X11,X12,X15,X16,X8
Pro,X11 Ultra,X12 Max,X15 Elite,X16
Turbo,X7 Mas,X8 Mas,X11 Frost,X12
Holly,X15 Noel,X16 Carol, Xyyyyyyyyyy("X"
is fixed and "y" is a variable that can be "0-
9""-" _ ""blank" "A-Z" or "a-z")
Serial Number : N/A
Report Number : EED32S81186202
FCC ID : 2BWNP-X
Date of Issue : Jul. 09, 2026
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF
Exposure Guidance v01
Test result : PASS

Prepared for:

Dongguan XUNJISHA Technology Co., Ltd.
Room1399,Building4,NO.6-1,Caotang Road, Nancheng Street,
Dongguan City, Guangdong Province, China

Prepared by:

Centre Testing International Group Co., Ltd.
Building C, Hongwei Industrial Park Block 70, Bao'an District,
Shenzhen, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385



Compiled by:

Win Wei

Win Wei

Approved by:

Aaron Ma

Aaron Ma

Reviewed by:

Keven Tan

Keven Tan

Date:

Jul. 09, 2026

Check No.:9336270526

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
2.4 TEST LOCATION	4
2.5 DEVIATION FROM STANDARDS	4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
3 SAR EVALUATION	5
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
3.1.1 Limits	5
3.1.2 Test Procedure	5
3.1.3 EUT RF Exposure Evaluation	6

2 General Information

2.1 Client Information

Applicant:	Dongguan XUNJISHA Technology Co., Ltd.
Address of Applicant:	Room1399,Building4,NO.6-1,Caotang Road, Nancheng Street, Dongguan City, Guangdong Province, China
Manufacturer:	Dongguan XUNJISHA Technology Co., Ltd.
Address of Manufacturer:	Room1399,Building4,NO.6-1,Caotang Road, Nancheng Street, Dongguan City, Guangdong Province, China

2.2 General Description of EUT

Product Name:	Wireless Mouse
Model No.:	X7,X7 Pro,X8,X11,X12,X15,X16,X8 Pro,X11 Ultra,X12 Max,X15 Elite,X16 Turbo,X7 Mas,X8 Mas,X11 Frost,X12 Holly,X15 Noel,X16 Carol, Xyyyyyyyyyy("X" is fixed and "y" is a variable that can be "0-9" "-" " _ ""blank" "A-Z" or "a-z")
Test Model No.:	X7
Model difference:	They have same electrical, PCB and layout, only the model name, color and sales region are different for marketing requirements.
Trade Mark:	XUNJISHA(迅极鲨)

2.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Test Power Grade:	Default	
Test Software of EUT:	Bluetooth LE: BK32xx RF Test_V2.1.0.exe	
Antenna Type:	PCB Antenna	
Antenna Gain:	-0.71dBi	
Power Supply:	Battery:	DC3.7V
Sample Received Date:	Jun. 12, 2026	
Sample tested Date:	Jun. 12, 2026 to Jun. 19, 2026	

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164, Test Firm Registration No.: 260439

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation**For Stand alone:**

Band	Freq. (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
BLE	2480	0.5	-2.85	-0.71	-5.71	0.27	2.717	0.0988	Pass

Note:

- ① EIRP=conducted power+antenna gain;
- ② ERP=EIRP-2.15;
- ③ $EIRP(dBm) = \text{Field strength of the fundamental signal}(dBuV/m@3m) - 95.23$;
- ④ $ERP(mW) = 10^{(ERP(dBm)/10)}$;
- ⑤ The estimation distance is 0.5cm;
- ⑥ The test data please refer to the report of EED32S81186201, EED32S81186202 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***