

FCC ID: 2BWQ2-YM05

Maximum Permissible Exposure (MPE)

According to FCC 2.1091, 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

BR,EDR:
Measurement Result
Antenna gain:2.73dBi;
R=20cm

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	1.44	1±1	2	1.585	2.73	1.87	0.0006	1
2441		1.82	1±1	2	1.585	2.73	1.87	0.0006	1
2480		1.58	1±1	2	1.585	2.73	1.87	0.0006	1
2402	π/4- DQPSK	0.77	0±1	1	1.259	2.73	1.87	0.0005	1
2441		0.51	0±1	1	1.259	2.73	1.87	0.0005	1
2480		0.5	0±1	1	1.259	2.73	1.87	0.0005	1
2402	8-DPSK	0.79	0±1	1	1.259	2.73	1.87	0.0005	1
2441		0.51	0±1	1	1.259	2.73	1.87	0.0005	1
2480		0.5	0±1	1	1.259	2.73	1.87	0.0005	1

BLE:
Measurement Result
Antenna gain:2.73dBi;
R=20cm

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density (mW/cm2)
		(dBm)		tune-up power		Gain			
				(dBm)	(dBm)	(mW)	(dBi)	Numeric	
2402	BLE 1M	1.26	1±1	2	1.585	2.73	1.87	0.0006	1
2440		0.87	0±1	1	1.259	2.73	1.87	0.0005	1
2480		1.37	1±1	2	1.585	2.73	1.87	0.0006	1
2402	BLE 2M	1.36	1±1	2	1.585	2.73	1.87	0.0006	1
2440		0.97	0±1	1	1.259	2.73	1.87	0.0005	1
2480		1.09	2±1	2	1.585	2.73	1.87	0.0006	1

2.4GWIFI:
Measurement Result
Antenna gain 1:2.73dBi
R=20cm

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density (mW/cm2)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2412	11b	15.67	15±1	16	39.811	2.73	1.87	0.0148	1
2437		16.88	16±1	17	50.119	2.73	1.87	0.0187	1
2462		16.03	16±1	17	50.119	2.73	1.87	0.0187	1
2412	11g	15.82	15±1	16	39.811	2.73	1.87	0.0148	1
2437		15.66	15±1	16	39.811	2.73	1.87	0.0148	1
2462		14.96	14±1	15	31.623	2.73	1.87	0.0118	1
2412	11n20	13.95	13±1	14	25.119	2.73	1.87	0.0094	1
2437		13.68	13±1	14	25.119	2.73	1.87	0.0094	1
2462		12.95	12±1	13	19.953	2.73	1.87	0.0074	1
2422	11n40	14.48	14±1	15	31.623	2.73	1.87	0.0118	1
2437		14.26	14±1	15	31.623	2.73	1.87	0.0118	1
2452		13.57	13±1	14	25.119	2.73	1.87	0.0094	1
2412	11ax20	14.01	14±1	15	31.623	2.73	1.87	0.0118	1
2437		13.8	13±1	14	25.119	2.73	1.87	0.0094	1
2462		13.09	13±1	14	25.119	2.73	1.87	0.0094	1
2422	11ax40	13.75	13±1	14	25.119	2.73	1.87	0.0094	1
2437		13.54	13±1	14	25.119	2.73	1.87	0.0094	1
2452		12.78	12±1	13	19.953	2.73	1.87	0.0074	1

5.2G WIFI:
Antenna gain 1:3.27dBi
R=20cm

modulation	Antenna	Channel Freq. (MHz)	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density (mW/cm2)
			(dBm)		tune-up power		Gain			
					(dBm)	(mW)	(dBi)	Numeric		
802.11a	Ant 1	5180	11.28	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5200	11.73	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5240	11.88	11±1	12.00	15.849	3.27	2.12	0.0067	1
802.11n20	Ant 1	5180	11.06	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5200	11.11	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5240	11.75	11±1	12.00	15.849	3.27	2.12	0.0067	1
802.11n40	Ant 1	5190	7.60	7±1	8.00	6.310	3.27	2.12	0.0027	1
	Ant 1	5230	7.61	7±1	8.00	6.310	3.27	2.12	0.0027	1
802.11ac20	Ant 1	5180	11.18	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5200	11.36	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5240	11.40	11±1	12.00	15.849	3.27	2.12	0.0067	1
802.11ac40	Ant 1	5190	7.56	7±1	8.00	6.310	3.27	2.12	0.0027	1
	Ant 1	5230	7.57	7±1	8.00	6.310	3.27	2.12	0.0027	1
802.11ax20	Ant 1	5180	10.99	10±1	11.00	12.589	3.27	2.12	0.0053	1
	Ant 1	5200	11.55	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5240	11.99	11±1	12.00	15.849	3.27	2.12	0.0067	1
802.11ax40	Ant 1	5190	7.56	7±1	8.00	6.310	3.27	2.12	0.0027	1
	Ant 1	5230	7.92	7±1	8.00	6.310	3.27	2.12	0.0027	1

5.8G

Antenna gain 1:3.27dBi

R=20cm

modulation	Antenna	Channel Freq. (MHz)	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
			(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
					(dBm)	(mW)	(dBi)	Numeric		
802.11a	Ant 1	5745	11.63	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5785	11.85	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5825	12.04	12±1	13.00	19.953	3.27	2.12	0.0084	1
802.11n20	Ant 1	5745	11.66	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5785	12.15	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5825	11.79	11±1	12.00	15.849	3.27	2.12	0.0067	1
802.11n40	Ant 1	5755	12.55	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5795	12.48	12±1	13.00	19.953	3.27	2.12	0.0084	1
802.11ac20	Ant 1	5745	11.93	11±1	12.00	15.849	3.27	2.12	0.0067	1
	Ant 1	5785	12.06	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5825	12.19	12±1	13.00	19.953	3.27	2.12	0.0084	1
802.11ac40	Ant 1	5755	12.13	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5795	12.31	12±1	13.00	19.953	3.27	2.12	0.0084	1
802.11ax20	Ant 1	5745	12.03	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5785	12.33	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5825	12.05	12±1	13.00	19.953	3.27	2.12	0.0084	1
802.11ax40	Ant 1	5755	12.43	12±1	13.00	19.953	3.27	2.12	0.0084	1
	Ant 1	5795	12.54	12±1	13.00	19.953	3.27	2.12	0.0084	1

SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E^2 , H^2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The BR,EDR/BLE/2.4G WLAN/5G WLAN share the same ANT cannot transmit at same time.

Conclusion: Pass

Signature: 

Date: 2026-06-08

NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China