

**Portable device**

According to §15.231 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

According to 2.1093

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Antenna Type: PCB Antenna

Antenna Gain: 0 dBi

Transmit power:

| Frequency (MHz) | EIRP power (dBuV/m) | EIRP power (dBm) | EIRP power (mW) |
|-----------------|---------------------|------------------|-----------------|
| 315.07          | 59.63               | -35.60           | 0.0003          |

$\text{EIRP} = \text{E} - 104.8 + 20 \log(D)$

Maximum Permissible Exposure:

| Modulation | Channel Freq. (MHz) | Conducted power (dBm) | Conducted power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | 1g SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|-----------------------|----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|----------------------------|--------------------|
| FSK        | 315.07              | -35.60                | 0.0003               | -35 $\pm$ 1         | -34.0                   | 0.0004                 | <5            | 0.001              | 3.00                       | YES                |

**Conclusion:**

For the max result :  $0.001 \leq 3.0$  for 1-g SAR, No SAR is required.

Signature:



Date: 2026-06-22

**NAME AND TITLE** (Please print or type): Alex /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ Building 1/2/11/12, No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China