

TEST REPORT

Report No.: 8433EU013106W4

Applicant: LOVE Synthesizers ehf.

Address: Vatnsholt 10, 105 Reykjavik, Iceland

Product Name: Music synthesizer

Model No.: First.Love

Trademark: Love synthesizers

FCC ID: 2BWST-LSFL01

Test Standard(s): 47 CFR Part 15E

Test Result: Pass

Date of Receipt: Jul. 31, 2026

Test Date: Aug. 03, 2026 - Sep. 01, 2026

Date of Issue: Oct. 12, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:



Landon Qiu/ Engineer

Reviewed and Approved by:



Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Oct. 12, 2026	Original	Valid



Table of Contents

1	COVER PAGE	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION	5
2.2	MANUFACTURER INFORMATION	5
2.3	FACTORY INFORMATION	5
2.4	GENERAL DESCRIPTION OF E.U.T.	5
2.5	TECHNICAL INFORMATION OF E.U.T.	6
3	TEST SUMMARY	8
3.1	TEST STANDARD	8
3.2	TEST VERDICT	8
3.3	TEST LABORATORY	9
4	TEST CONFIGURATION	10
4.1	TEST ENVIRONMENT	10
4.2	TEST EQUIPMENT	10
4.3	DESCRIPTION OF SUPPORT UNIT	13
4.4	TEST MODE	13
4.5	DESCRIPTION OF CALCULATION	13
4.5.1	Field Strength Calculation	13
4.5.2	Disturbance Calculation	13
4.6	MEASUREMENT UNCERTAINTY	14
4.7	DEVIATION FROM STANDARDS	14
4.8	ABNORMALITIES FROM STANDARD CONDITION	14
5	EVALUATION RESULTS (EVALUATION)	15
5.1	ANTENNA REQUIREMENT	15
5.1.1	Test Specification	15
5.1.2	Test Data	15
6	RADIO SPECTRUM MATTER TEST RESULTS (RF)	16
6.1	CONDUCTED EMISSION AT AC POWER LINE	16
6.1.1	Test Specification	16
6.1.2	E.U.T. Operation	16
6.1.3	Test Setup Diagram	16
6.1.4	Test Data	16
6.2	DUTY CYCLE	19
6.2.1	Test Specification	19
6.2.2	E.U.T. Operation	19
6.2.3	Test Setup Diagram	19
6.2.4	Test Data	19
6.3	EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	20
6.3.1	Test Specification	20
6.3.2	E.U.T. Operation	21
6.3.3	Test Setup Diagram	21
6.3.4	Test Data	21
6.4	MAXIMUM CONDUCTED OUTPUT POWER	22
6.4.1	Test Specification	22
6.4.2	E.U.T. Operation	22
6.4.3	Test Setup Diagram	22

6.4.4	Test Data	22
6.5	POWER SPECTRAL DENSITY	23
6.5.1	Test Specification	23
6.5.2	E.U.T. Operation.....	23
6.5.3	Test Setup Diagram.....	23
6.5.4	Test Data	23
6.6	FREQUENCY STABILITY	24
6.6.1	Test Specification	24
6.6.2	E.U.T. Operation.....	24
6.6.3	Test Setup Diagram.....	24
6.6.4	Test Data	24
6.7	BAND EDGE EMISSIONS (RADIATED)	25
6.7.1	Test Specification	25
6.7.2	E.U.T. Operation.....	27
6.7.3	Test Setup Diagram.....	27
6.7.4	Test Data	27
6.8	UNDESIRABLE EMISSION LIMITS (BELOW 1GHz).....	49
6.8.1	Test Specification	49
6.8.2	E.U.T. Operation.....	50
6.8.3	Test Setup Diagram.....	51
6.8.4	Test Data	51
6.9	UNDESIRABLE EMISSION LIMITS (ABOVE 1GHz)	54
6.9.1	Test Specification	54
6.9.2	E.U.T. Operation.....	56
6.9.3	Test Setup Diagram.....	56
6.9.4	Test Data	56
ANNEX A	TEST SETUP PHOTOS	63
ANNEX B	EXTERNAL PHOTOS	63
ANNEX C	INTERNAL PHOTOS	63
ANNEX D	TEST DATA	64

2 General Information

2.1 Applicant Information

Applicant	LOVE Synthesizers ehf.
Address	Vatnsholt 10, 105 Reykjavik, Iceland

2.2 Manufacturer Information

Manufacturer	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

2.3 Factory Information

Factory	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

2.4 General Description of E.U.T.

Product Name	Music synthesizer
Model No. Under Test	First.Love
List Model No.	N/A
Description of Model differentiation	N/A
Rating(s)	Adapter power supply: 5.0V===3.0A, 9.0V===3.0A, 12.0V===3.0A, 15.0V===2.4A, 20.0V===1.8A (Adapter 100-240V~, 50/60Hz, 1.2A Max; Output: 5.0V===3.0A, 15.0W Max; 9.0V===3.0A, 27.0W Max; 12.0V===3.0A, 36.0W Max; 15.0V===2.4A, 36.0W Max; 20.0V===1.8A, 36.0W Max)
Adapter	Model No.: FJ-GN236CN Input: 100-240V~, 50/60Hz, 1.2A Max Output: 5.0V===3.0A, 15.0W Max; 9.0V===3.0A, 27.0W Max; 12.0V===3.0A, 36.0W Max; 15.0V===2.4A, 36.0W Max; 20.0V===1.8A, 36.0W Max Manufacturer: HUIZHOU FUJIA APPLIANCE TECH. CO., LTD
Battery Capacity	7.4VDC, 2400mAh, 17.76Wh
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Test Sample No.	8433EU013106W-1/2(Normal), 8433EU013106W-2/2(Engineering)
Hardware Version	1.0
Software Version	4.0
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth (BDR+EDR+BLE) WiFi 2.4G: 802.11b, 802.11g, 802.11n(HT20/40) and 802.11ax(HEW20/40) WiFi 5G: 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40) and 802.11ax(HEW20/40) U-NII-1/3
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Technology	WiFi 5G
Operation Mode	a, n(HT20/40), ac(VHT20/40), ax(HEW20/40)
Operating Frequency	U-NII-1: 5150 MHz to 5250 MHz U-NII-3: 5725 MHz to 5850 MHz
Modulation Type	802.11a: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM).
Number of Channels	802.11a/n(HT20)/ac(VHT20)/ax(HEW20): U-NII Band 1: 4; U-NII Band 3: 5; 802.11n(HT40)/ac(VHT40)/ax(HEW40): U-NII Band 1: 2; U-NII Band 3: 2;
Antenna Type	FPC Antenna
Antenna Gain(Peak)	2.38 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

U-NII-1			
Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	/	/
48	5240	/	/
U-NII-3			
Bandwidth:	20MHz	Bandwidth:	40MHz
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755
153	5765	159	5795
157	5785	/	/
161	5805	/	/
165	5825	/	/

802.11ax RU configuration table							
Mode	Full RU (SU)	RU_26	RU_52	RU_106	RU_242	RU_484	RU_996
802.11ax (HEW20)	√	--	--	--	--	--	--
802.11ax (HEW40)	√	--	--	--	--	--	--

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

47 CFR Part 15E: Unlicensed National Information Infrastructure Devices

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

Test Items	Standard	Method	Requirement	Results
Antenna requirement	47 CFR Part 15E	---	Part 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.2	47 CFR Part 15.207(a)	Pass
Duty Cycle	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 12.2 (b)	---	Pass
Emission bandwidth and occupied bandwidth	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.9 & 12.5 KDB 789033 D02, Clause C.2	U-NII 1: No limits, only for report use. U-NII 3: 47 CFR Part 15.407(e)	Pass
Maximum conducted output power	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.4	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)	Pass
Power spectral density	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.6	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)	Pass
Frequency stability	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.8	47 CFR Part 15.407(g)	Pass
Band edge emissions	47 CFR Part 15E	ANSI C63.10-	47 CFR Part	Pass

(Radiated)		2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7	15.407(b)(1), 15.205, 15.209 47 CFR Part 15.407(b)(4), 15.205, 15.209 47 CFR Part 15.407(b)(10), 15.205, 15.209	
Undesirable emission limits (below 1GHz)	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.5	47 CFR Part 15.407(b)(9), 15.205, 15.209	Pass
Undesirable emission limits (above 1GHz)	47 CFR Part 15E	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1), 15.205, 15.209 47 CFR Part 15.407(b)(4), 15.205, 15.209 47 CFR Part 15.407(b)(10), 15.205, 15.209	Pass
Note: (1) "N/A" denotes test is not applicable in this Test Report.				

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15℃ to +35℃
Working Voltage of the EUT	NV (Normal Voltage)	120VAC, 60Hz for adapter

4.2 Test Equipment

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Test Software	Farad	EZ-EMC	EE-014	/	/
EMI Test Receiver	Rohde & Schwarz	ESCI	EE-005	2026-04-07	2027-04-06
L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	EE-004	2026-05-10	2027-05-09
8-Wire ISN CAT6	Schwarzbeck	NTFM 8158	EE-219	2026-05-18	2027-05-17

Maximum conducted output power Power spectral density Frequency stability Duty Cycle Emission bandwidth and occupied bandwidth					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-04-07	2027-04-06
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026-04-11	2027-04-10
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2026-02-13	2027-02-12
Power Meter	Anritsu	ML2495A	EE-416	2026-02-13	2027-02-12
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2026-07-14	2027-07-13
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	/	/
Band-Stop Filter	COM-MW	ZBSF8-L2400-2483.5-1016	EE-025	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	K6-5150-5850-250S5020-001	EE-026	2026-04-07	2027-04-06

Filter	COM-MW	ZHPF6-M3000-18000-174	EE-027	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M1300-18000-5356	EE-028	2026-04-07	2027-04-06
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-030	2026-04-07	2027-04-06

Band edge emissions (Radiated) Undesirable emission limits (above 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8449B	EE-010	2026-04-07	2027-04-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Band-Stop Filter	COM-MW	ZBSF8-L2400-2483.5-1016	EE-025	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	K6-5150-5850-250S5020-001	EE-026	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M3000-18000-174	EE-027	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M1300-18000-5356	EE-028	2026-04-07	2027-04-06
Spectrum Analyzer	ROHDE & SCHWARZ	FSV40-N	EE-029	2026-04-07	2027-04-06
40G Horn Antenna	HCT	HA-018040L	EE-031	2026-04-12	2027-04-11
40G Pre-amplifier	HCT	HC180400-50G25	EE-032	2026-04-07	2027-04-06

Undesirable emission limits (below 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8447D	EE-009	2026-04-08	2027-04-07

MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Loop Antenna	SCHWARZBECK	FMZB 1519-60	EE-022	2026-04-12	2027-04-11
Band-Stop Filter	COM-MW	ZBSF6-C902-928-2389	EE-023	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	ZBSF6-C855-880-5938	EE-024	2026-04-07	2027-04-06



4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Adapter	refer to clause 2.4	refer to clause 2.4	--
2	Pink Notebook	ADOL	ADOL13F	EMC-PJ-030

4.4 Test Mode

No.	Test Modes	Description
TM1	802.11a Mode	Keep the EUT in 802.11a transmitting mode.
TM2	802.11n(HT20) Mode	Keep the EUT in 802.11n(HT20) transmitting mode.
TM3	802.11n(HT40) Mode	Keep the EUT in 802.11n(HT40) transmitting mode.
TM4	802.11ac(VHT20) Mode	Keep the EUT in 802.11ac(VHT20) transmitting mode.
TM5	802.11ac(VHT40) Mode	Keep the EUT in 802.11ac(VHT40) transmitting mode.
TM6	802.11ax(HEW20) Mode	Keep the EUT in 802.11ax(HEW20) transmitting mode.
TM7	802.11ax(HEW40) Mode	Keep the EUT in 802.11ax(HEW40) transmitting mode.

4.5 Description of Calculation

4.5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Item	Measurement Uncertainty
Conducted Emission	2.65 dB
Time of Occupancy (Dwell Time)	1.8 %
Occupied Channel Bandwidth	69 kHz
RF output power, conducted	1.07 dB
Power Spectral Density, conducted	0.94 dB
Radiated Emission (1GHz- 18GHz)	Ur = 3.58 dB (Horizontal) Ur = 3.58 dB (Vertical)
Radiated Emission (9kHz- 30MHz)	Ur = 3.06 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.76 dB (Horizontal) Ur = 2.76 dB (Vertical)
Radiated Emission (18GHz- 40GHz)	Ur = 5.29 dB (Horizontal) Ur = 5.21 dB (Vertical)

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Condition

None

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

5.1.1 Test Specification

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.2 Test Data

PASS.


The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna-design is used.

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Conducted Emission at AC power line Test Data


TM1 / Line: Line / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1641	37.60	9.96	47.56	65.25	-17.69	QP	P	
2	0.1641	21.21	9.96	31.17	55.25	-24.08	AVG	P	
3	0.2455	32.37	9.97	42.34	61.91	-19.57	QP	P	
4	0.2455	12.17	9.97	22.14	51.91	-29.77	AVG	P	
5	0.5237	24.35	10.04	34.39	56.00	-21.61	QP	P	
6	0.5237	15.89	10.04	25.93	46.00	-20.07	AVG	P	
7	0.8174	14.72	10.04	24.76	56.00	-31.24	QP	P	
8	0.8174	-0.85	10.04	9.19	46.00	-36.81	AVG	P	
9	1.4796	10.18	10.03	20.21	56.00	-35.79	QP	P	
10	1.4796	-0.76	10.03	9.27	46.00	-36.73	AVG	P	
11	4.5015	10.02	10.04	20.06	56.00	-35.94	QP	P	
12	4.5015	-2.53	10.04	7.51	46.00	-38.49	AVG	P	

Conducted Emission at AC power line Test Data

TM1 / Line: Neutral / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1635	37.10	9.98	47.08	65.28	-18.20	QP	P	
2	0.1635	20.20	9.98	30.18	55.28	-25.10	AVG	P	
3	0.2805	28.73	10.01	38.74	60.80	-22.06	QP	P	
4	0.2805	7.78	10.01	17.79	50.80	-33.01	AVG	P	
5	0.5234	22.84	10.07	32.91	56.00	-23.09	QP	P	
6	0.5234	15.71	10.07	25.78	46.00	-20.22	AVG	P	
7	1.1310	12.79	10.06	22.85	56.00	-33.15	QP	P	
8	1.1310	2.72	10.06	12.78	46.00	-33.22	AVG	P	
9	2.0040	10.63	10.07	20.70	56.00	-35.30	QP	P	
10	2.0040	-1.91	10.07	8.16	46.00	-37.84	AVG	P	
11	4.8120	9.51	10.05	19.56	56.00	-36.44	QP	P	
12	4.8120	-2.27	10.05	7.78	46.00	-38.22	AVG	P	

6.2 Duty Cycle


6.2.1 Test Specification

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x , and maximum-power transmission duration, T , are required for each tested mode of operation.
Test Limit:	No limits, only for report use.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 12.2 (b)
Procedure:	i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW $\geq$ RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

6.2.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.2.3 Test Setup Diagram



6.2.4 Test Data

PASS.

Please refer to Annex D for details.

6.3 Emission bandwidth and occupied bandwidth

6.3.1 Test Specification


Test Requirement:	U-NII 1: No limits, only for report use. U-NII 3: 47 CFR Part 15.407(e)
Test Limit:	U-NII 1: No limits, only for report use. U-NII 3: Within the 5.725-5.850 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.9 & 12.5 KDB 789033 D02, Clause C.2
Procedure:	Emission bandwidth: a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth. b) Set the VBW > RBW. c) Detector = peak. d) Trace mode = max-hold. e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%. Occupied bandwidth: a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Step a) through step c) might require iteration to adjust within the specified range. e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies. h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

	6 dB emission bandwidth: a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
--	---

6.3.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.3.3 Test Setup Diagram



6.3.4 Test Data

PASS.

Please refer to Annex D for details.

6.4 Maximum conducted output power


6.4.1 Test Specification

Test Requirement:	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.4
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 12.4

6.4.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.4.3 Test Setup Diagram



6.4.4 Test Data

PASS.

Please refer to Annex D for details.

6.5 Power spectral density


6.5.1 Test Specification

Test Requirement:	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.6
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.6

6.5.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.5.3 Test Setup Diagram



6.5.4 Test Data

PASS.

Please refer to Annex D for details.

6.6 Frequency stability


6.6.1 Test Specification

Test Requirement:	47 CFR Part 15.407(g)
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 6.8
Procedure:	Refer to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.8

6.6.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.6.3 Test Setup Diagram



6.6.4 Test Data

PASS.

Please refer to Annex D for details.

6.7 Band edge emissions (Radiated)

6.7.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(1), 15.205, 15.209 47 CFR Part 15.407(b)(4), 15.205, 15.209 47 CFR Part 15.407(b)(10), 15.205, 15.209			
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.			
	For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.			
	MHz	MHz	MHz	GHz
	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
	6.31175-6.31225	123-138	2200-2300	14.47-14.5
	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
	12.57675-12.57725	322-335.4	3600-4400	(²)
	13.36-13.41			
	¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.			
² Above 38.6				
The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated				


	based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark:																								

	1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

6.7.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7

6.7.3 Test Setup Diagram



6.7.4 Test Data

PASS.

Please refer to the following pages.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11a					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.90	5.79	54.69	68.23	-13.55	PK	PASS
H	5350.00	45.42	6.45	51.87	68.23	-16.37	PK	PASS
V	5150.00	47.55	5.79	53.34	68.23	-14.90	PK	PASS
V	5350.00	44.66	6.45	51.11	68.23	-17.12	PK	PASS
H	5150.00	34.56	5.79	40.35	54.00	-13.66	AV	PASS
H	5350.00	32.26	6.45	38.71	54.00	-15.29	AV	PASS
V	5150.00	36.26	5.79	42.05	54.00	-11.95	AV	PASS
V	5350.00	31.83	6.45	38.28	54.00	-15.72	AV	PASS

Test Mode: 802.11a					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.08	5.79	53.87	68.23	-14.37	PK	PASS
H	5350.00	44.54	6.45	50.99	68.23	-17.24	PK	PASS
V	5150.00	49.66	5.79	55.45	68.23	-12.78	PK	PASS
V	5350.00	44.99	6.45	51.44	68.23	-16.79	PK	PASS
H	5150.00	36.97	5.79	42.76	54.00	-11.25	AV	PASS
H	5350.00	33.70	6.45	40.15	54.00	-13.85	AV	PASS
V	5150.00	36.97	5.79	42.76	54.00	-11.24	AV	PASS
V	5350.00	33.16	6.45	39.61	54.00	-14.39	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.29	5.79	53.08	68.23	-15.16	PK	PASS
H	5350.00	46.19	6.45	52.64	68.23	-15.60	PK	PASS
V	5150.00	48.36	5.79	54.15	68.23	-14.08	PK	PASS
V	5350.00	45.07	6.45	51.52	68.23	-16.72	PK	PASS
H	5150.00	35.98	5.79	41.77	54.00	-12.23	AV	PASS
H	5350.00	32.91	6.45	39.36	54.00	-14.65	AV	PASS
V	5150.00	34.21	5.79	40.00	54.00	-14.01	AV	PASS
V	5350.00	33.93	6.45	40.38	54.00	-13.62	AV	PASS

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.60	5.79	54.39	68.23	-13.84	PK	PASS
H	5350.00	44.45	6.45	50.90	68.23	-17.34	PK	PASS
V	5150.00	49.23	5.79	55.02	68.23	-13.22	PK	PASS
V	5350.00	45.97	6.45	52.42	68.23	-15.82	PK	PASS
H	5150.00	35.30	5.79	41.09	54.00	-12.91	AV	PASS
H	5350.00	31.93	6.45	38.38	54.00	-15.62	AV	PASS
V	5150.00	34.73	5.79	40.52	54.00	-13.49	AV	PASS
V	5350.00	31.14	6.45	37.59	54.00	-16.41	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11n(HT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.38	5.79	54.17	68.23	-14.06	PK	PASS
H	5350.00	44.62	6.45	51.07	68.23	-17.17	PK	PASS
V	5150.00	47.48	5.79	53.27	68.23	-14.97	PK	PASS
V	5350.00	44.56	6.45	51.01	68.23	-17.22	PK	PASS
H	5150.00	35.41	5.79	41.20	54.00	-12.81	AV	PASS
H	5350.00	33.99	6.45	40.44	54.00	-13.56	AV	PASS
V	5150.00	35.67	5.79	41.46	54.00	-12.54	AV	PASS
V	5350.00	32.12	6.45	38.57	54.00	-15.44	AV	PASS

Test Mode: 802.11n(HT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.55	5.79	55.34	68.23	-12.89	PK	PASS
H	5350.00	44.75	6.45	51.20	68.23	-17.03	PK	PASS
V	5150.00	47.34	5.79	53.13	68.23	-15.10	PK	PASS
V	5350.00	44.31	6.45	50.76	68.23	-17.48	PK	PASS
H	5150.00	35.55	5.79	41.34	54.00	-12.67	AV	PASS
H	5350.00	31.25	6.45	37.70	54.00	-16.31	AV	PASS
V	5150.00	34.93	5.79	40.72	54.00	-13.29	AV	PASS
V	5350.00	32.22	6.45	38.67	54.00	-15.33	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ac(VHT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.52	5.79	54.31	68.23	-13.92	PK	PASS
H	5350.00	46.74	6.45	53.19	68.23	-15.04	PK	PASS
V	5150.00	47.77	5.79	53.56	68.23	-14.68	PK	PASS
V	5350.00	45.01	6.45	51.46	68.23	-16.78	PK	PASS
H	5150.00	34.55	5.79	40.34	54.00	-13.67	AV	PASS
H	5350.00	31.47	6.45	37.92	54.00	-16.09	AV	PASS
V	5150.00	35.55	5.79	41.34	54.00	-12.67	AV	PASS
V	5350.00	33.62	6.45	40.07	54.00	-13.94	AV	PASS

Test Mode: 802.11ac(VHT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.40	5.79	55.19	68.23	-13.05	PK	PASS
H	5350.00	46.97	6.45	53.42	68.23	-14.81	PK	PASS
V	5150.00	47.71	5.79	53.50	68.23	-14.74	PK	PASS
V	5350.00	45.77	6.45	52.22	68.23	-16.02	PK	PASS
H	5150.00	36.53	5.79	42.32	54.00	-11.68	AV	PASS
H	5350.00	31.51	6.45	37.96	54.00	-16.04	AV	PASS
V	5150.00	34.20	5.79	39.99	54.00	-14.01	AV	PASS
V	5350.00	31.18	6.45	37.63	54.00	-16.38	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11 ac(VHT40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	48.87	5.79	54.66	68.23	-13.57	PK	PASS
H	5350.00	44.53	6.45	50.98	68.23	-17.26	PK	PASS
V	5150.00	47.43	5.79	53.22	68.23	-15.02	PK	PASS
V	5350.00	46.49	6.45	52.94	68.23	-15.29	PK	PASS
H	5150.00	35.94	5.79	41.73	54.00	-12.28	AV	PASS
H	5350.00	33.53	6.45	39.98	54.00	-14.03	AV	PASS
V	5150.00	34.88	5.79	40.67	54.00	-13.33	AV	PASS
V	5350.00	33.81	6.45	40.26	54.00	-13.74	AV	PASS

Test Mode: 802.11 ac(VHT40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.74	5.79	55.53	68.23	-12.70	PK	PASS
H	5350.00	44.30	6.45	50.75	68.23	-17.48	PK	PASS
V	5150.00	47.64	5.79	53.43	68.23	-14.80	PK	PASS
V	5350.00	45.03	6.45	51.48	68.23	-16.76	PK	PASS
H	5150.00	34.65	5.79	40.44	54.00	-13.57	AV	PASS
H	5350.00	32.78	6.45	39.23	54.00	-14.78	AV	PASS
V	5150.00	34.03	5.79	39.82	54.00	-14.18	AV	PASS
V	5350.00	31.65	6.45	38.10	54.00	-15.90	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.25	5.79	55.04	68.23	-13.19	PK	PASS
H	5350.00	45.69	6.45	52.14	68.23	-16.10	PK	PASS
V	5150.00	48.69	5.79	54.48	68.23	-13.75	PK	PASS
V	5350.00	44.14	6.45	50.59	68.23	-17.64	PK	PASS
H	5150.00	34.50	5.79	40.29	54.00	-13.71	AV	PASS
H	5350.00	31.85	6.45	38.30	54.00	-15.70	AV	PASS
V	5150.00	35.96	5.79	41.75	54.00	-12.26	AV	PASS
V	5350.00	32.71	6.45	39.16	54.00	-14.85	AV	PASS

Test Mode: 802.11ax(HEW20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.71	5.79	53.50	68.23	-14.74	PK	PASS
H	5350.00	44.91	6.45	51.36	68.23	-16.87	PK	PASS
V	5150.00	47.87	5.79	53.66	68.23	-14.58	PK	PASS
V	5350.00	45.70	6.45	52.15	68.23	-16.08	PK	PASS
H	5150.00	36.22	5.79	42.01	54.00	-11.99	AV	PASS
H	5350.00	31.04	6.45	37.49	54.00	-16.52	AV	PASS
V	5150.00	36.23	5.79	42.02	54.00	-11.99	AV	PASS
V	5350.00	33.62	6.45	40.07	54.00	-13.93	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-1:

Test Mode: 802.11ax(HEW40)					CH Low: 5190 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	47.67	5.79	53.46	68.23	-14.77	PK	PASS
H	5350.00	46.68	6.45	53.13	68.23	-15.11	PK	PASS
V	5150.00	49.65	5.79	55.44	68.23	-12.79	PK	PASS
V	5350.00	44.29	6.45	50.74	68.23	-17.50	PK	PASS
H	5150.00	35.14	5.79	40.93	54.00	-13.07	AV	PASS
H	5350.00	32.87	6.45	39.32	54.00	-14.69	AV	PASS
V	5150.00	34.82	5.79	40.61	54.00	-13.40	AV	PASS
V	5350.00	32.85	6.45	39.30	54.00	-14.70	AV	PASS

Test Mode: 802.11ax(HEW40)					CH High: 5230 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5150.00	49.21	5.79	55.00	68.23	-13.23	PK	PASS
H	5350.00	46.11	6.45	52.56	68.23	-15.67	PK	PASS
V	5150.00	48.33	5.79	54.12	68.23	-14.12	PK	PASS
V	5350.00	44.94	6.45	51.39	68.23	-16.84	PK	PASS
H	5150.00	36.65	5.79	42.44	54.00	-11.56	AV	PASS
H	5350.00	33.89	6.45	40.34	54.00	-13.67	AV	PASS
V	5150.00	35.51	5.79	41.30	54.00	-12.71	AV	PASS
V	5350.00	32.48	6.45	38.93	54.00	-15.07	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11a					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	43.57	7.55	51.12	68.23	-17.11	PK	PASS
H	5700.00	48.40	7.56	55.96	105.23	-49.28	PK	PASS
H	5720.00	47.97	7.59	55.56	110.83	-55.27	PK	PASS
H	5725.00	52.40	7.68	60.08	122.23	-62.15	PK	PASS
V	5650.00	44.29	7.55	51.84	68.23	-16.39	PK	PASS
V	5700.00	48.14	7.56	55.70	105.23	-49.53	PK	PASS
V	5720.00	49.54	7.59	57.13	110.83	-53.70	PK	PASS
V	5725.00	50.84	7.68	58.52	122.23	-63.72	PK	PASS
H	5650.00	30.93	7.55	38.48	54.00	-15.53	AV	PASS
H	5700.00	33.22	7.56	40.78	54.00	-13.23	AV	PASS
H	5720.00	35.54	7.59	43.13	54.00	-10.87	AV	PASS
H	5725.00	36.58	7.68	44.26	54.00	-9.75	AV	PASS
V	5650.00	28.15	7.55	35.70	54.00	-18.31	AV	PASS
V	5700.00	33.59	7.56	41.15	54.00	-12.85	AV	PASS
V	5720.00	32.65	7.59	40.24	54.00	-13.77	AV	PASS
V	5725.00	36.30	7.68	43.98	54.00	-10.02	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11a					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	52.39	7.55	59.94	122.23	-62.29	PK	PASS
H	5855.00	49.55	7.56	57.11	110.83	-53.73	PK	PASS
H	5875.00	46.55	7.59	54.14	105.23	-51.10	PK	PASS
H	5925.00	46.48	7.68	54.16	68.23	-14.08	PK	PASS
V	5850.00	49.98	7.55	57.53	122.23	-64.71	PK	PASS
V	5855.00	48.84	7.56	56.40	110.83	-54.44	PK	PASS
V	5875.00	45.31	7.59	52.90	105.23	-52.34	PK	PASS
V	5925.00	44.04	7.68	51.72	68.23	-16.52	PK	PASS
H	5850.00	35.39	7.55	42.94	54.00	-11.07	AV	PASS
H	5855.00	33.67	7.56	41.23	54.00	-12.77	AV	PASS
H	5875.00	33.49	7.59	41.08	54.00	-12.92	AV	PASS
H	5925.00	30.23	7.68	37.91	54.00	-16.09	AV	PASS
V	5850.00	36.68	7.55	44.23	54.00	-9.78	AV	PASS
V	5855.00	35.56	7.56	43.12	54.00	-10.88	AV	PASS
V	5875.00	30.81	7.59	38.40	54.00	-15.61	AV	PASS
V	5925.00	29.19	7.68	36.87	54.00	-17.14	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	46.85	7.55	54.40	68.23	-13.84	PK	PASS
H	5700.00	46.87	7.56	54.43	105.23	-50.81	PK	PASS
H	5720.00	48.68	7.59	56.27	110.83	-54.56	PK	PASS
H	5725.00	51.60	7.68	59.28	122.23	-62.96	PK	PASS
V	5650.00	46.52	7.55	54.07	68.23	-14.17	PK	PASS
V	5700.00	46.21	7.56	53.77	105.23	-51.47	PK	PASS
V	5720.00	48.53	7.59	56.12	110.83	-54.71	PK	PASS
V	5725.00	52.73	7.68	60.41	122.23	-61.83	PK	PASS
H	5650.00	30.27	7.55	37.82	54.00	-16.19	AV	PASS
H	5700.00	33.04	7.56	40.60	54.00	-13.40	AV	PASS
H	5720.00	35.35	7.59	42.94	54.00	-11.06	AV	PASS
H	5725.00	35.65	7.68	43.33	54.00	-10.67	AV	PASS
V	5650.00	30.47	7.55	38.02	54.00	-15.99	AV	PASS
V	5700.00	32.12	7.56	39.68	54.00	-14.32	AV	PASS
V	5720.00	33.49	7.59	41.08	54.00	-12.93	AV	PASS
V	5725.00	36.74	7.68	44.42	54.00	-9.58	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	52.69	7.55	60.24	122.23	-61.99	PK	PASS
H	5855.00	48.70	7.56	56.26	110.83	-54.57	PK	PASS
H	5875.00	46.30	7.59	53.89	105.23	-51.35	PK	PASS
H	5925.00	46.83	7.68	54.51	68.23	-13.72	PK	PASS
V	5850.00	52.59	7.55	60.14	122.23	-62.10	PK	PASS
V	5855.00	49.18	7.56	56.74	110.83	-54.09	PK	PASS
V	5875.00	46.53	7.59	54.12	105.23	-51.12	PK	PASS
V	5925.00	45.23	7.68	52.91	68.23	-15.32	PK	PASS
H	5850.00	34.52	7.55	42.07	54.00	-11.94	AV	PASS
H	5855.00	32.08	7.56	39.64	54.00	-14.36	AV	PASS
H	5875.00	30.41	7.59	38.00	54.00	-16.01	AV	PASS
H	5925.00	30.80	7.68	38.48	54.00	-15.53	AV	PASS
V	5850.00	37.37	7.55	44.92	54.00	-9.09	AV	PASS
V	5855.00	33.03	7.56	40.59	54.00	-13.41	AV	PASS
V	5875.00	32.58	7.59	40.17	54.00	-13.84	AV	PASS
V	5925.00	31.98	7.68	39.66	54.00	-14.34	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	45.21	7.55	52.76	68.23	-15.48	PK	PASS
H	5700.00	46.60	7.56	54.16	105.23	-51.08	PK	PASS
H	5720.00	49.10	7.59	56.69	110.83	-54.15	PK	PASS
H	5725.00	51.18	7.68	58.86	122.23	-63.37	PK	PASS
V	5650.00	44.47	7.55	52.02	68.23	-16.22	PK	PASS
V	5700.00	48.81	7.56	56.37	105.23	-48.86	PK	PASS
V	5720.00	47.66	7.59	55.25	110.83	-55.59	PK	PASS
V	5725.00	50.83	7.68	58.51	122.23	-63.72	PK	PASS
H	5650.00	28.31	7.55	35.86	54.00	-18.15	AV	PASS
H	5700.00	33.73	7.56	41.29	54.00	-12.71	AV	PASS
H	5720.00	32.90	7.59	40.49	54.00	-13.51	AV	PASS
H	5725.00	37.70	7.68	45.38	54.00	-8.62	AV	PASS
V	5650.00	31.14	7.55	38.69	54.00	-15.31	AV	PASS
V	5700.00	30.52	7.56	38.08	54.00	-15.92	AV	PASS
V	5720.00	32.31	7.59	39.90	54.00	-14.10	AV	PASS
V	5725.00	37.01	7.68	44.69	54.00	-9.31	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11n(HT40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	51.27	7.55	58.82	122.23	-63.41	PK	PASS
H	5855.00	48.65	7.56	56.21	110.83	-54.62	PK	PASS
H	5875.00	46.61	7.59	54.20	105.23	-51.03	PK	PASS
H	5925.00	43.49	7.68	51.17	68.23	-17.07	PK	PASS
V	5850.00	50.27	7.55	57.82	122.23	-64.42	PK	PASS
V	5855.00	49.07	7.56	56.63	110.83	-54.21	PK	PASS
V	5875.00	45.06	7.59	52.65	105.23	-52.58	PK	PASS
V	5925.00	45.06	7.68	52.74	68.23	-15.50	PK	PASS
H	5850.00	35.86	7.55	43.41	54.00	-10.60	AV	PASS
H	5855.00	35.16	7.56	42.72	54.00	-11.28	AV	PASS
H	5875.00	33.26	7.59	40.85	54.00	-13.16	AV	PASS
H	5925.00	30.61	7.68	38.29	54.00	-15.71	AV	PASS
V	5850.00	37.07	7.55	44.62	54.00	-9.38	AV	PASS
V	5855.00	34.70	7.56	42.26	54.00	-11.75	AV	PASS
V	5875.00	33.10	7.59	40.69	54.00	-13.31	AV	PASS
V	5925.00	28.11	7.68	35.79	54.00	-18.21	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	46.11	7.55	53.66	68.23	-14.58	PK	PASS
H	5700.00	47.89	7.56	55.45	105.23	-49.78	PK	PASS
H	5720.00	50.06	7.59	57.65	110.83	-53.19	PK	PASS
H	5725.00	52.72	7.68	60.40	122.23	-61.84	PK	PASS
V	5650.00	43.32	7.55	50.87	68.23	-17.36	PK	PASS
V	5700.00	47.89	7.56	55.45	105.23	-49.78	PK	PASS
V	5720.00	47.09	7.59	54.68	110.83	-56.15	PK	PASS
V	5725.00	50.08	7.68	57.76	122.23	-64.48	PK	PASS
H	5650.00	30.42	7.55	37.97	54.00	-16.03	AV	PASS
H	5700.00	32.66	7.56	40.22	54.00	-13.78	AV	PASS
H	5720.00	33.27	7.59	40.86	54.00	-13.15	AV	PASS
H	5725.00	34.62	7.68	42.30	54.00	-11.70	AV	PASS
V	5650.00	29.90	7.55	37.45	54.00	-16.56	AV	PASS
V	5700.00	32.28	7.56	39.84	54.00	-14.16	AV	PASS
V	5720.00	33.71	7.59	41.30	54.00	-12.71	AV	PASS
V	5725.00	34.94	7.68	42.62	54.00	-11.38	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	50.75	7.55	58.30	122.23	-63.94	PK	PASS
H	5855.00	50.86	7.56	58.42	110.83	-52.42	PK	PASS
H	5875.00	47.40	7.59	54.99	105.23	-50.25	PK	PASS
H	5925.00	44.01	7.68	51.69	68.23	-16.54	PK	PASS
V	5850.00	51.79	7.55	59.34	122.23	-62.90	PK	PASS
V	5855.00	48.33	7.56	55.89	110.83	-54.94	PK	PASS
V	5875.00	45.33	7.59	52.92	105.23	-52.31	PK	PASS
V	5925.00	45.37	7.68	53.05	68.23	-15.18	PK	PASS
H	5850.00	36.72	7.55	44.27	54.00	-9.74	AV	PASS
H	5855.00	32.79	7.56	40.35	54.00	-13.66	AV	PASS
H	5875.00	32.08	7.59	39.67	54.00	-14.34	AV	PASS
H	5925.00	31.82	7.68	39.50	54.00	-14.51	AV	PASS
V	5850.00	35.21	7.55	42.76	54.00	-11.25	AV	PASS
V	5855.00	33.57	7.56	41.13	54.00	-12.88	AV	PASS
V	5875.00	30.16	7.59	37.75	54.00	-16.25	AV	PASS
V	5925.00	28.03	7.68	35.71	54.00	-18.30	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	44.08	7.55	51.63	68.23	-16.61	PK	PASS
H	5700.00	47.14	7.56	54.70	105.23	-50.53	PK	PASS
H	5720.00	48.86	7.59	56.45	110.83	-54.39	PK	PASS
H	5725.00	49.54	7.68	57.22	122.23	-65.01	PK	PASS
V	5650.00	45.17	7.55	52.72	68.23	-15.52	PK	PASS
V	5700.00	45.59	7.56	53.15	105.23	-52.08	PK	PASS
V	5720.00	48.83	7.59	56.42	110.83	-54.41	PK	PASS
V	5725.00	51.59	7.68	59.27	122.23	-62.96	PK	PASS
H	5650.00	30.38	7.55	37.93	54.00	-16.07	AV	PASS
H	5700.00	33.77	7.56	41.33	54.00	-12.67	AV	PASS
H	5720.00	32.43	7.59	40.02	54.00	-13.98	AV	PASS
H	5725.00	36.43	7.68	44.11	54.00	-9.90	AV	PASS
V	5650.00	31.82	7.55	39.37	54.00	-14.64	AV	PASS
V	5700.00	30.03	7.56	37.59	54.00	-16.42	AV	PASS
V	5720.00	35.82	7.59	43.41	54.00	-10.60	AV	PASS
V	5725.00	37.44	7.68	45.12	54.00	-8.89	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ac(VHT40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	50.71	7.55	58.26	122.23	-63.97	PK	PASS
H	5855.00	49.71	7.56	57.27	110.83	-53.57	PK	PASS
H	5875.00	48.43	7.59	56.02	105.23	-49.21	PK	PASS
H	5925.00	43.11	7.68	50.79	68.23	-17.44	PK	PASS
V	5850.00	49.14	7.55	56.69	122.23	-65.54	PK	PASS
V	5855.00	47.09	7.56	54.65	110.83	-56.19	PK	PASS
V	5875.00	46.37	7.59	53.96	105.23	-51.27	PK	PASS
V	5925.00	43.16	7.68	50.84	68.23	-17.39	PK	PASS
H	5850.00	35.34	7.55	42.89	54.00	-11.11	AV	PASS
H	5855.00	34.82	7.56	42.38	54.00	-11.62	AV	PASS
H	5875.00	30.41	7.59	38.00	54.00	-16.00	AV	PASS
H	5925.00	28.26	7.68	35.94	54.00	-18.07	AV	PASS
V	5850.00	36.39	7.55	43.94	54.00	-10.07	AV	PASS
V	5855.00	35.75	7.56	43.31	54.00	-10.69	AV	PASS
V	5875.00	33.66	7.59	41.25	54.00	-12.75	AV	PASS
V	5925.00	31.56	7.68	39.24	54.00	-14.76	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	43.21	7.55	50.76	68.23	-17.48	PK	PASS
H	5700.00	47.35	7.56	54.91	105.23	-50.32	PK	PASS
H	5720.00	47.83	7.59	55.42	110.83	-55.41	PK	PASS
H	5725.00	50.15	7.68	57.83	122.23	-64.41	PK	PASS
V	5650.00	45.45	7.55	53.00	68.23	-15.24	PK	PASS
V	5700.00	47.32	7.56	54.88	105.23	-50.36	PK	PASS
V	5720.00	47.67	7.59	55.26	110.83	-55.58	PK	PASS
V	5725.00	49.98	7.68	57.66	122.23	-64.57	PK	PASS
H	5650.00	30.66	7.55	38.21	54.00	-15.79	AV	PASS
H	5700.00	32.82	7.56	40.38	54.00	-13.62	AV	PASS
H	5720.00	32.78	7.59	40.37	54.00	-13.63	AV	PASS
H	5725.00	36.61	7.68	44.29	54.00	-9.72	AV	PASS
V	5650.00	30.02	7.55	37.57	54.00	-16.43	AV	PASS
V	5700.00	31.81	7.56	39.37	54.00	-14.63	AV	PASS
V	5720.00	32.91	7.59	40.50	54.00	-13.51	AV	PASS
V	5725.00	37.53	7.68	45.21	54.00	-8.79	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW20)					CH High: 5825 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	50.54	7.55	58.09	122.23	-64.14	PK	PASS
H	5855.00	48.24	7.56	55.80	110.83	-55.03	PK	PASS
H	5875.00	46.92	7.59	54.51	105.23	-50.72	PK	PASS
H	5925.00	43.19	7.68	50.87	68.23	-17.36	PK	PASS
V	5850.00	49.21	7.55	56.76	122.23	-65.47	PK	PASS
V	5855.00	48.96	7.56	56.52	110.83	-54.32	PK	PASS
V	5875.00	48.36	7.59	55.95	105.23	-49.28	PK	PASS
V	5925.00	45.36	7.68	53.04	68.23	-15.20	PK	PASS
H	5850.00	37.28	7.55	44.83	54.00	-9.17	AV	PASS
H	5855.00	34.69	7.56	42.25	54.00	-11.75	AV	PASS
H	5875.00	30.46	7.59	38.05	54.00	-15.96	AV	PASS
H	5925.00	29.09	7.68	36.77	54.00	-17.24	AV	PASS
V	5850.00	36.58	7.55	44.13	54.00	-9.87	AV	PASS
V	5855.00	34.14	7.56	41.70	54.00	-12.30	AV	PASS
V	5875.00	31.51	7.59	39.10	54.00	-14.90	AV	PASS
V	5925.00	28.98	7.68	36.66	54.00	-17.35	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW40)					CH Low: 5755 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5650.00	46.00	7.55	53.55	68.23	-14.69	PK	PASS
H	5700.00	47.49	7.56	55.05	105.23	-50.18	PK	PASS
H	5720.00	50.06	7.59	57.65	110.83	-53.19	PK	PASS
H	5725.00	50.80	7.68	58.48	122.23	-63.76	PK	PASS
V	5650.00	44.96	7.55	52.51	68.23	-15.72	PK	PASS
V	5700.00	48.51	7.56	56.07	105.23	-49.16	PK	PASS
V	5720.00	48.76	7.59	56.35	110.83	-54.49	PK	PASS
V	5725.00	49.37	7.68	57.05	122.23	-65.18	PK	PASS
H	5650.00	31.76	7.55	39.31	54.00	-14.70	AV	PASS
H	5700.00	30.70	7.56	38.26	54.00	-15.74	AV	PASS
H	5720.00	32.47	7.59	40.06	54.00	-13.95	AV	PASS
H	5725.00	37.55	7.68	45.23	54.00	-8.77	AV	PASS
V	5650.00	29.64	7.55	37.19	54.00	-16.82	AV	PASS
V	5700.00	33.07	7.56	40.63	54.00	-13.37	AV	PASS
V	5720.00	35.05	7.59	42.64	54.00	-11.37	AV	PASS
V	5725.00	35.31	7.68	42.99	54.00	-11.02	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions Test Data:
U-NII-3:

Test Mode: 802.11ax(HEW40)					CH High: 5795 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	5850.00	51.91	7.55	59.46	122.23	-62.77	PK	PASS
H	5855.00	50.07	7.56	57.63	110.83	-53.21	PK	PASS
H	5875.00	46.31	7.59	53.90	105.23	-51.33	PK	PASS
H	5925.00	43.46	7.68	51.14	68.23	-17.10	PK	PASS
V	5850.00	52.85	7.55	60.40	122.23	-61.84	PK	PASS
V	5855.00	50.47	7.56	58.03	110.83	-52.81	PK	PASS
V	5875.00	45.89	7.59	53.48	105.23	-51.76	PK	PASS
V	5925.00	43.66	7.68	51.34	68.23	-16.90	PK	PASS
H	5850.00	36.18	7.55	43.73	54.00	-10.28	AV	PASS
H	5855.00	32.05	7.56	39.61	54.00	-14.40	AV	PASS
H	5875.00	30.60	7.59	38.19	54.00	-15.82	AV	PASS
H	5925.00	30.21	7.68	37.89	54.00	-16.12	AV	PASS
V	5850.00	36.19	7.55	43.74	54.00	-10.27	AV	PASS
V	5855.00	34.78	7.56	42.34	54.00	-11.66	AV	PASS
V	5875.00	31.53	7.59	39.12	54.00	-14.88	AV	PASS
V	5925.00	28.04	7.68	35.72	54.00	-18.28	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

6.8 Undesirable emission limits (below 1GHz)

6.8.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(9), 15.205, 15.209		
Test Limit:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.		
	Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:		
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.5		
Procedure:	Below 1GHz: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel.		

	h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

6.8.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
----------------	-----------------------------------

Final test mode:	TM1
------------------	-----

6.8.3 Test Setup Diagram




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz


6.8.4 Test Data

PASS.

Only the worst case data was showed in the report, please to see the following pages.

Undesirable emission limits (below 1GHz) Test Data


TM1 / Polarization: Horizontal / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	97.4560	48.89	-20.17	28.72	43.50	-14.78	QP	P	
2	121.9755	51.06	-20.14	30.92	43.50	-12.58	QP	P	
3	145.8611	52.47	-21.68	30.79	43.50	-12.71	QP	P	
4	256.5211	54.96	-17.63	37.33	46.00	-8.67	QP	P	
5 *	827.4934	47.71	-7.22	40.49	46.00	-5.51	QP	P	
6	900.1474	44.83	-5.89	38.94	46.00	-7.06	QP	P	

Undesirable emission limits (below 1GHz) Test Data

TM1 / Polarization: Vertical / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	53.6932	42.93	-18.92	24.01	40.00	-15.99	QP	P	
2 *	121.9755	56.02	-20.14	35.88	43.50	-7.62	QP	P	
3	139.3613	48.87	-21.26	27.61	43.50	-15.89	QP	P	
4	528.2458	41.55	-11.01	30.54	46.00	-15.46	QP	P	
5	900.1474	38.59	-5.89	32.70	46.00	-13.30	QP	P	
6	952.0937	34.04	-5.30	28.74	46.00	-17.26	QP	P	

6.9 Undesirable emission limits (above 1GHz)

6.9.1 Test Specification

Test Requirement:	47 CFR Part 15.407(b)(1), 15.205, 15.209 47 CFR Part 15.407(b)(4), 15.205, 15.209 47 CFR Part 15.407(b)(10), 15.205, 15.209			
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.			
	For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.			
	MHz	MHz	MHz	GHz
	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
	6.31175-6.31225	123-138	2200-2300	14.47-14.5
	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
	12.57675-12.57725	322-335.4	3600-4400	(²)
	13.36-13.41			
¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.				
² Above 38.6				
The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated				


	based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 12.7.4, 12.7.6, 12.7.7																								
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark:																								

	1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

6.9.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6, TM7
Final test mode:	TM2

6.9.3 Test Setup Diagram



6.9.4 Test Data

PASS.

Please to see the following pages.

For test of 1GHz-40GHz, during the test, pre-scan all modes, and found the U-NII-1 / 802.11n(HT20) & U-NII-3 / 802.11n(HT20) is worse case, the report only record this mode.

The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Undesirable emission limits (above 1GHz) Test Data
Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5180 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3218.94	45.58	0.07	45.64	68.23	-22.59	PK	PASS
V	7510.14	41.20	9.84	51.04	68.23	-17.19	PK	PASS
V	9507.64	36.96	13.17	50.13	68.23	-18.10	PK	PASS
V	10361.00	42.53	13.79	56.32	68.23	-11.91	PK	PASS
V	14019.76	35.17	17.35	52.53	68.23	-15.70	PK	PASS
V	15541.75	*	*	*	68.23	*	PK	PASS
H	3201.25	47.02	-0.87	46.16	68.23	-22.07	PK	PASS
H	7502.25	40.87	9.83	50.70	68.23	-17.53	PK	PASS
H	9500.25	37.52	13.14	50.66	68.23	-17.57	PK	PASS
H	10360.50	42.42	13.79	56.21	68.23	-12.02	PK	PASS
H	14003.99	37.99	17.34	55.33	68.23	-12.90	PK	PASS
H	15542.25	*	*	*	68.23	*	PK	PASS
V	3218.94	33.91	0.07	33.98	54.00	-20.02	AV	PASS
V	7510.14	28.30	9.84	38.14	54.00	-15.86	AV	PASS
V	9507.64	24.78	13.17	37.95	54.00	-16.05	AV	PASS
V	10361.00	30.91	13.79	44.70	54.00	-9.30	AV	PASS
V	14019.76	24.06	17.35	41.41	54.00	-12.59	AV	PASS
V	15541.75	*	*	*	54.00	*	AV	PASS
H	3201.25	34.34	-0.87	33.47	54.00	-20.53	AV	PASS
H	7502.25	30.96	9.83	40.79	54.00	-13.21	AV	PASS
H	9500.25	22.16	13.14	35.30	54.00	-18.70	AV	PASS
H	10360.50	31.85	13.79	45.64	54.00	-8.37	AV	PASS
H	14003.99	24.72	17.34	42.06	54.00	-11.94	AV	PASS
H	15542.25	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5200 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3402.09	45.53	-0.13	45.40	68.23	-22.83	PK	PASS
V	8003.64	40.26	10.33	50.59	68.23	-17.64	PK	PASS
V	9712.39	37.57	13.20	50.77	68.23	-17.46	PK	PASS
V	10400.00	44.74	13.91	58.65	68.23	-9.58	PK	PASS
V	14316.44	37.44	17.46	54.89	68.23	-13.34	PK	PASS
V	15601.50	*	*	*	68.23	*	PK	PASS
H	3405.68	46.80	-0.12	46.68	68.23	-21.55	PK	PASS
H	8010.76	41.31	10.35	51.65	68.23	-16.58	PK	PASS
H	9705.78	35.96	13.20	49.16	68.23	-19.07	PK	PASS
H	10402.25	44.74	13.91	58.65	68.23	-9.58	PK	PASS
H	14309.02	36.46	17.44	53.90	68.23	-14.33	PK	PASS
H	15600.00	*	*	*	68.23	*	PK	PASS
V	3402.09	34.57	-0.13	34.44	54.00	-19.56	AV	PASS
V	8003.64	29.55	10.33	39.88	54.00	-14.12	AV	PASS
V	9712.39	22.70	13.20	35.90	54.00	-18.10	AV	PASS
V	10400.00	31.94	13.91	45.85	54.00	-8.15	AV	PASS
V	14316.44	24.17	17.46	41.62	54.00	-12.38	AV	PASS
V	15601.50	*	*	*	54.00	*	AV	PASS
H	3405.68	32.18	-0.12	32.06	54.00	-21.94	AV	PASS
H	8010.76	28.78	10.35	39.13	54.00	-14.87	AV	PASS
H	9705.78	24.48	13.20	37.68	54.00	-16.32	AV	PASS
H	10402.25	30.03	13.91	43.94	54.00	-10.06	AV	PASS
H	14309.02	23.84	17.44	41.28	54.00	-12.72	AV	PASS
H	15600.00	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5240 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3702.66	45.03	1.09	46.12	68.23	-22.11	PK	PASS
V	8202.19	40.40	10.86	51.26	68.23	-16.97	PK	PASS
V	9804.57	36.67	13.23	49.90	68.23	-18.33	PK	PASS
V	10481.00	43.48	13.96	57.44	68.23	-10.79	PK	PASS
V	14708.72	35.93	17.58	53.51	68.23	-14.72	PK	PASS
V	15720.50	*	*	*	68.23	*	PK	PASS
H	3700.47	46.30	1.09	47.39	68.23	-20.84	PK	PASS
H	8215.52	41.24	10.89	52.13	68.23	-16.10	PK	PASS
H	9813.28	35.12	13.23	48.35	68.23	-19.88	PK	PASS
H	10481.50	44.38	13.96	58.34	68.23	-9.89	PK	PASS
H	14703.00	37.83	17.57	55.40	68.23	-12.83	PK	PASS
H	15721.25	*	*	*	68.23	*	PK	PASS
V	3702.66	32.16	1.09	33.25	54.00	-20.75	AV	PASS
V	8202.19	30.05	10.86	40.91	54.00	-13.09	AV	PASS
V	9804.57	23.68	13.23	36.91	54.00	-17.09	AV	PASS
V	10481.00	32.26	13.96	46.22	54.00	-7.78	AV	PASS
V	14708.72	24.70	17.58	42.28	54.00	-11.72	AV	PASS
V	15720.50	*	*	*	54.00	*	AV	PASS
H	3700.47	34.07	1.09	35.16	54.00	-18.84	AV	PASS
H	8215.52	29.33	10.89	40.22	54.00	-13.78	AV	PASS
H	9813.28	23.57	13.23	36.81	54.00	-17.19	AV	PASS
H	10481.50	30.09	13.96	44.05	54.00	-9.95	AV	PASS
H	14703.00	22.67	17.57	40.23	54.00	-13.77	AV	PASS
H	15721.25	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Low: 5745 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3212.20	47.48	-0.83	46.65	68.23	-21.58	PK	PASS
V	7514.20	41.18	9.84	51.02	68.23	-17.21	PK	PASS
V	9506.16	35.64	13.16	48.80	68.23	-19.43	PK	PASS
V	11491.00	42.53	15.22	57.75	68.23	-10.48	PK	PASS
V	14013.73	35.51	17.35	52.86	68.23	-15.37	PK	PASS
V	17237.50	*	*	*	68.23	*	PK	PASS
H	3202.00	45.50	-0.86	44.64	68.23	-23.59	PK	PASS
H	7502.25	41.15	9.83	50.98	68.23	-17.25	PK	PASS
H	9502.25	35.50	13.15	48.65	68.23	-19.58	PK	PASS
H	11491.25	44.68	15.22	59.90	68.23	-8.33	PK	PASS
H	14006.60	37.17	17.34	54.51	68.23	-13.72	PK	PASS
H	17235.25	*	*	*	68.23	*	PK	PASS
V	3212.20	33.56	-0.83	32.73	54.00	-21.27	AV	PASS
V	7514.20	29.45	9.84	39.30	54.00	-14.70	AV	PASS
V	9506.16	22.81	13.16	35.97	54.00	-18.03	AV	PASS
V	11491.00	32.33	15.22	47.55	54.00	-6.45	AV	PASS
V	14013.73	23.57	17.35	40.92	54.00	-13.08	AV	PASS
V	17237.50	*	*	*	54.00	*	AV	PASS
H	3202.00	32.64	-0.86	31.77	54.00	-22.23	AV	PASS
H	7502.25	30.38	9.83	40.22	54.00	-13.78	AV	PASS
H	9502.25	22.86	13.15	36.00	54.00	-18.00	AV	PASS
H	11491.25	31.20	15.22	46.42	54.00	-7.59	AV	PASS
H	14006.60	24.61	17.34	41.95	54.00	-12.05	AV	PASS
H	17235.25	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH Middle: 5785 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3419.97	47.10	-0.06	47.04	68.23	-21.19	PK	PASS
V	8001.30	41.52	10.32	51.84	68.23	-16.39	PK	PASS
V	9700.70	36.74	13.20	49.94	68.23	-18.29	PK	PASS
V	11570.00	43.90	15.31	59.21	68.23	-9.02	PK	PASS
V	14303.70	37.90	17.44	55.34	68.23	-12.89	PK	PASS
V	17357.00	*	*	*	68.23	*	PK	PASS
H	3419.66	47.54	-0.06	47.48	68.23	-20.75	PK	PASS
H	8014.84	42.74	10.36	53.10	68.23	-15.13	PK	PASS
H	9718.46	36.18	13.21	49.39	68.23	-18.84	PK	PASS
H	11571.25	44.68	15.31	59.99	68.23	-8.24	PK	PASS
H	14315.63	36.32	17.45	53.77	68.23	-14.46	PK	PASS
H	17356.25	*	*	*	68.23	*	PK	PASS
V	3419.97	32.99	-0.06	32.93	54.00	-21.07	AV	PASS
V	8001.30	29.15	10.32	39.47	54.00	-14.53	AV	PASS
V	9700.70	23.59	13.20	36.79	54.00	-17.21	AV	PASS
V	11570.00	32.76	15.31	48.07	54.00	-5.93	AV	PASS
V	14303.70	24.95	17.44	42.39	54.00	-11.61	AV	PASS
V	17357.00	*	*	*	54.00	*	AV	PASS
H	3419.66	34.43	-0.06	34.37	54.00	-19.63	AV	PASS
H	8014.84	29.93	10.36	40.29	54.00	-13.71	AV	PASS
H	9718.46	23.06	13.21	36.27	54.00	-17.73	AV	PASS
H	11571.25	31.36	15.31	46.67	54.00	-7.33	AV	PASS
H	14315.63	23.98	17.45	41.44	54.00	-12.56	AV	PASS
H	17356.25	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-40GHz)

Test Mode: 802.11n(HT20)					CH High: 5825MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	3719.34	47.46	1.11	48.57	68.23	-19.66	PK	PASS
V	8214.24	42.65	10.89	53.54	68.23	-14.69	PK	PASS
V	9817.45	36.76	13.24	50.00	68.23	-18.23	PK	PASS
V	11650.00	42.74	15.39	58.13	68.23	-10.10	PK	PASS
V	14711.09	35.86	17.58	53.43	68.23	-14.80	PK	PASS
V	17475.00	*	*	*	68.23	*	PK	PASS
H	3711.38	47.04	1.10	48.14	68.23	-20.09	PK	PASS
H	8218.73	41.24	10.90	52.14	68.23	-16.09	PK	PASS
H	9817.84	37.18	13.24	50.42	68.23	-17.81	PK	PASS
H	11650.50	43.53	15.39	58.92	68.23	-9.31	PK	PASS
H	14707.44	35.39	17.57	52.96	68.23	-15.27	PK	PASS
H	17476.75	*	*	*	68.23	*	PK	PASS
V	3719.34	34.00	1.11	35.11	54.00	-18.89	AV	PASS
V	8214.24	28.52	10.89	39.41	54.00	-14.59	AV	PASS
V	9817.45	22.61	13.24	35.84	54.00	-18.16	AV	PASS
V	11650.00	31.41	15.39	46.80	54.00	-7.20	AV	PASS
V	14711.09	23.76	17.58	41.34	54.00	-12.66	AV	PASS
V	17475.00	*	*	*	54.00	*	AV	PASS
H	3711.38	32.62	1.10	33.72	54.00	-20.28	AV	PASS
H	8218.73	29.64	10.90	40.54	54.00	-13.46	AV	PASS
H	9817.84	24.67	13.24	37.91	54.00	-16.09	AV	PASS
H	11650.50	31.82	15.39	47.21	54.00	-6.79	AV	PASS
H	14707.44	24.12	17.57	41.70	54.00	-12.30	AV	PASS
H	17476.75	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8433EU013106W1-ANNEX A.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8433EU013106W1-ANNEX B.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8433EU013106W1-ANNEX C.PDF"



ANNEX D TEST DATA

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1									
Mode	Tx Type	Frequency (MHz)	RU	RU Pos	T _{on} (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	/	/	2.033	12.050	16.87	7.73	0.03
		5200	/	/	2.033	12.057	16.86	7.73	0.03
		5240	/	/	2.030	12.046	16.85	7.73	0.03
		5745	/	/	2.034	12.097	16.81	7.74	0.08
		5785	/	/	2.033	12.076	16.84	7.74	0.06
		5825	/	/	2.033	12.057	16.86	7.73	0.01
802.11n (HT20)	SISO	5180	/	/	1.894	11.914	15.90	7.99	0.03
		5200	/	/	1.894	11.917	15.89	7.99	0.00
		5240	/	/	1.893	11.913	15.89	7.99	0.03
		5745	/	/	1.894	11.914	15.90	7.99	0.03
		5785	/	/	1.893	11.913	15.89	7.99	0.00
		5825	/	/	1.894	12.024	15.75	8.03	0.17
802.11n (HT40)	SISO	5190	/	/	0.934	10.954	8.53	10.69	0.00
		5230	/	/	0.933	10.950	8.52	10.70	0.00
		5755	/	/	0.934	11.130	8.39	10.76	0.16
		5795	/	/	0.934	11.144	8.38	10.77	0.15
802.11ac (VHT20)	SISO	5180	/	/	1.900	11.920	15.94	7.98	0.03
		5200	/	/	1.900	11.923	15.94	7.98	0.03
		5240	/	/	1.900	11.917	15.94	7.97	0.03
		5745	/	/	1.900	11.923	15.94	7.98	0.03
		5785	/	/	1.900	11.924	15.93	7.98	0.04
		5825	/	/	1.900	11.920	15.94	7.98	0.03
802.11ac (VHT40)	SISO	5190	/	/	0.937	10.957	8.55	10.68	0.03
		5230	/	/	0.937	10.953	8.55	10.68	0.03
		5755	/	/	0.937	11.047	8.48	10.72	0.10
		5795	/	/	0.940	11.026	8.53	10.69	0.03
802.11ax (HEW20)	SISO	5180	SU	/	1.460	11.483	12.71	8.96	0.03
		5200	SU	/	1.460	11.483	12.71	8.96	0.03
		5240	SU	/	1.464	11.594	12.63	8.99	0.12
		5745	SU	/	1.463	11.483	12.74	8.95	0.01
		5785	SU	/	1.464	11.487	12.74	8.95	0.03
		5825	SU	/	1.460	11.476	12.72	8.95	0.03
802.11ax (HEW40)	SISO	5190	SU	/	0.760	10.777	7.05	11.52	0.03
		5230	SU	/	0.760	10.780	7.05	11.52	0.03
		5755	SU	/	0.764	10.784	7.08	11.50	0.00
		5795	SU	/	0.760	10.780	7.05	11.52	0.03

1.2 Test Graph


1.2.1 Ant1




802.11a HCH 5240MHz Ant1 NTV




802.11a LCH 5745MHz Ant1 NTV




802.11a MCH 5785MHz Ant1 NTN




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1 NTN




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1 NTN




802.11n(HT40) HCH 5230MHz Ant1 NTN




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT20) LCH 5745MHz Ant1 NTN




802.11ac(VHT20) MCH 5785MHz Ant1 NTN




802.11ac(VHT20) HCH 5825MHz Ant1 NTN




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTV




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTV




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTN




802.11ax(HEW20) MCH_5785MHz_SU / Ant1_NTNV




802.11ax(HEW20) HCH_5825MHz_SU / Ant1_NTNV




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTNV




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTNV



802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTNV



802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	1	16.660	/	Pass
		5200	/	/	1	16.643	/	Pass
		5240	/	/	1	16.651	/	Pass
		5745	/	/	1	16.723	/	Pass
		5785	/	/	1	16.711	/	Pass
		5825	/	/	1	16.731	/	Pass
802.11n (HT20)	SISO	5180	/	/	1	17.852	/	Pass
		5200	/	/	1	17.848	/	Pass
		5240	/	/	1	17.838	/	Pass
		5745	/	/	1	17.984	/	Pass
		5785	/	/	1	17.861	/	Pass
		5825	/	/	1	17.946	/	Pass
802.11n (HT40)	SISO	5190	/	/	1	36.806	/	Pass
		5230	/	/	1	36.606	/	Pass
		5755	/	/	1	37.012	/	Pass
		5795	/	/	1	37.056	/	Pass
802.11ac (VHT20)	SISO	5180	/	/	1	17.836	/	Pass
		5200	/	/	1	17.866	/	Pass
		5240	/	/	1	17.775	/	Pass
		5745	/	/	1	17.930	/	Pass
		5785	/	/	1	17.897	/	Pass
		5825	/	/	1	17.961	/	Pass
802.11ac (VHT40)	SISO	5190	/	/	1	36.732	/	Pass
		5230	/	/	1	36.632	/	Pass
		5755	/	/	1	37.186	/	Pass
		5795	/	/	1	36.950	/	Pass
802.11ax (HEW20)	SISO	5180	SU	/	1	18.966	/	Pass
		5200	SU	/	1	19.030	/	Pass
		5240	SU	/	1	19.068	/	Pass
		5745	SU	/	1	19.024	/	Pass
		5785	SU	/	1	19.017	/	Pass
		5825	SU	/	1	19.138	/	Pass
802.11ax (HEW40)	SISO	5190	SU	/	1	38.110	/	Pass
		5230	SU	/	1	38.161	/	Pass
		5755	SU	/	1	38.244	/	Pass
		5795	SU	/	1	38.245	/	Pass

2.1.2 26dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	1	24.597	/	Pass
		5200	/	/	1	24.428	/	Pass
		5240	/	/	1	25.715	/	Pass
802.11n (HT20)	SISO	5180	/	/	1	25.949	/	Pass
		5200	/	/	1	24.550	/	Pass
		5240	/	/	1	24.937	/	Pass
802.11n (HT40)	SISO	5190	/	/	1	47.814	/	Pass
		5230	/	/	1	47.310	/	Pass
802.11ac (VHT20)	SISO	5180	/	/	1	25.466	/	Pass
		5200	/	/	1	24.491	/	Pass
		5240	/	/	1	25.919	/	Pass
802.11ac (VHT40)	SISO	5190	/	/	1	46.435	/	Pass
		5230	/	/	1	48.336	/	Pass
802.11ax (HEW20)	SISO	5180	SU	/	1	26.904	/	Pass
		5200	SU	/	1	23.947	/	Pass
		5240	SU	/	1	23.473	/	Pass
802.11ax (HEW40)	SISO	5190	SU	/	1	43.976	/	Pass
		5230	SU	/	1	45.769	/	Pass

2.1.3 6dB BW


Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5745	/	/	1	16.371	≥ 0.5	Pass
		5785	/	/	1	16.537	≥ 0.5	Pass
		5825	/	/	1	16.517	≥ 0.5	Pass
802.11n (HT20)	SISO	5745	/	/	1	17.625	≥ 0.5	Pass
		5785	/	/	1	17.795	≥ 0.5	Pass
		5825	/	/	1	17.623	≥ 0.5	Pass
802.11n (HT40)	SISO	5755	/	/	1	36.342	≥ 0.5	Pass
		5795	/	/	1	36.396	≥ 0.5	Pass
802.11ac (VHT20)	SISO	5745	/	/	1	17.621	≥ 0.5	Pass
		5785	/	/	1	17.583	≥ 0.5	Pass
		5825	/	/	1	17.649	≥ 0.5	Pass
802.11ac (VHT40)	SISO	5755	/	/	1	36.070	≥ 0.5	Pass
		5795	/	/	1	36.162	≥ 0.5	Pass
802.11ax (HEW20)	SISO	5745	SU	/	1	18.397	≥ 0.5	Pass
		5785	SU	/	1	19.081	≥ 0.5	Pass
		5825	SU	/	1	18.863	≥ 0.5	Pass
802.11ax (HEW40)	SISO	5755	SU	/	1	36.363	≥ 0.5	Pass
		5795	SU	/	1	37.717	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




802.11a HCH 5240MHz Ant1 NTN




802.11a LCH 5745MHz Ant1 NTN




802.11a MCH 5785MHz Ant1 NTN




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1_NTNV




802.11n(HT20) MCH 5200MHz Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1_NTNV




802.11n(HT40) HCH 5230MHz Ant1_NTNV




802.11n(HT40) LCH 5755MHz Ant1_NTNV




802.11n(HT40) HCH 5795MHz Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT20) LCH 5745MHz Ant1 NTN




802.11ac(VHT20) MCH 5785MHz Ant1 NTN




802.11ac(VHT20) HCH 5825MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTNV




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTNV




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTVN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTVN




802.11ax(HEW20) MCH_5785MHz_SU / Ant1_NTNV




802.11ax(HEW20) HCH_5825MHz_SU / Ant1_NTNV




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTN




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTN




802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTN




2.2.2 26dB BW




802.11a HCH 5240MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1 NTN




802.11n(HT20) MCH 5200MHz Ant1_NTNV




802.11n(HT20) HCH 5240MHz Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1 NTN




802.11n(HT40) HCH 5230MHz Ant1 NTN




802.11ac(VHT20) LCH 5180MHz Ant1 NTN




802.11ac(VHT20) MCH 5200MHz Ant1 NTN




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH_5200MHz_SU / Ant1_NTNV




802.11ax(HEW20) HCH_5240MHz_SU / Ant1_NTNV




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTVN




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTVN




2.2.3 6dB BW




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5745MHz Ant1 NTN




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40) LCH 5755MHz Ant1_NTNV




802.11n(HT40) HCH 5795MHz Ant1_NTNV




802.11ac(VHT20) LCH 5745MHz Ant1 NTN




802.11ac(VHT20) MCH 5785MHz Ant1 NTN




802.11ac(VHT20) HCH 5825MHz Ant1 NTN




802.11ac(VHT40) LCH 5755MHz Ant1 NTN




802.11ac(VHT40) HCH 5795MHz Ant1 NTN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTN




802.11ax(HEW20) MCH_5785MHz_SU / Ant1_NTNV




802.11ax(HEW20) HCH_5825MHz_SU / Ant1_NTNV



802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTVN



802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTVN



3. Maximum Conducted Output Power


3.1 Test Result

3.1.1 Power


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11a	SISO	5180	/	/	12.69	<=23.98	Pass
		5200	/	/	11.31	<=23.98	Pass
		5240	/	/	11.19	<=23.98	Pass
		5745	/	/	10.63	<=30	Pass
		5785	/	/	10.51	<=30	Pass
		5825	/	/	11.27	<=30	Pass
802.11n (HT20)	SISO	5180	/	/	10.08	<=23.98	Pass
		5200	/	/	10.94	<=23.98	Pass
		5240	/	/	11.58	<=23.98	Pass
		5745	/	/	10.90	<=30	Pass
		5785	/	/	11.43	<=30	Pass
		5825	/	/	11.56	<=30	Pass
802.11n (HT40)	SISO	5190	/	/	10.74	<=23.98	Pass
		5230	/	/	10.71	<=23.98	Pass
		5755	/	/	11.46	<=30	Pass
		5795	/	/	11.60	<=30	Pass
802.11ac (VHT20)	SISO	5180	/	/	9.59	<=23.98	Pass
		5200	/	/	10.89	<=23.98	Pass
		5240	/	/	9.68	<=23.98	Pass
		5745	/	/	10.66	<=30	Pass
		5785	/	/	12.34	<=30	Pass
		5825	/	/	11.27	<=30	Pass
802.11ac (VHT40)	SISO	5190	/	/	11.52	<=23.98	Pass
		5230	/	/	11.90	<=23.98	Pass
		5755	/	/	12.25	<=30	Pass
		5795	/	/	12.26	<=30	Pass
802.11ax (HEW20)	SISO	5180	SU	/	11.75	<=23.98	Pass
		5200	SU	/	10.84	<=23.98	Pass
		5240	SU	/	11.02	<=23.98	Pass
		5745	SU	/	11.67	<=30	Pass
		5785	SU	/	12.52	<=30	Pass
		5825	SU	/	10.41	<=30	Pass
802.11ax (HEW40)	SISO	5190	SU	/	11.23	<=23.98	Pass
		5230	SU	/	12.12	<=23.98	Pass
		5755	SU	/	11.11	<=30	Pass
		5795	SU	/	12.14	<=30	Pass
Note1: Antenna Gain: - Band: 1 Ant1: 2.38dBi; - Band: 3 Ant1: 2.38dBi:							

3.2 Test Graph


3.2.1 Power




802.11a HCH 5240MHz Ant1 NTVN




802.11a LCH 5745MHz Ant1 NTVN




802.11a MCH 5785MHz Ant1 NTN




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5180MHz Ant1_NTNV




802.11n(HT20) MCH 5200MHz Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5745MHz_Ant1_NTNV




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1 NTN




802.11n(HT40) HCH 5230MHz Ant1 NTN




802.11n(HT40) LCH 5755MHz Ant1 NTN




802.11n(HT40) HCH 5795MHz Ant1 NTN




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT20) LCH 5745MHz Ant1 NTN




802.11ac(VHT20)_MCH_5785MHz_Ant1_NTNV




802.11ac(VHT20)_HCH_5825MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5190MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5230MHz_Ant1_NTNV




802.11ac(VHT40)_LCH_5755MHz_Ant1_NTNV




802.11ac(VHT40)_HCH_5795MHz_Ant1_NTNV




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTNV




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTNV




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5785MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5825MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTN




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTN



802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTNV



802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTNV



4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)		Verdict
					ANT1	Limit	
802.11a	SISO	5180	/	/	0.44	<=11	Pass
		5200	/	/	1.40	<=11	Pass
		5240	/	/	0.92	<=11	Pass
802.11n (HT20)	SISO	5180	/	/	-0.37	<=11	Pass
		5200	/	/	-0.40	<=11	Pass
		5240	/	/	0.24	<=11	Pass
802.11n (HT40)	SISO	5190	/	/	-2.08	<=11	Pass
		5230	/	/	-2.47	<=11	Pass
802.11ac (VHT20)	SISO	5180	/	/	0.13	<=11	Pass
		5200	/	/	0.50	<=11	Pass
		5240	/	/	-0.20	<=11	Pass
802.11ac (VHT40)	SISO	5190	/	/	-1.72	<=11	Pass
		5230	/	/	-2.88	<=11	Pass
802.11ax (HEW20)	SISO	5180	SU	/	-0.25	<=11	Pass
		5200	SU	/	0.45	<=11	Pass
		5240	SU	/	0.88	<=11	Pass
802.11ax (HEW40)	SISO	5190	SU	/	-4.20	<=11	Pass
		5230	SU	/	-1.72	<=11	Pass

4.1.2 PSD-Band3


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/500kHz)		Verdict
					ANT1	Limit	
802.11a	SISO	5745	/	/	-2.92	<=30	Pass
		5785	/	/	-1.59	<=30	Pass
		5825	/	/	-1.91	<=30	Pass
802.11n (HT20)	SISO	5745	/	/	-3.00	<=30	Pass
		5785	/	/	-1.44	<=30	Pass
		5825	/	/	-1.65	<=30	Pass
802.11n (HT40)	SISO	5755	/	/	-5.15	<=30	Pass
		5795	/	/	-3.88	<=30	Pass
802.11ac (VHT20)	SISO	5745	/	/	-2.24	<=30	Pass
		5785	/	/	-1.48	<=30	Pass
		5825	/	/	-1.02	<=30	Pass
802.11ac (VHT40)	SISO	5755	/	/	-4.64	<=30	Pass
		5795	/	/	-4.58	<=30	Pass
802.11ax (HEW20)	SISO	5745	SU	/	-3.17	<=30	Pass
		5785	SU	/	-2.42	<=30	Pass
		5825	SU	/	-3.03	<=30	Pass
802.11ax (HEW40)	SISO	5755	SU	/	-4.26	<=30	Pass
		5795	SU	/	-3.74	<=30	Pass

4.2 Test Graph


4.2.1 PSD




802.11a HCH 5240MHz Ant1 NTNV




802.11n(HT20) LCH 5180MHz Ant1 NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11n(HT40) LCH 5190MHz Ant1_NTNV




802.11n(HT40) HCH 5230MHz Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV




802.11ac(VHT20) HCH 5240MHz Ant1 NTN




802.11ac(VHT40) LCH 5190MHz Ant1 NTN




802.11ac(VHT40) HCH 5230MHz Ant1 NTN




802.11ax(HEW20) LCH 5180MHz SU / Ant1 NTN




802.11ax(HEW20) MCH 5200MHz SU / Ant1 NTN




802.11ax(HEW20) HCH 5240MHz SU / Ant1 NTN




802.11ax(HEW40) LCH 5190MHz SU / Ant1 NTNV




802.11ax(HEW40) HCH 5230MHz SU / Ant1 NTNV




4.2.2 PSD-Band3




802.11a HCH 5825MHz Ant1 NTN




802.11n(HT20) LCH 5745MHz Ant1 NTN




802.11n(HT20)_MCH_5785MHz_Ant1_NTNV




802.11n(HT20)_HCH_5825MHz_Ant1_NTNV




802.11n(HT40)_LCH_5755MHz_Ant1_NTNV




802.11n(HT40)_HCH_5795MHz_Ant1_NTNV




802.11ac(VHT20) LCH 5745MHz Ant1 NTN




802.11ac(VHT20) MCH 5785MHz Ant1 NTN




802.11ac(VHT20) HCH 5825MHz Ant1 NTN




802.11ac(VHT40) LCH 5755MHz Ant1 NTN




802.11ac(VHT40) HCH 5795MHz Ant1 NTN




802.11ax(HEW20) LCH 5745MHz SU / Ant1 NTN




802.11ax(HEW20) MCH_5785MHz_SU / Ant1_NTNV




802.11ax(HEW20) HCH_5825MHz_SU / Ant1_NTNV



802.11ax(HEW40) LCH 5755MHz SU / Ant1 NTN



802.11ax(HEW40) HCH 5795MHz SU / Ant1 NTN



5. Frequency Stability

5.1 Test Result

5.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Temperature (°C)	Voltage	Measured Frequency (MHz)	Limit (MHz)	Verdict
Carrier Wave	SISO	5180	20	LV	5179.967	5150 to 5250	Pass
				NV	5179.967	5150 to 5250	Pass
				HV	5179.966	5150 to 5250	Pass
			-30	NV	5179.966	5150 to 5250	Pass
			-20	NV	5179.966	5150 to 5250	Pass
			-10	NV	5179.966	5150 to 5250	Pass
			0	NV	5179.966	5150 to 5250	Pass
			10	NV	5179.966	5150 to 5250	Pass
			30	NV	5179.966	5150 to 5250	Pass
			40	NV	5179.966	5150 to 5250	Pass
			50	NV	5179.966	5150 to 5250	Pass
		5200	20	LV	5199.966	5150 to 5250	Pass
				NV	5199.966	5150 to 5250	Pass
				HV	5199.966	5150 to 5250	Pass
			-30	NV	5199.966	5150 to 5250	Pass
			-20	NV	5199.966	5150 to 5250	Pass
			-10	NV	5199.966	5150 to 5250	Pass
			0	NV	5199.966	5150 to 5250	Pass
			10	NV	5199.966	5150 to 5250	Pass
			30	NV	5199.966	5150 to 5250	Pass
			40	NV	5199.966	5150 to 5250	Pass
			50	NV	5199.966	5150 to 5250	Pass
		5240	20	LV	5239.966	5150 to 5250	Pass
				NV	5239.966	5150 to 5250	Pass
				HV	5239.966	5150 to 5250	Pass
			-30	NV	5239.966	5150 to 5250	Pass
			-20	NV	5239.966	5150 to 5250	Pass
			-10	NV	5239.966	5150 to 5250	Pass
			0	NV	5239.966	5150 to 5250	Pass
			10	NV	5239.966	5150 to 5250	Pass
			30	NV	5239.966	5150 to 5250	Pass
			40	NV	5239.966	5150 to 5250	Pass
			50	NV	5239.966	5150 to 5250	Pass
		5745	20	LV	5744.962	5725 to 5850	Pass

				NV	5744.962	5725 to 5850	Pass
				HV	5744.962	5725 to 5850	Pass
				-30	5744.962	5725 to 5850	Pass
				-20	5744.962	5725 to 5850	Pass
				-10	5744.962	5725 to 5850	Pass
				0	5744.962	5725 to 5850	Pass
				10	5744.962	5725 to 5850	Pass
				30	5744.962	5725 to 5850	Pass
				40	5744.962	5725 to 5850	Pass
				50	5744.962	5725 to 5850	Pass
		5785	20	LV	5784.962	5725 to 5850	Pass
				NV	5784.962	5725 to 5850	Pass
				HV	5784.962	5725 to 5850	Pass
			-30	NV	5784.962	5725 to 5850	Pass
			-20	NV	5784.962	5725 to 5850	Pass
			-10	NV	5784.962	5725 to 5850	Pass
			0	NV	5784.962	5725 to 5850	Pass
			10	NV	5784.962	5725 to 5850	Pass
			30	NV	5784.962	5725 to 5850	Pass
			40	NV	5784.962	5725 to 5850	Pass
			50	NV	5784.962	5725 to 5850	Pass
		5825	20	LV	5824.962	5725 to 5850	Pass
				NV	5824.962	5725 to 5850	Pass
				HV	5824.962	5725 to 5850	Pass
			-30	NV	5824.962	5725 to 5850	Pass
			-20	NV	5824.962	5725 to 5850	Pass
			-10	NV	5824.962	5725 to 5850	Pass
			0	NV	5824.962	5725 to 5850	Pass
			10	NV	5824.962	5725 to 5850	Pass
			30	NV	5824.962	5725 to 5850	Pass
			40	NV	5824.961	5725 to 5850	Pass
			50	NV	5824.962	5725 to 5850	Pass
		5190	20	LV	5189.965	5150 to 5250	Pass
				NV	5189.966	5150 to 5250	Pass
				HV	5189.966	5150 to 5250	Pass
			-30	NV	5189.966	5150 to 5250	Pass
			-20	NV	5189.965	5150 to 5250	Pass
			-10	NV	5189.966	5150 to 5250	Pass
			0	NV	5189.966	5150 to 5250	Pass
			10	NV	5189.965	5150 to 5250	Pass
			30	NV	5189.966	5150 to 5250	Pass
			40	NV	5189.966	5150 to 5250	Pass
			50	NV	5189.966	5150 to 5250	Pass
		5230	20	LV	5229.966	5150 to 5250	Pass

				NV	5229.966	5150 to 5250	Pass
				HV	5229.965	5150 to 5250	Pass
			-30	NV	5229.966	5150 to 5250	Pass
			-20	NV	5229.965	5150 to 5250	Pass
			-10	NV	5229.966	5150 to 5250	Pass
			0	NV	5229.965	5150 to 5250	Pass
			10	NV	5229.966	5150 to 5250	Pass
			30	NV	5229.965	5150 to 5250	Pass
			40	NV	5229.965	5150 to 5250	Pass
			50	NV	5229.965	5150 to 5250	Pass
		5755	20	LV	5754.962	5725 to 5850	Pass
				NV	5754.962	5725 to 5850	Pass
				HV	5754.962	5725 to 5850	Pass
			-30	NV	5754.962	5725 to 5850	Pass
			-20	NV	5754.962	5725 to 5850	Pass
			-10	NV	5754.962	5725 to 5850	Pass
			0	NV	5754.962	5725 to 5850	Pass
			10	NV	5754.962	5725 to 5850	Pass
			30	NV	5754.962	5725 to 5850	Pass
			40	NV	5754.962	5725 to 5850	Pass
			50	NV	5754.962	5725 to 5850	Pass
		5795	20	LV	5794.962	5725 to 5850	Pass
				NV	5794.962	5725 to 5850	Pass
				HV	5794.962	5725 to 5850	Pass
			-30	NV	5794.962	5725 to 5850	Pass
			-20	NV	5794.962	5725 to 5850	Pass
			-10	NV	5794.962	5725 to 5850	Pass
			0	NV	5794.962	5725 to 5850	Pass
			10	NV	5794.962	5725 to 5850	Pass
			30	NV	5794.962	5725 to 5850	Pass
			40	NV	5794.962	5725 to 5850	Pass
			50	NV	5794.962	5725 to 5850	Pass

STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---