



SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V06
Report Template Revision Date: 2026-01-30

Test Report

Report No.: CQASZ20260601272E-01
Applicant: Dongguan Yu'aoran Electronic Technology Co., Ltd
Address of Applicant: Room 901, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province

Equipment Under Test (EUT):

EUT Name: Intelligent visual doorbell
Model No.: X8, K9S
Test Model No.: X8
Brand Name: N/A
FCC ID: 2BWUM-X8
Standards: 47 CFR Part 15, Subpart C
KDB558074 D01 15.247 Meas Guidance v05r02
Date of Receipt: 2026-06-18
Date of Test: 2026-06-18 to 2026-06-29
Date of Issue: 2026-7-1
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260601272E-01	Rev.01	Initial report	2026-7-1

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 (2020)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2020)	PASS
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.249 (a)	ANSI C63.10 (2020)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.249 (a)/15.209	ANSI C63.10 (2020)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.249(a)/15.205	ANSI C63.10 (2020)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.215 (c)	ANSI C63.10 (2020)	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 TEST ENVIRONMENT AND MODE	7
4.4 DESCRIPTION OF SUPPORT UNITS	7
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
4.6 TEST LOCATION	9
4.7 TEST FACILITY	9
4.8 DEVIATION FROM STANDARDS	9
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	9
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
4.11 EQUIPMENT LIST	10
5 TEST RESULTS AND MEASUREMENT DATA	11
5.1 ANTENNA REQUIREMENT	11
5.2 CONDUCTED EMISSIONS	12
5.3 RADIATED EMISSION	15
5.4 20dB BANDWIDTH	23
6 PHOTOGRAPHS	26
6.1 RADIATED EMISSION TEST SETUP	26
6.2 CONDUCTED EMISSION TEST SETUP	27
6.3 EUT CONSTRUCTIONAL DETAILS	28

4 General Information

4.1 Client Information

Applicant:	Dongguan Yu'aoran Electronic Technology Co., Ltd
Address of Applicant:	Room 901, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province
Manufacturer:	Dongguan Yu'aoran Electronic Technology Co., Ltd
Address of Manufacturer:	Room 901, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province
Factory:	Dongguan Yu'aoran Electronic Technology Co., Ltd
Address of Factory:	Room 901, Building 2, No. 23, Dalingshan Section, Guanchang Road, Dalingshan Town, Dongguan City, Guangdong Province

4.2 General Description of EUT

EUT Name:	Intelligent visual doorbell
Model No.:	X8, K9S
Test Model No.:	X8
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Frequency Range:	GFSK
Modulation Type:	2412Mhz-2469Mhz
Number of Channels:	58
Sample Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	Keep the EUT
Antenna Type:	Copper tube antenna
Antenna Gain:	2.07dBi
Power Supply:	Li-ion Battery: 1000mAh(3.7Wh/3.7V) By Adapter Charging DC 5V

Operation Frequency each of channel					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	21	2432MHz	41	2452MHz
2	2413MHz	22	2433MHz	42	2453MHz
3	2414MHz	23	2434MHz	43	2454MHz
4	2415MHz	24	2435MHz	44	2455MHz
5	2416MHz	25	2436MHz	45	2456MHz
6	2417MHz	26	2437MHz	46	2457MHz
7	2418MHz	27	2438MHz	47	2458MHz
8	2419MHz	28	2439MHz	48	2459MHz
9	2420MHz	29	2440MHz	49	2460MHz
10	2421MHz	30	2441MHz	50	2461MHz
11	2422MHz	31	2442MHz	51	2462MHz
12	2423MHz	32	2443MHz	52	2463MHz
13	2424MHz	33	2444MHz	53	2464MHz
14	2425MHz	34	2445MHz	54	2465MHz
15	2426MHz	35	2446MHz	55	2466MHz
16	2427MHz	36	2447MHz	56	2467MHz
17	2428MHz	37	2448MHz	57	2468MHz
18	2429MHz	38	2449MHz	58	2469MHz
19	2430MHz	39	2450MHz		
20	2431MHz	40	2451MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel(CH1)	2412MHz
The Middle channel(CH29)	2440MHz
The Highest channel(CH58)	2469MHz

4.3 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	27 °C
Humidity:	59 % RH
Atmospheric Pressure:	1009mbar
Temperature:	26 °C
Humidity:	59 % RH
Atmospheric Pressure:	1009mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009mbar
Test mode:	
Transmitting mode:	Use test software (RF test) to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.4 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Adapter	MI	/	/	CQA

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for **CQA** laboratory is reported:

Test	Range	Uncertainty	Notes
Radiated Emission	Below 1GHz	5.12dB	(1)
Radiated Emission	Above 1GHz	4.60dB	(1)
Conducted Disturbance	0.15~30MHz	3.34dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.6 Test Location

All tests were performed at:

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community,
Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

4.7 Test Facility

• **A2LA (Certificate No. 4742.01)**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory is accredited by the

American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU26	CQA-038	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU40	CQA-075	2025/9/1	2026/8/31
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2025/9/1	2026/8/31
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2025/9/1	2026/8/31
Preamplifier	EMCI	EMC184055SE	CQA-089	2025/9/1	2026/8/31
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2025/9/1	2026/8/31
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2025/9/1	2026/8/31
Antenna Connector	CQA	RFC-01	CQA-080	2025/9/1	2026/8/31
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2025/9/1	2026/8/31
Power meter	R&S	NRVD	CQA-029	2025/9/1	2026/8/31
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2025/9/1	2026/8/31
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
LISN	R&S	ENV216	CQA-003	2025/9/1	2026/8/31
Coaxial cable	CQA	N/A	CQA-C009	2025/9/1	2026/8/31
DC power	KEYSIGHT	E3631A	CQA-028	2025/9/1	2026/8/31

Test software:


	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

Note:

The temporary antenna connector is soldered on the pcb board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data


5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is Cylindrical antenna. The best case gain of the antenna is 2.07dBi.	

Test Mode:	Charge +Transmitting mode.
Final Test Mode:	Charge +Transmitting mode
Test Results:	Pass

Measurement Data:

Live line:




	Freq	Read		Limit	Over		
	MHz	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	Pol/Phase
1	0.180	11.77	9.49	21.26	54.49	-33.23	Average
2	0.180	19.13	9.49	28.62	64.49	-35.87	QP
3	0.285	10.65	9.49	20.14	50.67	-30.53	Average
4	0.285	17.86	9.49	27.35	60.67	-33.32	QP
5	0.615	8.65	9.73	18.38	46.00	-27.62	Average
6	0.615	15.81	9.73	25.54	56.00	-30.46	QP
7 PP	0.800	8.83	9.75	18.58	46.00	-27.42	Average
8	0.800	16.25	9.75	26.00	56.00	-30.00	QP
9	1.085	8.91	9.52	18.43	46.00	-27.57	Average
10 QP	1.085	16.67	9.52	26.19	56.00	-29.81	QP
11	1.365	8.66	9.53	18.19	46.00	-27.81	Average
12	1.365	15.72	9.53	25.25	56.00	-30.75	QP

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.330	10.39	9.52	19.91	49.45	-29.54	Average	Neutral
2	0.330	18.55	9.52	28.07	59.45	-31.38	QP	Neutral
3	0.425	10.02	9.63	19.65	47.35	-27.70	Average	Neutral
4	0.425	17.86	9.63	27.49	57.35	-29.86	QP	Neutral
5	0.700	8.71	9.90	18.61	46.00	-27.39	Average	Neutral
6	0.700	17.53	9.90	27.43	56.00	-28.57	QP	Neutral
7	1.010	10.32	9.70	20.02	46.00	-25.98	Average	Neutral
8	1.010	18.73	9.70	28.43	56.00	-27.57	QP	Neutral
9	1.120	10.53	9.71	20.24	46.00	-25.76	Average	Neutral
10	1.120	18.31	9.71	28.02	56.00	-27.98	QP	Neutral
11 PP	1.265	10.84	9.71	20.55	46.00	-25.45	Average	Neutral
12 QP	1.265	19.52	9.71	29.23	56.00	-26.77	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Radiated Emission

Test Requirement:	47 CFR Part 15C Section 15.249 and 15.209 and 15.205				
Test Method:	ANSI C63.10: 2020				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Note: For fundamental frequency, RBW=5MHz, VBW=5MHz, Peak detector is for PK value, RMS detector is for Average value.					
Limit: (Spurious Emissions and band edge)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. 2) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.0		Average Value	
		114.0		Peak Value	

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table

	was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel,the middle channel,the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting mode, Charge + Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

30MHz~1GHz		
Test mode:	Transmitting	Vertical



	Freq	Read		Limit	Over		
	MHz	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	271.32	10.92	16.21	27.13	46.00	-18.87	Peak
2	355.43	10.52	18.28	28.80	46.00	-17.20	Peak
3	475.50	13.81	20.19	34.00	46.00	-12.00	Peak
4	501.18	15.38	20.94	36.32	46.00	-9.68	Peak
5 pp	801.79	15.00	25.97	40.97	46.00	-5.03	Peak
6	900.15	10.20	28.79	38.99	46.00	-7.01	Peak
							Pol/Phase
							VERTICAL
							VERTICAL
							VERTICAL
							VERTICAL
							VERTICAL
							VERTICAL

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Read Freq	Level	Factor	Limit Level	Over Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	290.02	10.85	16.64	27.49	46.00	-18.51	Peak	HORIZONTAL
2	341.98	10.13	17.93	28.06	46.00	-17.94	Peak	HORIZONTAL
3	447.98	10.65	19.38	30.03	46.00	-15.97	Peak	HORIZONTAL
4	501.18	14.92	20.94	35.86	46.00	-10.14	Peak	HORIZONTAL
5	737.07	10.71	24.16	34.87	46.00	-11.13	Peak	HORIZONTAL
6 pp	887.61	9.72	29.09	38.81	46.00	-7.19	Peak	HORIZONTAL

Above 1GHz									
Test mode:		Transmitting		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant Pol	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390	60.20	-9.2	51.00	74	-23.00	Peak	H	1.5	213
2390	46.54	-9.2	37.34	54	-16.66	AVG	H	1.5	124
2400	44.55	-9.39	35.16	74	-38.84	Peak	H	1.5	77
2400	43.92	-9.39	34.53	54	-19.47	AVG	H	1.5	57
2412	99.53	-9.33	90.20	114	-23.80	peak	H	1.5	105
2412	95.82	-9.33	86.49	94	-7.51	AVG	H	1.5	174
4824	55.97	-4.28	51.69	74	-22.31	peak	H	1.5	140
4824	43.03	-4.28	38.75	54	-15.25	AVG	H	1.5	12
7236	51.38	1.13	52.51	74	-21.49	peak	H	1.5	120
7236	36.85	1.13	37.98	54	-16.02	AVG	H	1.5	214
2390	62.11	-9.2	52.91	74	-21.09	peak	V	1.5	129
2390	45.76	-9.2	36.56	54	-17.44	AVG	V	1.5	158
2400	62.52	-9.39	53.13	74	-20.87	peak	V	1.5	330
2400	44.20	-9.39	34.81	54	-19.19	AVG	V	1.5	311
2412	96.66	-9.33	87.33	114	-26.67	peak	V	1.5	34
2412	91.16	-9.33	81.83	94	-12.17	AVG	V	1.5	201
4824	55.15	-4.28	50.87	74	-23.13	peak	V	1.5	70
4824	43.53	-4.28	39.25	54	-14.75	AVG	V	1.5	185
7236	51.89	1.13	53.02	74	-20.98	peak	V	1.5	116
7236	36.73	1.13	37.86	54	-16.14	AVG	V	1.5	102


Test mode:		Transmitting		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant . Pol.	Antenna Height	Table Angle
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V	(m)	(Degree)
2440	99.90	-9.37	90.53	114	-23.47	peak	H	1.5	312
2440	95.57	-9.37	86.20	94	-7.80	AVG	H	1.5	181
4880	57.55	-4.14	53.41	74	-20.59	peak	H	1.5	227
4880	43.17	-4.14	39.03	54	-14.97	AVG	H	1.5	65
7336	50.77	0.56	51.33	74	-22.67	peak	H	1.5	349
7336	38.23	0.56	38.79	54	-15.21	AVG	H	1.5	200
2440	96.22	-9.36	86.86	114	-27.14	peak	V	1.5	27
2440	93.02	-9.36	83.66	94	-10.34	AVG	V	1.5	227
4880	57.25	-4.14	53.11	74	-20.89	peak	V	1.5	5
4880	40.98	-4.14	36.84	54	-17.16	AVG	V	1.5	131
7336	50.77	0.56	51.33	74	-22.67	peak	V	1.5	237
7336	36.15	0.56	36.71	54	-17.29	AVG	V	1.5	199

Test mode:		Transmitting		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant Pol	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2469	100.19	-9.23	90.96	114	-23.04	peak	H	1.5	242
2469	96.62	-9.23	87.39	94	-6.61	AVG	H	1.5	227
2483.5	60.91	-9.29	51.62	74	-22.38	Peak	H	1.5	77
2483.5	44.62	-9.29	35.33	54	-18.67	AVG	H	1.5	25
4938	57.32	-4.03	53.29	74	-20.71	peak	H	1.5	229
4938	42.46	-4.03	38.43	54	-15.57	AVG	H	1.5	67
7407	51.47	1.68	53.15	74	-20.85	peak	H	1.5	92
7407	35.76	1.68	37.44	54	-16.56	AVG	H	1.5	296
2469	95.31	-9.23	86.08	114	-27.92	peak	V	1.5	332
2469	92.59	-9.23	83.36	94	-10.64	AVG	V	1.5	63
2483.5	61.76	-9.29	52.47	74	-21.53	peak	V	1.5	357
2483.5	45.05	-9.29	35.76	54	-18.24	AVG	V	1.5	84
4938	54.93	-4.03	50.90	74	-23.10	peak	V	1.5	42
4938	43.40	-4.03	39.37	54	-14.63	AVG	V	1.5	239
7407	51.84	1.68	53.52	74	-20.48	peak	V	1.5	118
7407	38.00	1.68	39.68	54	-14.32	AVG	V	1.5	227

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz,The disturbance above 10GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .

5.4 20dB Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10:2020
Test Setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Mode:	Transmitting with OFDM modulation.
Limit:	N/A
Test Results:	Pass

Measurement Data

Test channel	20dB bandwidth (MHz)	Results
Lowest	2.17	Pass
Middle	2.18	Pass
Highest	2.17	Pass


Test plot as follows:

Test channel: Lowest




Date: 29.JUN.2026 09:11:15

Test channel: Middle



Date: 29.JUN.2026 09:13:19

Test channel:	Highest
---------------	---------




Date: 29.JUN.2026 09:23:11


6 Photographs

6.1 Radiated Emission Test Setup

9kHz~30MHz




30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission Test Setup




6.3 EUT Constructional Details
























***** END OF REPORT *****