



Shenzhen DEWEIMA Communication Equipment Co.Ltd

SPECIFICATION SHEET FOR APPROVAL

CUSTOMER NAME	Jixian technology
CUSTOMER P/N	UAC107
PART NAME	WIFI Antenna
Material code	QA-40-FPC24G-01
APPROVAL REV.	DWM-V1.0

CONTRACTOR			DATE: 2025-02-28
QA CHECKED	MR CHECKED	RF CHECKED	MANAGER CHECKED
高春彦	陈裕松	覃球铭	余奇学

Manufacturer: Shenzhen Reletech Technology Co., Ltd

**Address: Room 516&517, Building B, Xintang Smart Park, No. 11,
Zhongxing Road, Ma'antangCommunity, Bantian Subdistrict,
Longgang District, Shenzhen, Guangdong, China**

TEL: 13603094246

Content


SPECIFICATION	1
SHEET FOR APPROVAL	1
1. Product Application	3
2. The test environment, equipment	3
3. Technology Parameters	6
4. Product photo	10
5. Environmental Performance	10
6. Usage Precaution	11
7. Packing metho	11


				Product Specification		
				P/N:	Rev.: A	Page:



1. Product Application

Terminal of the antenna products can only be used for WIFI antenna.

2. The test environment, equipment

Item	Description	Test Condition	Requirement
2.1	Passive testing	The VSWR measurement devices are connected in sequence: Agilent5071B Network Analyzer → measurement Cable → Customer-providing Devices.	VSWR: 2400-2500MHz<2
		Test equipment	
			
Item	Description	Test Condition	Requirement

		Product Specification		
		P/N:	Rev.: A	Page:
2.2	Active test	Follow picture shows the measurement condition of the antenna been put on the measurement device, which is used for all measurement of electric performances.	Antenna efficiency: 2400-2500MHz >30%	
2.3	Microwave Anechoic (Satimo&ETS)	Test equipment/测试设备		
				

				Product Specification		
				P/N:	Rev.: A	Page:
						
2.4	CMW500 Agilent5071B AgilentE4405B Agilent8960					


Product Specification

P/N:

Rev.:

Page:

A




3. Technology Parameters

Frequency Range
Operating Humidity
Temperature Rating

2400-2500MHz
85% R.H.MAX
-40°C ~ +85°C

3.1 The matching test value

Element	Value
E1(0402)	
E2(0402)	
E3(0402)	
E4(0402)	



Product Specification

P/N:


Rev.:

Page:

A

3.2 VSWR

2400-2500MHz



3.3. Efficiency And Gain/效率和增益

Passive Test For WIFI		
Freq (MHz)	Effi (%)	Gain (dBi)
2400	49.22	1.30
2410	49.19	1.23
2420	48.97	1.12
2430	48.00	1.00
2440	49.81	1.21
2450	51.97	1.44
2460	51.39	1.40
2470	51.84	1.43
2480	52.99	1.48
2490	53.53	1.45
2500	50.61	1.10

Product Specification


P/N:

Rev.:

Page:

A

3.4 3D PHOTO



Product Specification


P/N:

Rev.:

Page:

A

4. Product photo



5.Environmental Performance

Item	Description	Test Condition	Requirement
5.1	High and low temperature test	Temp.: -40 °C Time: 48 hours Temp.: 85°C Time: 48 hours	1. No visible damage. 2. The electric performances reach the standard.
Item	Description	Test Condition	Requirement
5.2	Salt Spray	5±0.1% Nad salt fog PH Value: 6.5-7.2 Temp: 35±1 °C Time:24 hours	1. No color change. 2. the appearance of the antenna does not flake off.

		Product Specification	
		P/N:	Rev.: A
			Page:

6.Usage Precaution

No	Items	Matter
6.1	Precautions	a)Please avoid the cleaning of this producta)
No	Items	Matter
6.2	Stockpile condition	Use this product within 6 months after receipt Condition : Temp: 5~30℃ Humidity:≤70%

7. Packing metho

Bag shipment, 100pcs。