

RF Exposure

Applicant : Guangzhou Fangyu Hua Cross-border
E-commerce Co., Ltd.
Address : Room 1505, No.1 Junwen Street, Huangpu
District, Guangzhou
Product Name : Wireless Microphone
Brand Mark : N/A
Model : Q9Pro
Series model : Q9Max
FCC ID : 2BWY3-Q9PRO
Report Number : BLA-EMC-202606-A123-03
Date of Receipt : July 2, 2026
Date of Test : July 2, 2026 to Aug. 3, 2026
47 CFR Part 15, Part1.1307
47 CFR Part 15, Part2.1093
Test Standard : KDB447498D04 General RF Exposure
Guidance v01
Test Result : Pass

Compiled by:

Hugh

Review by:

Xavier

Approved by:

Blue Zheng

Issued Date: Aug. 3, 2026

BlueAsia Technical Services (Shenzhen) Co., Ltd.Address: No.41, South of Beihuan Road, Shangwu Community, Shiyuan
Subdistrict, Bao'an District, Shenzhen, Guangdong, China

The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1	General information	4
1.1	General information	4
1.2	General description of EUT	4
2	Laboratory and accreditations	5
3	RF Exposure Compliance Requirement	6
3.1	Standard Requirement	6
3.2	Limits	6
3.3	Result	7

Revise Record

Version No.	Date	Description
01	Aug. 3, 2026	Original

1 General information

1.1 General information

Applicant	Guangzhou Fangyu Hua Cross-border E-commerce Co., Ltd.
Address	Room 1505, No.1 Junwen Street, Huangpu District, Guangzhou
Manufacturer	Shenzhen Kaspersky Wanbang Industrial Co., Ltd.
Address	501, Factory 7, Tangdong Area, Tianxin Industrial Zone, Gushu Community, Xixiang Street, Bao'an District, Shenzhen
Factory	Shenzhen Kaspersky Wanbang Industrial Co., Ltd.
Address	501, Factory 7, Tangdong Area, Tianxin Industrial Zone, Gushu Community, Xixiang Street, Bao'an District, Shenzhen

1.2 General description of EUT

Product name	Wireless Microphone
Model no.	Q9Pro
Series model	Q9Max
Desc of series model	The company name is Guangzhou Fangyu Hua Cross-border E-commerce Co., Ltd., the main model name is Q9 and the series model name is Q9Pro Q9Max. Their electrical circuit design layout and components are exactly the same, but the model names are different. The appearance color is also different.
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	PCB antenna
Antenna Gain:	-0.58dBi(Provided by customer)
Power supply or adapter information	DC3.7V by battery
Hardware version	N/A
Software version	N/A
Engineer sample no.	BLA-EMC-202606-A123

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia Technical Services (Shenzhen) Co.,Ltd.
Address:	No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

3 RF Exposure Compliance Requirement

3.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.2 Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

3.3 Result

$$\text{EIRP} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2 / 30$$

Where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,

d = measurement distance in meters (m)

$$\text{Spot} = (\text{E} \times \text{d})^2 / 30 \times \text{gt}$$

Separation distance = 0.5cm

Ant gain = -0.58dBi

For BT(Worst):

Max Output power = 0.105dBm @ 2402MHz 8DPSK = 1.024mW < 2.788mW

EIRP = 0.105dBm - 0.58dBi = -0.475dBm

ERP = -0.475 - 2.15 = -2.625dBm

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia Technical Services (Shenzhen) Co., Ltd

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version: v1.1