

FCC RF Exposure

Applicant : Dongguan Meimei Technology Co., Ltd.
Address : Room 505, Liandong Building, No. 556 Guanwen Road,
Dongcheng District, Dongguan City
Product Name : obd2 scanner
Brand Mark : N/A
Model : elm327
Series model : N/A
FCC ID : 2BWY7-ELM327
Report Number : BLA-EMC-202607-A19-02
Date of Receipt : Jul. 03, 2026
Date of Test : Jul. 03, 2026 to Jul. 30, 2026
47 CFR Part 15, Part1.1307
Test Standard : 47 CFR Part 15, Part2.1091
KDB447498D04 General RF Exposure Guidance v01
Test Result : Pass

Compiled by: Mark Chen

Review by: Xavier



Approved by:

Issued Date: Jul. 31, 2026

BlueAsia Technical Services(Shenzhen) Co.,Ltd.

Address: No.41, South of Beihuan Road, Shangwu Community, Shiyuan Subdistrict, Bao'an District, Shenzhen, Guangdong, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information	4
1.1 General information	4
1.2 General description of EUT	4
2 RF Exposure Compliance Requirement	5
2.1 Standard Requirement	5
2.2 Limits	5
2.3 Result	6

Revise Record

Version No.	Date	Description
01	Jul. 31, 2026	Original

BlueAsia

1 General information

1.1 General information

Applicant	Dongguan Meimei Technology Co., Ltd.
Address	Room 505, Liandong Building, No. 556 Guanwen Road, Dongcheng District, Dongguan City
Manufacturer	Dongguan Meimei Technology Co., Ltd.
Address	Room 505, Liandong Building, No. 556 Guanwen Road, Dongcheng District, Dongguan City
Factory	Dongguan Meimei Technology Co., Ltd.
Address	Room 505, Liandong Building, No. 556 Guanwen Road, Dongcheng District, Dongguan City

1.2 General description of EUT

Product name	obd2 scanner
Model no.	elm327
Operation Frequency	2402MHz-2480MHz
Modulation Type	GFSK
Rate data	1Mbps, 2Mbps
Channel Spacing	2MHz
Number of Channels	40
Antenna Type	PCB antenna
Antenna Gain	-4.65dBi (Provided by customer)
Power supply	DC 12V
Hardware Version	N/A
Software Version	N/A

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.2 Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

2.3 Result

$$\text{EIRP} = p_t \times g_t = (E \times d)^{2/30}$$

Where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,

d = measurement distance in meters (m)

$$\text{Spot} = (E \times d)^{2/30} \times g_t$$

Separation distance= 20cm

Ant gain = -4.65dBi

For BLE 2M (Worst):

Max Output power = 1.387dBm @ 2480MHz

EIRP = 1.387dBm - 4.65dBi = -3.263dBm, because Max Output power > EIRP

So, Max Output power = 1.387dBm = 1.376mW < 3060 mW

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.