



FCC RF Exposure

EUT Description: Sing-E-ZQS

Model No.: ZQS-P1

SeriesModel:ZQS-P2,ZQS-K03,ZQS-B115,ZQS-T02,ZQS42108M,ZQS42103,ZQS4273M,ZQS14105,ZQS1483, ZQS1481,ZQS-L36,ZQS6141,ZQS6159

FCC ID: 2BWYA-SING-E

Equipment type: portable device

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

f (GHz) is the RF channel transmit frequency in GHz. The result is rounded to one decimal place for comparison.

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min test separation distance in mm})} \right] (1/f^2) < 3.0 \text{ for 1-g SAR, and } < 7.5 \text{ for 10-g extremity SAR, where}$$

Power and distance are rounded to the nearest mW and mm before calculation.

BT

Frequency (MHz)	Field strength (dBuV/m)	EIRP (dBm)	Max tune-up (mW)	Min. Distance (mm)	Calc. thresholds	limit
2402	89.11	-6.12	0.2443	5	0.0757	3
2441	88.94	-6.29	0.2350	5	0.0728	3
2480	85.46	-9.77	0.1054	5	0.0327	3

Conclusion: No SAR is required