

TEST REPORT

Product Name : Shake Sensor
Model Number : DC510
FCC ID : 2BX2H-DC510

Prepared for : Zhejiang Dooya Intelligent Technology Co., Ltd.
Address : Building 1, No.329 Rongji Road, Luotuo Street, zhenhai District, Ningbo City, Zhejiang Province, China

Prepared by : EMTEK (NINGBO) CO., LTD.
Address : No. 8, Building 8, Lane 216, Qingyi Road, Ningbo High-Tech Zone, Ningbo, Zhejiang, China

Tel: +86-574-27907998
Fax: +86-574-27721538

Report Number : ENB2608280169W00102R
Date(s) of Tests : September 01, 2026 to September 17, 2026
Date of issue : September 18, 2026

TABLE OF CONTENT

TEST REPORT	1
1. FACILITIES AND ACCREDITATIONS	5
1.1. TEST FACILITY.....	5
1.2. LABORATORY ACCREDITATIONS AND LISTINGS.....	5
2. GENERAL PRODUCT INFORMATION	6
3. LIMIT	7
4. TEST RESULTS	8



Test Report Description

Applicant : Zhejiang Dooya Intelligent Technology Co., Ltd.

Address : Building 1, No.329 Rongji Road, Luotuo Street, zhenhai District, Ningbo City, Zhejiang Province, China

Manufacturer : Ningbo Dooya Mechanic & Electronic Technology Co., Ltd.

Address : No.168 shengguang Road, Luotuo, Zhenhai, Ningbo, Zhejiang Province, P.R, China

EUT : Shake Sensor

Model Name : DC510

Trademark : DOOYA

The device described above is tested by EMTEK (NINGBO) CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the FCC 1.1310 and KDB 447498 D01 General RF Exposure Guidance v07 requirements. The test results are contained in this report and EMTEK (NINGBO) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of EMTEK (NINGBO) CO., LTD..

Date of Test : September 01, 2026 to September 17, 2026

Prepared by : 
WK Luo /Engineer

Reviewer : 
Monsieur Li /Supervisor

Approved & Authorized Signer : 
Tony Wei /Manager

Modified Information

Version	Report No.	Revision Date	Summary
/	ENB2608280169W00102R	/	Original Report



1. Facilities And Accreditations

1.1. Test Facility

All measurement facilities used to collect the measurement data are located at
EMTEK (NINGBO) CO., LTD.

No. 8, Building 8, Lane 216, Qingyi Road, Ningbo High-Tech Zone, Ningbo, Zhejiang, China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 32.

1.2. LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L6666.

The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

Designation by FCC

Designation Number: CN1354

Test Firm Registration Number: 427606

Accredited by A2LA

The Certificate Number is 4321.03.

Accredited by ISED

The Conformity Assessment Body Identifier is CN0114

Name of Firm : EMTEK (NINGBO) CO., LTD.

Site Location : No. 8, Building 8, Lane 216, Qingyi Road, Ningbo High-Tech Zone,
Ningbo, Zhejiang, China

2. General Product Information

Characteristics	Description
Product:	Shake Sensor
Model Number:	DC510
Modulation:	FSK
Operating Frequency Range(s):	433.92 MHz
Number of Channels:	1 Channel
Max Transmit Power:	85.07 dBuV/m
Antenna Type :	PCB Antenna
Antenna gain	-2.0 dBi
Power supply:	DC 3V from Battery
Temperature Range	-20°C ~ +55°C

Note: for more details, please refer to the User's manual of the EUT.

3. Limit

According to §15.249(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V07

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

4. Test Results

Maximum measured transmitter power:
 $EIRP = E + 20\log(d) - 104.7 = 85.07 + 9.54 - 104.7 = -10.09 \text{ dBm}$

Transmit Frequency (MHz)	Mode	EIRP Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
433.92	FSK	-10.09 dBm	1	0.15	3

Conclusion:
 For the max result : $0.15 \leq 3.0$ for 1-g SAR extremity SAR.

*** End of Report ***

