

TEST REPORT

Reference No...... : WTX26X08250779W003
FCC ID..... : 2BX33-FORII-01PRO
Applicant..... : Astraux Technology Limited
Address..... : RM 1917, 19/F LEE GARDEN ONE 33 HYSAN AVENUE CAUSEWAY BAY
HONG KONG
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Astraux AI PET
Model No...... : PRO-01
Standards..... : FCC Part 15.247
Date of Receipt sample..... : 2026-08-24
Date of Test..... : 2026-08-25 to 2026-10-12
Date of Issue..... : 2026-10-14
Test Report Form No...... : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China


Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	12
3. ANTENNA REQUIREMENT	13
3.1 STANDARD APPLICABLE	13
3.2 EVALUATION INFORMATION	13
4. POWER SPECTRAL DENSITY	14
4.1 STANDARD APPLICABLE	14
4.2 TEST SETUP BLOCK DIAGRAM	14
4.3 TEST PROCEDURE	14
4.4 SUMMARY OF TEST RESULTS/PLOTS	14
5. DTS BANDWIDTH	15
5.1 STANDARD APPLICABLE	15
5.2 TEST SETUP BLOCK DIAGRAM	15
5.3 TEST PROCEDURE	15
5.4 SUMMARY OF TEST RESULTS/PLOTS	15
6. RF OUTPUT POWER	16
6.1 STANDARD APPLICABLE	16
6.2 TEST SETUP BLOCK DIAGRAM	16
6.3 TEST PROCEDURE	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	17
7.1 STANDARD APPLICABLE	17
7.2 TEST PROCEDURE	17
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	19
7.4 SUMMARY OF TEST RESULTS/PLOTS	19
8. OUT OF BAND EMISSIONS	31
8.1 STANDARD APPLICABLE	31
8.2 TEST PROCEDURE	31
8.3 SUMMARY OF TEST RESULTS/PLOTS	32
9. CONDUCTED EMISSIONS	41
9.1 TEST PROCEDURE	41
9.2 BASIC TEST SETUP BLOCK DIAGRAM	41
9.3 TEST RECEIVER SETUP	41
9.4 SUMMARY OF TEST RESULTS/PLOTS	41
APPENDIX SUMMARY	44
APPENDIX A	45
APPENDIX B	50
APPENDIX C	55
APPENDIX D	60
APPENDIX PHOTOGRAPHS	68

Report version

Version No.	Date of issue	Description
Rev.00	2026-10-14	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Astraux AI PET
Trade Name:	/
Model No.:	PRO-01
Adding Model(s):	/
Rated Voltage:	Battery:DC3.7V Type-C:DC5V
Battery Capacity:	1800mAh
Power Adapter:	/
<i>Note: 1: The sample information is provided by the customer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n, 802.11ax
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20)/ax(HE20)
RF Output Power:	15.21dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20)/ax(HE20)
Channel Separation:	5MHz
Type of Antenna:	FPC Antenna
Antenna Gain:	2.15dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the FCC rules.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11ax-HE20	Low:2412MHz, Middle:2437MHz,High:2462MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	0.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	Xiaomi	MDY-11-EX	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.57\text{dB}$
Occupied Bandwidth	Conducted	$\pm 0.015\text{MHz}$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emission 1#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Conducted Emission 2#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: $\pm 5.36\text{dB}$
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.28\text{dB}$
		@1GHz to 6GHz: $\pm 5.56\text{dB}$
		@6GHz to 18GHz: $\pm 5.72\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$

1.7 Test Equipment List and Details

Internal No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1002	Communication Tester	Rohde & Schwarz	CMW500	1201.0002 k50-14865 0-FB	2026-03-25	2027-03-24
WTXE1005A 1005	MXA Signal Analyzer	Agilent	N9020A	US471401 02	2026-03-25	2027-03-24
WTXE1084A 1001	MXA Signal Analyzer	KEYSIGHT	N9020A	MY543205 48	2026-02-06	2027-02-05
WTXE1005A 1006	Spectrum Analyzer	Rohde & Schwarz	FSP40	1164.4391 K38Ser. 100368	2026-04-29	2027-04-28
WTXW1105A 1136	RF ATTENUATOR	FEIYANG	N-JK	/	2026-02-06	2027-02-05
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2026-02-23	2027-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2026-02-05	2027-02-04
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2026-02-05	2027-02-04
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2026-03-11	2029-03-10
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2026-02-05	2027-02-04
WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2026-02-05	2027-02-04
WTXE1010A	Horn Antenna	ETS	3117	00086197	2026-02-05	2027-02-04

1005						
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2026-02-05	2027-02-04
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2026-02-05	2027-02-04
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2026-02-23	2027-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2026-02-05	2027-02-04
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☒ Chamber C: Above 1GHz						

WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2026-02-05	2027-02-04
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2026-02-05	2027-02-04
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2026-02-05	2027-02-04
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2026-02-23	2027-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2026-02-05	2027-02-04
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2026-02-05	2027-02-04
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software/EZ-EMC (Radiated Emission A)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission B)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission C)	Farad	RA-03A1-2	1.1.4.2
EMI Test Software/EZ-EMC (Conducted Emission Room 1#)	Farad	3A1*CE-RE	1.1.4.3
EMI Test Software/EZ-EMC (Conducted Emission Room 2#)	Farad	3A1*CE-RE	1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has an FPC antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

4.4 Summary of Test Results/Plots


Please refer to Appendix A

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2020 Subclause 11.8.1, the test method of DTS Bandwidth as below:

Option 1:

The steps for the first option are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB downamplitude” value, then it shall be as close as possible to this value.

Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in ANSI C63.10-2020 Subclause 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB

5.4 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Sub clause 8.3.2.2 and ANSI C63.10-2020 Sub clause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth.

- Set span to at least 1.5 times the OBW.
- Set RBW = 1-5% of the OBW, not to exceed 1MHz.
- Set VBW $\geq 3 \times$ RBW.
- Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This gives bin-to-bin spacing $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto.
- Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10kHz,	RBW=120kHz,	RBW=1MHz,
VBW =30kHz	VBW=300kHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


7.4 Summary of Test Results/Plots

Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b_11Mbps) is recorded in this report.

➤ Spurious Emissions 9kHz to 30MHz


802.11b_11Mbps			
Test Channel	Low(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	0.0117	56.62	-7.24	49.38	126.22	-76.84	-	-	peak
2	0.0352	51.43	-7.46	43.97	116.66	-72.69	-	-	peak
3	0.0740	47.48	-7.78	39.70	110.21	-70.51	-	-	peak
4	0.6271	57.13	-8.03	49.10	71.66	-22.56	-	-	peak
5	1.4640	48.40	-7.68	40.72	64.32	-23.60	-	-	peak
6	10.7330	43.31	-7.81	35.50	69.50	-34.00	-	-	peak


➤ Spurious Emissions Below 1GHz

802.11b_11Mbps			
Test Channel	Low(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	37.3017	28.08	-9.17	18.91	40.00	-21.09	-	-	peak
2	74.7933	27.68	-11.32	16.36	40.00	-23.64	-	-	peak
3	157.5289	27.97	-8.28	19.69	43.50	-23.81	-	-	peak
4	373.8861	28.27	-6.87	21.40	46.00	-24.60	-	-	peak
5	642.2923	29.61	-0.38	29.23	46.00	-16.77	-	-	peak
6	979.1391	31.93	3.68	35.61	54.00	-18.39	-	-	peak


802.11b_11Mbps			
Test Channel	Low(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	38.6356	31.70	-9.00	22.70	40.00	-17.30	-	-	peak
2	74.2696	30.80	-11.20	19.60	40.00	-20.40	-	-	peak
3	164.3129	28.58	-8.42	20.16	43.50	-23.34	-	-	peak
4	327.1553	28.16	-7.58	20.58	46.00	-25.42	-	-	peak
5	550.2902	30.41	-2.75	27.66	46.00	-18.34	-	-	peak
6	952.0000	30.02	3.63	33.65	46.00	-12.35	-	-	peak


➤ Spurious Emissions Above 1GHz

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4824.000	53.10	-12.01	41.09	74.00	-32.91	-	-	peak
2	7236.000	52.21	-6.48	45.73	74.00	-28.27	-	-	peak

802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4824.000	52.73	-12.01	40.72	74.00	-33.28	-	-	peak
2	7236.000	51.47	-6.48	44.99	74.00	-29.01	-	-	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4874.000	51.65	-11.88	39.77	74.00	-34.23	-	-	peak
2	7311.000	49.20	-5.04	44.16	74.00	-29.84	-	-	peak

802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4874.000	51.52	-11.88	39.64	74.00	-34.36	-	-	peak
2	7311.000	50.91	-5.04	45.87	74.00	-28.13	-	-	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4924.000	51.19	-12.41	38.78	74.00	-35.22	-	-	peak
2	7386.000	52.79	-6.09	46.70	74.00	-27.30	-	-	peak

802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	4924.000	51.85	-12.41	39.44	74.00	-34.56	-	-	peak
2	7386.000	51.95	-6.09	45.86	74.00	-28.14	-	-	peak

Reference No.: WTX26X08250779W003

➤ Spurious Emission From Above 18GHz

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	25696	46.48	74.00	-27.52	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency	Reading	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	
1	25784	45.12	74.00	-28.88	peak

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2020 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots

➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	46.34	-18.90	27.44	54.00	-26.56	Average Detector
	2310.000	58.59	-18.90	39.69	74.00	-34.31	Peak Detector
2	2390.000	47.95	-18.82	29.13	54.00	-24.87	Average Detector
	2390.000	60.03	-18.82	41.21	74.00	-32.79	Peak Detector
3	2400.000	59.84	-18.86	40.98	54.00	-13.02	Average Detector
	2400.000	69.36	-18.86	50.50	74.00	-23.50	Peak Detector
4	2412.926	112.39	-18.76	93.63	/	/	Average Detector
	2413.647	115.54	-18.75	96.79	/	/	Peak Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.625	111.93	-18.53	93.40	/	/	Average Detector
	2463.327	116.58	-18.53	98.05	/	/	Peak Detector
2	2483.500	47.78	-18.65	29.13	54.00	-24.87	Average Detector
	2483.500	58.89	-18.65	40.24	74.00	-33.76	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	47.97	-18.90	29.07	54.00	-24.93	Average Detector
	2310.000	59.84	-18.90	40.94	74.00	-33.06	Peak Detector
2	2390.000	62.35	-18.82	43.53	54.00	-10.47	Average Detector
	2390.000	83.27	-18.82	64.45	74.00	-9.55	Peak Detector
3	2400.000	76.41	-18.86	57.55	Delta=33.56dBc		Average Detector
4	2414.369	109.86	-18.75	91.11			Average Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2465.230	108.63	-18.54	90.09	/	/	Average Detector
	2467.635	119.00	-18.56	100.44	/	/	Peak Detector
2	2483.500	55.56	-18.65	36.91	54.00	-17.09	Average Detector
	2483.500	76.84	-18.65	58.19	74.00	-15.81	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	47.82	-18.90	28.92	54.00	-25.08	Average Detector
	2310.000	59.78	-18.90	40.88	74.00	-33.12	Peak Detector
2	2390.000	66.16	-18.82	47.34	54.00	-6.66	Average Detector
	2390.000	84.99	-18.82	66.17	74.00	-7.83	Peak Detector
3	2400.000	77.76	-18.86	58.90	Delta=31.86dBc		Average Detector
4	2416.052	109.49	-18.73	90.76			Average Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2464.629	94.99	-18.54	76.45	/	/	Average Detector
	2465.531	119.19	-18.54	100.65	/	/	Peak Detector
2	2483.500	52.73	-18.65	34.08	54.00	-19.92	Average Detector
	2483.500	79.08	-18.65	60.43	74.00	-13.57	Peak Detector

802.11ax-HE20_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	47.99	-18.90	29.09	54.00	-24.91	Average Detector
	2310.000	59.17	-18.90	40.27	74.00	-33.73	Peak Detector
2	2390.000	66.32	-18.82	47.50	54.00	-6.50	Average Detector
	2390.000	85.70	-18.82	66.88	74.00	-7.12	Peak Detector
3	2400.000	77.12	-18.86	58.26	Delta=31.47dBc		Average Detector
4	2416.052	108.46	-18.73	89.73			Average Detector

802.11ax-HE20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2464.529	92.04	-18.54	73.50	/	/	Average Detector
	2466.533	121.21	-18.55	102.66	/	/	Peak Detector
2	2483.500	52.40	-18.65	33.75	54.00	-20.25	Average Detector
	2483.500	78.84	-18.65	60.19	74.00	-13.81	Peak Detector

➤ Conducted test
Please refer to Appendix D


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1779	15.72	10.26	25.98	54.58	-28.60	AVG
2	0.1940	26.41	10.26	36.67	63.86	-27.19	QP
3	0.3780	21.58	10.19	31.77	58.32	-26.55	QP
4	0.3860	12.62	10.19	22.81	48.15	-25.34	AVG
5	1.2660	22.31	10.29	32.60	56.00	-23.40	QP
6*	1.3340	12.92	10.29	23.21	46.00	-22.79	AVG
7	4.0658	10.37	10.09	20.46	46.00	-25.54	AVG
8	4.9379	18.18	10.03	28.21	56.00	-27.79	QP
9	17.8700	20.19	10.08	30.27	60.00	-29.73	QP
10	18.2340	7.72	10.11	17.83	50.00	-32.17	AVG
11	22.7020	6.23	10.19	16.42	50.00	-33.58	AVG
12	25.1818	19.40	10.15	29.55	60.00	-30.45	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1779	15.09	10.26	25.35	54.58	-29.23	AVG
2	0.1980	24.44	10.26	34.70	63.69	-28.99	QP
3	0.2779	22.71	10.26	32.97	60.88	-27.91	QP
4	0.3140	13.34	10.23	23.57	49.86	-26.29	AVG
5*	0.9379	12.50	10.29	22.79	46.00	-23.21	AVG
6	0.9939	22.33	10.31	32.64	56.00	-23.36	QP
7	4.0658	11.06	10.09	21.15	46.00	-24.85	AVG
8	4.9580	18.49	10.03	28.52	56.00	-27.48	QP
9	7.8220	12.34	9.96	22.30	50.00	-27.70	AVG
10	8.4459	19.00	9.93	28.93	60.00	-31.07	QP
11	12.1980	10.97	9.89	20.86	50.00	-29.14	AVG
12	18.1099	20.94	10.10	31.04	60.00	-28.96	QP

APPENDIX SUMMARY




Project No.	WTX26X08250779W003	Test Engineer	Jennifer Song
Start date	2026/9/1	Finish date	2026/9/2
Temperature	24℃	Humidity	51%
RF specifications	WIFI-2.4G		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	DTS Bandwidth	Compliant
C	RF Output Power	Compliant
D	Conducted Out of Band Emissions	Compliant

APPENDIX A

Power Spectral Density			
Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_1Mbps	2412	-18.67	8
	2437	-19.18	8
	2462	-19.33	8
802.11g_6Mbps	2412	-25.67	8
	2437	-25.02	8
	2462	-24.98	8
802.11n-HT20_MCS0	2412	-26.20	8
	2437	-26.94	8
	2462	-27.01	8
802.11ax-HE20_MCS0	2412	-27.87	8
	2437	-29.36	8
	2462	-29.54	8

802.11b-Low	<p> •RBW 3 kHz Marker 1 [T1] -18.67 dBm •VBW 10 kHz •Att. 30 dB SWT 3.4 s 2.41260000 GHz Ref 20 dBm Offset 1 dB 20 dB 10 dB 0 dB -10 dB -20 dB -30 dB -40 dB -50 dB -60 dB -70 dB -80 dB Center 2.412 GHz 3 MHz/ Span 30 MHz </p>	Date: 1.SEP.2026 15:55:11
802.11b-Middle	<p> •RBW 3 kHz Marker 1 [T1] -19.18 dBm •VBW 10 kHz •Att. 30 dB SWT 3.4 s 2.43760000 GHz Ref 20 dBm Offset 1 dB 20 dB 10 dB 0 dB -10 dB -20 dB -30 dB -40 dB -50 dB -60 dB -70 dB -80 dB Center 2.437 GHz 3 MHz/ Span 30 MHz </p>	Date: 1.SEP.2026 15:55:34
802.11b-High	<p> •RBW 3 kHz Marker 1 [T1] -19.33 dBm •VBW 10 kHz •Att. 30 dB SWT 3.4 s 2.46160000 GHz Ref 20 dBm Offset 1 dB 20 dB 10 dB 0 dB -10 dB -20 dB -30 dB -40 dB -50 dB -60 dB -70 dB -80 dB Center 2.462 GHz 3 MHz/ Span 30 MHz </p>	Date: 1.SEP.2026 16:02:18

<p>802.11g-Low</p>	<div data-bbox="644 232 1198 745"><p>Date: 1.SEP.2026 16:02:50</p></div>
<p>802.11g-Middle</p>	<div data-bbox="644 772 1198 1285"><p>Date: 1.SEP.2026 16:03:13</p></div>
<p>802.11g-High</p>	<div data-bbox="644 1312 1198 1825"><p>Date: 1.SEP.2026 16:04:01</p></div>




Channel	Frequency (GHz)	Power (dBm)	Bandwidth (kHz)	SWT (s)	Ref (dBm)	Att (dB)	Span (MHz)	Center (GHz)	Offset (dB)
802.11n-HT20-Low	2.412	-26.20	10	3.4	20	30	30	2.412	1
802.11n-HT20-Middle	2.437	-26.94	10	3.4	20	30	30	2.437	1
802.11n-HT20-High	2.462	-27.01	10	3.4	20	30	30	2.462	1




Channel	Frequency (GHz)	Power (dBm)	Bandwidth (kHz)	SWT (s)	Marker 1 [T1]
802.11ax-HE20-Low	2.412	-27.87	10	3.4	2.41199999 GHz
802.11ax-HE20-Middle	2.437	-29.36	10	3.4	2.43799999 GHz
802.11ax-HE20-High	2.462	-29.54	10	3.4	2.46299999 GHz

APPENDIX B

DTS Bandwidth			
Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_1Mbps	2412	10.24	≥500
	2437	10.32	≥500
	2462	10.24	≥500
802.11g_6Mbps	2412	16.48	≥500
	2437	16.40	≥500
	2462	16.40	≥500
802.11n-HT20_MCS0	2412	17.44	≥500
	2437	17.60	≥500
	2462	17.68	≥500
802.11ax-HE20_MCS0	2412	19.04	≥500
	2437	18.88	≥500
	2462	18.96	≥500

[illegible]




<p>802.11g-Low</p>	<div data-bbox="644 232 1198 745"><p>Date: 1.SEP.2026 16:25:52</p></div>
<p>802.11g-Middle</p>	<div data-bbox="644 775 1198 1288"><p>Date: 1.SEP.2026 16:26:10</p></div>
<p>802.11g-High</p>	<div data-bbox="644 1317 1198 1830"><p>Date: 1.SEP.2026 16:26:26</p></div>

802.11n-HT20-Low	<div><p>Ref 20 dBm *Att 30 dB SWT 2.5 ms</p><p>Marker 1 [T1] 2.409760000 GHz</p><p>dBm [T1] 0.00 dBm</p><p>SW 17.440000000 MHz</p><p>Temp 1 [T1] 0.00 dBm</p><p>2.403360000 GHz -3.69 dBm</p><p>2.420800000 GHz -4.13 dBm</p><p>Center 2.412 GHz 4 MHz/ Span 40 MHz</p><p>Date: 1.SEP.2026 16:26:58</p></div>
802.11n-HT20-Middle	<div><p>Ref 20 dBm *Att 30 dB SWT 2.5 ms</p><p>Marker 1 [T1] 2.434680000 GHz</p><p>dBm [T1] 0.00 dBm</p><p>SW 17.600000000 MHz</p><p>Temp 1 [T1] 0.00 dBm</p><p>2.428200000 GHz -5.09 dBm</p><p>2.445800000 GHz -4.58 dBm</p><p>Center 2.437 GHz 4 MHz/ Span 40 MHz</p><p>Date: 1.SEP.2026 16:27:15</p></div>
802.11n-HT20-High	<div><p>Ref 20 dBm *Att 30 dB SWT 2.5 ms</p><p>Marker 1 [T1] 2.464720000 GHz</p><p>dBm [T1] 0.00 dBm</p><p>SW 17.680000000 MHz</p><p>Temp 1 [T1] 0.00 dBm</p><p>2.459200000 GHz -5.41 dBm</p><p>2.470800000 GHz -4.39 dBm</p><p>Center 2.462 GHz 4 MHz/ Span 40 MHz</p><p>Date: 1.SEP.2026 16:27:31</p></div>




<div data-bbox="175 477 421 510" data-label="Section-Header"> <h2>802.11ax-HE20-Low</h2> </div>	<div data-bbox="635 235 1193 672" data-label="Figure"> </div> <div data-bbox="635 721 847 745" data-label="Text"> <p>Date: 1.SEP.2026 16:28:07</p> </div>
<div data-bbox="175 1014 421 1046" data-label="Section-Header"> <h2>802.11ax-HE20-Middle</h2> </div>	<div data-bbox="635 761 1193 1209" data-label="Figure"> </div> <div data-bbox="635 1256 847 1281" data-label="Text"> <p>Date: 1.SEP.2026 16:28:27</p> </div>
<div data-bbox="175 1556 421 1590" data-label="Section-Header"> <h2>802.11ax-HE20-High</h2> </div>	<div data-bbox="635 1296 1193 1744" data-label="Figure"> </div> <div data-bbox="635 1794 847 1816" data-label="Text"> <p>Date: 1.SEP.2026 16:28:54</p> </div>




APPENDIX C

Test Mode	Frequency MHz	Reading dBm	Limit dBm
802.11b _ 1Mbps	2412	15.21	30.00
	2437	14.08	30.00
	2462	14.65	30.00
802.11g_6Mbps	2412	14.20	30.00
	2437	14.06	30.00
	2462	13.65	30.00
802.11n HT20_MCS0	2412	13.07	30.00
	2437	13.21	30.00
	2462	12.61	30.00
802.11ax HE20_MCS0	2412	12.47	30.00
	2437	12.69	30.00
	2462	12.48	30.00

802.11b-Low	<div><p>Date: 1.SEP.2026 15:41:52</p></div>
802.11b-Middle	<div><p>Date: 1.SEP.2026 15:43:01</p></div>
802.11b-High	<div><p>Date: 1.SEP.2026 15:43:37</p></div>

<p>802.11g-Low</p>	<div data-bbox="644 232 1198 488"></div> <p>Date: 1.SEP.2026 15:45:18</p>
<p>802.11g-Middle</p>	<div data-bbox="644 772 1198 1028"></div> <p>Date: 1.SEP.2026 15:46:12</p>
<p>802.11g-High</p>	<div data-bbox="644 1312 1198 1568"></div> <p>Date: 1.SEP.2026 15:47:18</p>




802.11n-HT20-Low	<div><p>Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 300 kHz VBW: 1 MHz SWT: 2.5 ms</p><p>Center: 2.412 GHz Span: 30 MHz</p><p>Tx Channel Bandwidth: 20 MHz Power: 13.07 dBm</p><p>Date: 1.SEP.2026 15:48:17</p></div>
802.11n-HT20-Middle	<div><p>Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 300 kHz VBW: 1 MHz SWT: 2.5 ms</p><p>Center: 2.437 GHz Span: 30 MHz</p><p>Tx Channel Bandwidth: 20 MHz Power: 13.21 dBm</p><p>Date: 1.SEP.2026 15:49:01</p></div>
802.11n-HT20-High	<div><p>Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 300 kHz VBW: 1 MHz SWT: 2.5 ms</p><p>Center: 2.462 GHz Span: 30 MHz</p><p>Tx Channel Bandwidth: 20 MHz Power: 12.61 dBm</p><p>Date: 1.SEP.2026 15:49:17</p></div>

802.11ax-HE20-Low	<div><p>Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 300 kHz VBW: 1 MHz SWT: 2.5 ms</p><p>Center: 2.412 GHz Span: 30 MHz 3 MHz/</p><p>Tx Channel Bandwidth: 20 MHz Power: 12.47 dBm</p></div> <p>Date: 1.SEP.2026 15:49:48</p>
802.11ax-HE20-Middle	<div><p>Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 300 kHz VBW: 1 MHz SWT: 2.5 ms</p><p>Center: 2.437 GHz Span: 30 MHz 3 MHz/</p><p>Tx Channel Bandwidth: 20 MHz Power: 12.69 dBm</p></div> <p>Date: 1.SEP.2026 15:50:08</p>
802.11ax-HE20-High	<div><p>Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 300 kHz VBW: 1 MHz SWT: 2.5 ms</p><p>Center: 2.462 GHz Span: 30 MHz 3 MHz/</p><p>Tx Channel Bandwidth: 20 MHz Power: 12.48 dBm</p></div> <p>Date: 1.SEP.2026 15:50:23</p>



APPENDIX D

Conducted Out of Band Emissions


<p>802.11b-Low</p>	<div data-bbox="646 405 1198 842"></div> <p>Date: 1.SEP.2026 16:30:52</p>
	<div data-bbox="646 943 1198 1379"></div> <p>Date: 1.SEP.2026 16:31:32</p>
<p>802.11b-Middle</p>	<div data-bbox="646 1485 1198 1921"></div> <p>Date: 1.SEP.2026 16:32:03</p>




	<div><p>Date: 1.SEP.2026 16:32:22</p></div>
802.11b-High	<div><p>Date: 1.SEP.2026 16:32:53</p></div>
	<div><p>Date: 1.SEP.2026 16:33:06</p></div>

802.11g-Low




802.11g-High







	<div><p>Date: 1.SEP.2026 16:34:51</p></div>
802.11g-High	<div><p>Date: 1.SEP.2026 16:35:26</p></div>
	<div><p>Date: 1.SEP.2026 16:35:38</p></div>

802.11n-HT20-Low




802.11n-HT20-Middle








	<div><p>Date: 1.SEP.2026 16:37:54</p></div>
802.11n-HT20-High	<div><p>Date: 1.SEP.2026 16:38:21</p></div>
	<div><p>Date: 1.SEP.2026 16:38:34</p></div>

802.11ax-HE20-Low



802.11ax-HE20-Middle



	<div><p>Date: 1.SEP.2026 16:40:06</p></div>
802.11ax-HE20-High	<div><p>Date: 1.SEP.2026 16:40:35</p></div>
	<div><p>Date: 1.SEP.2026 16:40:46</p></div>

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****