

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.249

Report Reference No..... : MAX26080086P1-R01

FCC ID..... : 2BX3C-SREST1

Compiled by
(position+printed name+signature)..: Engineer/ Cindy Zheng

Supervised by
(position+printed name+signature)..: Manager/Haley Wen

Approved by
(position+printed name+signature)..: RF Manager/ Vivian Jiang

Date of issue.....: September 4, 2026

Cindy Zheng

Haley Wen

Vivian Jiang

Testing Laboratory Name.....: MAXLAB Testing Co.,Ltd.

Address.....: 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District,
Shenzhen, Guangdong, 518052, People' s Republic of China

Applicant's name.....: Gbeing Smart Ag Co., Ltd.

Address.....: Room 503, Block A, Wanhe Technology Building, No.7 Huitong Road,
Fenghuang Street, Guangming, Shenzhen, China

Test specification..... :

FCC CFR Title 47 Part 15 Subpart C Section 15.249

Standard.....: **ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to
C63.10a-2024**

MAXLAB Testing Co.,Ltd.All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment description.....: remote control of Light Stand

Trade Mark.....: N/A

Manufacturer.....: Gbeing Smart Ag Co., Ltd.

Model/Type reference.....: SREST-1

Listed Models: ET01, EX-RLT-STAND02, PTEST-1, PTEST-L, PTEST-S,
SREST-L, SREST-S, SSEST-L, SSEST-S, EST-L, EST-S, STAND

Modulation: GFSK

Frequency.....: 2404MHz- 2455MHz

Rating.....: DC 3.0V

Result.....: **PASS**

TEST REPORT

Equipment under Test : remote control of Light Stand

Model /Type : SREST-1

Listed Models : ET01, EX-RLT-STAND02, PTEST-1, PTEST-L, PTEST-S, SREST-L, SREST-S, SSEST-L, SSEST-S, EST-L, EST-S, STAND

Model Declaration : All the models are electrical identical including the same software parameter and hardware design, same mechanical structure and design, the only difference is the model named different.

Applicant : Gbeing Smart Ag Co., Ltd.

Address : Room 503, Block A, Wanhe Technology Building, No.7 Huitong Road, Fenghuang Street, Guangming, Shenzhen, China

Manufacturer : Gbeing Smart Ag Co., Ltd.

Address : Room 503, Block A, Wanhe Technology Building, No.7 Huitong Road, Fenghuang Street, Guangming, Shenzhen, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 TEST STANDARDS	4
2 SUMMARY	5
2.1 General Remarks	5
2.2 Product Description	5
2.3 Equipment Under Test	5
2.4 Short description of the Equipment under Test (EUT)	5
2.5 EUT operation mode	6
2.6 Block Diagram of Test Setup	6
2.7 Related Submittal(s) / Grant (s)	6
2.8 Modifications	6
3 TEST ENVIRONMENT	7
3.1 Address of the test laboratory	7
3.2 Test Facility	7
3.3 Environmental conditions	7
3.4 Summary of measurement results	8
3.5 Statement of the measurement uncertainty	8
3.6 Equipments Used during the Test	9
4 TEST CONDITIONS AND RESULTS	11
4.1 AC Power Conducted Emission	11
4.2 Radiated Emissions	12
4.3 Fundamental & Band Edge	18
4.4 Channel Bandwidth	22
4.5 Antenna Requirement	25
4.6 On Time, Duty Cycle and Measurement methods	26
5 TEST SETUP PHOTOS OF THE EUT	27
6 PHOTOS OF THE EUT	28

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz and 24.0-24.25 GHz
[ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	August 19, 2026
Testing commenced on	:	August 19, 2026
Testing concluded on	:	September 4, 2026

2.2 Product Description

Product Description:	remote control of Light Stand
Model/Type reference:	SREST-1
Listed Models:	ET01, EX-RLT-STAND02, PTEST-1, PTEST-L, PTEST-S, SREST-L, SREST-S, SSEST-L, SSEST-S, EST-L, EST-S, STAND
Rating:	DC 3.0V
Testing sample ID:	MAX26080086P1-R01-1# (Engineer sample) MAX26080086P1-R01-2# (Normal sample)
2.4G	
Supported type:	2.4G
Modulation:	GFSK
Operation frequency:	2404MHz, 2439MHz, 2455MHz
Channel number:	3
Antenna type:	PCB antenna
Antenna gain:	1.78 dBi

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☒ 3.0V DC	☐ 24 V DC
		☐ Other (specified in blank below)	

2.4 Short description of the Equipment under Test (EUT)

This is a remote control of Light Stand.
For more details, refer to the user's manual of the EUT.


2.5 EUT operation mode

The Applicant provides the product emits signals through buttons to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 3 channels provided to the EUT.

Operation Frequency:

Channel	Frequency (MHz)
01	2404
02	2439
03	2455

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

MAXLAB Testing Co.,Ltd.

1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052,
People's Republic of China

3.2 Test Facility

FCC-Registration No.: 562200 Designation Number: CN1338

MAXLAB Testing Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

Industry Canada Registration Number. Is: 11093A CAB identifier: CN0019

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

A2LA-Lab Cert. No.: 4707.01

MAXLAB Testing Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	23 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	47 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	46 %
Atmospheric pressure:	950-1050mbar

3.4 Summary of measurement results

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	N/A	
FCC part 15.209	Radiated Spurious Emission Measurement	PASS	
FCC part 15.219	20dB Channel Bandwidth	PASS	
FCC part 15.249 FCC part 15.205 FCC part 15.209	Fundamental & Band Edge	PASS	

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report
3. “ N/A ” denotes test is not applicable in this Test Report

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1” and TR-100028-02 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 “ and is documented in the MAXLAB Testing Co.,Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for MAXLAB Testing Co.,Ltd.:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.82 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Transmitter power conducted	1~40GHz	0.57 dB	(1)
Conducted spurious emission	1~40GHz	1.60 dB	(1)
OBW	1~40GHz	25 Hz	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Conducted Emission					
Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	BSL252	2025-10-27	2026-10-26
EMI Test Receiver	R&S	ESCI 7	BSL552	2025-10-27	2026-10-26
Coaxial Switch	ANRITSU CORP	MP59B	BSL225	2025-10-27	2026-10-26
ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	BSL226	2025-10-27	2026-10-26
Coaxial Cable	BSL	N/A	BSL227	N/A	N/A
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Thermo meter	KTJ	TA328	BSL233	2025-10-27	2026-10-26
Absorbing clamp	Elektronik-Feinmechanik	MDS21	BSL229	2025-10-27	2026-10-26
LISN	R&S	ENV216	308	2025-10-27	2026-10-26
LISN	R&S	ENV216	314	2025-10-27	2026-10-26

Radiation Test equipment					
Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	BSL250	2025-10-27	2026-10-26
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	BSL251	N/A	N/A
EMI Test Receiver	Rohde & Schwarz	ESU26	BSL203	2025-10-27	2026-10-26
BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	BSL214	2025-10-27	2026-10-26
Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	BSL208	2025-10-27	2026-10-26
Horn Antenna	ETS-LINDGREN	3160	BSL217	2025-10-27	2026-10-26
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Coaxial Cable	BSL	N/A	BSL213	2025-10-27	2026-10-26
Coaxial Cable	BSL	N/A	BSL211	2025-10-27	2026-10-26
Coaxial cable	BSL	N/A	BSL210	2025-10-27	2026-10-26
Coaxial Cable	BSL	N/A	BSL212	2025-10-27	2026-10-26
Amplifier(100kHz-3GHz)	HP	8347A	BSL204	2025-10-27	2026-10-26
Amplifier(2GHz-20GHz)	HP	84722A	BSL206	2025-10-27	2026-10-26
Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	BSL218	2025-10-27	2026-10-26
Band filter	Amindeon	82346	BSL219	2025-10-27	2026-10-26
Power Meter	Anritsu	ML2495A	BSL540	2025-10-27	2026-10-26
Power Sensor	Anritsu	MA2411B	BSL541	2025-10-27	2026-10-26

Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	BSL575	2025-10-27	2026-10-26
Splitter	Agilent	11636B	BSL237	2025-10-27	2026-10-26
Loop Antenna	ZHINAN	ZN30900A	BSL534	2025-10-27	2026-10-26
Breitband hornantenne	SCHWARZBECK	BBHA 9170	BSL579	2025-10-27	2026-10-26
Amplifier	TDK	PA-02-02	BSL574	2025-10-27	2026-10-26
Amplifier	TDK	PA-02-03	BSL576	2025-10-27	2026-10-26
PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	BSL578	2025-10-27	2026-10-26
Antenna tower	SKET	BK-4AT	BSL589	2025-10-27	2026-10-26


RF Conducted Test:

Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
MXA Signal Analyzer	Agilent	N9020A	BSL566	2025-10-27	2026-10-26
EMI Test Receiver	R&S	ESCI 7	BSL552	2025-10-27	2026-10-26
Spectrum Analyzer	Agilent	E4440A	BSL533	2025-10-27	2026-10-26
MXG vector Signal Generator	Agilent	N5182A	BSL567	2025-10-27	2026-10-26
ESG Analog Signal Generator	Agilent	E4428C	BSL568	2025-10-27	2026-10-26
USB RF Power Sensor	DARE	RPR3006W	BSL569	2025-10-27	2026-10-26
RF Switch Box	Shongyi	RFSW3003328	BSL571	2025-10-27	2026-10-26
Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	BSL572	2025-10-27	2026-10-26

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


TEST RESULTS

The EUT is powered by the Battery, So this test item is not applicable for the EUT.


4.2 Radiated Emissions

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 2420MHz and maximum operation frequency was 2420MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500


TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. 2.4G were tested at Low, Middle, and High channel and recorded worst mode at 2.4G 1Mbps.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz





GFSK (above 1GHz)

Frequency(MHz):			2404			Peak value		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4808	56.54	21.52	3.52	33.12	48.46	74	-25.54	Vertical
4808	51.23	23.65	4.56	33.08	46.36	74	-27.64	Vertical
7212	46.34	25.58	6.15	33.57	44.5	74	-29.5	Horizontal
7212	41.65	27.68	6.98	33.26	43.05	74	-30.95	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4808	45.85	21.52	3.52	33.12	37.77	54	-16.23	Horizontal
4808	41.47	23.65	4.56	33.08	36.6	54	-17.4	Horizontal
7212	35.65	25.58	6.15	33.57	33.81	54	-20.19	Vertical
7212	30.45	27.68	6.98	33.26	31.85	54	-22.15	Vertical

Frequency(MHz):			2439			Peak value		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4878	56.42	21.78	3.58	33.27	48.51	74	-25.49	Horizontal
4878	51.24	24.15	4.57	33.87	46.09	74	-27.91	Horizontal
7317	45.63	26.04	6.24	33.19	44.72	74	-29.28	Vertical
7317	41.36	27.98	7.18	33.68	42.84	74	-31.16	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4878	46.74	21.78	3.58	33.27	38.83	54	-15.17	Horizontal
4878	41.32	24.15	4.57	33.87	36.17	54	-17.83	Horizontal
7317	36.63	26.04	6.24	33.19	35.72	54	-18.28	Vertical
7317	31.36	27.98	7.18	33.68	32.84	54	-21.16	Vertical

Frequency(MHz):			2455			Peak value		
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4910	55.42	22.56	4.17	33.75	48.4	74	-25.6	Horizontal
4910	51.63	24.78	5.36	33.17	48.6	74	-25.4	Horizontal
7365	45.65	27.14	6.97	33.62	46.14	74	-27.86	Vertical
7365	41.36	28.16	7.65	33.58	43.59	74	-30.41	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4910	45.85	22.56	4.17	33.75	38.83	54	-15.17	Horizontal
4910	41.63	24.78	5.36	33.17	38.6	54	-15.4	Horizontal
7365	35.65	27.14	6.97	33.62	36.14	54	-17.86	Vertical
7365	31.42	28.16	7.65	33.58	33.65	54	-20.35	Vertical

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

4.3 Fundamental & Band Edge

4.3.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205 and 15.249				
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation

4.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function/Average Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.3.3 DEVIATION FROM TEST STANDARD

No deviation

4.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



4.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.3.6 TEST RESULT

2404MHz Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	55.12	21.25	3.26	33.14	46.49	74	-27.51	Horizontal
2400	53.41	21.75	3.54	33.42	45.28	74	-28.72	Horizontal
2310	51.26	21.25	3.26	33.14	42.63	74	-31.37	Vertical
2400	48.66	21.75	3.54	33.42	40.53	74	-33.47	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	53.32	21.25	3.26	33.14	44.69	54	-9.31	Horizontal
2400	51.24	21.75	3.54	33.42	43.11	54	-10.89	Horizontal
2310	48.63	21.25	3.26	33.14	40	54	-14	Vertical
2400	45.36	21.75	3.54	33.42	37.23	54	-16.77	Vertical

2455MHz Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	54.63	22.12	3.65	33.54	46.86	74	-27.14	Horizontal
2500	53.24	22.35	3.98	33.27	46.3	74	-27.7	Horizontal
2483.5	52.24	22.12	3.65	33.54	44.47	74	-29.53	Vertical
2500	49.65	22.35	3.98	33.27	42.71	74	-31.29	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	51.32	22.12	3.65	33.54	43.55	54	-10.45	Horizontal
2500	50.24	22.35	3.98	33.27	43.3	54	-10.7	Horizontal
2483.5	47.65	22.12	3.65	33.54	39.88	54	-14.12	Vertical
2500	45.34	22.35	3.98	33.27	38.4	54	-15.6	Vertical

Remark: Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
All of the restriction bands were tested, and only the data of worst case was exhibited.

Measurement data:

Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2404	100.52	22.55	3.25	33.45	92.87	114	-21.13	Horizontal
2404	98.65	22.55	3.25	33.45	91.00	114	-23.00	Vertical
2439	96.41	23.05	3.36	33.15	89.67	114	-24.33	Horizontal
2439	95.65	23.05	3.36	33.15	88.91	114	-25.09	Vertical
2455	93.24	23.57	3.67	33.68	86.80	114	-27.20	Horizontal
2455	91.74	23.57	3.67	33.68	85.30	114	-28.70	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2404	91.62	22.55	3.25	33.45	83.97	94	-10.03	Horizontal
2404	88.65	22.55	3.25	33.45	81	94	-13.00	Vertical
2439	86.65	23.05	3.36	33.15	79.91	94	-14.09	Horizontal
2439	84.63	23.05	3.36	33.15	77.89	94	-16.11	Vertical
2455	82.64	23.57	3.67	33.68	76.2	94	-17.80	Horizontal
2455	81.09	23.57	3.67	33.68	74.65	94	-19.35	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

4.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.215
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

4.4.1 Applied procedures / limit

FCC Part15 (15.215) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.215	Bandwidth	2400-2483.5	PASS

4.4.2 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.4.3 DEVIATION FROM STANDARD

No deviation.

4.4.4 TEST SETUP




4.4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.4.6 TEST RESULTS

Temperature:	26℃	Relative Humidity:	54%
Test Mode :	GFSK	Test Voltage :	DC 3.0V

Test channel	Channel Bandwidth (MHz)	Result
2404MHz	0.955	Pass
2439MHz	0.955	Pass
2455MHz	0.960	Pass



Lowest channel



Middle channel



Highest channel

4.5 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

Antenna Connected Construction

The maximum gain of antenna was 1.78dBi.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, MAXLAB Testing Co.,Ltd. does not assume any responsibility.

4.6 On Time, Duty Cycle and Measurement methods

Limit

None; for reporting purposes only.

Test Procedure




KDB 789033 Zero-Span Spectrum Analyzer Method.

Test Configuration





Test Result and Data

Condition	Mode	Frequency(MHz)	Ton(ms)	Toff(ms)	TP(ms)	Duty Cycle(%)	Duty Factor(dB)
NVNT	1M,PHY	2404	1.400	0.000	1.400	100.00	0.00
NVNT	1M,PHY	2439	1.400	0.000	1.400	100.00	0.00
NVNT	1M,PHY	2455	1.400	0.000	1.400	100.00	0.00



5 Test Setup Photos of the EUT



6 Photos of the EUT

Reference to the report ANNEX A of external photos and ANNEX B of internal photos.

***** End of Report *****