



REPORT No.: SZ26050223W02

TEST REPORT

APPLICANT : Rokk Inc.

PRODUCT NAME : Rokk

MODEL NAME : Rokk A1

BRAND NAME : Rokk

FCC ID : 2BX3SROKK-A1

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2026-05-18

TEST DATE : 2026-06-29 to 2026-09-02

ISSUE DATE : 2026-10-14



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Hopping Mechanism	15
3.3. Number of Hopping Frequency	16
3.4. Duty Cycle of Test Signal	17
3.5. Maximum Peak Conducted Output Power	18
3.6. Maximum Average Conducted Output Power	19
3.7. 20 dB Bandwidth	20
3.8. Carried Frequency Separation	21
3.9. Time of Occupancy (Dwell time)	22
3.10. Conducted Spurious Emissions and Band Edge	23
3.11. Conducted Emission	24
3.12. Restricted Frequency Bands	25
3.13. Radiated Emission	26



REPORT No.: SZ26050223W02

Annex A Test Data and Result 28

Notes 105

Change History		
Version	Date	Reason for change
1.0	2026-10-14	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	15.247(a) 15.247(h)	Hopping Mechanism	N/A	N/A	PASS	/
3	15.247(a)	Number of Hopping Frequency	Jul. 17, 2026	Li Xinpeng	PASS	/
4	ANSI C63.10	Duty Cycle	Jul. 17, 2026	Li Xinpeng	PASS	/
5	15.247(b)	Maximum Peak Conducted Output Power	Jul. 09, 2026	Li Xinpeng	PASS	/
6	15.247(b)	Maximum Average Conducted Output Power	Jul. 09, 2026	Li Xinpeng	PASS	/
7	15.247(a)	20dB Bandwidth	Jul. 09, 2026	Li Xinpeng	PASS	/
8	15.247(a)	Carrier Frequency Separation	Jul. 17, 2026	Li Xinpeng	PASS	/
9	15.247(a)	Time of Occupancy (Dwell time)	Jul. 17, 2026	Li Xinpeng	PASS	/
10	15.247(d)	Conducted Spurious Emission and Band Edge	Jul. 17, 2026	Li Xinpeng	PASS	/
11	15.207	Conducted Emission	Jun. 29, 2026	Wang Yapeng	PASS	/
12	15.247(d)	Restricted Frequency Bands	Jul. 13, 2026	Tian Xin	PASS	/
13	15.209, 15.247(d)	Radiated Emission	Jul. 13, 2026	Tian Xin	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020, KDB 558074 D01 v05r02 and DA 00-075.



Note 2: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.12.23	2026.12.22
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2026.05.07	2027.05.06
LISN	103131	ENV 216	R&S	2026.03.18	2027.03.17
RF Coaxial Cable (DC-100MHz)	EMC-CE-00514	N/A	N/A	2026.05.06	2027.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2026.04.28	2027.04.27
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2026.06.28	2027.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2026.05.09	2027.05.08
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2026.05.30	2027.05.29
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2026.05.30	2027.05.29
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2026.05.07	2027.05.06
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2026.05.07	2027.05.06
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2026.05.07	2027.05.06
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2025.09.03	2026.09.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Number of Hopping Frequency	±5%	Confidence levels of 95%
Peak Output Power	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Carrier Frequency Separation	±5%	Confidence levels of 95%
Time of Occupancy (Dwell time)	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Rokk Inc.
Applicant Address:	2450 Colorado Avenue Suite 100E Santa Monica CA 90404 USA
Manufacturer:	Zhuhai Fenda Technology Co., Ltd.
Manufacturer Address:	3/F Building 3, 3/F Building 4, Building 5, 629 Damen Road, Sanzao Town, Jinwan District, Zhuhai City

2.2. Information of EUT

Product Name:	Rokk
Sample No.:	1#, 15#, 16#
Hardware Version:	Rokk
Software Version:	V1.0
Equipment Type:	Bluetooth classic
Bluetooth Version:	5.2
Modulation Type:	FHSS (GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))
Operating Frequency Range:	2402MHz-2480MHz
Antenna Type:	Chip Antenna
Antenna Gain:	2.23dBi

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☒ Chip Antenna ☐ PIFA Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☒ Layout



3.2. Hopping Mechanism

3.2.1. Requirement

According to FCC section 15.247(a)(1), a frequency hopping spread spectrum system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to FCC section 15.247(h), the incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3.2.2. Test Result

The hopping mechanism of the EUT is in compliance with the document "**Bluetooth core specification v5.1**".



3.3. Number of Hopping Frequency

3.3.1. Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

3.3.2. Test Procedures

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.1 in this report.

3.4. Duty Cycle of Test Signal

3.4.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.4.2. Test Result

Refer to Annex A.2 in this report.



3.5. Maximum Peak Conducted Output Power

3.5.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.5.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.3 in this report.



3.6. Maximum Average Conducted Output Power

3.6.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.6.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.4 in this report.



3.7.20 dB Bandwidth

3.7.1.Requirement

According to FCC section 15.247(a)(1), the 20 dB bandwidth is known as the 99% emission bandwidth, or 20 dB bandwidth ($10 \cdot \log 1\% = 20 \text{ dB}$) taking the total RF output power.

3.7.1.Test Procedures

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW, centered on the test channel

RBW= 1% to 5% of the OBW

VBW $\geq 3 \times$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

3.7.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.3.Test Result

Refer to Annex A.5 in this report.



3.8. Carried Frequency Separation

3.8.1. Requirement

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

3.8.2. Test Procedures

The EUT must have its hopping function enabled. According to DA 00-705, use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.8.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.8.4. Test Result

Refer to Annex A.6 in this report.



3.9. Time of Occupancy (Dwell time)

3.9.1. Requirement

According to FCC section 15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.9.2. Test Procedures

Normal Mode:

DH1: Dwell time equal to Pulse time (ms) $\times (1600 / 2 / 79) \times 31.6$ Millisecond
DH3: Dwell time equal to Pulse time (ms) $\times (1600 / 4 / 79) \times 31.6$ Millisecond
DH5: Dwell time equal to Pulse Time (ms) $\times (1600 / 6 / 79) \times 31.6$ Millisecond

AFH Mode:

DH1: Dwell time equal to Pulse time (ms) $\times (800 / 2 / 20) \times (0.4 \times 20)$ Millisecond
DH3: Dwell time equal to Pulse time (ms) $\times (800 / 4 / 20) \times (0.4 \times 20)$ Millisecond
DH5: Dwell time equal to Pulse Time (ms) $\times (800 / 6 / 20) \times (0.4 \times 20)$ Millisecond.

3.9.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.9.4. Test Result

Refer to Annex A.7 in this report.



3.10. Conducted Spurious Emissions and Band Edge

3.10.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.10.2.Test Procedures

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

3.10.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.10.4.Test Result

Refer to Annex A.8 and A.9 in this report.

3.11. Conducted Emission

3.11.1.Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.11.2.Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

3.11.3.Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.11.4.Test Result

Refer to Annex A.10 in this report.

3.12. Restricted Frequency Bands

3.12.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.12.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.12.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.12.4.Test Result

Refer to Annex A.11 in this report.

3.13. Radiated Emission

3.13.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.13.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.13.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.13.4.Test Result


Refer to Annex A.12 in this report.




Annex A Test Data and Result

A.1. Number of Hopping Frequency


Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass



Hopping No. NVNT 1-DH5 2441MHz Ant1




Hopping No. NVNT 2-DH5 2441MHz Ant1




**A.2. Duty Cycle of Test Signal**


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	1-DH5	2402	Ant1	77.04	1.13	0.35
NVNT	1-DH5	2441	Ant1	77.04	1.13	0.35
NVNT	1-DH5	2480	Ant1	77.01	1.13	0.35
NVNT	2-DH5	2402	Ant1	76.03	1.19	0.35
NVNT	2-DH5	2441	Ant1	76.03	1.19	0.35
NVNT	2-DH5	2480	Ant1	76.03	1.19	0.35
NVNT	3-DH5	2402	Ant1	77.15	1.13	0.35
NVNT	3-DH5	2441	Ant1	77.15	1.13	0.35
NVNT	3-DH5	2480	Ant1	77.15	1.13	0.35




Duty Cycle NVNT 1-DH5 2402MHz Ant1




Duty Cycle NVNT 1-DH5 2441MHz Ant1




Duty Cycle NVNT 1-DH5 2480MHz Ant1




Duty Cycle NVNT 2-DH5 2402MHz Ant1




Duty Cycle NVNT 2-DH5 2441MHz Ant1




Duty Cycle NVNT 2-DH5 2480MHz Ant1



Duty Cycle NVNT 3-DH5 2402MHz Ant1



Duty Cycle NVNT 3-DH5 2441MHz Ant1



**A.3. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	5.3	0	5.3	0.00339	30	Pass
NVNT	1-DH5	2441	Ant1	5.11	0	5.11	0.00324	30	Pass
NVNT	1-DH5	2480	Ant1	3.79	0	3.79	0.00239	30	Pass
NVNT	2-DH5	2402	Ant1	2.8	0	2.8	0.00191	30	Pass
NVNT	2-DH5	2441	Ant1	2.74	0	2.74	0.00188	30	Pass
NVNT	2-DH5	2480	Ant1	3.13	0	3.13	0.00206	30	Pass
NVNT	3-DH5	2402	Ant1	3.26	0	3.26	0.00212	30	Pass
NVNT	3-DH5	2441	Ant1	3.18	0	3.18	0.00208	30	Pass
NVNT	3-DH5	2480	Ant1	3.55	0	3.55	0.00226	30	Pass




Peak Power NVNT 1-DH5 2402MHz Ant1




Peak Power NVNT 1-DH5 2441MHz Ant1




Peak Power NVNT 1-DH5 2480MHz Ant1




Peak Power NVNT 2-DH5 2402MHz Ant1




Peak Power NVNT 2-DH5 2441MHz Ant1




Peak Power NVNT 2-DH5 2480MHz Ant1



Peak Power NVNT 3-DH5 2402MHz Ant1



Peak Power NVNT 3-DH5 2441MHz Ant1




**A.4. Maximum Average Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	4.12	1.13	5.25	0.00335	30	Pass
NVNT	1-DH5	2441	Ant1	3.68	1.13	4.81	0.00303	30	Pass
NVNT	1-DH5	2480	Ant1	2.3	1.13	3.43	0.0022	30	Pass
NVNT	2-DH5	2402	Ant1	-0.65	1.19	0.54	0.00113	30	Pass
NVNT	2-DH5	2441	Ant1	-0.73	1.19	0.46	0.00111	30	Pass
NVNT	2-DH5	2480	Ant1	-0.31	1.19	0.88	0.00122	30	Pass
NVNT	3-DH5	2402	Ant1	-0.6	1.13	0.53	0.00113	30	Pass
NVNT	3-DH5	2441	Ant1	-0.62	1.13	0.51	0.00112	30	Pass
NVNT	3-DH5	2480	Ant1	-0.27	1.13	0.86	0.00122	30	Pass



Average Power NVNT 1-DH5 2402MHz Ant1




Average Power NVNT 1-DH5 2441MHz Ant1




Average Power NVNT 1-DH5 2480MHz Ant1




Average Power NVNT 2-DH5 2402MHz Ant1




Average Power NVNT 2-DH5 2441MHz Ant1




Average Power NVNT 2-DH5 2480MHz Ant1



Average Power NVNT 3-DH5 2402MHz Ant1



Average Power NVNT 3-DH5 2441MHz Ant1



**A.5. 20 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)
NVNT	1-DH5	2402	Ant1	0.9534
NVNT	1-DH5	2441	Ant1	0.9421
NVNT	1-DH5	2480	Ant1	0.9552
NVNT	2-DH5	2402	Ant1	1.325
NVNT	2-DH5	2441	Ant1	1.327
NVNT	2-DH5	2480	Ant1	1.34
NVNT	3-DH5	2402	Ant1	1.303
NVNT	3-DH5	2441	Ant1	1.306
NVNT	3-DH5	2480	Ant1	1.297



-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1




**A.6. Carried Frequency Separation**


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1- DH5	Ant1	2441.018	2442.072	1.054	0.628	Pass
NVNT	2- DH5	Ant1	2440.91	2442.172	1.262	0.885	Pass
NVNT	3- DH5	Ant1	2441.13	2442.134	1.004	0.871	Pass



CFS NVNT 1-DH5 2441MHz Ant1






CFS NVNT 2-DH5 2441MHz Ant1



**A.7. Time of Occupancy (Dwell time)**

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2441	Ant1	2.887	8.661	3	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.879	316.69	110	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.89	297.67	103	31600	400	Pass







Dwell NVNT 2-DH5 2441MHz Ant1 One Burst



Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst




Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated

**A.8. Conducted Spurious Emissions**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-54.45	-20	Pass
NVNT	1-DH5	2441	Ant1	-53.79	-20	Pass
NVNT	1-DH5	2480	Ant1	-54.39	-20	Pass
NVNT	2-DH5	2402	Ant1	-49.46	-20	Pass
NVNT	2-DH5	2441	Ant1	-48.92	-20	Pass
NVNT	2-DH5	2480	Ant1	-48.07	-20	Pass
NVNT	3-DH5	2402	Ant1	-49.19	-20	Pass
NVNT	3-DH5	2441	Ant1	-47.68	-20	Pass
NVNT	3-DH5	2480	Ant1	-49.07	-20	Pass




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission

**A.9. Band Edge**


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-60.06	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-61.21	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-52.92	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-56.13	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-54.28	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-54.27	-20	Pass
NVNT	1-DH5	2402	Ant1	Hopping	-53.81	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-60.43	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-54.42	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-54.19	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-53.63	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-55.06	-20	Pass




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission




Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission




Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission

**A.10. Conducted Emission**

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+Charge Cable+Notebook+Serial port board+BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.5055	38.76	34.95	56.00	46.00	Line	PASS
2	1.5134	36.17	32.11	56.00	46.00		PASS
3	2.1883	22.34	17.64	56.00	46.00		PASS
4	4.5326	32.04	26.98	56.00	46.00		PASS
5	25.8396	31.00	18.32	60.00	50.00		PASS
6	26.5096	34.12	20.43	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.5010	39.35	35.61	56.00	46.00	Neutral	PASS
2	2.1794	39.09	35.33	56.00	46.00		PASS
3	2.8498	37.02	32.98	56.00	46.00		PASS
4	3.1830	39.30	35.74	56.00	46.00		PASS
5	25.5820	47.07	33.35	60.00	50.00		PASS
6	26.1239	48.65	32.70	60.00	50.00		PASS


A.11. Restricted Frequency Bands

Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Horizontal) was recorded in this test report.

Note 2: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

GFSK Mode


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2345.04	4.8	37.11	32.350	54.00	16.89	155	124	AV	PASS
2350.67	17.2	49.55	32.400	74.00	24.45	155	105	PK	PASS
2362.94	4.7	37.10	32.450	54.00	16.90	155	233	AV	PASS
2374.45	18.4	50.90	32.490	74.00	23.10	155	271	PK	PASS
2378.70	4.7	37.25	32.510	54.00	16.75	155	12	AV	PASS
2389.21	17.7	50.19	32.540	74.00	23.81	155	281	PK	PASS



Plot for Channel 78




Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2484.09	5.0	38.06	33.030	54.00	15.94	155	71	AV	PASS
2485.71	17.1	50.11	33.030	74.00	23.89	155	322	PK	PASS
2488.10	4.9	37.90	33.020	54.00	16.10	155	97	AV	PASS
2489.22	17.7	50.70	33.020	74.00	23.30	155	163	PK	PASS
2491.60	18.0	51.06	33.020	74.00	22.94	155	266	PK	PASS
2491.85	4.9	37.90	33.020	54.00	16.10	155	79	AV	PASS



8-DPSK Mode


Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2312.76	17.4	49.43	32.040	74.00	24.57	155	138	PK	PASS
2341.67	4.8	37.12	32.320	54.00	16.88	155	340	AV	PASS
2344.54	17.5	49.81	32.350	74.00	24.19	155	61	PK	PASS
2364.44	4.8	37.22	32.450	54.00	16.78	155	194	AV	PASS
2370.94	17.4	49.91	32.470	74.00	24.09	155	243	PK	PASS
2381.70	4.7	37.20	32.510	54.00	16.80	155	262	AV	PASS



Plot for Channel 78



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2485.71	17.7	50.76	33.030	74.00	23.24	155	248	PK	PASS
2485.96	5.0	38.03	33.030	54.00	15.97	155	89	AV	PASS
2491.60	4.9	37.90	33.020	54.00	16.10	155	79	AV	PASS
2492.86	18.0	51.01	33.010	74.00	22.99	155	134	PK	PASS
2493.98	4.9	37.89	33.010	54.00	16.11	155	0	AV	PASS
2496.49	18.1	51.15	33.010	74.00	22.85	155	267	PK	PASS



A.12. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.


**GFSK Mode**

Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
105.90	68.5	38.07	-30.410	43.50	5.43	155	196	PK	PASS
213.31	67.3	37.59	-29.660	43.50	5.91	155	132	PK	PASS
224.95	69.5	40.49	-28.960	46.00	5.51	155	120	PK	PASS
250.00	70.8	42.67	-28.120	46.00	3.33	155	108	PK	PASS
532.08	57.9	36.51	-21.390	46.00	9.49	155	94	PK	PASS
799.82	55.1	38.49	-16.570	46.00	7.51	155	94	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2402.20	39.0	39.78	0.750	-	-	160	50	AV	NA
2402.20	45.3	46.06	0.750	-	-	160	284	PK	NA
3843.02	51.9	38.38	-13.500	54.00	15.62	160	188	AV	PASS
3843.02	56.5	43.03	-13.500	74.00	30.97	160	188	PK	PASS
13325.87	38.2	43.44	5.290	54.00	10.56	160	10	AV	PASS
13550.87	47.7	52.48	4.770	74.00	21.52	160	337	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
66.27	69.8	36.69	-33.100	40.00	3.31	155	11	PK	PASS
215.43	65.3	35.73	-29.530	43.50	7.77	155	178	PK	PASS
250.00	65.0	36.85	-28.120	46.00	9.15	155	62	PK	PASS
479.87	56.6	34.24	-22.330	46.00	11.76	155	317	PK	PASS
533.14	55.4	33.98	-21.390	46.00	12.02	155	26	PK	PASS
839.73	52.3	36.46	-15.810	46.00	9.54	155	190	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2402.20	34.0	34.71	0.750	-	-	160	316	AV	NA
3843.02	55.8	42.25	-13.500	54.00	11.75	160	214	AV	PASS
7974.14	52.1	48.74	-3.380	74.00	25.26	160	264	PK	PASS
11504.39	47.9	50.59	2.660	74.00	23.41	160	360	PK	PASS
12163.98	40.0	42.86	2.880	54.00	11.14	160	161	AV	PASS
13252.15	47.6	52.57	5.000	74.00	21.43	160	214	PK	PASS




Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
108.78	60.7	30.01	-30.680	43.50	13.49	155	286	PK	PASS
199.97	68.4	38.16	-30.220	43.50	5.34	155	109	PK	PASS
214.90	69.2	39.67	-29.570	43.50	3.83	155	146	PK	PASS
250.00	70.0	41.85	-28.120	46.00	4.15	155	84	PK	PASS
479.87	64.2	41.86	-22.330	46.00	4.14	155	184	PK	PASS
838.62	53.4	37.57	-15.830	46.00	8.43	155	46	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2440.78	44.4	45.44	1.020	-	-	160	47	PK	NA
2441.27	37.2	38.18	1.010	-	-	160	47	AV	NA
3905.60	52.6	39.45	-13.160	54.00	14.55	160	60	AV	PASS
4793.62	52.4	41.72	-10.700	54.00	12.28	160	338	AV	PASS
5320.35	55.6	46.72	-8.830	74.00	27.28	160	86	PK	PASS
13999.17	47.4	52.91	5.500	74.00	21.09	160	338	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
60.16	64.3	33.36	-30.970	40.00	6.64	155	136	PK	PASS
81.15	68.4	33.37	-35.020	40.00	6.63	155	111	PK	PASS
199.50	65.0	34.82	-30.130	43.50	8.68	155	123	PK	PASS
213.66	64.8	35.14	-29.630	43.50	8.36	155	150	PK	PASS
250.00	65.0	36.88	-28.120	46.00	9.12	155	136	PK	PASS
532.43	59.7	38.31	-21.390	46.00	7.69	155	358	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
3905.60	59.1	45.92	-13.160	74.00	28.08	160	213	PK	PASS
3905.60	56.7	43.55	-13.160	54.00	10.45	160	213	AV	PASS
4793.62	50.2	39.49	-10.700	54.00	14.51	160	61	AV	PASS
4794.05	54.3	43.63	-10.700	74.00	30.37	160	61	PK	PASS
11350.95	40.0	42.34	2.370	54.00	11.66	160	61	AV	PASS
13880.03	47.8	52.50	4.750	74.00	21.50	160	37	PK	PASS




Plot for Channel 78




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
108.78	60.5	29.77	-30.680	43.50	13.73	155	312	PK	PASS
207.31	67.4	37.34	-30.010	43.50	6.16	155	135	PK	PASS
224.95	69.2	40.27	-28.960	46.00	5.73	155	109	PK	PASS
250.00	70.5	42.40	-28.120	46.00	3.60	155	109	PK	PASS
533.20	58.1	36.76	-21.380	46.00	9.24	155	186	PK	PASS
835.91	54.1	38.19	-15.880	46.00	7.81	155	46	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.85	45.7	46.66	0.920	-	-	160	52	PK	NA
2479.85	39.7	40.64	0.920	-	-	160	52	AV	NA
3967.74	56.5	43.22	-13.250	74.00	30.78	160	197	PK	PASS
3967.74	52.8	39.54	-13.250	54.00	14.46	160	224	AV	PASS
4794.05	52.5	41.77	-10.700	54.00	12.23	160	275	AV	PASS
4794.05	55.2	44.51	-10.700	74.00	29.49	160	275	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
60.16	64.5	33.48	-30.970	40.00	6.52	155	61	PK	PASS
81.15	68.9	33.90	-35.020	40.00	6.10	155	111	PK	PASS
215.60	65.5	35.93	-29.520	43.50	7.57	155	138	PK	PASS
250.00	65.1	36.95	-28.120	46.00	9.05	155	37	PK	PASS
532.43	55.6	34.16	-21.390	46.00	11.84	155	37	PK	PASS
835.38	52.0	36.10	-15.890	46.00	9.90	155	73	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2480.34	33.9	34.80	0.920	-	-	160	97	AV	NA
3967.74	54.6	41.37	-13.250	54.00	12.63	160	264	AV	PASS
3967.74	57.8	44.58	-13.250	74.00	29.42	160	264	PK	PASS
4747.34	53.3	42.94	-10.340	74.00	31.06	160	290	PK	PASS
4793.62	47.1	36.44	-10.700	54.00	17.56	160	340	AV	PASS
5320.35	53.6	44.73	-8.830	74.00	29.27	160	112	PK	PASS



Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.
5. Conformity declaration:
 - ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
 - ☐ Morlab issues a statement of conformity based on the applicant requirement
6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

————— END OF REPORT —————