



FCC RF Exposure

EUT Description: Electric Bicycle

Model No.: M12, M9, M8, M6

FCC ID: 2BX6D-M12

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,

Where:

Result = $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

	Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power (dBm /mW)	Min test separation distance (mm)	Result	Limit	SAR Test Exclusion
NFC	13.56	-79.57	-79 $\pm$ 1	-78/0.0000000158	5	0.000000000369	3.0	Pass

Note:

Max PK Output power(dBm) = 15.63(dBuV/m) - 95.2 = -79.57(dBm)

PK Output power = conducted power.

Conducted power see the test report **DLE-260910001R**, antenna gain = -18.2dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.000000000369 which is ≤ 3 , SAR testing is not required.

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

f(GHz) is the RF channel transmit frequency in GHz

Distance = 5mm