


Manual

Press and hold the power button and RGB button simultaneously within 20 seconds after turning on to pair with the 2.4G remote. The lights will flash once after



Color Temperature Memory:

First, select a common color temperature. Turn off the light for more than 15 seconds, then turn it back on. The color temperature will remain at the setting before turning off. If you turn it off for a short time (less than 15 seconds), the color temperature will switch automatically.

Wall switch logic function:

After the switch is turned off (the light is completely extinguished), turn the light on again. Generates white light, warm light, neutral light, dim light, RGB gradient, RGB rainbow light.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and

(2) This device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- - Reorient or relocate the receiving antenna.
- - Increase the separation between the equipment and receiver.
- - Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- - Consult the dealer or an experienced radio/TV technician for help.ct.

The device has been evaluated to meet general RF exposure requirement.