

TEST REPORT

Report No.: 8435EU120102W

Applicant: Jingtel (shenzhen) Technology Co., Ltd.

Address: 318-3 Area D, Floor 3, Building A, Tengfei Industrial Building, No.6 Taohua Road, Fubao Community, Fubao Street, Shenzhen Guangdong, 518045 China

Product Name: Y88 Camera Detector

Model No.: Y88 (refer to clause 2.4)

Trademark: N/A

FCC ID: 2BX6T-Y88

Test Standard(s): 47 CFR Part 15, Subpart B

Test Result: Pass

Date of Receipt: Sep. 01, 2026

Test Date: Sep. 02, 2026 - Sep. 04, 2026

Date of Issue: Sep. 10, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:

Peach Zheng

Peach Zheng/ Engineer

Reviewed and Approved by:

Sally Zhang

Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Sep. 10, 2026	Original	Valid



Table of Contents

1	COVER PAGE.....	1
2	GENERAL INFORMATION	4
2.1	APPLICANT INFORMATION	4
2.2	MANUFACTURER INFORMATION	4
2.3	FACTORY INFORMATION	4
2.4	GENERAL DESCRIPTION OF E.U.T.	4
2.5	TECHNICAL INFORMATION OF E.U.T.	4
3	TEST SUMMARY	5
3.1	TEST STANDARD	5
3.2	TEST VERDICT	5
3.3	TEST LABORATORY	5
4	TEST CONFIGURATION	6
4.1	TEST ENVIRONMENT	6
4.2	TEST EQUIPMENT	6
4.3	DESCRIPTION OF SUPPORT UNIT	7
4.4	TEST MODE	7
4.5	DESCRIPTION OF CALCULATION	7
4.5.1	Field Strength Calculation	7
4.5.2	Disturbance Calculation	7
4.6	MEASUREMENT UNCERTAINTY	8
4.7	DEVIATION FROM STANDARDS	8
4.8	ABNORMALITIES FROM STANDARD CONDITION	8
5	EMISSION TEST RESULTS (EMI)	9
5.1	CONDUCTED EMISSIONS ON AC MAINS	9
5.1.1	Test Specification	9
5.1.2	E.U.T. Operation	9
5.1.3	Test Setup Diagram	9
5.1.4	Test Data	9
5.2	RADIATED EMISSIONS (BELOW 1GHz)	12
5.2.1	Test Specification	12
5.2.2	E.U.T. Operation	12
5.2.3	Test Setup Diagram	12
5.2.4	Test Data	12
ANNEX A	TEST SETUP PHOTOS	15
ANNEX B	EXTERNAL PHOTOS	15
ANNEX C	INTERNAL PHOTOS	15

2 General Information

2.1 Applicant Information

Applicant	Jingtel (shenzhen) Technology Co., Ltd.
Address	318-3 Area D, Floor 3, Building A, Tengfei Industrial Building, No.6 Taohua Road, Fubao Community, Fubao Street, Shenzhen Guangdong, 518045 China

2.2 Manufacturer Information

Manufacturer	Jingtel (shenzhen) Technology Co., Ltd.
Address	318-3 Area D, Floor 3, Building A, Tengfei Industrial Building, No.6 Taohua Road, Fubao Community, Fubao Street, Shenzhen Guangdong, 518045 China

2.3 Factory Information

Factory	Jingtel (shenzhen) Technology Co., Ltd.
Address	318-3 Area D, Floor 3, Building A, Tengfei Industrial Building, No.6 Taohua Road, Fubao Community, Fubao Street, Shenzhen Guangdong, 518045 China

2.4 General Description of E.U.T.

Product Name	Y88 Camera Detector
Model No. Under Test	Y88
List Model No.	Y16, Y18, Y26, Y28, Y66, Y68
Description of Model differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in appearance color and model name. (this information provided by the customer)
Rating(s)	Input: 5VDC, 1A Battery Capacity: 3.7VDC, 130mAh, 0.481Wh
Test Sample No.	8435EU120102W-1/1
Hardware Version	N/A
Software Version	N/A
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Classification of equipment	Class B
F _x (Highest internal frequency)	1.705-108MHz
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

47 CFR Part 15, Subpart B: Unintentional Radiators

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

Test Items	Standard	Method	Requirement	Results
Conducted emissions on AC mains	47 CFR Part 15, Subpart B	ANSI C63.4a-2017	15.107, Class B	Pass
Radiated emissions (Below 1GHz)	47 CFR Part 15, Subpart B	ANSI C63.4a-2017	15.109, Class B	Pass
Note: (1) "N/A" denotes test is not applicable in this Test Report.				

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15°C to +35°C
Working Voltage of the EUT	NV (Normal Voltage)	120VAC, 60Hz for adapter or 3.7VDC battery inside

4.2 Test Equipment

Conducted emissions on AC mains					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
Test Software	Farad	EZ-EMC	EE-014	/	/
EMI Test Receiver	Rohde & Schwarz	ESCI	EE-005	2026-04-07	2027-04-06
L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	EE-004	2026-05-10	2027-05-09
8-Wire ISN CAT6	Schwarzbeck	NTFM 8158	EE-219	2026-05-18	2027-05-17

Radiated emissions (Below 1GHz)					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8447D	EE-009	2026-04-08	2027-04-07
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Band-Stop Filter	COM-MW	ZBSF6-C902-928-2389	EE-023	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	ZBSF6-C855-880-5938	EE-024	2026-04-07	2027-04-06

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Adapter	Apple	A1443	EMC-PJ-001

4.4 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned bellow was evaluated respectively.

No.	Test Modes	Description
TM1	Working Mode	Keep the EUT in working mode.

4.5 Description of Calculation

4.5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Item	Measurement Uncertainty
Conducted Emission	2.65 dB
Radiated Emission (30MHz- 1GHz)	2.76 dB

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Condition

None

5 Emission Test Results (EMI)

5.1 Conducted emissions on AC mains


5.1.1 Test Specification

Test Requirement:	15.107, Class B		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.4a-2017		
Procedure:	An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected. Remark: Level= Read Level+ Cable Loss+ LISN Factor		

5.1.2 E.U.T. Operation

Pre test mode:	TM1
Final test mode:	TM1

5.1.3 Test Setup Diagram




5.1.4 Test Data

PASS.

Only the worst case data was showed in the report, please to see the following pages.

Conducted emissions on AC mains Test Data


TM1 / Line: Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2220	49.06	0.09	49.15	62.74	-13.59	QP	P	
2 *	0.2220	44.85	0.09	44.94	52.74	-7.80	AVG	P	
3	0.5639	44.50	0.12	44.62	56.00	-11.38	QP	P	
4	0.5639	30.52	0.12	30.64	46.00	-15.36	AVG	P	
5	0.8430	38.41	0.11	38.52	56.00	-17.48	QP	P	
6	0.8430	27.11	0.11	27.22	46.00	-18.78	AVG	P	
7	2.2200	35.16	0.10	35.26	56.00	-20.74	QP	P	
8	2.2200	21.49	0.10	21.59	46.00	-24.41	AVG	P	
9	4.5870	27.59	0.09	27.68	56.00	-28.32	QP	P	
10	4.5870	14.80	0.09	14.89	46.00	-31.11	AVG	P	
11	12.3045	32.16	0.03	32.19	60.00	-27.81	QP	P	
12	12.3045	17.83	0.03	17.86	50.00	-32.14	AVG	P	

Conducted emissions on AC mains Test Data

TM1 / Line: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1882	51.14	0.09	51.23	64.12	-12.89	QP	P	
2 *	0.1882	46.34	0.09	46.43	54.12	-7.69	AVG	P	
3	0.5594	44.69	0.12	44.81	56.00	-11.19	QP	P	
4	0.5594	28.87	0.12	28.99	46.00	-17.01	AVG	P	
5	1.2795	38.39	0.10	38.49	56.00	-17.51	QP	P	
6	1.2795	26.57	0.10	26.67	46.00	-19.33	AVG	P	
7	3.8040	37.33	0.09	37.42	56.00	-18.58	QP	P	
8	3.8040	25.30	0.09	25.39	46.00	-20.61	AVG	P	
9	12.3945	37.55	0.03	37.58	60.00	-22.42	QP	P	
10	12.3945	23.10	0.03	23.13	50.00	-26.87	AVG	P	
11	18.3255	37.19	0.03	37.22	60.00	-22.78	QP	P	
12	18.3255	28.29	0.03	28.32	50.00	-21.68	AVG	P	

5.2 Radiated emissions (Below 1GHz)


5.2.1 Test Specification

Test Requirement:	15.109, Class B				
Test Limit:	Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:				
	Frequency of emission (MHz)	Field strength @3m		Field strength @10m	
		($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
	30 – 88	100	40	30	29.5
	88 – 216	150	43.5	45	33.1
	216 – 960	200	46	60	35.6
	Above 960	500	54	150	43.5
Test Method:	ANSI C63.4a-2017				
Procedure:	An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor				

5.2.2 E.U.T. Operation

Pre test mode:	TM1
Final test mode:	TM1

5.2.3 Test Setup Diagram




5.2.4 Test Data

PASS.

Only the worst case data was showed in the report, please to see the following pages.

Radiated emissions (Below 1GHz) Test Data


TM1 / Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	37.6796	27.05	-20.10	6.95	40.00	-33.05	QP	P	
2	79.8002	30.64	-21.76	8.88	40.00	-31.12	QP	P	
3	106.3850	30.42	-19.77	10.65	43.50	-32.85	QP	P	
4	210.0481	28.07	-18.92	9.15	43.50	-34.35	QP	P	
5	468.8761	27.92	-12.75	15.17	46.00	-30.83	QP	P	
6 *	896.9964	28.16	-5.94	22.22	46.00	-23.78	QP	P	

Radiated emissions (Below 1GHz) Test Data

TM1 / Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	39.8541	45.91	-19.93	25.98	40.00	-14.02	QP	P	
2	52.7600	38.40	-18.86	19.54	40.00	-20.46	QP	P	
3	93.7682	33.15	-20.43	12.72	43.50	-30.78	QP	P	
4	250.3010	28.89	-17.79	11.10	46.00	-34.90	QP	P	
5	590.9737	27.31	-9.43	17.88	46.00	-28.12	QP	P	
6	912.8620	29.76	-5.75	24.01	46.00	-21.99	QP	P	

Note: Level = Reading + Factor

Margin = Level - Limit

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8435EU120102W-ANNEX A.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8435EU120102W-ANNEX B.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8435EU120102W-ANNEX C.PDF"



STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---