Report No.: ET-26094793E01

TEST REPORT

Applicant:	SwiftForce Electronic Technology Co., Ltd.
Address of Applicant:	60 Qinglonggang Road, STE 1210 ,Xiangcheng District, Suzhou City, Jiangsu Province, China
Manufacturer:	SwiftForce Electronic Technology Co., Ltd.
Address of Manufacturer:	60 Qinglonggang Road, STE 1210 ,Xiangcheng District, Suzhou City, Jiangsu Province, China
Product Name:	POS System.
Model No.:	Eva-S01,Eva-B01,Eva-C01,Eva-G01, Eva-H01,Eva-K01, Eva-X01,Nova-A01, Nova-B01, Nova-E01, Nova-K01, Nova-M01, Nova-P01, Nova-Q01, Core-A01, Core-B01, Core-C01, Omni-K01, Omni-K02(The variations between the models in this application lie solely in their naming conventions, which are used to distinguish between different sales schemes and regional markets. These differences do not impact product safety or performance)
Trade Mark:	N/A
FCC ID:	2BX9S-EVA-S01
Applicable standards:	CFR Title 47 Part 15.247
Date of Test:	Sep.08, 2026-Sep.24, 2026
Date of report issued:	Sep.24, 2026

Remark:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:	Reviewed by:	Approved by:
Project Engineer	Project Manager	Authorized Signature

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen ETR Standard Technology Co., Ltd.

Report Revision History		
Report No.	Description	Issue Date
ET-26094793E01	Original	Sep.24, 2026

Contents

Page

1. TEST SUMMARY 4

2. GENERAL INFORMATION 5

2.1 GENERAL DESCRIPTION OF EUT 5
2.2 TEST MODE 7
2.3 DESCRIPTION OF SUPPORT UNITS 7
2.4 TEST FACILITY 7
2.5 ADDITIONAL INSTRUCTIONS 7

3. TEST INSTRUMENTS LIST 8

4. TEST RESULTS AND MEASUREMENT DATA 9

4.1 ANTENNA REQUIREMENT 9
4.2 CONDUCTED EMISSIONS 10
4.3 DUTY CYCLE 13
4.4 CONDUCTED OUTPUT POWER 14
4.5 6DB BANDWIDTH 17
4.6 POWER SPECTRAL DENSITY 20
4.7 BAND EDGES 23
Conducted Emission Method 23
Radiated Emission Method 26
4.8 SPURIOUS EMISSION 28
Conducted Emission Method 28
Radiated Emission Method 32

5. TEST SETUP PHOTO 39

6. EUT CONSTRUCTIONAL DETAILS 39

1. Test Summary

Test Item	Section	Result	Test by
Antenna requirement	47CFR part 15.203/15.247 (b)(4)	Pass	/
AC Power Line Conducted Emission	47CFR part 15.207	Pass	Jason Huang
Conducted Peak Output Power	47CFR part 15.247 (b)(3)	Pass	Oliver Wang
6dB Bandwidth	47CFR part 15.247 (a)(2)	Pass	Oliver Wang
Power Spectral Density	47CFR part 15.247 (e)	Pass	Oliver Wang
Band Edge	47CFR part 15.247(d) 47CFR part 15.205/15.209	Pass	Oliver Wang
Spurious Emission	47CFR part 15.247(d) 47CFR part 15.205/15.209	Pass	Leo Zhong

Remarks:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and KDB558074 D01 15.247 Meas Guidance v05r02.*
3. *Note: Compliance determination rules*

1).The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacturer. If measurement uncertainty is taken into account, the applicant/manufacturer will bear all possible risks of non-compliance.

2).The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"

Measurement Uncertainty

Test Item	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	0.72%	(1)
RF output power, conducted	±0.67 dB	(1)
Power Spectral Density, conducted	±0.51 dB	(1)
Unwanted Emissions, conducted	±0.64 dB	(1)
AC Power Line Conducted Emission	± 3.38 dB	(1)
Radiated emissions 9K-30MHz	±4.26 dB	(1)
Radiated emissions 30M- 1GHz	±4.88 dB	(1)
Radiated emissions 1GHz-18GHz	± 4.16 dB	(1)
Radiated emissions 18GHz-40GHz	±4.14 dB	(1)
Frequency error	Uc=6X10-7	(1)
Duty Cycle	±0.03%	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.		

2. General Information

2.1 General Description of EUT

Product Name:	POS System
Model No.:	Eva-S01,Eva-B01,Eva-C01,Eva-G01,Eva-H01,Eva-K01,Eva-X01, Nova-A01, Nova-B01, Nova-E01, Nova-K01, Nova-M01, Nova-P01, Nova-Q01, Core-A01, Core-B01, Core-C01, Omni-K01, Omni-K02(The variations between the models in this application lie solely in their naming conventions, which are used to distinguish between different sales schemes and regional markets. These differences do not impact product safety or performance)
Difference of model(s)	All models have the same electrical design (i.e. circuit design, PCB layout, RF module/circuit, antenna type and position, components on PCB, etc.), mechanical structure and design are the same, only the model name different
Test Model:	Eva-S01
Hardware version:	N/A
Software version:	N/A
Power supply:	DC 12V/5A with AC 120V/60Hz from adapter
Adapter information:	Model: GM60-120500-F Input: 100-240V~50/60Hz 2.0A Output: 12.0V-5.0A;60.0W
Battery:	N/A
Radio Technology:	BT(LE)
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel separation:	2MHz
Modulation technology:	GFSK
Antenna Type:	FPC antenna
Antenna gain:	2.98dBi
Note: *1. Other information please Reference user manual.* *2. Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information.*	

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
Lowest channel	2402MHz
Middle channel	2440MHz
Highest channel	2480MHz

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
1	MOUSE	DELL	MS116	/
2	KEYBOARD	DELL	KB216T	/
3	EARPHONE	/	/	/

2.4 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064
IC Company Number:	28440
IC CAB identifier:	CN0132
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

2.5 Additional Instructions

Test Software	Manufacturer-specific serial commands
Power level setup	Default

3. Test Instruments list

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101214	2026.3.05	2027.3.04
2	EMI Test Receiver	Rohde&schwarz	ESCI3	102696	2026.3.05	2027.3.04
3	Loop Antenna	schwarabeck	FMZB 1519 B	128	2026.3.08	2028.3.07
4	Broadband antenna	schwarabeck	VULB9168	1064	2026.3.11	2028.3.10
5	Horn antenna	schwarabeck	BBHA9120D	2288	2026.3.08	2028.3.07
6	amplifier	EMtrace	RP01A	50117	2026.3.05	2027.3.04
7	AMN	schwarabeck	NSLK8127	8127483	2026.3.05	2027.3.04
8	AMN	ETS	3186/2NM	1132	2026.3.05	2027.3.04
9	10dB attenuator	HUBER+SUHNR	10dB	/	2026.3.05	2027.3.04
10	amplifier	Space-Dtronics	EWLAN0118G-P40	19113001	2026.3.05	2027.3.04
11	Filter	Xingbo	XBLBQ-GTA19	210410-3-1	2026.3.05	2027.3.04
12	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2026.3.05	2027.3.04
13	Power control box	MWRFtest	MW100-PSB	MW201020JYT	2026.3.05	2027.3.04
14	Power Sensor	Keysight	U2021XA	MY54111006	2026.3.05	2027.3.04
15	amplifier	SKET	LNPA_1840-50 (18-40GHz)	19113001	2026.3.05	2027.3.04
16	Horn antenna	schwarabeck	BBHA 9170	946	2026.3.08	2028.3.07
17	Temp. & Humidity Chamber	Jiecheng Instrument	QA-LP-80	20160705001	2026/3/06	2027/3/05

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4. Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:	47CFR Part 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(b) (4) requirement:** If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power limit shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is FPC antenna, the best case gain of the antenna is 2.98 dBi, reference to the internal photo for details.	

4.2 Conducted Emissions

Test Requirement:	47CFR part 15.207
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 6.2
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 on conducted measurement.

Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	24.2°C	Humid.:	53%	Press.:	1012mbar
Test voltage:	AC 120V/60Hz					
Test results:	Pass					

Remark:

1. Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V/60Hz.

2. All models and modes have been tested, and the report only show the worst mode (2440MHz) data.

Measurement data

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	45.59	9.97	55.56	66.00	-10.44	QP
2	0.1500	28.98	9.97	38.95	56.00	-17.05	AVG
3	0.2039	38.44	9.97	48.41	63.45	-15.04	QP
4	0.2039	19.60	9.97	29.57	53.45	-23.88	AVG
5	0.2939	30.65	10.00	40.65	60.41	-19.76	QP
6	0.2939	15.09	10.00	25.09	50.41	-25.32	AVG
7	0.5323	26.22	10.08	36.30	56.00	-19.70	QP
8	0.5323	16.90	10.08	26.98	46.00	-19.02	AVG
9	8.9384	26.58	10.07	36.65	60.00	-23.35	QP
10	8.9384	18.61	10.07	28.68	50.00	-21.32	AVG
11	18.2443	28.43	9.95	38.38	60.00	-21.62	QP
12	18.2443	20.09	9.95	30.04	50.00	-19.96	AVG

Neutral:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	45.59	9.97	55.56	66.00	-10.44	QP
2	0.1500	28.98	9.97	38.95	56.00	-17.05	AVG
3	0.1905	39.75	9.97	49.72	64.01	-14.29	QP
4	0.1905	19.31	9.97	29.28	54.01	-24.73	AVG
5	0.5322	25.22	10.08	35.30	56.00	-20.70	QP
6	0.5322	15.90	10.08	25.98	46.00	-20.02	AVG
7	2.3549	24.97	10.00	34.97	56.00	-21.03	QP
8	2.3549	10.03	10.00	20.03	46.00	-25.97	AVG
9	9.9555	25.44	10.08	35.52	60.00	-24.48	QP
10	9.9555	16.02	10.08	26.10	50.00	-23.90	AVG
11	18.2443	25.43	9.95	35.38	60.00	-24.62	QP
12	18.2443	17.09	9.95	27.04	50.00	-22.96	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Level =Receiver Read level + Factor (Factor= LISN Factor + Cable Loss+ Attenuator Factor)
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Duty cycle

Test Method :	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 11.6	
Limit:	/	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Measurement Result

Test channel	Duty Cycle (%)	Correction Factor (dB)
Lowest	84.8	0.72
Middle	84.8	0.72
Highest	84.8	0.72

*Note: Duty cycle factor (dB) =10 * log (1/ Duty cycle)*

Test plot as follows:

Duty Cycle NVNT a 2402MHz Ant1



Duty Cycle NVNT a 2440MHz Ant1



Duty Cycle NVNT a 2480MHz Ant1



4.4 Conducted Output Power

Test Requirement :	47CFR Part 15.247 (b)(3)	
Test Method :	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 11.9.1.2 KDB558074 D01 15.247 Meas Guidance v05r02	
Limit:	30dBm for conducted	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Measurement Result

Test channel	Output Power (dBm)	Limit(dBm)	Result
Lowest	4.05	30.00	Pass
Middle	4.30		
Highest	2.87		

4.5 6dB Bandwidth

Test Requirement :	47CFR part 15.247 (a)(2)	
Test Method :	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 11.8.2	
Limit:	>500KHz	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Measurement Result

Test channel	6dB Bandwidth (MHz)	Limit(KHz)	Result
Lowest	0.6625	>500	Pass
Middle	0.6550		
Highest	0.6756		

Test plot as follows:

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



4.6 Power Spectral Density

Test Requirement:	47CFR Part 15.247 (e)	
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 11.10.2 KDB558074 D01 15.247 Meas Guidance v05r02	
Limit:	8dBm/3kHz	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Measurement Result

Test channel	Power Spectral Density (dBm/3kHz)	Limit(dBm/3kHz)	Result
Lowest	-12.676	8.00	Pass
Middle	-11.817		
Highest	-13.260		

Test plot as follows:

PSD NVNT BLE 1M 2402MHz Ant1

PSD NVNT BLE 1M 2440MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1

4.7 Band edges

Conducted Emission Method

Test Requirement:	47CFR Part 15.247 (d)	
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 6.10.2	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Test plot as follows:

Condition	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	2402	Ant1	-59.16	-20	Pass
NVNT	2480	Ant1	-58.74	-20	Pass

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Radiated Emission Method

Test Requirement:	47CFR Part 15.209 and 15.205
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 6.10.4&11.12.1
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

Limit:

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC12V from adapter	
Test results:	Pass	

Measurement Result:

Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Polarization
2310.00	68.59	-13.36	55.23	74.00	-18.77	Horizontal
2390.00	74.29	-13.03	61.26	74.00	-12.74	Horizontal
2310.00	69.77	-13.36	56.41	74.00	-17.59	Vertical
2390.00	74.69	-13.03	61.66	74.00	-12.34	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	57.34	-13.36	43.98	54.00	-10.02	Horizontal
2390.00	62.46	-13.03	49.43	54.00	-4.57	Horizontal
2310.00	58.21	-13.36	44.85	54.00	-9.15	Vertical
2390.00	62.61	-13.03	49.58	54.00	-4.42	Vertical

Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	69.67	-12.57	57.10	74.00	-16.90	Horizontal
2500.00	76.20	-12.64	63.56	74.00	-10.44	Horizontal
2483.50	69.71	-12.57	57.14	74.00	-16.86	Vertical
2500.00	69.67	-12.57	57.10	74.00	-16.90	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	62.98	-12.64	50.34	54.00	-3.66	Horizontal
2500.00	58.41	-12.57	45.84	54.00	-8.16	Horizontal
2483.50	63.97	-12.64	51.33	54.00	-2.67	Vertical
2500.00	57.66	-12.57	45.09	54.00	-8.91	Vertical

Remarks:

1. *Level = Read level + Factor*
2. *Factor=Antenna Factor + Cable Loss – Preamplifier Factor*
3. *Emissions more than 20 dB below the limit do not need to be reported.*
4. *The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

4.8 Spurious Emission

Conducted Emission Method

Test Requirement:	47CFR Part 15.247(d),47CFR Part 15.209 and 15.205	
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 11.12.2	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Remark:

1. Cable loss data included in Offset.

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-46.82	-20	Pass
NVNT	BLE 1M	2440	Ant1	-46.55	-20	Pass
NVNT	BLE 1M	2480	Ant1	-45.65	-20	Pass

Test plot as follows:

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Radiated Emission Method

Test Requirement:	47CFR part 15.247(d),47CFR Part 15.209 and 15.205
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 6.4&6.5&6.6
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	300m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



	For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remarks:

1. *The report only shows the worst mode.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*
3. *All models and modes have been tested, and the report only show the worst mode (2440MHz) data.*

Measurement Result:

■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 47CFR part 15.31(o), the test result no need to reported.

■ **Below 1GHz**

Test polarization:	Vertical	Test voltage:	DC12V From adapter with AC 120V/60Hz
Temp.:	23.6°C	Humid.:	64%RH



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.5197	58.01	-22.41	35.60	40.00	-4.40	QP
2	45.2165	58.22	-21.43	36.79	40.00	-3.21	QP
3	66.0340	56.64	-23.81	32.83	40.00	-7.17	QP
4	143.8291	54.68	-21.55	33.13	43.50	-10.37	QP
5	210.0481	61.39	-23.93	37.46	43.50	-6.04	QP
6	842.1295	44.77	-6.07	38.70	46.00	-7.30	QP

Factor= Antenna Factor + Cable Loss – Preamplifier Factor
Level = Reading + Factor, Margin=level-Limit

Test polarization:	Horizontal	Test voltage:	DC12V From adapter with AC 120V/60Hz
Temp.:	23.6°C	Humid.:	64%RH



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.8292	59.41	-21.55	37.86	43.50	-5.64	QP
2	213.0149	62.68	-23.95	38.73	43.50	-4.77	QP
3	237.4756	62.24	-23.03	39.21	46.00	-6.79	QP
4	294.1136	58.81	-20.94	37.87	46.00	-8.13	QP
5	420.5803	55.73	-16.68	39.05	46.00	-6.95	QP
6	842.1295	44.51	-6.07	38.44	46.00	-7.56	QP

Remarks:
Level =Receiver Reading + Factor
Factor= Antenna Factor + Cable Factor – Preamplifier Factor

■ **1GHz-25GHz**

Temp.:	23.6°C	Humid.:	64%RH
Test voltage:	DC12V From adapter with AC 120V/60Hz		
Test channel:	Lowest		

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	62.49	-7.69	54.80	74.00	-19.20	Vertical
7206.00	58.96	-1.70	57.26	74.00	-16.74	Vertical
9608.00	55.70	1.31	57.01	74.00	-16.99	Vertical
12010.00	*	--	--	74.00	--	Vertical
14412.00	*	--	--	74.00	--	Vertical
4804.00	62.22	-7.69	54.53	74.00	-19.47	Horizontal
7206.00	57.93	-1.70	56.23	74.00	-17.77	Horizontal
9608.00	56.26	1.31	57.57	74.00	-16.43	Horizontal
12010.00	*	--	--	74.00	--	Horizontal
14412.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m	Over Limit (dB)	polarization
4804.00	50.80	-7.69	43.11	54.00	-10.89	Vertical
7206.00	46.31	-1.70	44.61	54.00	-9.39	Vertical
9608.00	43.78	1.31	45.09	54.00	-8.91	Vertical
12010.00	*	--	--	54.00	--	Vertical
14412.00	*	--	--	54.00	--	Vertical
4804.00	51.46	-7.69	43.77	54.00	-10.23	Horizontal
7206.00	47.44	-1.70	45.74	54.00	-8.26	Horizontal
9608.00	44.29	1.31	45.60	54.00	-8.40	Horizontal
12010.00	*	--	--	54.00	--	Horizontal
14412.00	*	--	--	54.00	--	Horizontal

Remarks:

1. *Level = Read level + Factor*
2. *Factor =Antenna Factor + Cable Loss – Preamplifier Factor*
3. *"*", means this data is the too weak instrument of signal is unable to test.*
4. *Emissions more than 20 dB below the limit do not need to be reported.*

Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	63.65	-7.56	56.09	74.00	-17.91	Vertical
7320.00	57.63	-1.38	56.25	74.00	-17.75	Vertical
9760.00	56.67	1.19	57.86	74.00	-16.14	Vertical
12200.00	*	--	--	74.00	--	Vertical
14640.00	*	--	--	74.00	--	Vertical
4880.00	62.89	-7.56	55.33	74.00	-18.67	Horizontal
7320.00	57.04	-1.38	55.66	74.00	-18.34	Horizontal
9760.00	58.00	1.19	59.19	74.00	-14.81	Horizontal
12200.00	*	--	--	74.00	--	Horizontal
14640.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	51.11	-7.56	43.55	54.00	-10.45	Vertical
7320.00	45.41	-1.38	44.03	54.00	-9.97	Vertical
9760.00	46.71	1.19	47.90	54.00	-6.10	Vertical
12200.00	*	--	--	54.00	--	Vertical
14640.00	*	--	--	54.00	--	Vertical
4880.00	51.67	-7.56	44.11	54.00	-9.89	Horizontal
7320.00	46.86	-1.38	45.48	54.00	-8.52	Horizontal
9760.00	45.82	1.19	47.01	54.00	-6.99	Horizontal
12200.00	*	--	--	54.00	--	Horizontal
14640.00	*	--	--	54.00	--	Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *Emissions more than 20 dB below the limit do not need to be reported.*

Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	62.50	-7.43	55.07	74.00	-18.93	Vertical
7440.00	57.63	-1.02	56.61	74.00	-17.39	Vertical
9920.00	55.09	1.08	56.17	74.00	-17.83	Vertical
12400.00	*	--	--	74.00	--	Vertical
14880.00	*	--	--	74.00	--	Vertical
4960.00	62.98	-7.43	55.55	74.00	-18.45	Horizontal
7440.00	56.82	-1.02	55.80	74.00	-18.20	Horizontal
9920.00	55.13	1.08	56.21	74.00	-17.79	Horizontal
12400.00	*	--	--	74.00	--	Horizontal
14880.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	51.37	-7.43	43.94	54.00	-10.06	Vertical
7440.00	46.95	-1.02	45.93	54.00	-8.07	Vertical
9920.00	45.36	1.08	46.44	54.00	-7.56	Vertical
12400.00	*	--	--	54.00	--	Vertical
14880.00	*	--	--	54.00	--	Vertical
4960.00	51.91	-7.43	44.48	54.00	-9.52	Horizontal
7440.00	48.82	-1.02	47.80	54.00	-6.20	Horizontal
9920.00	44.94	1.08	46.02	54.00	-7.98	Horizontal
12400.00	*	--	--	54.00	--	Horizontal
14880.00	*	--	--	54.00	--	Horizontal

Remarks:

1. *Level = Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*
3. *Emissions more than 20 dB below the limit do not need to be reported.*

5. Test Setup Photo

Reference to the file No.: ET-26094793SP for details.

6. EUT Constructional Details

Reference to the file No.: ET-26094793EP and ET-26094793IP for details.

------End------