




Band Edge NVNT g 2462MHz Ant1 Ref




Band Edge NVNT g 2462MHz Ant1 Emission




Band Edge NVNT n20 2412MHz Ant1 Ref




Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref




Band Edge NVNT n20 2462MHz Ant1 Emission




Band Edge NVNT n40 2422MHz Ant1 Ref




Band Edge NVNT n40 2422MHz Ant1 Emission




Band Edge NVNT n40 2452MHz Ant1 Ref



Band Edge NVNT n40 2452MHz Ant1 Emission



Radiated Emission Method

Test Requirement:	47CFR Part 15.209 and 15.205				
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 6.10.4&11.12.1				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.				
Test Instruments:	Refer to section 3.0 for details				
Test mode:	Refer to section 2.2 for details				
Test environment:	Temp.: 24.2°C		Humid.: 53%RH		
Test voltage:	DC 12V from adapter				
Test results:	Pass				



Measurement data:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	62.15	-13.36	48.79	74.00	-25.21	Horizontal
2390.00	63.93	-13.03	50.90	74.00	-23.10	Horizontal
2310.00	61.81	-13.36	48.45	74.00	-25.55	Vertical
2390.00	64.60	-13.03	51.57	74.00	-22.43	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	52.10	-13.36	38.74	54.00	-15.26	Horizontal
2390.00	54.44	-13.03	41.41	54.00	-12.60	Horizontal
2310.00	51.49	-13.36	38.13	54.00	-15.87	Vertical
2390.00	54.28	-13.03	41.25	54.00	-12.75	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	65.89	-12.64	53.25	74.00	-20.75	Horizontal
2500.00	61.97	-12.57	49.40	74.00	-24.60	Horizontal
2483.50	65.67	-12.64	53.03	74.00	-20.97	Vertical
2500.00	62.13	-12.57	49.56	74.00	-24.44	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	55.06	-12.64	42.42	54.00	-11.58	Horizontal
2500.00	51.33	-12.57	38.76	54.00	-15.24	Horizontal
2483.50	55.67	-12.64	43.03	54.00	-10.97	Vertical
2500.00	51.65	-12.57	39.08	54.00	-14.92	Vertical

Remarks:

1. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
2. Final Level = Receiver Read level + Factor
3. Factor = Antenna Factor + Cable Loss – Preamplifier Factor
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	62.67	-13.36	49.31	74.00	-24.69	Horizontal
2390.00	64.38	-13.03	51.35	74.00	-22.65	Horizontal
2310.00	63.00	-13.36	49.64	74.00	-24.36	Vertical
2390.00	64.87	-13.03	51.84	74.00	-22.16	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	52.12	-13.36	38.76	54.00	-15.24	Horizontal
2390.00	53.94	-13.03	40.91	54.00	-13.09	Horizontal
2310.00	52.46	-13.36	39.10	54.00	-14.90	Vertical
2390.00	54.60	-13.03	41.57	54.00	-12.43	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	64.94	-12.64	52.30	74.00	-21.70	Horizontal
2500.00	62.48	-12.57	49.91	74.00	-24.09	Horizontal
2483.50	65.35	-12.64	52.71	74.00	-21.29	Vertical
2500.00	62.96	-12.57	50.39	74.00	-23.61	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	53.93	-12.64	41.29	54.00	-12.71	Horizontal
2500.00	52.20	-12.57	39.63	54.00	-14.37	Horizontal
2483.50	54.53	-12.64	41.89	54.00	-12.11	Vertical
2500.00	52.68	-12.57	40.11	54.00	-13.89	Vertical

Remarks:

1. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
2. Final Level = Receiver Read level + Factor
3. Factor = Antenna Factor + Cable Loss – Preamplifier Factor
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	63.14	-13.36	49.78	74.00	-24.22	Horizontal
2390.00	65.21	-13.03	52.18	74.00	-21.82	Horizontal
2310.00	62.85	-13.36	49.49	74.00	-24.51	Vertical
2390.00	64.90	-13.03	51.87	74.00	-22.13	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	53.07	-13.36	39.71	54.00	-14.29	Horizontal
2390.00	54.67	-13.03	41.64	54.00	-12.36	Horizontal
2310.00	52.19	-13.36	38.83	54.00	-15.17	Vertical
2390.00	54.04	-13.03	41.01	54.00	-12.99	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	65.06	-12.64	52.42	74.00	-21.58	Horizontal
2500.00	62.44	-12.57	49.87	74.00	-24.13	Horizontal
2483.50	65.27	-12.64	52.63	74.00	-21.37	Vertical
2500.00	62.47	-12.57	49.90	74.00	-24.10	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	54.43	-12.64	41.79	54.00	-12.21	Horizontal
2500.00	52.26	-12.57	39.69	54.00	-14.31	Horizontal
2483.50	54.78	-12.64	42.14	54.00	-11.86	Vertical
2500.00	52.65	-12.57	40.08	54.00	-13.92	Vertical

Remarks:

1. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
2. Final Level =Receiver Read level + Factor
3. Factor =Antenna Factor + Cable Loss – Preamplifier Factor
4. Emissions more than 20 dB below the limit do not need to be reported.

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	62.99	-13.36	49.63	74.00	-24.38	Horizontal
2390.00	63.52	-13.03	50.49	74.00	-23.51	Horizontal
2310.00	62.26	-13.36	48.90	74.00	-25.10	Vertical
2390.00	65.28	-13.03	52.25	74.00	-21.75	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	52.36	-13.36	39.00	54.00	-15.00	Horizontal
2390.00	81.08	-13.03	68.05	54.00	14.05	Horizontal
2310.00	54.06	-13.36	40.70	54.00	-13.30	Vertical
2390.00	56.38	-13.36	43.02	54.00	-10.98	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	67.37	-12.64	54.73	74.00	-19.27	Horizontal
2500.00	64.88	-12.57	52.31	74.00	-21.69	Horizontal
2483.50	66.66	-12.64	54.02	74.00	-19.98	Vertical
2500.00	63.90	-12.57	51.33	74.00	-22.67	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	57.27	-12.64	44.63	54.00	-9.37	Horizontal
2500.00	54.16	-12.57	41.59	54.00	-12.41	Horizontal
2483.50	57.46	-12.64	44.82	54.00	-9.18	Vertical
2500.00	53.29	-12.57	40.72	54.00	-13.28	Vertical

Remarks:

1. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
2. Final Level =Receiver Read level + Factor
3. Factor =Antenna Factor + Cable Loss – Preamplifier Factor
4. Emissions more than 20 dB below the limit do not need to be reported.

4.8 Spurious Emission

Conducted Emission Method

Test Requirement:	47CFR Part 15.247 (d), 47CFR Part 15.209	
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 § 11.12.2	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.2°C	Humid.: 53%RH
Test voltage:	DC 12V from adapter	
Test results:	Pass	

Remark:

1. Cable loss data included in Offset.


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-46.77	-20	Pass
NVNT	b	2437	Ant1	-47.06	-20	Pass
NVNT	b	2462	Ant1	-46.88	-20	Pass
NVNT	g	2412	Ant1	-39.98	-20	Pass
NVNT	g	2437	Ant1	-39.14	-20	Pass
NVNT	g	2462	Ant1	-41.35	-20	Pass
NVNT	n20	2412	Ant1	-38.79	-20	Pass
NVNT	n20	2437	Ant1	-39.56	-20	Pass
NVNT	n20	2462	Ant1	-39.32	-20	Pass
NVNT	n40	2422	Ant1	-35.13	-20	Pass
NVNT	n40	2437	Ant1	-35.35	-20	Pass
NVNT	n40	2452	Ant1	-34.96	-20	Pass

Test plot as follows:

Tx. Spurious NVNT b 2412MHz Ant1 Ref




Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref




Tx. Spurious NVNT b 2437MHz Ant1 Emission




Tx. Spurious NVNT b 2462MHz Ant1 Ref




Tx. Spurious NVNT b 2462MHz Ant1 Emission



Tx. Spurious NVNT g 2412MHz Ant1 Ref




Tx. Spurious NVNT g 2412MHz Ant1 Emission



Tx. Spurious NVNT g 2437MHz Ant1 Ref




Tx. Spurious NVNT g 2437MHz Ant1 Emission




Tx. Spurious NVNT g 2462MHz Ant1 Ref




Tx. Spurious NVNT g 2462MHz Ant1 Emission




Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Tx. Spurious NVNT n20 2412MHz Ant1 Emission




Tx. Spurious NVNT n20 2437MHz Ant1 Ref




Tx. Spurious NVNT n20 2437MHz Ant1 Emission



Tx. Spurious NVNT n20 2462MHz Ant1 Ref




Tx. Spurious NVNT n20 2462MHz Ant1 Emission




Tx. Spurious NVNT n40 2422MHz Ant1 Ref




Tx. Spurious NVNT n40 2422MHz Ant1 Emission



Tx. Spurious NVNT n40 2437MHz Ant1 Ref




Tx. Spurious NVNT n40 2437MHz Ant1 Emission





Tx. Spurious NVNT n40 2452MHz Ant1 Ref




Tx. Spurious NVNT n40 2452MHz Ant1 Emission



Radiated Emission Method

Test Requirement:	47CFR part 15.247(d),47CFR Part 15.209 and 15.205				
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024§6.4&6.5&6.6				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to1GHz				
					
	For radiated emissions above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remarks:


1. The report only shows the worst mode.
2. Pre-scan all kind of the place mode (X-axis, Y-(axis, Z-axis), and found the Y-axis which it is worse case.
3. All models and modes have been tested, and the report only displays the worst mode 802.11g (24 62MHz) data.

Measurement data:
■ 9kHz~30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ Below 1GHz

Test polarization:	Vertical	Test voltage:	DC 12V from adapter with AC 120V/60Hz
Temp.:	23.6°C	Humid.:	64%RH




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.5197	58.01	-22.41	35.60	40.00	-4.40	QP
2	45.2165	59.22	-21.43	37.79	40.00	-2.21	QP
3	143.8291	54.68	-21.55	33.13	43.50	-10.37	QP
4	210.0481	61.89	-23.93	37.96	43.50	-5.54	QP
5	560.6928	50.21	-12.35	37.86	46.00	-8.14	QP
6	842.1295	44.77	-6.07	38.70	46.00	-7.30	QP

Remarks:

Level = Receiver Reading + Factor

Factor = Antenna Factor + Cable Factor – Preamplifier Factor

Test polarization:	Horizontal	Test voltage:	DC 12V from adapter with AC 120V/60Hz
Temp.:	23.6°C	Humid.:	64%RH



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	143.8291	58.91	-21.55	37.36	43.50	-6.14	QP
2	213.0149	64.68	-23.95	40.73	43.50	-2.77	QP
3	237.4755	62.24	-23.03	39.21	46.00	-6.79	QP
4	294.1136	58.81	-20.94	37.87	46.00	-8.13	QP
5	420.5803	55.73	-16.68	39.05	46.00	-6.95	QP
6	842.1295	44.51	-6.07	38.44	46.00	-7.56	QP

Remarks:

Level = Receiver Reading + Factor

Factor = Antenna Factor + Cable Factor - Preamplifier Factor



■ 1GHz-25GHz

Temp.:	23.6°C	Humid.:	64%RH
Test voltage:	DC 12V from adapter with AC 120V/60Hz		

Test mode:	802.11b	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	56.68	-7.66	49.02	74.00	-24.98	Vertical
7236.00	53.32	-1.62	51.70	74.00	-22.30	Vertical
9648.00	51.53	1.27	52.80	74.00	-21.20	Vertical
12060.00	*	--	--	74.00	--	Vertical
14472.00	*	--	--	74.00	--	Vertical
16884.00	*	--	--	74.00	--	Vertical
4824.00	57.48	-7.66	49.82	74.00	-24.19	Horizontal
7236.00	53.33	-1.62	51.71	74.00	-22.29	Horizontal
9648.00	50.64	1.27	51.91	74.00	-22.10	Horizontal
12060.00	*	--		74.00		Horizontal
14472.00	*	--		74.00		Horizontal
16884.00	*	--		74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	46.63	-7.66	38.97	54.00	-15.03	Vertical
7236.00	42.57	-1.62	40.95	54.00	-13.05	Vertical
9648.00	39.92	1.27	41.19	54.00	-12.81	Vertical
12060.00	*	--	--	54.00	--	Vertical
14472.00	*	--	--	54.00	--	Vertical
16884.00	*	--	--	54.00	--	Vertical
4824.00	47.06	-7.66	39.40	54.00	-14.60	Horizontal
7236.00	42.66	-1.62	41.04	54.00	-12.97	Horizontal
9648.00	40.72	1.27	41.99	54.00	-12.01	Horizontal
12060.00	*	--		54.00		Horizontal
14472.00	*	--		54.00		Horizontal
16884.00	*	--		54.00		Horizontal

Remark:

1. *Level = Read level + Factor*
2. *Factor =Antenna Factor + Cable Loss – Preamplifier Factor*
3. *“*” , means this data is the too weak instrument of signal is unable to test.*
4. *Emissions more than 20 dB below the limit do not need to be reported.*



Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	57.39	-7.58	49.81	74.00	-24.19	Vertical
7311.00	53.46	-1.40	52.06	74.00	-21.94	Vertical
9748.00	50.58	1.20	51.78	74.00	-22.22	Vertical
12185.00	*	--	--	74.00	--	Vertical
14622.00	*	--	--	74.00	--	Vertical
17059.00	*	--	--	74.00	--	Vertical
4874.00	57.14	-7.58	49.56	74.00	-24.44	Horizontal
7311.00	51.67	-1.40	50.27	74.00	-23.73	Horizontal
9748.00	49.66	1.20	50.86	74.00	-23.14	Horizontal
12185.00	*	--		74.00		Horizontal
14622.00	*	--		74.00		Horizontal
17059.00	*	--		74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	46.71	-7.58	39.13	54.00	-14.87	Vertical
7311.00	41.50	-1.40	40.10	54.00	-13.90	Vertical
9748.00	40.43	1.20	41.63	54.00	-12.37	Vertical
12185.00	*	--	--	54.00	--	Vertical
14622.00	*	--	--	54.00	--	Vertical
17059.00	*	--	--	54.00	--	Vertical
4874.00	46.47	-7.58	38.89	54.00	-15.11	Horizontal
7311.00	42.29	-1.40	40.89	54.00	-13.11	Horizontal
9748.00	40.65	1.20	41.85	54.00	-12.15	Horizontal
12185.00	*	--		54.00		Horizontal
14622.00	*	--		54.00		Horizontal
17059.00	*	--		54.00		Horizontal

Remark:

1. Level = Read level + Factor
2. Factor =Antenna Factor + Cable Loss – Preamplifier Factor
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	57.51	-7.49	50.02	74.00	-23.98	Vertical
7386.00	52.92	-1.18	51.74	74.00	-22.27	Vertical
9848.00	54.16	1.12	55.28	74.00	-18.72	Vertical
12310.00	*	--	--	74.00	--	Vertical
14772.00	*	--	--	74.00	--	Vertical
17234.00	*	--	--	74.00	--	Vertical
4924.00	57.02	-7.49	49.53	74.00	-24.47	Horizontal
7386.00	53.89	-1.18	52.71	74.00	-21.29	Horizontal
9848.00	50.32	1.12	51.44	74.00	-22.56	Horizontal
12310.00	*	--	--	74.00	--	Horizontal
14772.00	*	--	--	74.00	--	Horizontal
17234.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	46.67	-7.49	39.18	54.00	-14.82	Vertical
7386.00	43.16	-1.18	41.98	54.00	-12.02	Vertical
9848.00	41.33	1.12	42.45	54.00	-11.55	Vertical
12310.00	*	--	--	54.00	--	Vertical
14772.00	*	--	--	54.00	--	Vertical
17234.00	*	--	--	54.00	--	Vertical
4924.00	47.84	-7.49	40.35	54.00	-13.65	Horizontal
7386.00	43.82	-1.18	42.64	54.00	-11.36	Horizontal
9848.00	41.14	1.12	42.26	54.00	-11.75	Horizontal
12310.00	*	--	--	54.00	--	Horizontal
14772.00	*	--	--	54.00	--	Horizontal
17234.00	*	--	--	54.00	--	Horizontal

Remark:

1. $Level = Read\ level + Factor$
2. $Factor = Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	58.02	-7.66	50.36	74.00	-23.64	Vertical
7236.00	54.26	-1.62	52.64	74.00	-21.36	Vertical
9648.00	51.33	1.27	52.60	74.00	-21.40	Vertical
12060.00	*	--	--	74.00	--	Vertical
14472.00	*	--	--	74.00	--	Vertical
16884.00	*	--	--	74.00	--	Vertical
4824.00	59.03	-7.66	51.37	74.00	-22.63	Horizontal
7236.00	51.79	-1.62	50.17	74.00	-23.83	Horizontal
9648.00	53.98	1.27	55.25	74.00	-18.75	Horizontal
12060.00	*	--	--	74.00	--	Horizontal
14472.00	*	--	--	74.00	--	Horizontal
16884.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	47.90	-7.66	40.24	54.00	-13.76	Vertical
7236.00	43.47	-1.62	41.85	54.00	-12.15	Vertical
9648.00	68.67	1.27	69.94	54.00	15.94	Vertical
12060.00	*	--	--	54.00	--	Vertical
14472.00	*	--	--	54.00	--	Vertical
16884.00	*	--	--	54.00	--	Vertical
4824.00	48.52	-7.66	40.86	54.00	-13.14	Horizontal
7236.00	42.60	-1.62	40.98	54.00	-13.02	Horizontal
9648.00	43.53	1.27	44.80	54.00	-9.20	Horizontal
12060.00	*	--	--	54.00	--	Horizontal
14472.00	*	--	--	54.00	--	Horizontal
16884.00	*	--	--	54.00	--	Horizontal

Remark:

1. Level = Read level + Factor
2. Factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	57.83	-7.58	50.25	74.00	-23.75	Vertical
7311.00	57.88	-1.40	56.48	74.00	-17.52	Vertical
9748.00	51.96	1.20	53.16	74.00	-20.84	Vertical
12185.00	*	--	--	74.00	--	Vertical
14622.00	*	--	--	74.00	--	Vertical
17059.00	*	--	--	74.00	--	Vertical
4874.00	58.56	-7.58	50.98	74.00	-23.02	Horizontal
7311.00	52.13	-1.40	50.73	74.00	-23.27	Horizontal
9748.00	51.07	1.20	52.27	74.00	-21.73	Horizontal
12185.00	*	--	--	74.00	--	Horizontal
14622.00	*	--	--	74.00	--	Horizontal
17059.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	48.46	-7.58	40.88	54.00	-13.12	Vertical
7311.00	44.94	-1.40	43.54	54.00	-10.46	Vertical
9748.00	41.40	1.20	42.60	54.00	-11.40	Vertical
12185.00	*	--	--	54.00	--	Vertical
14622.00	*	--	--	54.00	--	Vertical
17059.00	*	--	--	54.00	--	Vertical
4874.00	48.70	-7.58	41.12	54.00	-12.88	Horizontal
7311.00	42.01	-1.40	40.61	54.00	-13.39	Horizontal
9748.00	40.92	1.20	42.12	54.00	-11.88	Horizontal
12185.00	*	--	--	54.00	--	Horizontal
14622.00	*	--	--	54.00	--	Horizontal
17059.00	*	--	--	54.00	--	Horizontal

Remark:

1. *Level = Read level + Factor*
2. *Factor = Antenna Factor + Cable Loss – Preamplifier Factor*
3. *“*”*, means this data is the too weak instrument of signal is unable to test.
4. *Emissions more than 20 dB below the limit do not need to be reported.*



Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	59.69	-7.49	52.20	74.00	-21.80	Vertical
7386.00	51.41	-1.18	50.23	74.00	-23.77	Vertical
9848.00	53.99	1.12	55.11	74.00	-18.89	Vertical
12310.00	*	--	--	74.00	--	Vertical
14772.00	*	--	--	74.00	--	Vertical
17234.00	*	--	--	74.00	--	Vertical
4924.00	58.96	-7.49	51.47	74.00	-22.53	Horizontal
7386.00	52.40	-1.18	51.22	74.00	-22.78	Horizontal
9848.00	51.73	1.12	52.85	74.00	-21.15	Horizontal
12310.00	*	--	--	74.00	--	Horizontal
14772.00	*	--	--	74.00	--	Horizontal
17234.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	48.80	-7.49	41.31	54.00	-12.69	Vertical
7386.00	42.27	-1.18	41.09	54.00	-12.91	Vertical
9848.00	42.66	1.12	43.78	54.00	-10.23	Vertical
12310.00	*	--	--	54.00	--	Vertical
14772.00	*	--	--	54.00	--	Vertical
17234.00	*	--	--	54.00	--	Vertical
4924.00	48.37	-7.49	40.88	54.00	-13.12	Horizontal
7386.00	42.70	-1.18	41.52	54.00	-12.48	Horizontal
9848.00	40.89	1.12	42.01	54.00	-11.99	Horizontal
12310.00	*	--	--	54.00	--	Horizontal
14772.00	*	--	--	54.00	--	Horizontal
17234.00	*	--	--	54.00	--	Horizontal

Remark:

1. *Level = Read level + Factor*
2. *Factor = Antenna Factor + Cable Loss – Preamplifier Factor*
3. *“*”*, means this data is the too weak instrument of signal is unable to test.
4. *Emissions more than 20 dB below the limit do not need to be reported.*



Test mode:	802.11n20	Test channel:	Lowest
------------	-----------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	58.03	-7.66	50.37	74.00	-23.63	Vertical
7236.00	56.81	-1.62	55.19	74.00	-18.81	Vertical
9648.00	53.84	1.27	55.11	74.00	-18.89	Vertical
12060.00	*	--	--	74.00	--	Vertical
14472.00	*	--	--	74.00	--	Vertical
16884.00	*	--	--	74.00	--	Vertical
4824.00	59.61	-7.66	51.95	74.00	-22.05	Horizontal
7236.00	52.35	-1.62	50.73	74.00	-23.28	Horizontal
9648.00	53.06	1.27	54.33	74.00	-19.67	Horizontal
12060.00	*	--	--	74.00	--	Horizontal
14472.00	*	--	--	74.00	--	Horizontal
16884.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	48.17	-7.66	40.51	54.00	-13.50	Vertical
7236.00	44.71	-1.62	43.09	54.00	-10.91	Vertical
9648.00	42.47	1.27	43.74	54.00	-10.26	Vertical
12060.00	*	--	--	54.00	--	Vertical
14472.00	*	--	--	54.00	--	Vertical
16884.00	*	--	--	54.00	--	Vertical
4824.00	49.42	-7.66	41.76	54.00	-12.24	Horizontal
7236.00	42.68	-1.62	41.06	54.00	-12.94	Horizontal
9648.00	41.14	1.27	42.41	54.00	-11.60	Horizontal
12060.00	*	--	--	54.00	--	Horizontal
14472.00	*	--	--	54.00	--	Horizontal
16884.00	*	--	--	54.00	--	Horizontal

Remark:

1. $Level = Read\ level + Factor$
2. $Factor = Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.

Test mode:	802.11n20	Test channel:	Middle
------------	-----------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	58.55	-7.58	50.97	74.00	-23.03	Vertical
7311.00	52.11	-1.40	50.71	74.00	-23.29	Vertical
9748.00	50.68	1.20	51.88	74.00	-22.12	Vertical
12185.00	*	--	--	74.00	--	Vertical
14622.00	*	--	--	74.00	--	Vertical
17059.00	*	--	--	74.00	--	Vertical
4874.00	59.95	-7.58	52.37	74.00	-21.63	Horizontal
7311.00	54.56	-1.40	53.16	74.00	-20.84	Horizontal
9748.00	51.32	1.20	52.52	74.00	-21.48	Horizontal
12185.00		--	--	74.00	--	Horizontal
14622.00	*	--	--	74.00	--	Horizontal
17059.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	48.88	-7.58	41.30	54.00	-12.70	Vertical
7311.00	42.48	-1.40	41.08	54.00	-12.92	Vertical
9748.00	42.32	1.20	43.52	54.00	-10.48	Vertical
12185.00	*	--	--	54.00	--	Vertical
14622.00	*	--	--	54.00	--	Vertical
17059.00	*	--	--	54.00	--	Vertical
4874.00	48.98	-7.58	41.40	54.00	-12.60	Horizontal
7311.00	44.14	-1.40	42.74	54.00	-11.26	Horizontal
9748.00	41.88	1.20	43.08	54.00	-10.92	Horizontal
12185.00	*	--	--	54.00	--	Horizontal
14622.00	*	--	--	54.00	--	Horizontal
17059.00	*	--	--	54.00	--	Horizontal

Remark:

1. $Level = Read\ level + Factor$
2. $Factor = Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11n20	Test channel:	Highest
------------	-----------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	59.00	-7.49	51.51	74.00	-22.50	Vertical
7386.00	50.89	-1.18	49.71	74.00	-24.29	Vertical
9848.00	54.20	1.12	55.32	74.00	-18.68	Vertical
12310.00	*	--	--	74.00	--	Vertical
14772.00	*	--	--	74.00	--	Vertical
17234.00	*	--	--	74.00	--	Vertical
4924.00	60.27	-7.49	52.78	74.00	-21.22	Horizontal
7386.00	51.66	-1.18	50.48	74.00	-23.52	Horizontal
9848.00	53.13	1.12	54.25	74.00	-19.75	Horizontal
12310.00	*	--	--	74.00	--	Horizontal
14772.00	*	--	--	74.00	--	Horizontal
17234.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	49.78	-7.49	42.29	54.00	-11.71	Vertical
7386.00	42.09	-1.18	40.91	54.00	-13.10	Vertical
9848.00	44.24	1.12	45.36	54.00	-8.64	Vertical
12310.00	*	--	--	54.00	--	Vertical
14772.00	*	--	--	54.00	--	Vertical
17234.00	*	--	--	54.00	--	Vertical
4924.00	49.41	-7.49	41.92	54.00	-12.08	Horizontal
7386.00	43.23	-1.18	42.05	54.00	-11.95	Horizontal
9848.00	42.49	1.12	43.61	54.00	-10.39	Horizontal
12310.00	*	--	--	54.00	--	Horizontal
14772.00	*	--	--	54.00	--	Horizontal
17234.00	*	--	--	54.00	--	Horizontal

Remark:

1. *Level = Read level + Factor*
2. *Factor = Antenna Factor + Cable Loss – Preamplifier Factor*
3. *“*” means this data is too weak for the instrument to test.*
4. *Emissions more than 20 dB below the limit do not need to be reported.*

Test mode:	802.11n40	Test channel:	Lowest
------------	-----------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	59.77	-7.63	52.14	74.00	-21.86	Vertical
7266.00	52.72	-1.53	51.19	74.00	-22.81	Vertical
9688.00	50.47	1.24	51.71	74.00	-22.29	Vertical
12060.00	*	--	--	74.00	--	Vertical
14472.00	*	--	--	74.00	--	Vertical
16884.00	*	--	--	74.00	--	Vertical
4844.00	60.69	-7.63	53.06	74.00	-20.94	Horizontal
7266.00	52.51	-1.53	50.98	74.00	-23.02	Horizontal
9688.00	51.30	1.24	52.54	74.00	-21.46	Horizontal
12060.00	*	--	--	74.00	--	Horizontal
14472.00	*	--	--	74.00	--	Horizontal
16884.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	48.96	-7.63	41.33	54.00	-12.67	Vertical
7266.00	42.60	-1.53	41.07	54.00	-12.93	Vertical
9688.00	42.41	1.24	43.65	54.00	-10.35	Vertical
12060.00	*	--		54.00		Vertical
14472.00	*	--		54.00		Vertical
16884.00	*	--		54.00		Vertical
4844.00	48.49	-7.63	40.86	54.00	-13.14	Horizontal
7266.00	41.54	-1.53	40.01	54.00	-13.99	Horizontal
9688.00	41.32	1.24	42.56	54.00	-11.44	Horizontal
12060.00	*	--		54.00		Horizontal
14472.00	*	--		54.00		Horizontal
16884.00	*	--		54.00		Horizontal

Remark:

1. $Level = Read\ level + Factor$
2. $Factor = Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11n40	Test channel:	Middle
------------	-----------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	60.02	-7.58	52.44	74.00	-21.56	Vertical
7311.00	52.83	-1.40	51.43	74.00	-22.57	Vertical
9748.00	52.52	1.20	53.72	74.00	-20.28	Vertical
12185.00	*	--	--	74.00	--	Vertical
14622.00	*	--	--	74.00	--	Vertical
17059.00	*	--	--	74.00	--	Vertical
4874.00	61.46	-7.58	53.88	74.00	-20.12	Horizontal
7311.00	52.15	-1.40	50.75	74.00	-23.25	Horizontal
9748.00	52.15	1.20	53.35	74.00	-20.65	Horizontal
12185.00	*	--	--	74.00	--	Horizontal
14622.00	*	--	--	74.00	--	Horizontal
17059.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	49.42	-7.58	41.84	54.00	-12.16	Vertical
7311.00	43.51	-1.40	42.11	54.00	-11.89	Vertical
9748.00	42.47	1.20	43.67	54.00	-10.34	Vertical
12185.00	*	--	--	54.00	--	Vertical
14622.00	*	--	--	54.00	--	Vertical
17059.00	*	--	--	54.00	--	Vertical
4874.00	50.39	-7.58	42.81	54.00	-11.19	Horizontal
7311.00	42.90	-1.40	41.50	54.00	-12.50	Horizontal
9748.00	41.90	1.20	43.10	54.00	-10.91	Horizontal
12185.00	*	--	--	54.00	--	Horizontal
14622.00	*	--	--	54.00	--	Horizontal
17059.00	*	--	--	54.00	--	Horizontal

Remark:

1. $Level = Read\ level + Factor$
2. $Factor = Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$
3. “*”, means this data is the too weak instrument of signal is unable to test.
4. Emissions more than 20 dB below the limit do not need to be reported.



Test mode:	802.11n40	Test channel:	Highest
------------	-----------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	56.82	-7.52	49.30	74.00	-24.70	Vertical
7356.00	56.74	-1.26	55.48	74.00	-18.52	Vertical
9808.00	53.05	1.16	54.21	74.00	-19.79	Vertical
12310.00		--	--	74.00	--	Vertical
14772.00	*	--	--	74.00	--	Vertical
17234.00	*	--	--	74.00	--	Vertical
4904.00	58.06	-7.52	50.54	74.00	-23.46	Horizontal
7356.00	53.54	-1.26	52.28	74.00	-21.72	Horizontal
9808.00	51.51	1.16	52.67	74.00	-21.33	Horizontal
12310.00	*	--	--	74.00	--	Horizontal
14772.00	*	--	--	74.00	--	Horizontal
17234.00	*	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	46.80	-7.52	39.28	54.00	-14.72	Vertical
7356.00	45.02	-1.26	43.76	54.00	-10.24	Vertical
9808.00	42.50	1.16	43.66	54.00	-10.34	Vertical
12310.00	*	--	--	54.00	--	Vertical
14772.00	*	--	--	54.00	--	Vertical
17234.00	*	--	--	54.00	--	Vertical
4904.00	47.69	-7.52	40.17	54.00	-13.83	Horizontal
7356.00	45.05	-1.26	43.79	54.00	-10.21	Horizontal
9808.00	41.31	1.16	42.47	54.00	-11.53	Horizontal
12310.00	*	--	--	54.00	--	Horizontal
14772.00	*	--	--	54.00	--	Horizontal
17234.00	*	--	--	54.00	--	Horizontal

Remark:

1. *Level = Read level + Factor*
2. *Factor =Antenna Factor + Cable Loss – Preamplifier Factor*
3. *“*” , means this data is the too weak instrument of signal is unable to test.*
4. *Emissions more than 20 dB below the limit do not need to be reported.*



5. Test Setup Photo

Reference to the file No.: ET-26094793SP for details.

6. EUT Constructional Details

Reference to the file No.: ET-26094793EP and ET-26094793IP for details.

-----End-----