Case No. : GTS20260521003-1-01
Ambient Condition: 22 ℃, 47 %RH
According Standard: ■Part15C
Test Date: 2026.7.13-2026.7.27 **Test Engineer:** Evan ouyang

Appendix A.1: DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	0.736	2401.792	2402.528	0.5	PASS
		2440	0.756	2439.784	2440.540	0.5	PASS
		2480	0.748	2479.804	2480.552	0.5	PASS

Test Graphs

BLE_Ant1_2402

BLE_Ant1_2440

BLE_Ant1_2480


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 40 dB
#Avg Type: RMS
Avg|Hold: 100/100
06:51:33 AM Jul 13, 2026
Ref Offset 9.05 dB
10 dB/div
Ref 30.00 dBm
ΔMkr3 748 kHz
-0.069 dB
Center 2.480000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 4.000 MHz
Sweep 1.000 ms (1001 pts)
1 N 1 f 2.479 804 GHz -5.453 dBm
2 N 1 f 2.480 420 GHz 0.446 dBm
3 Δ1 1 f (Δ) 748 kHz (Δ) -0.069 dB
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.478000000 GHz
Stop Freq
2.482000000 GHz
CF Step
400.000 kHz
Auto
Man
Freq Offset
0 Hz

Appendix A.2: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	1.0503	2401.6480	2402.6983	---	---
		2440	1.0658	2439.6420	2440.7078	---	---
		2480	1.0766	2479.6363	2480.7129	---	---

Test Graphs

BLE_Ant1_2402



BLE_Ant1_2440

BLE_Ant1_2480

Keysight Spectrum Analyzer - Occupied BW
RL
RF
50 Ω AC
SENSE:INT
ALIGN AUTO
06:51:41 AM Jul 13, 2026
Center Freq 2.480000000 GHz
#IFGain:Low
Center Freq: 2.480000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 40 dB
Radio Std: None
Radio Device: BTS
Frequency
Ref Offset 9.05 dB
10 dB/div
Ref 30.00 dBm
Log
Mkr1 2.479924 GHz
-2.1753 dBm
20.0
10.0
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
Center 2.48 GHz
#Res BW 43 kHz
#VBW 130 kHz
Span 4 MHz
Sweep 2.067 ms
Occupied Bandwidth
1.0766 MHz
Total Power
8.11 dBm
Transmit Freq Error
174.63 kHz
% of OBW Power
99.00 %
x dB Bandwidth
1.343 MHz
x dB
-26.00 dB
Center Freq
2.480000000 GHz
CF Step
400.000 kHz
Auto
Man
Freq Offset
0 Hz
MSG
STATUS

Appendix A.3: Maximum conducted output power

Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Powert[dBm]	Conducted Limit[dBm]	Verdict
BLE	Ant1	2402	1.34	≤30	PASS
		2440	1.84	≤30	PASS
		2480	1.56	≤30	PASS

Appendix A.4: Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant1	2402	-14.92	≤8.00	PASS
		2440	-14.43	≤8.00	PASS
		2480	-14.45	≤8.00	PASS

Test Graphs

BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 30 dB
#Avg Type: RMS
Avg|Hold: 100/100
06:52:32 AM Jul 13, 2026
Ref Offset 9.05 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.480 173 9 GHz
-14.454 dBm
Center 2.480000 GHz
#Res BW 3.0 kHz
#VBW 10 kHz
Span 3.000 MHz
Sweep 318.0 ms (30000 pts)
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.478500000 GHz
Stop Freq
2.481500000 GHz
CF Step
300.000 kHz
Auto
Man
Freq Offset
0 Hz

Appendix A.5: Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	Low	2402	0.45	-44.12	≤-19.55	PASS
		High	2480	0.68	-45.4	≤-19.33	PASS

Test Graphs

BLE_Ant1_Low_2402



BLE_Ant1_High_2480



Appendix A.6: Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	2402	Reference	0.25	0.25	---	PASS
			30~1000	0.25	-55.74	≤-19.75	PASS
			1000~26500	0.25	-47.75	≤-19.75	PASS
		2440	Reference	0.77	0.77	---	PASS
			30~1000	0.77	-55.26	≤-19.23	PASS
			1000~26500	0.77	-47.53	≤-19.23	PASS
		2480	Reference	0.42	0.42	---	PASS
			30~1000	0.42	-55.57	≤-19.58	PASS
			1000~26500	0.42	-46.56	≤-19.58	PASS

Test Graphs

BLE_Ant1_2402_0~Reference

BLE_Ant1_2402_30~1000



BLE_Ant1_2402_1000~26500



BLE_Ant1_2440_0~Reference

BLE_Ant1_2440_30~1000



BLE_Ant1_2440_1000~26500

BLE_Ant1_2480_0~Reference
BLE_Ant1_2480_30~1000



BLE_Ant1_2480_1000~26500



Appendix A.7: Duty Cycle

Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	Duty Cycle Factor[dB]	1/T Factor[KHz]
BLE	Ant1	2402	0.61	1.25	0.4880	48.80	3.12	1.64
		2440	0.61	1.25	0.4880	48.80	3.12	1.64
		2480	0.61	1.25	0.4880	48.80	3.12	1.64

Test Graphs

BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
PNO: Fast
IFGain:Low
Trig Delay-200.0 µs
Trig: Video
#Avg Type: RMS
#Atten: 30 dB
10:06:42 PM Jul 13, 2026
Frequency
Auto Tune
Ref Offset 9.05 dB
10 dB/div
Ref 20.00 dBm
ΔMkr3 1.250 ms
-3.37 dB
Center 2.480000000 GHz
Res BW 8 MHz
#VBW 8.0 MHz*
Span 0 Hz
Sweep 10.13 ms (8000 pts)
1 N 1 t 7.690 ms -5.59 dBm
2 Δ1 1 t (Δ) 610.0 µs (Δ) -33.41 dB
3 Δ1 1 t (Δ) 1.250 ms (Δ) -3.37 dB
Center Freq
2.480000000 GHz
Start Freq
2.480000000 GHz
Stop Freq
2.480000000 GHz
CF Step
8.000000 MHz
Auto
Man
Freq Offset
0 Hz

Appendix A.8: Emissions in Restricted Bands

Test Result

TestMode	Antenna	ChName	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE	Ant1	Low	2402	AV	2310.000	-48.98	≤-41.20	46.22	≤54	PASS
				AV	2378.750	-48.17	≤-41.20	47.03	≤54	PASS
				AV	2390.000	-48.47	≤-41.20	46.73	≤54	PASS
				Peak	2310.000	-42.09	≤-21.20	53.11	≤74	PASS
				Peak	2386.415	-38.47	≤-21.20	56.73	≤74	PASS
				Peak	2390.000	-41.76	≤-21.20	53.44	≤74	PASS
		High	2480	AV	2483.500	-47.13	≤-41.20	48.07	≤54	PASS
				AV	2483.840	-47.02	≤-41.20	48.18	≤54	PASS
				AV	2500.000	-48.01	≤-41.20	47.19	≤54	PASS
				Peak	2483.500	-40.65	≤-21.20	54.55	≤74	PASS
				Peak	2488.480	-38.63	≤-21.20	56.57	≤74	PASS
				Peak	2500.000	-40.82	≤-21.20	54.38	≤74	PASS

Note：

1. The Antenna Gain is compensated in the graph.
2. The Duty Cycle Factor and RBW Factor is compensated in the graph.
3. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

BLE_BT4.0_Ant1_Low_2402_AV



BLE_BT4.0_Ant1_Low_2402_Peak



BLE_BT4.0_Ant1_High_2480_AV



BLE_BT4.0_Ant1_High_2480_Peak