

RF Exposure Evaluation
FOR
Foshan Chentu Changxing Technology Co., Ltd.
Portable Wireless Display Monitor
Test Model: AUSTA-A9

Prepared for	:	Foshan Chentu Changxing Technology Co., Ltd.
Address	:	Room 401-2, 4th Floor, Workshop, No.26 North Lake 2nd Road, Shishan Town, Nanhai District, Foshan City, Guangdong, China
Prepared by	:	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	:	No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Tel	:	(+86) 020-39166689
Fax	:	(+86) 020-39166619
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	June 17, 2026
Number of tested samples	:	2
Sample No.	:	C260608004-1, C260608004-2
Serial number	:	Prototype
Date of Test	:	June 17, 2026 ~ July 21, 2026
Date of Report	:	July 22, 2026


RF Exposure Evaluation

Report Reference No. : LCSC06036005EG
Date of Issue..... : July 22, 2026
Testing Laboratory Name..... : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address..... : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
**Testing Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**
Applicant's Name..... : Foshan Chentu Changxing Technology Co., Ltd.
Address..... : Room 401-2, 4th Floor, Workshop, No.26 North Lake 2nd Road, Shishan Town, Nanhai District, Foshan City, Guangdong, China
Test Specification
**Standard..... : FCC KDB publication 447498 D01 General RF Exposure Guidance v06
FCC CFR 47 part1 1.1310
FCC CFR 47 part2 2.1091**
Test Report Form No..... : TRF-4-E-214 A/0
TRF Originator..... : Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF..... : Dated 2011-03
Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.


This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Portable Wireless Display Monitor
Trade Mark..... : N/A
Test Model..... : AUSTA-A9
Ratings..... : Please Refer to Page 6
Result : Pass
Compiled by:


Lifeng Le/ Administrators

Supervised by:


Justin Zhu/ Technique Director

Approved by:


Gavin Liang/ Manager

RF Exposure Evaluation

Test Report No. : LCSC06036005EG	<u>July 22, 2026</u> Date of issue
----------------------------------	---------------------------------------

EUT.....	: Portable Wireless Display Monitor
Test Model.....	: AUSTA-A9
Applicant.....	: Foshan Chentu Changxing Technology Co., Ltd.
Address.....	: Room 401-2, 4th Floor, Workshop, No.26 North Lake 2nd Road, Shishan Town, Nanhai District, Foshan City, Guangdong, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Foshan Chentu Changxing Technology Co., Ltd.
Address.....	: Room 401-2, 4th Floor, Workshop, No.26 North Lake 2nd Road, Shishan Town, Nanhai District, Foshan City, Guangdong, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Foshan Chentu Changxing Technology Co., Ltd.
Address.....	: Room 401-2, 4th Floor, Workshop, No.26 North Lake 2nd Road, Shishan Town, Nanhai District, Foshan City, Guangdong, China
Telephone.....	: /
Fax.....	: /

Test Result	Pass
-------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	July 22, 2026	Initial Issue	---

TABLE OF CONTENTS

Description	Page
1. Product Information	6
2. Evaluation Method	8
3. Limit	8
4. MPE Calculation Method	9
5. Conducted Power	9
6. Manufacturing Tolerance	10
7. Measurement Results	13
8. Conclusion	15
9. Description of Test Facility	15
10.Measurement Uncertainty	15

1. Product Information

EUT	: Portable Wireless Display Monitor
Test Model	: AUSTA-A9
Ratings	: Input: DC 12-24V
Hardware Version	: /
Software Version	: SL32_NDFZ_S217201-20260515.17.37
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.4(DSS)
Channel Spacing	: 1MHz for Bluetooth V5.4 (DSS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.4(DSS)
Bluetooth Version	: V5.4
Antenna Description	: External Antenna, 2.41dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: External Antenna, 2.61dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: External Antenna, -0.02dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: External Antenna, 3.68dBi(Max.)
3G	:
Support Band	: ☒ WCDMA Band II (U.S.-Band) ☒ WCDMA Band IV (U.S.-Band) ☒ WCDMA Band V (U.S.-Band)
Release Version	: R7
Type Of Modulation	: QPSK/16QAM
Antenna Description	: External Antenna 1.03dBi (max.) For WCDMA Band II 1.25dBi (max.) For WCDMA Band IV 1.08dBi (max.) For WCDMA Band V
LTE	:
Support Band	: ☒ E-UTRA Band 2(U.S.-Band) ☒ E-UTRA Band 4(U.S.-Band) ☒ E-UTRA Band 5(U.S.-Band) ☒ E-UTRA Band 12(U.S.-Band) ☒ E-UTRA Band 13(U.S.-Band) ☒ E-UTRA Band 17(U.S.-Band)

- ☒ E-UTRA Band 25(U.S.-Band)
- ☒ E-UTRA Band 26(U.S.-Band)
- ☒ E-UTRA Band 41(U.S.-Band)
- ☒ E-UTRA Band 66(U.S.-Band)
- ☒ E-UTRA Band 71(U.S.-Band)

LTE Release Version : R11

Type Of Modulation : QPSK/16QAM

Antenna Description : External Antenna

- 1.03dBi (max.) For E-UTRA Band 2
- 1.25dBi (max.) For E-UTRA Band 4
- 1.08dBi (max.) For E-UTRA Band 5
- 7.77dBi (max.) For E-UTRA Band 12
- 2.39dBi (max.) For E-UTRA Band 13
- 9.49dBi (max.) For E-UTRA Band 17
- 1.03dBi (max.) For E-UTRA Band 25
- 0.45dBi (max.) For E-UTRA Band 26
- 0.57dBi (max.) For E-UTRA Band 41
- 1.25dBi (max.) For E-UTRA Band 66
- 5.78dBi (max.) For E-UTRA Band 71

Power Class : Class 3

Extreme temp. Tolerance : -30°C to +50°C

Extreme vol. Limits : 10.2VDC to 13.8VDC (nominal: 12VDC)

Exposure category : General population/uncontrolled environment

EUT Type : Production Unit

Device Type : Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer Evaluation Method

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	2.24
	39	2441	3.49
	78	2480	2.28
$\pi/4$ -DQPSK	0	2402	3.78
	39	2441	3.47
	78	2480	3.41
8DPSK	0	2402	2.81
	39	2441	3.67
	78	2480	3.58

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
11B	1	2412	13.37
	6	2437	13.81
	11	2462	13.03
11G	1	2412	13.4
	6	2437	14.13
	11	2462	13.14
11N20 SISO	1	2412	13.1
	6	2437	13.93
	11	2462	14.09
11N40 SISO	3	2422	13.89
	6	2437	13.28
	9	2452	14.41

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	36	5180	12.44
	40	5200	12.46
	48	5240	12.04
11N20 SISO	36	5180	12.38

	40	5200	12.19
	48	5240	11.8
11N40 SISO	38	5190	12.23
	46	5230	12.16
11AC20 SISO	36	5180	12.13
	40	5200	12.2
	48	5240	11.74
11AC40 SISO	38	5190	12.37
	46	5230	11.96

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	149	5745	12.89
	157	5785	11.65
	165	5825	10.78
11N20 SISO	149	5745	12.88
	157	5785	11.7
	165	5825	10.81
11N40 SISO	151	5755	12.9
	159	5795	11.6
11AC20 SISO	149	5745	12.93
	157	5785	11.69
	165	5825	10.81
11AC40 SISO	151	5755	12.73
	159	5795	11.73

6. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	3.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	3.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	3.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI]

11B (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	12.0	12.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	12.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[5.8G WIFI]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[WCDMA Max Average Power]

Test Mode	Channel	Frequency (MHz)	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)
WCDMA Band II	Low	1852.4	23.38	23.0 $\pm$ 1.0
	Middle	1880	23.24	23.0 $\pm$ 1.0
	High	1907.6	23.09	23.0 $\pm$ 1.0
WCDMA Band IV	Low	1712.4	23.28	23.0 $\pm$ 1.0
	Middle	1732.6	23.41	23.0 $\pm$ 1.0
	High	1752.6	23.33	23.0 $\pm$ 1.0
WCDMA Band V	Low	826.4	23.08	23.0 $\pm$ 1.0
	Middle	836.4	23.14	23.0 $\pm$ 1.0
	High	846.6	23.11	23.0 $\pm$ 1.0

[LTE Max Average Power]

Test Mode		Channel	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)
LTE	Band 2	LCH	24.77	24.0 $\pm$ 1.0
		MCH	24.93	24.0 $\pm$ 1.0
		HCH	24.72	24.0 $\pm$ 1.0
	Band 4	LCH	24.88	24.0 $\pm$ 1.0
		MCH	24.85	24.0 $\pm$ 1.0
		HCH	25.05	25.0 $\pm$ 1.0
	Band 5	LCH	24.31	24.0 $\pm$ 1.0
		MCH	24.25	24.0 $\pm$ 1.0
		HCH	24.44	24.0 $\pm$ 1.0

	Band 12	LCH	24.22	24.0±1.0
		MCH	24.3	24.0±1.0
		HCH	24.32	24.0±1.0
	Band 13	LCH	24.34	24.0±1.0
		MCH	24.37	24.0±1.0
		HCH	24.29	24.0±1.0
	Band 17	LCH	24.33	24.0±1.0
		MCH	24.28	24.0±1.0
		HCH	24.3	24.0±1.0
	Band 25	LCH	25.02	25.0±1.0
		MCH	25.07	25.0±1.0
		HCH	24.79	24.0±1.0
	Band 26-1	LCH	24.44	24.0±1.0
		MCH	24.52	24.0±1.0
		HCH	24.63	24.0±1.0
	Band 26-2	LCH	24.59	24.0±1.0
		MCH	24.43	24.0±1.0
		HCH	24.33	24.0±1.0
	Band 41	LCH	24.73	24.0±1.0
		MCH	24.79	24.0±1.0
		HCH	25.61	25.0±1.0
	Band 66	LCH	24.95	24.0±1.0
		MCH	25.05	25.0±1.0
		HCH	25.29	25.0±1.0
	Band 71	LCH	24.2	24.0±1.0
		MCH	24.01	24.0±1.0
		HCH	24.11	24.0±1.0

7. Measurement Results

7.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios ¹
	dBm	mW					
GFSK	4.0	2.5119	2.41	1.7418	0.0009	1.0000	0.0009
$\pi/4$ -DQPSK	4.0	2.5119	2.41	1.7418	0.0009	1.0000	0.0009
8-DPSK	4.0	2.5119	2.41	1.7418	0.0009	1.0000	0.0009

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios ¹
	dBm	mW					
IEEE 802.11b	14.0	25.1189	2.61	1.8239	0.0091	1.0000	0.0091
IEEE 802.11g	15.0	31.6228	2.61	1.8239	0.0115	1.0000	0.0115
IEEE 802.11n HT20	15.0	31.6228	2.61	1.8239	0.0115	1.0000	0.0115
IEEE 802.11n HT40	15.0	31.6228	2.61	1.8239	0.0115	1.0000	0.0115

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
IEEE 802.11a	13.0	19.9526	-0.02	0.9954	0.0040	1.0000	0.0040
IEEE 802.11n HT20	13.0	19.9526	-0.02	0.9954	0.0040	1.0000	0.0040
IEEE 802.11n HT40	13.0	19.9526	-0.02	0.9954	0.0040	1.0000	0.0040
IEEE 802.11ac VHT20	13.0	19.9526	-0.02	0.9954	0.0040	1.0000	0.0040
IEEE 802.11ac VHT40	13.0	19.9526	-0.02	0.9954	0.0040	1.0000	0.0040

[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
IEEE 802.11a	13.0	19.9526	3.68	2.3335	0.0093	1.0000	0.0093
IEEE 802.11n HT20	13.0	19.9526	3.68	2.3335	0.0093	1.0000	0.0093
IEEE 802.11n HT40	13.0	19.9526	3.68	2.3335	0.0093	1.0000	0.0093
IEEE 802.11ac VHT20	13.0	19.9526	3.68	2.3335	0.0093	1.0000	0.0093
IEEE 802.11ac VHT40	13.0	19.9526	3.68	2.3335	0.0093	1.0000	0.0093

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios2
	dBm	mW					
WCDMA Band II	24.0	251.1886	1.03	1.2677	0.0634	1.0000	0.0634
WCDMA Band IV	24.0	251.1886	1.25	1.3335	0.0667	1.0000	0.0667
WCDMA Band V	24.0	251.1886	1.08	1.2823	0.0641	0.5493	0.1167
LTE Band 2	25.0	316.2278	1.03	1.2677	0.0798	1.0000	0.0798
LTE Band 4	25.0	316.2278	1.25	1.3335	0.0839	1.0000	0.0839
LTE Band 5	25.0	316.2278	1.08	1.2823	0.0807	0.5493	0.1469
LTE Band 12	25.0	316.2278	-2.39	0.5768	0.0363	0.4660	0.0779
LTE Band 13	25.0	316.2278	-9.49	0.1125	0.0071	0.5180	0.0137
LTE Band 17	25.0	316.2278	1.03	1.2677	0.0798	0.4693	0.1700
LTE Band 25	26.0	398.1072	0.45	1.1092	0.0879	1.0000	0.0879
LTE Band 26	25.0	316.2278	0.57	1.1402	0.0718	0.5427	0.1322
LTE Band 41	26.0	398.1072	1.25	1.3335	0.1057	1.0000	0.1057
LTE Band 66	26.0	398.1072	-5.78	0.2642	0.0209	1.0000	0.0209
LTE Band 71	25.0	316.2278	1.03	1.2677	0.0798	0.4420	0.1805

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7.2 Simultaneous Transmission MPE Evaluation

The sample support one BT & 2.4G WLAN, one 5.2G WLAN & 5.8G WLAN, another WCDMA & LTE transmit antenna, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$$TER = \sum_{k=1}^{N_S} \left(\frac{SAR_k}{SAR_{lim}} \right) + \sum_{k=1}^{N_f} \left(\frac{MPE_{field,k}}{MPE_{field,lim}} \right)^2 + \sum_{k=1}^{N_{PD}} \left(\frac{MPE_{PD,k}}{MPE_{PD,lim}} \right)$$

$\sum \sum$ of MPE ratios ≤ 1.0

Max MPE ratios1	Max MPE ratios2	Max MPE ratios3	$\sum$ MPE ratios	Limit	Results
0.0115	0.0093	0.1805	0.2013	1.000	Pass

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

9. Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

10.Measurement Uncertainty

BT/2.4G WLAN/5.2G WLAN/5.8G WLAN/WCDMA/LTE:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	± 0.57 dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----