

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

digital calendar

MODEL NUMBER: LW-DC215, LW-DC156

REPORT NUMBER: 4792341462-2-RF-1

ISSUE DATE: September 1, 2026

FCC ID: 2BXYF-LW-DC156

Prepared for

**Guangdong Liwan Intelligent Electrical Appliances Co., Ltd.
Room 101, No. 1, Dongye Road, Houjie Town, DONGGUAN CITY, Guangdong
Province**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	September 1, 2026	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2020, Clause 11.9.2.3.1	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020, Clause 11.8.1 & 6.9.3	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2020, Clause 11.10.5 & 11.10.3	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2020, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020, Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

Note:

1. For FCC, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 standards.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <FCC 47 CFR PART 15 SUBPART C> when <Simple Acceptance> decision rule is applied. Decision rule for statement of conformity: The measurement uncertainty is not taken into account for statement of conformity.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>8</i>
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	<i>9</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>MAXIMUM POWER</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>10</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>11</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	<i>12</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	13
7. ANTENNA PORT TEST RESULTS	16
7.1. <i>CONDUCTED OUTPUT POWER</i>	<i>16</i>
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>	<i>17</i>
7.3. <i>POWER SPECTRAL DENSITY</i>	<i>19</i>
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION.....</i>	<i>20</i>
7.5. <i>DUTY CYCLE</i>	<i>22</i>
8. RADIATED TEST RESULTS.....	23
8.1. <i>RESTRICTED BANDEDGE</i>	<i>30</i>
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i>	<i>48</i>
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i>	<i>54</i>
8.4. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i>	<i>78</i>
8.5. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-21.5'.....</i>	<i>80</i>
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-21.5'</i>	<i>83</i>
8.7. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-15.6'.....</i>	<i>85</i>
8.8. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-15.6'</i>	<i>88</i>
9. ANTENNA REQUIREMENT	90

10.	AC POWER LINE CONDUCTED EMISSION	91
11.	TEST DATA.....	96
11.1.	<i>APPENDIX A: DTS BANDWIDTH.....</i>	<i>96</i>
11.1.1.	Test Result.....	96
11.1.2.	Test Graphs	97
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....</i>	<i>101</i>
11.2.1.	Test Result.....	101
11.2.2.	Test Graphs	102
11.3.	<i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....</i>	<i>106</i>
11.3.1.	Test Result.....	106
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY.....</i>	<i>107</i>
11.4.1.	Test Result.....	107
11.4.2.	Test Graphs	108
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS.....</i>	<i>112</i>
11.5.1.	Test Result.....	112
11.5.2.	Test Graphs	113
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i>	<i>116</i>
11.6.1.	Test Result.....	116
11.6.2.	Test Graphs	117
11.7.	<i>APPENDIX G: DUTY CYCLE.....</i>	<i>129</i>
11.7.1.	Test Result.....	129
11.7.2.	Test Graphs	130

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Guangdong Liwan Intelligent Electrical Appliances Co., Ltd.
Address: Room 101, No. 1, Dongye Road, Houjie Town, DONGGUAN CITY, Guangdong Province

Manufacturer Information

Company Name: Guangdong Liwan Intelligent Electrical Appliances Co., Ltd.
Address: Room 101, No. 1, Dongye Road, Houjie Town, DONGGUAN CITY, Guangdong Province

EUT Information

EUT Name: digital calendar
Model: LW-DC215
Series Model: LW-DC156
Model Difference: Please refer to the Model Difference Letter.
Sample Received Date: August 4, 2026
Sample ID: 10024146
Date Tested: August 9, 2026 to September 1, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR PART 15 SUBPART C	Pass


Prepared By:



Johnson Liu

Laboratory Engineer Associate

Checked By:



Kebo Zhang

Operations Leader

Approved By:



Stephen Guo

Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC 47 CFR PART 15 SUBPART C, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, FCC 47 CFR Part 2, ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	4.36 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.47 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.65 dB (1 GHz ~ 18 GHz)
	4.73 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

Remark: For Radiated Emission measurements (200 MHz - 18 GHz), the EUT support table is made of Expanded Polystyrene (EPS). This material is characterized by a low dielectric constant, as recognized in CISPR 16-1-4, to minimize its influence on field strength measurements. This influence has been considered in the uncertainty budget.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	digital calendar
Model:	LW-DC215
Series Model:	LW-DC156
Model Difference:	Please refer to the Model Difference Letter.

Note: For the two different sized models, after preliminary investigation and comparison, the RF circuitry and performance of the RF section are the same, so only the radiation below 1 GHz and the AC Conducted Power Line Emission test results are recorded in the report.

Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Radio Technology:	IEEE 802.11b/g/n HT20/n HT40
Normal Test Voltage:	AC 120 V, 60 Hz

5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List For Bandwidth=40 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)
b	2412 ~ 2462	1-11[11]	2.55
g	2412 ~ 2462	1-11[11]	9.86
n HT20	2412 ~ 2462	1-11[11]	8.8
n HT40	2422 ~ 2452	3-9[7]	9.39

Note:

- Maximum conducted output power = measured value + cable loss (provided by UL)

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		ADB					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	2	2	2	/		
802.11g	1	11	11	11			
802.11n HT20	1	10	10	10			
802.11n HT40	1	/			11	11	11

WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

802.11n HT40 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	Monopole Type	1.65

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

5.7. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E14	/
2	Adaptor	/	AED24H-1202000VWSW0	Input: AC 100-240V, 50-60Hz, 1A Output: DC 12V, 2A
3	USB Flash Drive	/	/	/
4	Earphone	/	/	/
5	SD Memory Card	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.26,2025	Dec.25,2026
Vector Signal Generator	R&S	SMBV100A	261637	Sep.12, 2025	Sep.11, 2026
Signal Generator	R&S	SMB100A	178553	Sep.12, 2025	Sep.11, 2026
Signal Analyzer	R&S	FSV40	101118	Sep.12, 2025	Sep.11, 2026
Software					
Description		Manufacturer	Name		Version
For R&S TS 8997 Test System		Rohde & Schwarz	EMC 32		10.60.10
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.12, 2025	Sep.11, 2026
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.12, 2025	Sep.11, 2026
DC power supply	TSSTAKASAGO	ZX-400L	409150160137	Sep.12, 2025	Sep.11, 2026
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.12, 2025	Sep.11, 2026
Attenuator	Aglient	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.26,2025	Dec.25,2026
Software					
Description	Manufacturer	Name			Version
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System			V3.2.22

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.12, 2025	Sep.11, 2026
Two-Line V-Network	R&S	ENV216	101983	Sep.12, 2025	Sep.11, 2026
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.12, 2025	Sep.11, 2026
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.12, 2025	Sep.11, 2026
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.12, 2025	Sep.11, 2026
EMI Measurement Receiver	R&S	ESR26	101377	Sep.12, 2025	Sep.11, 2026
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.12, 2025	Sep.11, 2026
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.12, 2025	Sep.11, 2026
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.12, 2025	Sep.11, 2026
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.12, 2025	Sep.11, 2026
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.12, 2025	Sep.11, 2026
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Sep.16, 2025	Sep.15, 2026
Barometer	Baumer	N/A	N/A	Sep.19, 2025	Sep.18, 2026
Attenuator	Agilent	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(b)(3) ISED RSS-247 6.3.2	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.7°C	Relative Humidity	55.0%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	August 17, 2026	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 1 % to 5 % of the OBW but not less than 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.7℃	Relative Humidity	55.0%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	August 17, 2026	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$> 1.5 \times \text{OBW bandwidth}$
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.7°C	Relative Humidity	55.0%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	August 17, 2026	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

FCC 47 CFR Part15 (15.247) Subpart C		
Section	Test Item	Limit
FCC 47 CFR §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.11.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$\geq 1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP**TEST ENVIRONMENT**

Temperature	24.7℃	Relative Humidity	55.0%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	August 17, 2026	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.7°C	Relative Humidity	55.0%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	August 17, 2026	Test By	Bairong Liu
-----------	-----------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to FCC 47 CFR §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC 47 CFR §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For above 1GHz radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For below 1GHz radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (Y axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/T_{on}$, where: T_{on} is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	22.3°C	Relative Humidity	61.4%
Atmosphere Pressure	101kPa	Test Voltage	


TEST DATE / ENGINEER

Test Date	August 13, 2026	Test By	Stipe Zheng
-----------	-----------------	---------	-------------

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2354.045	20.83	31.82	52.65	74.00	-21.35	peak
2	2390.000	18.77	31.99	50.76	74.00	-23.24	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2354.045	5.93	31.81	37.74	54.00	-16.26	AVG
2	2390.000	6.30	31.99	38.29	54.00	-15.71	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2375.780	20.12	31.92	52.04	74.00	-21.96	peak
2	2390.000	18.57	31.99	50.56	74.00	-23.44	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2375.780	6.81	31.92	38.73	54.00	-15.27	AVG
2	2390.000	6.18	31.99	38.17	54.00	-15.83	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.95	32.35	52.30	74.00	-21.70	peak
2	2497.250	20.91	32.40	53.31	74.00	-20.69	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	6.25	32.35	38.60	54.00	-15.40	AVG
2	2497.250	6.42	32.40	38.82	54.00	-15.18	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.350	24.65	31.98	56.63	74.00	-17.37	peak
2	2390.000	21.00	31.99	52.99	74.00	-21.01	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.350	7.50	31.98	39.48	54.00	-14.52	AVG
2	2390.000	7.62	31.99	39.61	54.00	-14.39	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	23.95	32.35	56.30	74.00	-17.70	peak
2	2484.400	29.29	32.35	61.64	74.00	-12.36	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.50	32.35	39.85	54.00	-14.15	AVG
2	2484.400	7.47	32.35	39.82	54.00	-14.18	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.925	40.84	31.99	72.83	74.00	-1.17	peak
2	2390.000	31.35	31.99	63.34	74.00	-10.66	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.925	14.42	31.99	46.41	54.00	-7.59	AVG
2	2390.000	14.69	31.99	46.68	54.00	-7.32	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	33.62	32.35	65.97	74.00	-8.03	peak
2	2483.750	40.36	32.35	72.71	74.00	-1.29	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	11.29	32.35	43.64	54.00	-10.36	AVG
2	2483.750	11.07	32.35	43.42	54.00	-10.58	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	40.64	31.99	72.63	74.00	-1.37	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	15.60	31.99	47.59	54.00	-6.41	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.11	32.35	71.46	74.00	-2.54	peak
2	2483.620	40.27	32.35	72.62	74.00	-1.38	peak
3	2483.690	37.79	32.35	70.14	74.00	-3.86	peak


Test Mode:	802.11n HT40 AV	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.16	32.35	49.51	54.00	-4.49	AVG
2	2483.620	17.28	32.35	49.63	54.00	-4.37	AVG
3	2483.690	17.69	32.35	50.04	54.00	-3.96	AVG


8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1006.000	54.38	-13.87	40.51	74.00	-33.49	peak
2	1458.000	52.59	-11.83	40.76	74.00	-33.24	peak
3	1950.000	48.29	-9.93	38.36	74.00	-35.64	peak
4	2342.000	55.91	-8.82	47.09	74.00	-26.91	peak
5	2412.000	55.34	-8.43	46.91	/	/	Fundamental
6	2640.000	52.40	-7.38	45.02	74.00	-28.98	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1148.000	50.92	-13.25	37.67	74.00	-36.33	peak
2	1498.000	51.56	-11.65	39.91	74.00	-34.09	peak
3	1850.000	50.53	-10.38	40.15	74.00	-33.85	peak
4	2150.000	50.03	-9.72	40.31	74.00	-33.69	peak
5	2412.000	50.18	-8.42	41.76	/	/	Fundamental
6	2640.000	55.50	-7.38	48.12	74.00	-25.88	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1018.000	53.06	-13.82	39.24	74.00	-34.76	peak
2	1348.000	52.96	-12.33	40.63	74.00	-33.37	peak
3	1950.000	50.53	-9.93	40.60	74.00	-33.40	peak
4	2348.000	54.58	-8.78	45.80	74.00	-28.20	peak
5	2437.000	56.46	-8.26	48.20	/	/	Fundamental
6	2640.000	52.33	-7.38	44.95	74.00	-29.05	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1050.000	53.88	-13.68	40.20	74.00	-33.80	peak
2	1348.000	52.26	-12.33	39.93	74.00	-34.07	peak
3	1950.000	52.88	-9.93	42.95	74.00	-31.05	peak
4	2437.000	47.77	-8.27	39.50	/	/	Fundamental
5	2640.000	55.11	-7.38	47.73	74.00	-26.27	peak
6	2696.000	52.78	-7.18	45.60	74.00	-28.40	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1016.000	54.13	-13.83	40.30	74.00	-33.70	peak
2	1474.000	52.82	-11.75	41.07	74.00	-32.93	peak
3	2050.000	47.95	-9.72	38.23	74.00	-35.77	peak
4	2348.000	51.92	-8.78	43.14	74.00	-30.86	peak
5	2462.000	51.45	-8.15	43.30	/	/	Fundamental
6	2640.000	52.94	-7.38	45.56	74.00	-28.44	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1056.000	50.97	-13.65	37.32	74.00	-36.68	peak
2	1346.000	53.05	-12.34	40.71	74.00	-33.29	peak
3	1950.000	53.54	-9.93	43.61	74.00	-30.39	peak
4	2348.000	46.96	-8.78	38.18	74.00	-35.82	peak
5	2640.000	53.61	-7.38	46.23	74.00	-27.77	peak
6	2700.000	52.25	-7.17	45.08	74.00	-28.92	peak


8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	52.49	0.22	52.71	74.00	-21.29	peak
2	9405.000	35.84	10.78	46.62	74.00	-27.38	peak
3	10500.000	34.25	14.04	48.29	74.00	-25.71	peak
4	12645.000	28.08	19.30	47.38	74.00	-26.62	peak
5	14040.000	26.97	23.83	50.80	74.00	-23.20	peak
6	17955.000	23.13	27.69	50.82	74.00	-23.18	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	45.61	0.22	45.83	74.00	-28.17	peak
2	7920.000	37.75	7.76	45.51	74.00	-28.49	peak
3	10620.000	32.62	14.36	46.98	74.00	-27.02	peak
4	12330.000	28.25	18.88	47.13	74.00	-26.87	peak
5	13965.000	26.80	23.93	50.73	74.00	-23.27	peak
6	18000.000	22.41	27.98	50.39	74.00	-23.61	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	53.27	0.35	53.62	74.00	-20.38	peak
2	4875.000	51.72	0.35	52.07	54.00	-1.93	AVG
3	6990.000	38.25	5.97	44.22	74.00	-29.78	peak
4	10140.000	33.33	13.06	46.39	74.00	-27.61	peak
5	11730.000	29.82	17.53	47.35	74.00	-26.65	peak
6	13980.000	26.39	23.98	50.37	74.00	-23.63	peak
7	18000.000	22.67	27.98	50.65	74.00	-23.35	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5805.000	42.66	2.15	44.81	74.00	-29.19	peak
2	7920.000	38.40	7.76	46.16	74.00	-27.84	peak
3	10230.000	33.18	13.34	46.52	74.00	-27.48	peak
4	11265.000	30.16	16.18	46.34	74.00	-27.66	peak
5	13980.000	26.25	23.98	50.23	74.00	-23.77	peak
6	18000.000	22.40	27.98	50.38	74.00	-23.62	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	52.71	0.45	53.16	74.00	-20.84	peak
2	4920.000	52.09	0.45	52.54	54.00	-1.46	AVG
3	8040.000	37.95	7.98	45.93	74.00	-28.07	peak
4	10590.000	32.09	14.27	46.36	74.00	-27.64	peak
5	12630.000	28.72	19.28	48.00	74.00	-26.00	peak
6	13950.000	26.16	23.87	50.03	74.00	-23.97	peak
7	18000.000	22.86	27.98	50.84	74.00	-23.16	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5805.000	42.23	2.15	44.38	74.00	-29.62	peak
2	7920.000	38.57	7.76	46.33	74.00	-27.67	peak
3	9960.000	34.72	12.49	47.21	74.00	-26.79	peak
4	11595.000	29.90	17.13	47.03	74.00	-26.97	peak
5	14010.000	26.43	24.00	50.43	74.00	-23.57	peak
6	17955.000	22.65	27.69	50.34	74.00	-23.66	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	58.25	0.22	58.47	74.00	-15.53	peak
2	4815.000	52.04	0.22	52.26	54.00	-1.74	AVG
3	8190.000	37.27	8.06	45.33	74.00	-28.67	peak
4	10410.000	34.16	13.79	47.95	74.00	-26.05	peak
5	11790.000	30.61	17.71	48.32	74.00	-25.68	peak
6	13995.000	26.83	24.04	50.87	74.00	-23.13	peak
7	18000.000	22.52	27.98	50.50	74.00	-23.50	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	48.18	0.26	48.44	74.00	-25.56	peak
2	7920.000	40.14	7.76	47.90	74.00	-26.10	peak
3	10590.000	32.52	14.27	46.79	74.00	-27.21	peak
4	11805.000	29.60	17.76	47.36	74.00	-26.64	peak
5	13980.000	26.22	23.98	50.20	74.00	-23.80	peak
6	18000.000	22.94	27.98	50.92	74.00	-23.08	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	55.65	0.35	56.00	74.00	-18.00	peak
2	4875.000	49.48	0.35	49.83	54.00	-4.17	AVG
3	8025.000	36.51	7.97	44.48	74.00	-29.52	peak
4	10560.000	32.85	14.20	47.05	74.00	-26.95	peak
5	11820.000	28.91	17.80	46.71	74.00	-27.29	peak
6	13965.000	26.60	23.93	50.53	74.00	-23.47	peak
7	18000.000	22.64	27.98	50.62	74.00	-23.38	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.09	0.35	46.44	74.00	-27.56	peak
2	7920.000	38.62	7.76	46.38	74.00	-27.62	peak
3	10530.000	32.60	14.12	46.72	74.00	-27.28	peak
4	11640.000	30.36	17.27	47.63	74.00	-26.37	peak
5	13890.000	26.88	23.64	50.52	74.00	-23.48	peak
6	17955.000	22.92	27.69	50.61	74.00	-23.39	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	56.02	0.45	56.47	74.00	-17.53	peak
2	4920.000	51.68	0.45	52.13	54.00	-1.87	AVG
3	7380.000	39.83	6.59	46.42	74.00	-27.58	peak
4	10410.000	33.15	13.79	46.94	74.00	-27.06	peak
5	11700.000	30.60	17.44	48.04	74.00	-25.96	peak
6	14340.000	28.31	22.28	50.59	74.00	-23.41	peak
7	18000.000	22.56	27.98	50.54	74.00	-23.46	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	45.85	0.45	46.30	74.00	-27.70	peak
2	7920.000	39.02	7.76	46.78	74.00	-27.22	peak
3	10215.000	33.37	13.31	46.68	74.00	-27.32	peak
4	11895.000	29.51	17.99	47.50	74.00	-26.50	peak
5	14025.000	26.62	23.92	50.54	74.00	-23.46	peak
6	17970.000	22.28	27.79	50.07	74.00	-23.93	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	57.51	0.22	57.73	74.00	-16.27	peak
2	4815.000	52.23	0.22	52.45	54.00	-1.55	AVG
3	6960.000	38.86	5.88	44.74	74.00	-29.26	peak
4	10875.000	34.19	15.05	49.24	74.00	-24.76	peak
5	11565.000	33.40	17.03	50.43	74.00	-23.57	peak
6	13935.000	26.78	23.81	50.59	74.00	-23.41	peak
7	17955.000	22.39	27.69	50.08	74.00	-23.92	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	49.98	0.22	50.20	74.00	-23.80	peak
2	5805.000	43.68	2.15	45.83	74.00	-28.17	peak
3	7920.000	38.93	7.76	46.69	74.00	-27.31	peak
4	11805.000	32.56	17.76	50.32	74.00	-23.68	peak
5	13875.000	27.24	23.59	50.83	74.00	-23.17	peak
6	17955.000	22.85	27.69	50.54	74.00	-23.46	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	55.41	0.35	55.76	74.00	-18.24	peak
2	4875.000	50.23	0.35	50.58	54.00	-3.42	AVG
3	6960.000	39.28	5.88	45.16	74.00	-28.84	peak
4	8175.000	38.20	8.04	46.24	74.00	-27.76	peak
5	10935.000	33.90	15.20	49.10	74.00	-24.90	peak
6	13500.000	28.43	22.48	50.91	74.00	-23.09	peak
7	18000.000	22.75	27.98	50.73	74.00	-23.27	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3690.000	48.75	-4.00	44.75	74.00	-29.25	peak
2	4875.000	46.35	0.35	46.70	74.00	-27.30	peak
3	7920.000	38.56	7.76	46.32	74.00	-27.68	peak
4	10575.000	35.03	14.23	49.26	74.00	-24.74	peak
5	13590.000	27.91	22.72	50.63	74.00	-23.37	peak
6	17925.000	22.95	27.50	50.45	74.00	-23.55	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	53.64	0.45	54.09	74.00	-19.91	peak
2	4920.000	48.42	0.45	48.87	54.00	-5.13	AVG
3	6975.000	39.55	5.92	45.47	74.00	-28.53	peak
4	10380.000	34.95	13.70	48.65	74.00	-25.35	peak
5	13995.000	26.90	24.04	50.94	74.00	-23.06	peak
6	17955.000	22.62	27.69	50.31	74.00	-23.69	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3690.000	48.44	-4.00	44.44	74.00	-29.56	peak
2	4920.000	45.38	0.45	45.83	74.00	-28.17	peak
3	7920.000	39.52	7.76	47.28	74.00	-26.72	peak
4	11805.000	32.59	17.76	50.35	74.00	-23.65	peak
5	13905.000	26.90	23.69	50.59	74.00	-23.41	peak
6	18000.000	22.85	27.98	50.83	74.00	-23.17	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	55.08	0.28	55.36	74.00	-18.64	peak
2	4845.000	51.21	0.28	51.49	54.00	-2.51	AVG
3	6990.000	38.99	5.97	44.96	74.00	-29.04	peak
4	9210.000	36.32	10.14	46.46	74.00	-27.54	peak
5	11055.000	33.51	15.54	49.05	74.00	-24.95	peak
6	12555.000	31.48	19.20	50.68	74.00	-23.32	peak
7	17940.000	22.60	27.61	50.21	74.00	-23.79	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	47.77	0.28	48.05	74.00	-25.95	peak
2	5805.000	43.92	2.15	46.07	74.00	-27.93	peak
3	7920.000	39.99	7.76	47.75	74.00	-26.25	peak
4	10575.000	35.32	14.23	49.55	74.00	-24.45	peak
5	13995.000	26.54	24.04	50.58	74.00	-23.42	peak
6	18000.000	21.76	27.98	49.74	74.00	-24.26	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	54.07	0.35	54.42	74.00	-19.58	peak
2	4875.000	49.61	0.35	49.96	54.00	-4.04	AVG
3	6990.000	39.29	5.97	45.26	74.00	-28.74	peak
4	9240.000	36.29	10.25	46.54	74.00	-27.46	peak
5	10575.000	35.15	14.23	49.38	74.00	-24.62	peak
6	13980.000	26.70	23.98	50.68	74.00	-23.32	peak
7	17940.000	23.27	27.61	50.88	74.00	-23.12	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.56	0.35	43.91	74.00	-30.09	peak
2	5805.000	43.05	2.15	45.20	74.00	-28.80	peak
3	7920.000	38.67	7.76	46.43	74.00	-27.57	peak
4	11520.000	33.12	16.89	50.01	74.00	-23.99	peak
5	14025.000	26.97	23.92	50.89	74.00	-23.11	peak
6	17955.000	23.13	27.69	50.82	74.00	-23.18	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	53.28	0.42	53.70	74.00	-20.30	peak
2	4905.000	48.64	0.42	49.06	54.00	-4.94	AVG
3	6975.000	39.52	5.92	45.44	74.00	-28.56	peak
4	9330.000	36.62	10.53	47.15	74.00	-26.85	peak
5	10560.000	35.31	14.20	49.51	74.00	-24.49	peak
6	13995.000	26.49	24.04	50.53	74.00	-23.47	peak
7	18000.000	22.53	27.98	50.51	74.00	-23.49	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4440.000	46.60	-1.05	45.55	74.00	-28.45	peak
2	5805.000	43.16	2.15	45.31	74.00	-28.69	peak
3	7920.000	40.06	7.76	47.82	74.00	-26.18	peak
4	10530.000	35.32	14.12	49.44	74.00	-24.56	peak
5	14025.000	26.81	23.92	50.73	74.00	-23.27	peak
6	18000.000	22.86	27.98	50.84	74.00	-23.16	peak


8.4. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18160.000	50.80	-5.49	45.31	74.00	-28.69	peak
2	19328.000	49.77	-5.58	44.19	74.00	-29.81	peak
3	21384.000	49.49	-4.72	44.77	74.00	-29.23	peak
4	22968.000	47.58	-3.48	44.10	74.00	-29.90	peak
5	24512.000	46.80	-2.32	44.48	74.00	-29.52	peak
6	25720.000	45.47	-0.75	44.72	74.00	-29.28	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18856.000	49.23	-5.34	43.89	74.00	-30.11	peak
2	19960.000	49.06	-5.42	43.64	74.00	-30.36	peak
3	21848.000	49.08	-4.39	44.69	74.00	-29.31	peak
4	23544.000	47.62	-3.15	44.47	74.00	-29.53	peak
5	24640.000	46.55	-2.32	44.23	74.00	-29.77	peak
6	25728.000	44.61	-0.72	43.89	74.00	-30.11	peak


8.5. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-21.5'

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0105	76.10	-101.40	-25.30	47.18	-72.48	peak
2	0.0171	72.88	-101.36	-28.48	42.94	-71.42	peak
3	0.0303	67.85	-101.39	-33.54	37.97	-71.51	peak
4	0.0483	63.70	-101.47	-37.77	33.92	-71.69	peak
5	0.0777	60.26	-101.61	-41.35	29.79	-71.14	peak
6	0.1150	57.44	-101.75	-44.31	26.39	-70.70	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1597	76.33	-101.65	-25.32	23.54	-48.86	peak
2	0.1925	71.46	-101.70	-30.24	21.92	-52.16	peak
3	0.2275	67.93	-101.77	-33.84	20.46	-54.30	peak
4	0.2620	65.31	-101.81	-36.50	19.24	-55.74	peak
5	0.3379	62.19	-101.90	-39.71	17.03	-56.74	peak
6	0.4430	59.53	-102.01	-42.48	14.67	-57.15	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6118	65.51	-62.09	3.42	31.87	-28.45	peak
2	1.2418	62.01	-62.16	-0.15	25.72	-25.87	peak
3	4.1787	57.78	-61.35	-3.57	29.54	-33.11	peak
4	6.7755	58.46	-61.24	-2.78	29.54	-32.32	peak
5	11.3792	55.59	-60.86	-5.27	29.54	-34.81	peak
6	23.1233	54.08	-60.59	-6.51	29.54	-36.05	peak


8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-21.5'

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	153.1900	50.48	-13.35	37.13	43.50	-6.37	peak
2	237.5800	52.53	-14.00	38.53	46.00	-7.47	peak
3	320.0300	52.09	-10.56	41.53	46.00	-4.47	QP
4	403.4500	47.71	-9.53	38.18	46.00	-7.82	peak
5	806.9699	45.31	-2.41	42.90	46.00	-3.10	peak
6	887.4800	40.42	-0.71	39.71	46.00	-6.29	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	48.4300	53.57	-15.20	38.37	40.00	-1.63	QP
2	102.7500	54.42	-16.23	38.19	43.50	-5.31	peak
3	150.2800	50.94	-13.54	37.40	43.50	-6.10	peak
4	240.4900	51.16	-14.15	37.01	46.00	-8.99	peak
5	806.9699	42.81	-2.41	40.40	46.00	-5.60	peak
6	887.4800	40.69	-0.71	39.98	46.00	-6.02	peak


8.7. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)-15.6'

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	78.22	-101.40	-23.18	47.60	-70.78	peak
2	0.0131	76.47	-101.38	-24.91	45.25	-70.16	peak
3	0.0235	70.11	-101.36	-31.25	40.18	-71.43	peak
4	0.0309	68.18	-101.39	-33.21	37.80	-71.01	peak
5	0.0575	62.91	-101.51	-38.60	32.41	-71.01	peak
6	0.0946	59.48	-101.76	-42.28	28.08	-70.36	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1559	75.65	-101.65	-26.00	23.74	-49.74	peak
2	0.1774	74.47	-101.68	-27.21	22.63	-49.84	peak
3	0.1966	73.18	-101.71	-28.53	21.73	-50.26	peak
4	0.2346	69.35	-101.77	-32.42	20.19	-52.61	peak
5	0.3195	64.46	-101.88	-37.42	17.51	-54.93	peak
6	0.4122	61.13	-101.98	-40.85	15.30	-56.15	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6590	64.88	-62.10	2.78	31.22	-28.44	peak
2	0.8296	64.44	-62.17	2.27	29.23	-26.96	peak
3	1.7617	60.49	-61.93	-1.44	29.54	-30.98	peak
4	3.6194	58.78	-61.43	-2.65	29.54	-32.19	peak
5	10.3460	56.27	-60.81	-4.54	29.54	-34.08	peak
6	22.1503	55.20	-60.67	-5.47	29.54	-35.01	peak


8.8. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)-15.6'

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	55.2200	45.22	-15.19	30.03	40.00	-9.97	peak
2	224.0000	41.76	-13.38	28.38	46.00	-17.62	peak
3	331.6700	43.40	-10.09	33.31	46.00	-12.69	peak
4	497.5400	38.59	-7.27	31.32	46.00	-14.68	peak
5	883.6000	28.58	-0.76	27.82	46.00	-18.18	peak
6	999.0300	31.74	0.31	32.05	54.00	-21.95	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	49.73	-14.58	35.15	40.00	-4.85	peak
2	150.2800	47.36	-13.54	33.82	43.50	-9.68	peak
3	217.2100	40.22	-13.14	27.08	46.00	-18.92	peak
4	497.5400	38.25	-7.27	30.98	46.00	-15.02	peak
5	713.8500	29.85	-3.92	25.93	46.00	-20.07	peak
6	1000.0000	27.99	0.33	28.32	54.00	-25.68	peak

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to FCC 47 CFR §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	23.8°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

TEST DATE / ENGINEER

Test Date	August 16, 2026	Test By	Kevin Zhang
-----------	-----------------	---------	-------------

TEST RESULTS-21.5'

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1580	23.15	10.44	33.59	65.57	-31.98	QP
2	0.1580	8.99	10.44	19.43	55.57	-36.14	AVG
3	0.4780	32.81	10.35	43.16	56.37	-13.21	QP
4	0.4780	20.34	10.35	30.69	46.37	-15.68	AVG
5	0.5311	38.27	10.31	48.58	56.00	-7.42	QP
6	0.5311	30.10	10.31	40.41	46.00	-5.59	AVG
7	0.5746	32.65	10.27	42.92	56.00	-13.08	QP
8	0.5746	19.81	10.27	30.08	46.00	-15.92	AVG
9	3.7153	26.43	10.42	36.85	56.00	-19.15	QP
10	3.7153	18.31	10.42	28.73	46.00	-17.27	AVG
11	8.9470	22.51	10.44	32.95	60.00	-27.05	QP
12	8.9470	14.76	10.44	25.20	50.00	-24.80	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1658	20.97	10.41	31.38	65.17	-33.79	QP
2	0.1658	5.53	10.41	15.94	55.17	-39.23	AVG
3	0.2662	23.34	10.18	33.52	61.24	-27.72	QP
4	0.2662	9.71	10.18	19.89	51.24	-31.35	AVG
5	0.5350	33.72	10.34	44.06	56.00	-11.94	QP
6	0.5350	25.18	10.34	35.52	46.00	-10.48	AVG
7	0.8567	20.59	10.33	30.92	56.00	-25.08	QP
8	0.8567	7.68	10.33	18.01	46.00	-27.99	AVG
9	4.1133	17.92	10.54	28.46	56.00	-27.54	QP
10	4.1133	12.50	10.54	23.04	46.00	-22.96	AVG
11	16.3056	18.08	10.72	28.80	60.00	-31.20	QP
12	16.3056	7.54	10.72	18.26	50.00	-31.74	AVG


Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

TEST RESULTS-15.6'

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1550	28.29	10.44	38.73	65.73	-27.00	QP
2	0.1550	15.54	10.44	25.98	55.73	-29.75	AVG
3	0.4858	35.99	10.34	46.33	56.24	-9.91	QP
4	0.4858	25.98	10.34	36.32	46.24	-9.92	AVG
5	0.6344	31.32	10.20	41.52	56.00	-14.48	QP
6	0.6344	23.70	10.20	33.90	46.00	-12.10	AVG
7	0.9688	27.95	10.49	38.44	56.00	-17.56	QP
8	0.9688	16.68	10.49	27.17	46.00	-18.83	AVG
9	6.4603	20.33	10.59	30.92	60.00	-29.08	QP
10	6.4603	10.66	10.59	21.25	50.00	-28.75	AVG
11	17.9391	18.81	11.03	29.84	60.00	-30.16	QP
12	17.9391	7.70	11.03	18.73	50.00	-31.27	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1610	26.49	10.45	36.94	65.41	-28.47	QP
2	0.1610	12.61	10.45	23.06	55.41	-32.35	AVG
3	0.4849	32.61	10.33	42.94	56.25	-13.31	QP
4	0.4849	26.48	10.33	36.81	46.25	-9.44	AVG
5	0.6369	24.36	10.33	34.69	56.00	-21.31	QP
6	0.6369	16.40	10.33	26.73	46.00	-19.27	AVG
7	1.2192	20.06	10.26	30.32	56.00	-25.68	QP
8	1.2192	14.53	10.26	24.79	46.00	-21.21	AVG
9	17.6795	18.68	10.80	29.48	60.00	-30.52	QP
10	17.6795	4.61	10.80	15.41	50.00	-34.59	AVG
11	24.5462	15.74	11.00	26.74	60.00	-33.26	QP
12	24.5462	4.31	11.00	15.31	50.00	-34.69	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

11. TEST DATA


11.1. APPENDIX A: DTS BANDWIDTH

11.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.16	2406.92	2417.08	≥ 0.5	PASS
		2437	10.16	2431.92	2442.08	≥ 0.5	PASS
		2462	10.16	2456.92	2467.08	≥ 0.5	PASS
11G	Ant1	2412	16.20	2403.84	2420.04	≥ 0.5	PASS
		2437	16.16	2428.92	2445.08	≥ 0.5	PASS
		2462	16.28	2453.84	2470.12	≥ 0.5	PASS
11N20SISO	Ant1	2412	17.44	2403.24	2420.68	≥ 0.5	PASS
		2437	17.32	2428.28	2445.60	≥ 0.5	PASS
		2462	17.44	2453.24	2470.68	≥ 0.5	PASS
11N40SISO	Ant1	2422	36.24	2403.76	2440.00	≥ 0.5	PASS
		2437	35.92	2418.92	2454.84	≥ 0.5	PASS
		2452	36.24	2433.84	2470.08	≥ 0.5	PASS

11.1.2. Test Graphs







11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452


11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

11.2.1. Test Result


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant1	2412	14.820	2404.5599	2419.3797	PASS
		2437	14.672	2429.6691	2444.3415	PASS
		2462	14.645	2454.6778	2469.3227	PASS
11G	Ant1	2412	18.243	2402.7321	2420.9751	PASS
		2437	18.166	2427.8320	2445.9980	PASS
		2462	20.267	2451.3491	2471.6159	PASS
11N20SISO	Ant1	2412	19.328	2402.2547	2421.5825	PASS
		2437	19.256	2427.2932	2446.5495	PASS
		2462	19.293	2452.2582	2471.5510	PASS
11N40SISO	Ant1	2422	38.165	2402.7999	2440.9649	PASS
		2437	38.165	2417.8127	2455.9776	PASS
		2452	38.055	2432.8611	2470.9160	PASS

11.2.2. Test Graphs







11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452

11.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

11.3.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Peak Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	5.18	≤30.00	PASS
		2437	4.73	≤30.00	PASS
		2462	4.85	≤30.00	PASS
11G	Ant1	2412	22.63	≤30.00	PASS
		2437	21.72	≤30.00	PASS
		2462	22.00	≤30.00	PASS
11N20SISO	Ant1	2412	21.60	≤30.00	PASS
		2437	21.84	≤30.00	PASS
		2462	21.24	≤30.00	PASS
11N40SISO	Ant1	2422	21.99	≤30.00	PASS
		2437	20.76	≤30.00	PASS
		2452	20.83	≤30.00	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

Test Mode	Antenna	Frequency[MHz]	Average Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	2.55	≤30.00	PASS
		2437	2.15	≤30.00	PASS
		2462	2.19	≤30.00	PASS
11G	Ant1	2412	9.86	≤30.00	PASS
		2437	8.94	≤30.00	PASS
		2462	9.06	≤30.00	PASS
11N20SISO	Ant1	2412	8.68	≤30.00	PASS
		2437	8.80	≤30.00	PASS
		2462	8.47	≤30.00	PASS
11N40SISO	Ant1	2422	9.39	≤30.00	PASS
		2437	8.66	≤30.00	PASS
		2452	8.70	≤30.00	PASS


Note: 1. Conducted Power=Meas. Level+ Correction Factor


2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.


11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY**11.4.1. Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-18.25	≤8.00	PASS
		2437	-20.21	≤8.00	PASS
		2462	-18.77	≤8.00	PASS
11G	Ant1	2412	-13.74	≤8.00	PASS
		2437	-15.18	≤8.00	PASS
		2462	-15.29	≤8.00	PASS
11N20SISO	Ant1	2412	-14.83	≤8.00	PASS
		2437	-14.93	≤8.00	PASS
		2462	-15.41	≤8.00	PASS
11N40SISO	Ant1	2422	-18.16	≤8.00	PASS
		2437	-18.60	≤8.00	PASS
		2452	-17.91	≤8.00	PASS


11.4.2. Test Graphs









11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422



11N40SISO_Ant1_2437





11N40SISO_Ant1_2452

11.5. APPENDIX E: BAND EDGE MEASUREMENTS**11.5.1. Test Result**

Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	-5.65	-44.73	≤-25.65	PASS
		High	2462	-6.07	-47.56	≤-26.07	PASS
11G	Ant1	Low	2412	-0.40	-29.48	≤-20.4	PASS
		High	2462	-1.34	-38.53	≤-21.34	PASS
11N20SISO	Ant1	Low	2412	-1.42	-29.93	≤-21.42	PASS
		High	2462	-1.62	-47.06	≤-21.62	PASS
11N40SISO	Ant1	Low	2422	-3.46	-32.46	≤-23.46	PASS
		High	2452	-4.14	-44.14	≤-24.14	PASS

11.5.2. Test Graphs







11G_Ant1_High_2462



11N20SISO_Ant1_Low_2412



11N20SISO_Ant1_High_2462





11.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION

11.6.1. Test Result


Test Mode	Antenna	Frequency[MHz]	FreqRange [Mhz]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	-5.55	---	PASS
			30~1000	-46.41	≤ -25.55	PASS
			1000~26500	-39.47	≤ -25.55	PASS
		2437	Reference	-5.68	---	PASS
			30~1000	-47.39	≤ -35.68	PASS
			1000~26500	-39.94	≤ -35.68	PASS
		2462	Reference	-5.89	---	PASS
			30~1000	-46.97	≤ -35.89	PASS
			1000~26500	-39.58	≤ -35.89	PASS
11G	Ant1	2412	Reference	-0.25	---	PASS
			30~1000	-46.95	≤ -20.25	PASS
			1000~26500	-39.37	≤ -20.25	PASS
		2437	Reference	-1.14	---	PASS
			30~1000	-47.02	≤ -21.14	PASS
			1000~26500	-38.31	≤ -21.14	PASS
		2462	Reference	-1.31	---	PASS
			30~1000	-46.73	≤ -21.31	PASS
			1000~26500	-39.38	≤ -21.31	PASS
11N20SISO	Ant1	2412	Reference	-1.39	---	PASS
			30~1000	-46.57	≤ -21.39	PASS
			1000~26500	-38.02	≤ -21.39	PASS
		2437	Reference	-1.21	---	PASS
			30~1000	-46.9	≤ -21.21	PASS
			1000~26500	-37.47	≤ -21.21	PASS
		2462	Reference	-1.61	---	PASS
			30~1000	-46.04	≤ -21.61	PASS
			1000~26500	-39.07	≤ -21.61	PASS
11N40SISO	Ant1	2422	Reference	-3.51	---	PASS
			30~1000	-46.07	≤ -23.51	PASS
			1000~26500	-39.1	≤ -23.51	PASS
		2437	Reference	-4.20	---	PASS
			30~1000	-45.53	≤ -24.2	PASS
			1000~26500	-39.32	≤ -24.2	PASS
		2452	Reference	-4.09	---	PASS
			30~1000	-46.05	≤ -24.09	PASS
			1000~26500	-39.35	≤ -24.09	PASS

11.6.2. Test Graphs







11B_Ant1_2437_0~Reference




11B_Ant1_2437_30~1000




11B_Ant1_2437_1000~26500




11B_Ant1_2462_0~Reference




11B_Ant1_2462_30~1000




11B_Ant1_2462_1000~26500




11G_Ant1_2412_0~Reference




11G_Ant1_2412_30~1000




11G_Ant1_2412_1000~26500




11G_Ant1_2437_0~Reference




11G_Ant1_2437_30~1000




11G_Ant1_2437_1000~26500




11G_Ant1_2462_0~Reference




11G_Ant1_2462_30~1000




11G_Ant1_2462_1000~26500




11N20SISO_Ant1_2412_0~Reference




11N20SISO_Ant1_2412_30~1000




11N20SISO_Ant1_2412_1000~26500




11N20SISO_Ant1_2437_0~Reference




11N20SISO_Ant1_2437_30~1000




11N20SISO_Ant1_2437_1000~26500




11N20SISO_Ant1_2462_0~Reference




11N20SISO_Ant1_2462_30~1000




11N20SISO_Ant1_2462_1000~26500




11N40SISO_Ant1_2422_0~Reference




11N40SISO_Ant1_2422_30~1000




11N40SISO_Ant1_2422_1000~26500






11N40SISO_Ant1_2452_0~Reference



11N40SISO_Ant1_2452_30~1000



11N40SISO_Ant1_2452_1000~26500

11.7. APPENDIX G: DUTY CYCLE**11.7.1. Test Result**

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11B	12.22	12.38	0.9871	98.71	0.06	0.08	0.01
11G	2.03	2.19	0.9269	92.69	0.33	0.49	1
11N20SISO	1.89	2.07	0.9130	91.30	0.40	0.53	1
11N40SISO	0.93	1.09	0.8532	85.32	0.69	1.08	2

Note:

Duty Cycle Correction Factor= $10\log(1/x)$.


Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

11.7.2. Test Graphs





END OF REPORT