

Scan QR code
verification of authenticity

FCC PART 15 SUBPART C FCC PART 15.247 BLE RADIO TEST REPORT

FCC ID:2BXGB-LIGHT005**Report No:** CTSL2620730359E**Product Name:** Permanent lights**Main Test Model:** Light-005**Series Models:** Light-005-150, Light-005-120, Light-005-90,
Light-005-75, Light-005-60, Light-005-45,
Light-005-30, Light-005-15, Light-005-XX, XX
represents the length**Applicant:** Dongguan Tuoyu Technology Co., Ltd

EXECUTIVE SUMMARY

A sample of this product was tested and found to be in compliance with
FCC PART 15C, FCC PART 15 SUBPART C (15.247).

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from CTSL. All Test Data Presented in this report is only applicable to presented Test sample.

CTSL Testing (Dongguan) Co., Ltd.

Main company address: Building 1, Houjie Road, Houjie Town, Guangdong Province
Dongguan City, China

Test Report

FCC ID:2BXGB-LIGHT005

Applicant Name	Dongguan Tuoyu Technology Co., Ltd				
Applicant Address	Room 301, Building 2, No. 7 Tianxin Butterfly 1st Road, Huangjiang Town, Dongguan City, Guangdong Province, China				
Manufacturer Name	Dongguan Tuoyu Technology Co., Ltd				
Manufacturer Address	Room 301, Building 2, No. 7 Tianxin Butterfly 1st Road, Huangjiang Town, Dongguan City, Guangdong Province, China				
Trade Mark	-				
Product name	Permanent lights				
Main Test Model	Light-005				
Series Models	Light-005-150, Light-005-120, Light-005-90, Light-005-75, Light-005-60, Light-005-45, Light-005-30, Light-005-15, Light-005-XX, XX represents the length				
Standard	FCC Part 15 Subpart C (15.247) ANSI C63.10:2020 FCC KDB 558074 D01 15.247 Meas Guidance v05r02				
Test Location	ISO/IEC 17025 by ILAC-MRA is A2LA 7556.01 CTSL Testing (Dongguan) Co., Ltd. 1/F, Building 1, No. 15, Jiaoyuansongshan Hetian Village, Houjie Town Dongguan City, Guangdong, People's Republic of China				
Receipt Date	2026.07.21	Test period	2026.07.22-2026.07.29	Issue Date	2026.07.30
Conclusion	The equipment under test was found to be compliance with the requirements of the standards applied.				
Performs Testing:	Ethan Zhao	-Ethan Zhao			
Test Report Reviewer:	Steve Qin	Steve Qin			
Test Report Authorizer:	Alan Li	Alan Li			

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. General Description of EUT (Equipment Under Test)	5
1.2. Antenna Information	6
1.3. Information of RF Cable	6
2. SUMMARY OF TEST	7
2.1. Test Standards	7
2.2. Summary of test result	7
2.3. Test Facilities	8
2.4. Measurement uncertainty	8
2.5. Block Diagram	9
2.6. Assistant equipment used for test	9
2.7. Test mode	10
2.8. Channel List	11
2.9. Power Setting of Test Software	11
2.10. Test Equipment	12
3. DUTY CYCLE	14
3.1. Limit	14
3.2. Test Setup	14
3.3. Spectrum Analyzer Setting	14
3.4. Test Procedure	14
3.5. Test Conditions	14
3.6. Test Result	15
3.7. Original Test record	15
4. 6DB BANDWIDTH	16
4.1. Limit	16
4.2. Test Setup	16
4.3. Spectrum Analyzer Setting	16
4.4. Test Procedure	16
4.5. Test Conditions	16
4.6. Test Result	17
4.7. Original Test record	17
5. 99% BANDWIDTH	19
5.1. Limit	19
5.2. Test Setup	19
5.3. Spectrum Analyzer Setting	19
5.4. Test Procedure	19
5.5. Test Conditions	19
5.6. Test Data	20
5.7. Original Test record	20
6. MAXIMUM PEAK OUTPUT POWER	22
6.1. Limit	22
6.2. Test Setup	22
6.3. Spectrum Analyzer Setting	22
6.4. Test Procedure	22
6.5. Test Conditions	22
6.6. Test Result	23

6.7. Original Test record	23
7. POWER SPECTRAL DENSITY	25
7.1. Limit.....	25
7.2. Test Setup.....	25
7.3. Spectrum Analyzer Setting	25
7.4. Test Procedure	25
7.5. Test Conditions.....	25
7.6. Test Result	26
7.7. Original Test record	26
8. CONDUCTED BAND EDGE.....	28
8.1. Limit.....	28
8.2. Test Setup	28
8.3. Spectrum Analyzer Setting	28
8.4. Test Procedure	28
8.5. Test Conditions.....	29
8.6. Test Result	29
9. CONDUCTED SPURIOUS EMISSIONS	30
9.1. Limit.....	30
9.2. Test Setup	30
9.3. Spectrum Analyzer Setting	30
9.4. Test Procedure	30
9.5. Test Conditions.....	31
9.6. Test Result	32
10. RADIATED SPURIOUS EMISSIONS AND BAND EDGE	34
10.1. Limit.....	34
10.2. Test Setup.....	35
10.3. Spectrum Analyzer Setting	36
10.4. Test Procedure	38
10.5. Test Conditions	39
10.6. Test Result.....	40
11. AC POWER LINE CONDUCTED EMISSIONS	45
11.1. Limit.....	45
11.2. Test Setup.....	45
11.3. Spectrum Analyzer Setting	45
11.4. Test Procedure.....	46
11.5. Test Conditions	46
11.6. Test Result.....	47
12. ANTENNA REQUIREMENTS	49
12.1. Limit.....	49
12.2. Test Result.....	49
13. APPENDIX	50

1. GENERAL INFORMATION

1.1. General Description of EUT (Equipment Under Test)

Product Information	
Product Name	: Permanent lights
Main Test Model	: Light-005
Series Models	: Light-005-150, Light-005-120, Light-005-90, Light-005-75, Light-005-60, Light-005-45, Light-005-30, Light-005-15, Light-005-XX, XX represents the length
Model Difference	: PCB board, structure and internal of these model(s) are the same, only differing in appearance, length and color. So no additional models were tested. (The Number at the end of the model designation denotes the length of the product.) (Model Light-005 denotes the maximum size. Testing performed on this maximum size is intended to cover all smaller lengths.)
Power supply	: AC 120V/60Hz
Battery	: -
Software Version	: V 1.0
Hardware Version	: V 1.0
Equipment Under Test	
Testing sample ID	: CTSL2620730359-S1 (Engineer sample) CTSL2620730359-S2 (Normal sample)
Test supplied	: ☒ supplied by the manufacturer ☐ supplied by the lab (Auxiliary test equipment supplied by test Lab, Details reference Section 2.6.)
Power supply information	: LED CONTROLLER Input: 120V~ 50/60Hz 1A; LED CONTROLLER Output: 24Vdc, Max.1.5A.
Wireless Specification	
Supported Type	: Bluetooth V5.2 (BLE)
Modulation Type	: GFSK
Transmit data rate (LE)	: LE 1 Mbps
Operation frequency	: 2402-2480MHz
Number of channels	: 40 Channels
Channel separation	: 2MHz
Max Output Power (PEAK)	: 1.46 (1±1.0dBm)
Antenna Gain& type	: Refer to Section 1.2 of the report.
Sample Type	: Prototype production
Type of Device	: ☐ Portable Device; ☒ Mobile Device; ☐ Modular Device

Note: For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.2. Antenna Information

Ant No.	Band	Model Name	Antenna Type	Connector	Gain (dBi)
1	2400-2500MHz	AED-HC05	PCB Antenna	/	-2.63

Note:

1. The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
2. The test results of this report only apply to the sample as received.

1.3. Information of RF Cable

Cable Loss(dB)	Provided by
1.0	Dongguan Tuoyu Technology Co., Ltd

Note:

1. The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received.
2. The laboratory is not responsible for the accuracy of the cable loss.

2. SUMMARY OF TEST

2.1. Test Standards

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10:2020: American National Standard for Testing Unlicensed Wireless Devices
FCC KDB 558074 D01 15.247 Meas Guidance v05r02

2.2. Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	6dB Bandwidth & 99% Bandwidth	§15.247(a)(2)	PASS
2	Maximum Peak Output Power	15.247(b)(3)	PASS
3	Power Spectral Density	15.247(e)	PASS
4	Conducted Band Edge	15.247(d)	PASS
5	Conducted Spurious Emissions	15.247(d)	PASS
6	Radiated Spurious Emissions and Band Edge	15.109/ 15.205/ 15.209/ 15.247(d)	PASS
7	AC Power Line Conducted Emissions	15.207(a)	PASS
8	Antenna Requirement	15.203	PASS

Note: "N/A" denotes test is not applicable in this test report.

2.3. Test Facilities

EMC Lab :

A2LA Certificate Number: 7556.01;
CTSL Testing (Dongguan) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.
The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

FCC Designation Number: CN1425;
Test Firm Registration Number:750639;
CTSL Testing (Dongguan) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

Industry Canada Registration Number. Is: 34801;
CAB identifier: CN0192;
CTSL Testing (Dongguan) Co., Ltd. The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

Name of Firm : CTSL Testing (Dongguan) Co.,Ltd.

Main company address:

Building 1, Houjie Road, Houjie Town, Guangdong Province Dongguan City, China

EMC test location/satellite location:

1/F, Building 1, No. 15, Jiaoyuansongshan Hetian Village, Houjie Town Dongguan City, Guangdong, People's Republic of China City, Guangdong, China

2.4. Measurement uncertainty


Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (Below 30MHz)	$\pm 1.62\text{ dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 25GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB
Uncertainty for Temperature	0.5°C
Uncertainty for Relative Humidity	1.8%RH
Uncertainty for Atmospheric Pressure	0.16 kPa

Note: This uncertainty represents an expanded uncertainty expressed at approximately The 95% confidence level using a coverage factor of k=2.


2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into Bluetooth test mode by software before test.

Connect EUT Antenna Terminal, Radiated Spurious Emissions& Band Edge Test



AC Power Line Conducted Emissions& Radiated Emission Test (30-1000MHz):



(EUT: Permanent lights)

2.6. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
1	Notebook PC	-	Inspiron 14R-5421 (Manufacturer: Dell)	-	25TZHW1
2	Power Adapter (supplied by the manufacturer)	DONGGUAN GUANQING ELECTRONICS CO., LTD.	GAT-0501000U (Manufacturer: GAT)	-	-

Supported cables				
Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	0.5m	USB Extension Cable, supplied by the Lab.

2.7. Test mode

Combining all the rates, modulations, and packet types, the Pre-scans had been carried out. The worst-case test mode was selected for the final test as listed below.

Test Item	Mode	Data Rate	Test Channel
6dB Bandwidth & 99% Bandwidth	GFSK BLE 1M	1Mbps	Low / Middle / High
Maximum Peak Output Power	GFSK BLE 1M	1Mbps	Low / Middle / High
Power Spectral Density	GFSK BLE 1M	1Mbps	Low / Middle / High
Conducted Band Edge	GFSK BLE 1M	1Mbps	Low / High
Conducted Spurious Emissions	GFSK BLE 1M	1Mbps	Low / Middle / High
Radiated Spurious Emissions (Below 1GHz)	GFSK BLE 1M	1Mbps	Low / Middle / High
Radiated Spurious Emissions (Above 1GHz)	GFSK BLE 1M	1Mbps	Low / Middle / High
Radiated Band Edge	GFSK BLE 1M	1Mbps	Low / High
AC Power Line Conducted Emissions	GFSK BLE 1M	1Mbps	Low / Middle / High

Note: In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis (X, Y, Z), the worst case was found when positioned on **X-plane**.

2.8. Channel List

BLE 1M							
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
00	2402	01	2404	02	2406	03	2408
04	2410	05	2412	06	2414	07	2416
08	2418	09	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

2.9. Power Setting of Test Software

Software Name	bt_tool_v1.1.4		
Frequency (MHz)	2402	2440	2480
BLE 1M-GFSK Setting	5	5	5

Note: This information is provided by the applicant.

2.10. Test Equipment

For Conducted Emission Test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI 3	AT005	GUANGZHOU NEM	May 28,26	May 27,27
LISN	Rohde & Schwarz	ENV216	AT006	GUANGZHOU NEM	May 28,26	May 27,27
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	AT007	GUANGZHOU NEM	May 28,26	May 27,27
CE Cable	Times Microwave	LMR195UF-N MNM-1.50M	AT041	GUANGZHOU NEM	May 28,26	May 27,27
Test Software	FARAD	EZ-EMC Ver.3A1.1+	N/A	N/A	N/A	N/A

For Radiated Emission Test (9kHz-30MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI TestReceiver	Rohde& Schwarz	ESCI 7	AT001	GUANGZHOU NEM	May 28,26	May 27,27
Active Loop Antenna	HCT	6505	AT064	GRG METROLOGY	Mar 22,26	Mar 21,27
Test Software	FARAD	EZ-EMC Ver.3A1.1+	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	Times Microwave	LMR195UF-N MNM-9M	AT045	GUANGZHOU NEM	May 28,26	May 27,27

For Radiated Emissions Test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde& Schwarz	ESCI 7	AT001	GUANGZHOU NEM	May 28,26	May 27,27
Trilog-Broadband Antenna (Including 6dB attenuator)	SCHWARZBECK	VULB 9168	AT002	LISAI	May 30,26	May 29,27
Test Software	FARAD	EZ-EMC Ver.3A1.1+	N/A	N/A	N/A	N/A
30-1000MHz Cable	Times Microwave Systems	LMR195UF-N MRNMR-3.00M+ LMR400UF-N MNM-3.00M+ LMR400UF-N MNM-3.00M	AT042+AT043+AT044	GUANGZHOU NEM	May 28,26	May 27,27

For Radiated Emission test (Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna 1-18G	SCHWARZBEC K	BBHA 9120 D	AT003	LISAI	May 30,26	May 29,27
Horn Antenna 18-40GHz	XIBAO	XB-WDB18-40K	AT064	LISAI	May 30,26	May 29,27
Broadband Preamplifier	SCHWARZBEC K	BBV 9718 D	AT004	GUANGZHOU NEM	May 28,26	May 27,27
Low Noise Amplifier	MWRFTest	DLA8-18-40G-2078	AT065	GUANGZHOU NEM	May 28,26	May 27,27
Spectrum Analyzer 40G	Keysight	N9020B	AT066	GUANGZHOU NEM	May 28,26	May 27,27
Spectrum Analyzer 26.5G	Keysight	N9020A	AT050	GUANGZHOU NEM	May 28,26	May 27,27
Radio switching unit	TiGroup	SU319	AT055	N/A	N/A	N/A
Filtering unit	TiGroup	SU319F	AT056	N/A	N/A	N/A
Test Software	BL	BL410-E V25.5 en	N/A	N/A	N/A	N/A
Above 1GHz Cable	Times Microwave Systems	SFT205-NMN M-7.0M+ SFT205-NMN M-2.0M	AT057+ AT058	GUANGZHOU NEM	May 28,26	May 27,27

For Connect EUT Antenna Terminal Test (RF Test system)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Spectrum analyzer	Keysight	N9020A	AT050	GUANGZHOU NEM	May 28,26	May 27,27
Analog signal source	Keysight	N5173B	AT051	GUANGZHOU NEM	May 28,26	May 27,27
WIDEBAND RADIO COMMUNICATION TESTER	Rohde&Schwarz	CMW500	AT052	GUANGZHOU NEM	May 28,26	May 27,27
Power probe unit	Ti Group	SU319P	AT053	GUANGZHOU NEM	May 28,26	May 27,27
Switch unit	Ti Group	SU319S	AT054	N/A	N/A	N/A
Test Software	BL	BL410R 3.5.2.621	N/A	N/A	N/A	N/A

3. DUTY CYCLE

3.1. Limit

None; for reporting purpose only.

3.2. Test Setup



3.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
Centre frequency	2440MHz
RBW	8
VBW	8
Span	0
Sweep Time	Auto
Detector	Peak
Trace Mode	Single hold

3.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- Duty Cycle= Transmission Duration (Tx On (s))/ Transmission Period(s)
- Repeat above procedures until all channels and test modes were measured.
- Record the results in the test report.

3.5. Test Conditions

EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7℃	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		


3.6. Test Result

Mode	Channel	Center Frequency (MHz)	RBW (MHz)	Detector	Tx On (s)	Tx Off (s)	Period (s)	Duty Cycle
GFSK BLE 1M	CH19	2440	8	RMS	0.000412	0.000213	0.000624	65.94%

Note:

1. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle ≥98 %, the EUT is consider to be transmitting continuously, the conducted average output power and average power spectral density no need to add duty factor (consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. Tx On time is transmission duration(s).

3.7. Original Test record




4. 6DB BANDWIDTH

4.1. Limit

Systems using digital modulation techniques operate in the 2400-2483.5 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.2. Test Setup



4.3. Spectrum Analyzer Setting

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	2MHz(BLE 1M mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

4.4. Test Procedure

- The test according to ANSI C63.10 clause 11.8.
- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 4.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all channels and test modes were measured.
- Record the results in the test report.


4.5. Test Conditions



EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		

4.6. Test Result

Test Mode	Antenna	Channel& Frequency	6dB Bandwidth	6dB Bandwidth Conducted Limit	Result
		MHz	MHz	KHz	
BLE 1M-GFSK	Ant1	CH00 2402	0.72	≥500	PASS
		CH19 2440	0.730		
		CH39 2480	0.715		

4.7.Original Test record






5. 99% BANDWIDTH

5.1.Limit

None; for reporting purpose only.

5.2. Test Setup



5.3. Spectrum Analyzer Setting

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1-5% OBW
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{BW}$
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

5.4. Test Procedure

- The test according to ANSI C63.10 clause 6.9.3.
- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Repeat above procedures until all channels and test modes were measured.
- Record the results in the test report.


5.5. Test Conditions



EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		

5.6.Test Data

Test Mode	Antenna	Channel& Frequency	Occupied Channel Bandwidth
		MHz	MHz
BLE 1M-GFSK	Ant1	CH00 2402	1.025
		CH19 2440	1.022
		CH39 2480	1.022

5.7.Original Test record






6. MAXIMUM PEAK OUTPUT POWER

6.1. Limit

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2. Test Setup



6.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	2MHz
VBW	6MHz
Span	10MHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.4. Test Procedure

- The test according to ANSI C63.10 clause 11.9.2.3.
- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 6.3.
- Set the EUT transmit continuously with maximum output power.
- Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

6.5. Test Conditions

EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		


6.6. Test Result



Test Mode	Antenna	Channel& Frequency	Peak Output Power	Limit	Result
		MHz	dBm	dBm	
BLE 1M-GFSK	Ant1	CH00 2402	-0.07	≤30	PASS
		CH19 2440	1.46		
		CH39 2480	1.46		

Note:

- 1) If the test results under the Peak detector meet the limit requirements, then there is no need to consider the coefficient obtained by multiplying by the Duty cycle.

6.7.Original Test record






7. POWER SPECTRAL DENSITY

7.1.Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.2.Test Setup



7.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	3KHz
VBW	10KHz
Span	1.5MHz(BLE 1M mode) (Set the span >1.5 times the DTS bandwidth.)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

7.4.Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 7.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

7.5. Test Conditions

EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7℃	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		


7.6.Test Result



Test Mode	Antenna	Channel& Frequency	Peak Power Spectral Density	Limit	Result
		MHz	dBm/3KHz	dBm/3KHz	
BLE 1M-GFSK	Ant1	CH00 2402	-15.10	8.00	PASS
		CH19 2440	-13.49		
		CH39 2480	-13.57		

Note:

- 1) If the test results under the Peak detector meet the limit requirements, then there is no need to consider the coefficient obtained by multiplying by the Duty cycle.

7.7.Original Test record






8. CONDUCTED BAND EDGE

8.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

8.2. Test Setup



8.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	2310-2410MHz: 100MHz 2475-2500MHz: 25MHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

8.4. Test Procedure


- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 8.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report

BLE 1M-GFSK all have been tested, the test data was recorded in report.

8.5. Test Conditions

EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		

8.6. Test Result




9. CONDUCTED SPURIOUS EMISSIONS

9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

9.2. Test Setup



9.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting	
RBW	100KHz	
VBW	300KHz	
Start frequency	30MHz	1.0GHz
Stop frequency	1000MHz	25.0GHz
Sweep Time	Auto	
Detector	Peak	
Trace Mode	Max Hold	

9.4. Test Procedure


- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 9.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.
- BLE 1M-GFSK all have been tested, the test data was recorded in report.


9.5. Test Conditions

EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		



9.6. Test Result





10. RADIATED SPURIOUS EMISSIONS AND BAND EDGE

10.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band			
MHZ	MHz	MHZ	GHZ
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)


15.209 Limit		
Frequency (MHz)	Field Strength($\mu\text{V/m}$)	Distance(m)
0.009-0.490	$2400/F(\text{kHz})$	300
0.490-1.705	$24000/F(\text{kHz})$	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:


- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$.
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

10.2. Test Setup

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz




(B) Radiated Emission Test Set-Up, Frequency below 1000MHz Below 1 GHz and above 30 MHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz

Above 1GHz



10.3. Spectrum Analyzer Setting

For 9KHz-150KHz	
Spectrum Parameters	Setting
RBW	300Hz (for Peak&AVG)/CISPR 200Hz (for QP)
VBW	300Hz (for Peak&AVG)/CISPR 200Hz (for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

Note: For 9KHz-90KHz&110KHz-150KHz,the detector is average,other frequency is CISPR QP detector.

For 150KHz-30MHz	
Spectrum Parameters	Setting
RBW	9KHz
VBW	30KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

Note : For 150KHz-490KHz,the detector is average,other frequency is CISPR QP detector.

For 30MHz-1GHz	
Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz		
Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle $\geq$ 98%, VBW=10Hz
		Duty cycle $<$ 98%,VBW $\geq$ 1/T
Start frequency	1GHz	
Stop frequency	40GHz	
Sweep Time	Auto	
Detector	PEAK	
Trace Mode	Max Hold	

Note: T is the on-time time of the duty cycle, when EUT transmit continuously with maximum output power, unit is seconds. reference section 3 for the on-time time.

10.4. Test Procedure

- a. EUT was placed on a turn table, which is 0.8-meter high above ground for below 1GHz test, and which is 1.5-meter high above ground for above 1GHz test.
- b. The diameter of the turntable is 2 meters. The EUT is located at the center of the edge of the test support table. Since the turntable is large enough, the EUT is placed at the center of the edge of the test support table as well as at the center of the turntable.
- c. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- d. Set the EUT transmit continuously with maximum output power.
- e. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- f. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- g. Spectrum analyzer setting parameters in accordance with section 10.3.
- h. Repeat above procedures until all channels and test modes were measured.
- i. Record the results in the test report.

Note:

1. For emissions above 1GHz, if peak level complies with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2402MHz ,2440MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.
3. For 30-1000MHz Radiation emissions, BLE 1M-GFSK mode all have been tested, only worse case: BLE 1M-GFSK mode with CH39 2480MHz is reported. it was conducted under both AC 120V/60Hz and AC 240V/50Hz input voltages. There was no significant change in radiation emission. Only the test data under AC 120V/60Hz voltage was recorded and included in the report.
4. Radiated emission test from 9KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9KHz to 30MHz and not recorded in this report.
5. The amplitude of 18GHz to 25GHz spurious emission-that-is attenuated by more than 20dB below the-permissible-limit has no need-to-be-reported.
6. Radiated emission test from 25GHz to 40GHz of fundamental was verified, and no emission found except system noise floor in 25GHz to 40GHz and not recorded in this report.

10.5. Test Conditions

Radiated Emissions 30-1000MHz			
EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.1kPa		

Radiated Emissions Above 1GHz & Radiated Band Edge			
EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.6kPa		

10.6. Test Result

Radiated Emissions 30-1000MHz

EUT: Permanent lights

M/N: Light-005


Test Voltage: AC 120V/60Hz

Ant. Pol.: Vertical

Test Mode: TX Mode

Note: only worse case: BLE 1M-GFSK mode with CH39 2480MHz is reported

Detailed results are shown below



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.620	10.60	18.82	29.42	40.00	-10.58	QP
2	42.302	7.43	19.76	27.19	40.00	-12.81	QP
3	60.917	8.57	18.64	27.21	40.00	-12.79	QP
4	80.362	13.86	15.49	29.35	40.00	-10.65	QP
5 *	86.807	16.04	15.69	31.73	40.00	-8.27	QP
6	145.861	11.60	20.03	31.63	43.50	-11.87	QP

Remarks: 1). Level (dBuV/m) = Reading (dBuV/m) + Factor (dB/m)
 2). Factor(dB/m) =Antenna Factor (dB/m) + Cable loss (dB)
 3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)

EUT: Permanent lights

M/N: Light-005


Test Voltage: AC 120V/60Hz

Ant. Pol.: Horizontal

Test Mode: TX Mode

Note: only worse case: BLE 1M-GFSK mode with CH39 2480MHz is reported

Detailed results are shown below



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	73.876	9.49	16.29	25.78	40.00	-14.22	QP
2	83.522	9.69	15.45	25.14	40.00	-14.86	QP
3 *	102.360	13.17	16.52	29.69	43.50	-13.81	QP
4	133.619	8.86	19.44	28.30	43.50	-15.20	QP
5	147.404	8.12	20.37	28.49	43.50	-15.01	QP
6	206.398	6.40	16.95	23.35	43.50	-20.15	QP

Remarks: 1). Level (dBuV/m) = Reading (dBuV/m) + Factor (dB/m)
 2). Factor(dB/m) = Antenna Factor (dB/m) + Cable loss (dB)
 3). Margin(dB) = Limit (dBuV/m) - Level (dBuV/m)

Radiated Emissions Above 1GHz - BLE 1M-GFSK

BLE 1M-GFSK-CH00 2402MHz										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2375.788	43.61	-19.39	74.0	30.39	Peak	108.00	150	Horizontal	Pass
1**	2375.788	39.80	-19.39	54.0	14.20	AV	108.00	150	Horizontal	Pass
2	4752.500	48.56	-10.43	74.0	25.44	Peak	72.00	150	Horizontal	Pass
2**	4752.500	39.20	-10.43	54.0	14.80	AV	72.00	150	Horizontal	Pass
3	4804.000	48.09	-11.07	74.0	25.91	Peak	216.00	150	Horizontal	Pass
3**	4804.000	42.92	-11.07	54.0	11.08	AV	216.00	150	Horizontal	Pass
4	7205.750	50.18	-6.87	74.0	23.82	Peak	216.00	150	Horizontal	Pass
4**	7205.750	42.86	-6.87	54.0	11.14	AV	216.00	150	Horizontal	Pass
5	7896.750	53.25	-6.14	74.0	20.75	Peak	324.00	150	Horizontal	Pass
5**	7896.750	43.70	-6.14	54.0	10.30	AV	324.00	150	Horizontal	Pass
6	17929.501	52.97	1.61	74.0	21.03	Peak	288.00	150	Horizontal	Pass
6**	17929.501	44.11	1.61	54.0	9.89	AV	288.00	150	Horizontal	Pass

BLE 1M-GFSK-CH00 2402MHz										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2375.387	41.21	-19.40	74.0	32.79	Peak	216.00	150	Vertical	Pass
1**	2375.387	32.76	-19.40	54.0	21.24	AV	216.00	150	Vertical	Pass
2	4780.500	49.21	-10.48	74.0	24.79	Peak	288.00	150	Vertical	Pass
2**	4780.500	40.67	-10.48	54.0	13.33	AV	288.00	150	Vertical	Pass
3	4804.000	54.02	-11.07	74.0	19.98	Peak	36.00	150	Vertical	Pass
3**	4804.000	50.73	-11.07	54.0	3.27	AV	36.00	150	Vertical	Pass
4	7205.750	48.97	-6.87	74.0	25.03	Peak	180.00	150	Vertical	Pass
4**	7205.750	42.24	-6.87	54.0	11.76	AV	180.00	150	Vertical	Pass
5	8000.000	52.67	-6.36	74.0	21.33	Peak	108.00	150	Vertical	Pass
5**	8000.000	42.97	-6.36	54.0	11.03	AV	108.00	150	Vertical	Pass
6	17927.500	52.10	1.45	74.0	21.90	Peak	144.00	150	Vertical	Pass
6**	17927.500	45.20	1.45	54.0	8.80	AV	144.00	150	Vertical	Pass

BLE 1M-GFSK-CH19 2440MHz										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2273.636	40.56	-19.36	74.0	33.44	Peak	324.00	150	Vertical	Pass
1**	2273.636	31.55	-19.36	54.0	22.45	AV	324.00	150	Vertical	Pass
2	4748.000	49.45	-10.44	74.0	24.55	Peak	324.00	150	Vertical	Pass
2**	4748.000	39.84	-10.44	54.0	14.16	AV	324.00	150	Vertical	Pass
3	4879.750	54.21	-10.57	74.0	19.79	Peak	72.00	150	Vertical	Pass
3**	4879.750	50.50	-10.57	54.0	3.50	AV	72.00	150	Vertical	Pass
4	7319.750	48.66	-6.79	74.0	25.34	Peak	252.00	150	Vertical	Pass
4**	7319.750	42.56	-6.79	54.0	11.44	AV	252.00	150	Vertical	Pass
5	7913.750	52.35	-6.33	74.0	21.65	Peak	180.00	150	Vertical	Pass
5**	7913.750	44.04	-6.33	54.0	9.96	AV	180.00	150	Vertical	Pass
6	17823.001	52.50	1.08	74.0	21.50	Peak	144.00	150	Vertical	Pass
6**	17823.001	43.10	1.08	54.0	10.90	AV	144.00	150	Vertical	Pass

BLE 1M-GFSK-CH19 2440MHz										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2351.976	41.66	-19.68	74.0	32.34	Peak	360.00	150	Horizontal	Pass
1**	2351.976	30.58	-19.68	54.0	23.42	AV	360.00	150	Horizontal	Pass
2	4310.500	49.40	-12.50	74.0	24.60	Peak	324.00	150	Horizontal	Pass
2**	4310.500	40.01	-12.50	54.0	13.99	AV	324.00	150	Horizontal	Pass
3	4879.750	50.22	-10.57	74.0	23.78	Peak	36.00	150	Horizontal	Pass
3**	4879.750	44.86	-10.57	54.0	9.14	AV	36.00	150	Horizontal	Pass
4	7319.750	49.08	-6.79	74.0	24.92	Peak	72.00	150	Horizontal	Pass
4**	7319.750	42.73	-6.79	54.0	11.27	AV	72.00	150	Horizontal	Pass
5	7914.500	52.10	-6.31	74.0	21.90	Peak	72.00	150	Horizontal	Pass
5**	7914.500	44.74	-6.31	54.0	9.26	AV	72.00	150	Horizontal	Pass
6	17927.500	53.03	1.45	74.0	20.97	Peak	180.00	150	Horizontal	Pass
6**	17927.500	44.43	1.45	54.0	9.57	AV	180.00	150	Horizontal	Pass

BLE 1M-GFSK-CH39 2480MHz										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2178.889	41.33	-20.10	74.0	32.67	Peak	360.00	150	Horizontal	Pass
1**	2178.889	30.29	-20.10	54.0	23.71	AV	360.00	150	Horizontal	Pass
2	4762.500	48.95	-10.56	74.0	25.05	Peak	0.00	150	Horizontal	Pass
2**	4762.500	39.84	-10.56	54.0	14.16	AV	0.00	150	Horizontal	Pass
3	4959.750	47.87	-10.88	74.0	26.13	Peak	288.00	150	Horizontal	Pass
3**	4959.750	43.88	-10.88	54.0	10.12	AV	288.00	150	Horizontal	Pass
4	7439.750	49.21	-6.77	74.0	24.79	Peak	252.00	150	Horizontal	Pass
4**	7439.750	42.56	-6.77	54.0	11.44	AV	252.00	150	Horizontal	Pass
5	7975.750	52.22	-6.33	74.0	21.78	Peak	360.00	150	Horizontal	Pass
5**	7975.750	42.06	-6.33	54.0	11.94	AV	360.00	150	Horizontal	Pass
6	17818.499	53.06	1.06	74.0	20.94	Peak	72.00	150	Horizontal	Pass
6**	17818.499	44.53	1.06	54.0	9.47	AV	72.00	150	Horizontal	Pass

BLE 1M-GFSK-CH39 2480MHz										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2127.063	40.99	-20.45	74.0	33.01	Peak	360.00	150	Vertical	Pass
1**	2127.063	28.97	-20.45	54.0	25.03	AV	360.00	150	Vertical	Pass
2	4752.250	49.64	-10.42	74.0	24.36	Peak	288.00	150	Vertical	Pass
2**	4752.250	39.24	-10.42	54.0	14.76	AV	288.00	150	Vertical	Pass
3	4959.750	48.13	-10.88	74.0	25.87	Peak	108.00	150	Vertical	Pass
3**	4959.750	41.80	-10.88	54.0	12.20	AV	108.00	150	Vertical	Pass
4	7439.750	48.34	-6.77	74.0	25.66	Peak	36.00	150	Vertical	Pass
4**	7439.750	41.93	-6.77	54.0	12.07	AV	36.00	150	Vertical	Pass
5	7850.500	52.19	-6.38	74.0	21.81	Peak	252.00	150	Vertical	Pass
5**	7850.500	42.78	-6.38	54.0	11.22	AV	252.00	150	Vertical	Pass
6	17924.000	53.11	1.18	74.0	20.89	Peak	180.00	150	Vertical	Pass
6**	17924.000	43.60	1.18	54.0	10.40	AV	180.00	150	Vertical	Pass

Note:

1. Results (dBuV/m) = Raw Value (dBuV) + Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Pre-amplifier
3. Margin value = Limit - Results.

Radiated Band Edge - BLE 1M-GFSK

BLE 1M-GFSK-CH00 2402MHz-Low Band Edge										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2376.000	42.71	-19.63	74.0	31.29	Peak	359.20	150	Vertical	Pass
1**	2376.000	35.53	-19.63	54.0	18.47	AV	359.20	150	Vertical	Pass
2	2389.970	41.65	-19.56	74.0	32.35	Peak	355.40	150	Vertical	Pass
2**	2389.970	30.34	-19.56	54.0	23.66	AV	355.40	150	Vertical	Pass
3	2399.980	60.31	-19.64	74.0	13.69	Peak	231.40	150	Vertical	Pass
3**	2399.980	44.56	-19.64	54.0	9.44	AV	231.40	150	Vertical	Pass

BLE 1M-GFSK-CH00 2402MHz-Low Band Edge										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2376.000	45.15	-19.63	74.0	28.85	Peak	22.00	150	Horizontal	Pass
1**	2376.000	40.42	-19.63	54.0	13.58	AV	22.00	150	Horizontal	Pass
2	2389.970	39.91	-19.56	74.0	34.09	Peak	7.00	150	Horizontal	Pass
2**	2389.970	30.53	-19.56	54.0	23.47	AV	7.00	150	Horizontal	Pass
3	2399.980	57.01	-19.64	74.0	16.99	Peak	235.40	150	Horizontal	Pass
3**	2399.980	42.10	-19.64	54.0	11.90	AV	235.40	150	Horizontal	Pass

BLE 1M-GFSK-CH39 2480MHz-High Band Edge										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.485	40.85	-19.50	74.0	33.15	Peak	72.00	150	Vertical	Pass
1**	2483.485	30.73	-19.50	54.0	23.27	AV	72.00	150	Vertical	Pass
2	2483.620	44.05	-19.50	74.0	29.95	Peak	180.00	150	Vertical	Pass
2**	2483.620	30.74	-19.50	54.0	23.26	AV	180.00	150	Vertical	Pass
3	2499.985	41.86	-19.46	74.0	32.14	Peak	360.00	150	Vertical	Pass
3**	2499.985	30.50	-19.46	54.0	23.50	AV	360.00	150	Vertical	Pass

BLE 1M-GFSK-CH39 2480MHz-High Band Edge										
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.485	51.33	-19.50	74.0	22.67	Peak	207.30	150	Horizontal	Pass
1**	2483.485	33.21	-19.50	54.0	20.79	AV	207.30	150	Horizontal	Pass
2	2483.770	50.94	-19.50	74.0	23.06	Peak	215.30	150	Horizontal	Pass
2**	2483.770	32.57	-19.50	54.0	21.43	AV	215.30	150	Horizontal	Pass
3	2498.470	41.95	-19.47	74.0	32.05	Peak	164.70	150	Horizontal	Pass
3**	2498.470	31.05	-19.47	54.0	22.95	AV	164.70	150	Horizontal	Pass

Note:

1. Results (dBuV/m) = Raw Value (dBuV) + Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Pre-amplifier
3. Margin value = Limit - Results.

11. AC POWER LINE CONDUCTED EMISSIONS


11.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

11.2. Test Setup



11.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	30KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold

11.4. Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 11.3.
- f. The AC line is checked to find out the maximum conducted emission. To find the maximum emission levels, the relative positions of equipment and all the interface cables shall be changed according to ANSI C63.10:2020 on Conducted Emission Test.
- g. It was conducted under both AC 120V/60Hz and AC 240V/50Hz input voltages, there was no significant change in radiation emission. Only worse case: GFSK mode with CH78 2480MHz with AC 120V/60Hz voltage is reported.

11.5. Test Conditions

EUT:	Permanent lights	M/N:	Light-005
Test Voltage:	AC 120V/60Hz		
Temperature:	23.7°C	Humidity:	49 % RH
Atmosphere Pressure:	100.9kPa		

11.6. Test Result

EUT: Permanent lights

M/N: Light-005


Test Voltage: AC 120V/60Hz

Phase: Live

Test Mode: TX Mode

Note: only worse case: BLE 1M-GFSK mode with CH39 2480MHz is reported

Detailed results are shown below



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.150	33.56	20.72	54.28	66.00	-11.72	QP	P	
2	0.150	14.90	20.72	35.62	56.00	-20.38	AVG	P	
3	0.210	27.77	20.73	48.50	63.21	-14.71	QP	P	
4	0.210	10.56	20.73	31.29	53.21	-21.92	AVG	P	
5	0.290	26.21	20.71	46.92	60.52	-13.60	QP	P	
6	0.290	6.12	20.71	26.83	50.52	-23.69	AVG	P	
7	0.362	19.69	20.73	40.42	58.68	-18.26	QP	P	
8	0.362	3.25	20.73	23.98	48.68	-24.70	AVG	P	
9	4.646	16.81	21.08	37.89	56.00	-18.11	QP	P	
10	4.646	4.16	21.08	25.24	46.00	-20.76	AVG	P	
11	22.466	19.92	23.85	43.77	60.00	-16.23	QP	P	
12	22.466	6.02	23.85	29.87	50.00	-20.13	AVG	P	

Remark: The test Result=Reading+ Lisn+ Cab L.

If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

EUT: Permanent lights

M/N: Light-005


Test Voltage: AC 120V/60Hz

Phase: Neutral

Test Mode: TX Mode

Note: only worse case: BLE 1M-GFSK mode with CH39 2480MHz is reported

Detailed results are shown below



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.154	32.07	20.55	52.62	65.79	-13.17	QP	P	
2	0.154	21.26	20.55	41.81	55.79	-13.98	AVG	P	
3 *	0.214	30.97	20.55	51.52	63.05	-11.53	QP	P	
4	0.214	12.70	20.55	33.25	53.05	-19.80	AVG	P	
5	0.277	25.25	20.55	45.80	60.91	-15.11	QP	P	
6	0.277	9.26	20.55	29.81	50.91	-21.10	AVG	P	
7	0.418	21.34	20.57	41.91	57.49	-15.58	QP	P	
8	0.418	4.59	20.57	25.16	47.49	-22.33	AVG	P	
9	3.134	18.95	20.83	39.78	56.00	-16.22	QP	P	
10	3.134	5.25	20.83	26.08	46.00	-19.92	AVG	P	
11	22.286	17.91	23.89	41.80	60.00	-18.20	QP	P	
12	22.286	5.03	23.89	28.92	50.00	-21.08	AVG	P	

Remark: The test Result=Reading+ Lisn+ Cab L.

If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

12. ANTENNA REQUIREMENTS

12.1. Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

12.2. Test Result

The antennas used for this product is PCB antenna, so compliance with antenna requirements. (Please refer to the **Annex B. EUT Internal Photos** for details)



13. APPENDIX

"EUT of External Photos, EUT Internal Photos & Test Setup Photos" Please refer to the Annex A, Annex B& Annex C document.

CTSL2620730359E Annex A. EUT External Photos

CTSL2620730359E Annex B. EUT Internal Photos

CTSL2620730359E Annex C. Test Setup Photos

-----**End of Test Report**-----

