



FCC RF Exposure

EUT Description: Smart watch

Model No.: C68L

FCC ID: 2BXIH-C68L

Equipment type: portable device

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

f (GHz) is the RF channel transmit frequency in GHz. The result is rounded to one decimal place for comparison.

$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min test separation distance mm})} \right] (\text{W/kg}) < 3.0$ for 1-g SAR, and < 7.5 for 10-g extremity SAR, where Power and distance are rounded to the nearest mW and mm before calculation.

Limits for Maximum Permissible Exposure (MPE)

BLE

Frequency (MHz)	Output power (dBm)	Max tune-up (mW)	Antenna Gain (dBi)	Min. distance (mm)	Calc. thresholds	Limit	Result
2402	2.20	1.6596	0.08	5	0.5144	3.0000	Pass
2440	2.68	1.8535	0.08	5	0.5791	3.0000	Pass
2480	2.40	1.7378	0.08	5	0.5473	3.0000	Pass

Conclusion: No SAR is required